High- sensitivity capacitance method for measuring thermal diffusivity and thermal expansion: results on aluminum and copper

Original

High- sensitivity capacitance method for measuring thermal diffusivity and thermal expansion: results on aluminum and copper / Sparavigna, Amelia Carolina; Giachello, G.; Omini, M.; Strigazzi, Alfredo. - In: INTERNATIONAL JOURNAL OF THERMOPHYSICS. - ISSN 0195-928X. - 11:(1990), pp. 1111-1111.

Availability:

This version is available at: 11583/1405989 since:

Publisher:

Published

DOI:

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Athens Authentication Point

Welcome!

To use the personalized features of this site, please log in or register.

If you have forgotten your username or password, we can help.

My SpringerLink

Marked Items

Alerts

Order History

Saved Items

All

Favorites

Content Types Subject Collections

English

Journal Article

High-sensitivity capacitance method for measuring thermal diffusivity and thermal expansion: Results on aluminum and copper

Journal International Journal of Thermophysics
 Publisher Springer Netherlands
 ISSN 0195-928X (Print) 1572-9567 (Online)
 Issue Volume 11, Number 6 / November, 1990
 DOI 10.1007/BF00500564
 Pages 1111-1126
 Subject Collection Physics and Astronomy
 SpringerLink Date Monday, December 06, 2004

Add to marked items
 Add to shopping cart
 Add to saved items
 Request Permissions
 Recommend this article

Physics of Surfaces and Interfaces

Ibach, Harald

A. Sparavigna¹, G. Giachello¹, M. Omini¹ and A. Strigazzi¹

(1) Dipartimento di Fisica and I.N.F.M., Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy

Received: 13 November 1989

Abstract Thermal diffusivity and thermal expansion in high-conducting solids can be measured by means of a capacitance method, which turns out to be simple, reliable, and accurate and yields the first property with an accuracy of $\sim 1\%$ and the second one with an accuracy of $\sim 2\%$. Preliminary results, which are consistent with the literature, have been obtained on pure aluminum (99.999%) and on commercial copper, both at near room temperature.

Key words capacitance method - thermal diffusivity - thermal expansion

References secured to subscribers.

Find more options

- ☒ Within all content
☐ Within this journal
☐ Within this issue

Export this article

Export this article as RIS | Text

Text

PDF

The size of this document is 700 kilobytes. Although it may be a lengthier download, this is the most authoritative online format.

Open: Entire document

Referenced by

3 newer articles

1. Rotter, M. (1998) A miniature capacitance dilatometer for thermal expansion and magnetostriction. Review of Scientific Instruments 69(7) [CrossRef]
2. Sparavigna, A. (1992) Thermal diffusivity and conductivity in low-conducting materials: A new technique. International Journal of Thermophysics 13 (2) [CrossRef]
3. Omini, M. (1992) Thermal diffusivity of solids with a low expansion coefficient: A dilatometric technique. International Journal of Thermophysics 13(4) [CrossRef]

Ads by Google

Measurement services

Thermal Conductivity /
Diffusivity / CTE / CP
measurement services
www.tprl.com

Aluminum Properties

MatWeb, the free materials
database Datasheets for
many aluminum grades
www.matweb.com

CIM Marketing Courses

Innovative Online Study
Programmes Expert
Support, Proven Results!
www.marketingknowledge.co.uk

**Tensile Testing
Machines**

Testing from 1N to 100kN,
and more, and a history of
superior support
www.TiniusOlsen.com

Slide Bearing Plates

Teflon, graphite & bronze
plates & pads for high or
low temperatures
www.pipingtech.com

Frequently asked questions | General information on journals and books | Send us your feedback | Impressum

© Springer. Part of Springer Science+Business Media

Privacy, Disclaimer, Terms and Conditions, © Copyright Information

Remote Address: 82.60.138.180 • Server: mpweb19

HTTP User Agent: Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 5.1; .NET CLR 2.0.50727)