

Network coding meets multimedia: a review

*Original*

Network coding meets multimedia: a review / Magli, Enrico; M., Wang; P., Frossard; A., Markopoulou. - In: IEEE TRANSACTIONS ON MULTIMEDIA. - ISSN 1520-9210. - STAMPA. - 15:5(2013), pp. 1195-1212. [10.1109/TMM.2013.2241415]

*Availability:*

This version is available at: 11583/2504192 since:

*Publisher:*

IEEE

*Published*

DOI:10.1109/TMM.2013.2241415

*Terms of use:*

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

*Publisher copyright*

(Article begins on next page)

# Network Coding Meets Multimedia: a Review

Enrico Magli, Mea Wang, Pascal Frossard, Athina Markopoulou

**Abstract**—While every network node only relays messages in a traditional communication system, the recent network coding (NC) paradigm proposes to implement simple in-network processing with packet combinations in the nodes. NC extends the concept of “encoding” a message beyond source coding (for compression) and channel coding (for protection against errors and losses). It has been shown to increase network throughput compared to traditional networks implementation, to reduce delay and to provide robustness to transmission errors and network dynamics. These features are so appealing for multimedia applications that they have spurred a large research effort towards the development of multimedia-specific NC techniques. This paper reviews the recent work in NC for multimedia applications and focuses on the techniques that fill the gap between NC theory and practical applications. It outlines the benefits of NC and presents the open challenges in this area. The paper initially focuses on multimedia-specific aspects of network coding, in particular delay, in-network error control, and media-specific error control. These aspects permit to handle varying network conditions as well as client heterogeneity, which are critical to the design and deployment of multimedia systems. After introducing these general concepts, the paper reviews in detail two applications that lend themselves naturally to NC via the cooperation and broadcast models, namely peer-to-peer multimedia streaming and wireless networking.

**Index Terms**—network coding, multimedia communications, error resilience, wireless media, video streaming, distributed media systems, peer-to-peer.

## I. INTRODUCTION

Network coding (NC) is one of the recent breakthroughs in communications research. It has first been proposed in [1] and potentially impacts all areas of communications and networking. In a nutshell, the conventional networking paradigm is based on routing, where packets are forwarded towards the destination by each network node. NC is based on the idea that intermediate network nodes process packets in addition to relaying them. Processing typically involves generating and sending new output packets as linear combinations of the incoming ones. It can be done at different levels of the classical protocol stack (transport/application, MAC/IP, physical layer, and joint processing involving multiple layers). This new paradigm entails a radical change in the design of communication networks and applications.

Multimedia delivery techniques heavily rely on the transport and network layers of the communication protocol stack. Multimedia communications have been optimized to fully exploit the traditional protocols and maximize the quality of service. With the new NC paradigm in networks with source, path and peer diversity, the traditional coding and communication methods have to be rethought in terms of the way packets

are created, combined and delivered. In particular, multimedia applications could clearly benefit from the improvements offered by NC in terms of augmented throughput, reduced vulnerability to packet erasures and ease of deployment in large scale distributed systems.

The NC concept has been initially devised in the information theory community. The gap between the information theoretic models and the models of real multimedia applications is fairly large. This has generated a lot of interest in developing NC schemes that yield significant benefits in multimedia applications, especially in peer-to-peer (P2P) streaming and wireless communication systems. In particular, multimedia applications pose unique and important challenges depending on the application scenario, such as large amounts of data, stringent timing constraints, heterogeneity in the packet importance as well as in the client set. Therefore, practical NC algorithms have to be specifically designed to cope with these challenges under several additional constraints from realistic settings.

First, the decoding complexity has to stay reasonable for realtime decoding. Second, the algorithms need to be scalable and robust to handle the dynamics of the sources, the intermediate nodes and the paths in a large network infrastructure. Finally, the NC solutions must be adaptive to accommodate various timing constraints in delivering multimedia content, as these are among the most fundamental issues to be addressed in a realistic multimedia system. All these issues call for an appropriate design of the distributed communication protocol and effective coding strategies. Similarly to the traditional multimedia communication framework, the most promising solutions in NC systems certainly rely on end-to-end system optimization based on a joint design of the source and network code, where timing or complexity constraints are added to the data communication problem.

The objective of this paper is to review recent work in NC-based multimedia communication and to provide a comprehensive survey of the problems that have been fully or partially solved, along with the open research questions. The paper guides the readers through these problems in the following way. In Section II, we briefly review the theory of NC, we summarize the main theoretical results, and we put them in the context of practical multimedia communications applications. In Section III, we review the specific NC techniques that have been developed to tackle the issues mentioned above. Our analysis covers in-network error control, as well as media-specific error control. The former refers to NC techniques that have the objective of maximizing *network* performance from a “multimedia” point of view, *e.g.* minimizing delay. Media-specific error control introduces *distortion* into the NC setting, employing network-oriented source coders based on layered and multiple description coding. Low-complexity NC techniques are also considered. Sections IV and V describe two specific application domains of NC principles, namely P2P and wireless networks. These are important because they naturally

Copyright (c) 2012 IEEE. Personal use of this material is permitted. However, permission to use this material for any other purposes must be obtained from the IEEE by sending a request to [pubs-permissions@ieee.org](mailto:pubs-permissions@ieee.org).

lend themselves to NC due the cooperation and broadcast models. In particular, Section IV is concerned with the use of NC for P2P media streaming. It describes in detail how NC can radically change the way P2P streaming systems are designed, leveraging a coded representation that facilitates content distribution and streaming. It further includes a discussion of NC for both live and on-demand streaming. Section V is dedicated to the applications of NC in wireless networks, considering various topologies, traffic scenarios and coding schemes. It first describes how NC can be used to improve throughput in general wireless single and multiple unicasts. Then, media-specific issues are considered, and augmented versions of general-purpose NC solutions are discussed, which explicitly take into account the media format and structure. NC-based collaboration among mobile devices is discussed, reviewing the relevant techniques and open problems. Finally, Section VI concludes the paper and outlines open problems. It should be noted that the other papers [2], [3] also review multimedia applications of NC, and the survey in [4] particularly focuses on wireless multimedia applications. In this paper we provide a more comprehensive overview, with particular emphasis on both the P2P and wireless streaming problems.

## II. NETWORK CODING FRAMEWORK

### A. Basics

NC is a new paradigm for sending information over networks. Instead of simply relaying packets (as it is the case with routing), network nodes can also combine incoming packets and send the resulting *coded* packets to outgoing edges. While these operations do not generate new information in the network, they augment the diversity in the representation of the source information, with several potential benefits.

In particular, NC has been shown to improve on throughput, delay, resilience to packet loss, and system complexity, when properly applied in favorable scenarios. At the same time, these gains do not come for free: NC requires processing in the middle of the network, which may lead to additional delays, complexity and vulnerability to byzantine attacks [5]. Therefore, NC is not equally attractive in all application settings. For example, NC has not been implemented in classic wireline networks (because of the cost and complexity of introducing changes to high speed routers), while it has been successfully applied to peer-to-peer and wireless mesh systems, where it is feasible for nodes to process incoming packets. For this reason, NC is particularly well suited to multicast traffic scenarios (as is the case in peer-to-peer networks where all nodes cooperate to get the same file) and wireless networks (where the broadcast medium provides opportunities for combination of diverse representations of the source information). Furthermore, NC is theoretically well-understood in these two types of network systems.

Before discussing applications in more detail, we now spend time on describing the principles of network coding. The seminal paper that defined the beginning of the NC research is the work in [1]. It considers a multicast session over a directed graph with lossless links and shows that, when operations at intermediate nodes are allowed, the maximum multicast rate is equal to the minimum min-cut from the source to each receiver. Essentially, if all receivers have the same min-cut




Fig. 1. Butterfly network [1] and one multicast session. There is one source and two sinks. Links have a unit capacity, and zero delay. *Intra-session* network coding is used on edge 4 – 5.

from the source, network coding permits to achieve the min-cut capacity simultaneously for all the nodes. This capacity corresponds to the maximum flow rate that each receiver could get if it were alone in the network. Later, the work in [6] showed that linear network coding operations are sufficient for achieving this maximum multicast rate, and the work in [7] further fostered the area by confirming these results in an algebraic coding framework.

The simplest example that demonstrates the key idea and the benefit of network coding in the multicast case is the butterfly network depicted in Fig. 1. The source 1 sends two different symbols  $b_1$  and  $b_2$ . The symbols are then transmitted towards the receivers<sup>1</sup>. Conventionally, two transmission slots are necessary to send both symbols through the bottleneck link between nodes 4 and 5. However, when the symbols are combined at node 4, one transmission slot is sufficient to transmit the coded information that is useful to both sink nodes 6 and 7. Each of them receives the coded symbol (from the bottleneck links) and one of the original symbols (from the side links). The receivers can then decode both symbols  $b_1$  and  $b_2$ . This simple example demonstrates that NC requires fewer time slots to convey the source information, compared to a routing solution. Network throughput is increased, as indeed each receiver achieves its min-cut, which is equal to 2. Moreover, the delivery delay is reduced by the combination of symbols at the intermediate node.

The main multicast theorem and the above example refer to *intra-session network coding*, because the symbols  $b_1, b_2$  belong to the same multicast session<sup>2</sup>. Over the last decade, network coding has been applied to many network and traffic

<sup>1</sup>In this paper, the terms “receiver”, “sink”, or “client” are used interchangeably.

<sup>2</sup>The term “session” refers to one source and one or more receivers interested in that source.




Fig. 2. Modified butterfly network [8] and two unicast sessions (1-6 and 2-5). All links have a unit capacity, and zero delay. Inter-session network coding combines symbols from the two different sessions at node 3.




Fig. 3. Two-link tandem network. Toy example of network with one source node and one sink node connected by lossy channels via a network node. Error resilience can be increased when NC is implemented in node 2.

scenarios<sup>3</sup>, beyond a single multicast session over lossless graphs. In particular, it has been extended to *inter-session network coding*, which refers to coding packets from different (unicast or multicast) sessions that share the network resources. Furthermore, network coding in networks with erasures and/or broadcast links have also been studied.

The simplest example that demonstrates inter-session coding is the modified butterfly example shown in Fig. 2. The sources 1 and 2 send information to receivers 5 and 6, respectively; the key difference with Fig.1 is that each receiver is only interested in receiving its intended symbol, not in both symbols. The combination of symbols from both sessions with *Inter-Session network coding* at node 3 efficiently uses the central bottleneck link, since the transmitted information is useful to both clients. The clients receive both coded symbols and the original symbols that are used together for decoding the information of interest in only one time slot. In contrast, routing needs two time slots to deliver the same information to the receivers in this network. In general, inter-session NC can be more efficient than a solution where the concurrent sessions are allocated different subgraphs, with intra-session NC in each subgraph [7] [9]. However, defining the optimal inter-session network coding operations is still an open problem, and suboptimal or heuristic approaches are used in practice.

NC is also helpful for transmission over lossy channels, where it can help to increase the resilience to data loss. We illustrate this advantage by the simple example of a two-link tandem network given in Figure 3. A source transmits information towards a sink node via two lossy links with

<sup>3</sup>A “traffic scenario” consists of one or more sessions taking place at the same time on the same network.

symbol erasure probabilities  $p_{12}$  and  $p_{23}$ . One could apply channel coding at the source, with a channel rate being computed based on the end-to-end loss probability. This leads to a communication rate of  $(1-p_{12})(1-p_{23})$ . It can be shown that, if the source implements a channel code for the first link, and then if node 2 decodes and re-encodes with a channel code adapted to the reliability of the second link, the system can achieve a transmission rate of  $\min(1-p_{12}, 1-p_{23})$ ; this is usually larger than  $(1-p_{12})(1-p_{23})$  and hence better than an end-to-end channel coding strategy. But this form of in-network processing usually involves large delays due to the decoding operations in the network nodes. Interestingly enough, it is possible to achieve the same transmission rate of  $\min(1-p_{12}, 1-p_{23})$  with NC [10]. Node 2 can simply combine packets as in intra-session NC in order to achieve capacity on the two-link tandem network, without decoding and recoding packets in the network nodes. It provides an effective and low-delay solution to combat losses with help of network nodes close to the failure points. It is interesting to note that this approach bears some resemblance with rateless or Fountain codes [11] [12], where effective combinations of packets have led to error-resilient communications with a low overhead.

The above examples illustrate the benefits of NC in different communication problems that are commonly encountered in media streaming applications. The theoretical limits of NC are well studied in the field of network information theory. Interested readers may refer to [13], [14], [8], [15], [16], [7] for an in-depth understanding of NC foundations. In this paper, we concentrate on the application of NC for solving multimedia communication problems.

## B. Algebraic Network Coding

We give now more details on the network coding principles, from the perspective of the algebraic NC framework. We consider general communication systems that are composed of source nodes, network nodes and sink nodes, which are connected by channels that are potentially lossy. We represent the system as a directed graph  $\mathcal{G} = \{\mathcal{V}, \mathcal{E}\}$ , where the vertices  $\mathcal{V}$  represent the different nodes in the network. The set of edges  $\mathcal{E}$  consists of arcs between nodes and denotes the links in the network.<sup>4</sup> The NC problem first estimates a set of rates to be used on each edge for data delivery. This leads to the definition of the coding subgraph, *i.e.*, the subset of the capacitated graph to be used for data delivery. The problem is then to determine the proper NC assignment among nodes in the coding subgraph.

The general framework of NC is not limited to specific types of network nodes. Most of the theoretical results, however, use linear codes, where the output symbols are linear combinations of the input symbols. Linear codes are sufficient to achieve capacity in the lossless multicast problem [17], [6], but insufficient for optimal inter-session NC, where pathological counter-examples exist. However, they lead to a computationally tractable yet effective solution; therefore, linear network coding is the only type of coding used in practice and is thus of interest to this paper. Algebraic linear network coding

<sup>4</sup>For simplicity, links here are considered point-to-point, but the framework can be extended to include wireless broadcast channels (using hyperarcs and a hypergraph).

can be summarized as follows [17], [7]. Consider an edge  $e = (u, v) \in \mathcal{E}$  with  $head(e) = u$  and  $tail(e) = v$ . Then, a symbol  $y(e)$  that is sent over an edge  $e$  emanating from node  $u$  can be represented as a linear combination of the symbols  $y(e')$  that have been received by the node  $u$  over the set of edges  $e' = \{e \in \mathcal{E} | tail(e) = u\}$ . It can be expressed as

$$y(e) = \sum_{e'} \alpha(e')y(e'), \quad (1)$$

where each edge is associated with a vector of local coding coefficients  $\alpha$  whose length is equal to the indegree of node  $u$ . The coded symbols are actually combinations of the source symbols  $x_i$ , with  $i \in 1..N$ . Indeed, it can be shown by induction that the successive encoding operations in the different nodes of the network result in the following relation

$$y(e) = \sum_i^N \beta(i)x_i \quad (2)$$

The vector of global coding coefficients  $\beta$  for the edge  $e$  can be written as a function of the local encoding coefficients  $\alpha$  used at the different network nodes. It has a length equal to the number of source symbols,  $N$ . The sink nodes decode the linear system of equations generated based on the set of received packets, with classical techniques such as Gaussian elimination, in order to recover the source symbols.

While several works have been conducted towards optimal linear code design (*i.e.*, the proper selection of the coefficients  $\alpha_i$ ) based on the network constraints [18], the coding coefficients are typically chosen randomly based on Random Linear Network Coding (RLNC). Remarkably, it has been shown in [19] that taking the coefficients at random from a uniform distribution over a Galois field of size  $q$  leads to good performance. As  $q$  becomes large, the probability that randomly drawn encoding vectors yield linearly dependent packets becomes arbitrarily small. Furthermore, since the random drawings can be performed independently at each network node, there is no need for centralized knowledge of the topology, nor of the buffer states: this leads to a fully distributed algorithm. RLNC is thus particularly interesting in distributed systems where it leads to easy deployment without the need for coordination between nodes. In practice, a common choice of the Galois field size is to set  $q = 256$ . It is also possible to take a smaller field size, *e.g.*,  $q = 2$  as in [20]. The advantage of this latter choice resides in reduced complexity, which is very appealing in a wireless scenario for example.

### C. Practical Network Coding

In practical implementations for multimedia communications over packet networks, the NC operations described in the previous subsection are applied to full data packets and not on bytes or elementary symbols independently. In particular, a packet is treated as a vector of symbols (typically one byte each), and the same coding coefficients are applied to all symbols in the packet with the coding operations on packets being done symbol-wise.

The design of practical network coding systems also implies that the sink nodes have to receive sufficient information for decoding the NC packets. This is solved in [21] by tagging

each packet with the set of coefficients that describe the coding operations, so that the sink node can perform the appropriate decoding operations. In practice, a header that conveys information about the coding coefficients (typically the global encoding vector  $\beta$ ) is added to each packet. The global encoding vector entails a rate overhead, whose size depends on the number of source symbols and the size of the finite field.

An important difference between NC theory and practical settings lies in the timing constraints that are inherent in multimedia communications applications. Real networks transmit packets asynchronously and media streaming sources continuously transmit new packets that have to be decoded before their expiration deadlines. Therefore, packets belonging to a multimedia stream are generally grouped into generations of size  $L$  (*i.e.*, sets of  $L$  time consecutive multimedia packets) and network coding operations are applied to packets of the same generation [21]. Each packet must also be tagged with the generation number, and each node may have to keep multiple buffers in order to separately process packets of different generations. The overall process is sketched in Figure 4. We finally remark that the values of the generation size ( $L$ ) and of the coding field  $q$  play an important role in the performance of the system, leading to a trade-off between the header size, the computational complexity, and the decoding performance.




Fig. 4. Practical network coding system. Packets from a generation are encoded together, and the encoding coefficients are conveyed in the header of the resulting packet.

Equipped with the main principles for practical NC, we discuss in the next sections how NC solutions can be deployed in media streaming systems. We review solutions for data communication problems where data packets are heterogeneous in terms of their importance in multimedia quality, where timing and computational complexity pose stringent constraints to the media delivery, or where the network topology changes during the session. We survey different tools and algorithms that potentially benefit from the inclusion of NC in multimedia communications applications.

## III. NETWORK CODING ADAPTED TO MULTIMEDIA

Section II has discussed the main aspects of NC for multimedia communications. There is, however, a gap between such models and multimedia applications in several aspects.

- In practical networks, packet losses may occur due to congestion, and large delays may render packets useless in multimedia applications. These aspects are not taken into

account in the graph-based network model introduced in Section II.

- The computation of optimal NC schemes usually considers that the network topology or the nodes' buffer content is known *a priori*. However, in many multimedia applications such as peer-to-peer streaming, the topology is rarely known by any peer, and the buffer content changes over time. Moreover, the network is generally non-static and of large-scale.
- The network model does not consider aspects such as delay jitter and bandwidth fluctuations, which are challenging issues for multimedia streaming.
- NC is all about increasing the available bit-rate, while in general multimedia applications are evaluated in terms of rate *and* distortion (or other suitable utility metrics).

The objective of this section is to review design techniques for NC, with a specific focus on the requirements posed by practical multimedia applications. We consider the practical NC framework defined in Section II-C and discuss methods for designing NC algorithms that are tailored to multimedia streaming systems. In addition to improvement in throughput, we pay a special attention to error resiliency and to algorithms that adapt NC operations to the video information in data packets. Finally, we review methods that address the delay and complexity constraints in multimedia applications.

#### A. In-network error control

If a node does not receive sufficiently many packets due to congestions or delays, decoding of the content is not possible; this leads to dramatic quality degradations. Applying Forward Error Correction (FEC) codes to the media amounts to adding redundancy symbols for loss recovery. Since most multimedia communications occur in packet network environments, losses typically occur in the form of packet erasures. Erasure correction codes are a nice and viable solution, *e.g.*, Reed-Solomon codes, low-density parity-check codes, turbo codes, as well as the more recent digital fountain codes such as LT codes [12] or Raptor codes [11]. The latter are based on the cascade application of a FEC block code, followed by an LT code. This results in linear encoding and decoding complexity that is attractive for NC.

These concepts can be extended to a distributed environment with multiple senders and receivers, particularly when the intermediate nodes are allowed to apply NC. This leads to the concept of “network error correction”, which has become increasingly popular in the information theory community [22], [23]. Practical coding solutions have mostly employed rank-metric codes [24]. In these codes, codewords are matrices, as opposed to vectors, and the *rank* is employed as a distance metric between two codewords, *i.e.*, the rank of the matrix difference. Rank-metric codes have become popular for storage applications, where information is stored in two-dimensional arrays but errors are typically confined to one or few rows or columns. Gabidulin codes are the rank-metric analog of Reed-Solomon codes, and are probably the most studied rank-metric codes [25], [26]. These codes are interesting for NC, as they can be used to solve a distributed erasure correction problem of the form  $Y = AX + Z$ , where the received packets  $Y$  are modeled as combinations of the source packets  $X$  using a linear transformation matrix  $A$ , plus

a matrix  $Z$  of error packets. It should be noted that, while there have been many recent theoretical advances in the area of network error correction, practical coding solutions have yet to be proposed.

In [27], the concept of “network-embedded forward error correction” has been proposed. Conventional multicast systems apply FEC codes in an end-to-end fashion, that is, only the source nodes and the destination nodes are involved in the coding and decoding processes. These are delivered to the receivers, which attempt to perform FEC decoding in order to recover the original data. The idea behind network-embedded FEC is to have a few enhanced “supernodes” that perform FEC decoding and re-encoding, instead of simply relaying packets. These nodes act as signal regenerators: they are able to locally recover from information losses and thereby to significantly improve the overall performance, at the price of added complexity. In [27], a greedy algorithm is proposed to select the near-optimal locations of the enhanced nodes. The main conceptual difference between network-embedded FEC and NC lies in the decoding-recoding approach. In network-embedded FEC, every enhanced node has to wait until enough packets are received in order to be able to decode and then re-encode a data segment. Therefore, it is not possible for an enhanced node to *immediately* forward re-encoded packets on its outgoing links, which may induce delays in the system. While network-embedded FEC can be seen as a very simple form of NC, it is not as good as a true NC solution, which would immediately re-encode and transmit packets without additional delay.

Channel coding techniques have also been employed in [28], [29] to perform NC on multimedia sessions in overlay networks. Rateless codes are used to construct an NC scheme in which the source packets are initially encoded by the server using a non-systematic Raptor code and then disseminated in the overlay. Each node schedules packet transmissions according to the amount of available bandwidth. If the number of received packets for a given media segment exceeds the available outgoing bandwidth, then only a part of the received packets are forwarded. Alternatively, if the available bandwidth is larger than the number of received packets, a node forwards the received packets, and then creates and forwards new linear combinations, leading to full exploitation of the available resources. In generating linear combinations of received symbols, one has to make sure that the new symbols are linearly independent to the original ones in order to avoid unnecessary redundancy. In [29], this has been taken care of by using combinations of only two symbols, and making sure that the same symbol is not used in multiple combinations. In general, this scheme is very effective computation-wise, but symbols cannot be recombined repeatedly, as this would generate linear dependencies in the new symbols. The scheme might thus present limitations for very large-scale networks.

Finally, another class of error control solutions is based on employing NC in the context of packet retransmission. In particular, it has been shown that existing transport protocols such as TCP can be augmented by NC, leading to significantly improved performance [30]. Similarly, NC has been employed in wireless networks in order to recover from packet losses. These aspects are discussed in more detail in Section V.

### B. Media-specific error control

Media-specific error control tackles the problem of considering distortion, in addition to rate, in the NC design. This is achieved by employing media compression techniques that exhibit graceful quality degradation upon occurrence of packet losses.

Similarly to joint source and channel coding or in general joint optimization among multiple layers of the communication protocol stack in client/server scenarios, information about content availability can be used in network error control algorithms in order to improve resource utilization. The video content can be arranged in classes of different importance in terms of video quality, or in multiple versions that gracefully increase the video quality. Such arrangements provided by techniques like scalable or multiple description video coding permit to design effective content-specific error control solutions.




Fig. 5. Scalable video coding with  $P$  layers at increasing bit-rates. Decoding is done at different cumulative rates, yielding a video at increasing frame-rate and spatial resolution.

In scalable video coding (SVC) [31], multiple “quality layers” are created in order to adapt to the different capabilities of heterogeneous clients. The quality layers are typically decoded in a hierarchical way, as shown in Figure 5. In a  $P$ -layer system, the first layer provides a baseline level in terms of video quality and/or spatial and temporal resolutions. Additional enhancement layers can be used to improve on quality, resolution, or a combination thereof. SVC should be coupled with unequal error protection techniques in order to provide a more reliable delivery of the most important layers. This can be obtained in various ways, *e.g.*, allocating a lower FEC code rate or more retransmission opportunities to the first layers. A very flexible scheme for the transmission of scalable coded media is represented by priority encoding transmission [32]. In this scheme, one can specify priorities for different media segments (*e.g.*, quality layers), and packets are created as a combination of source and erasure correction code symbols, such that the most important layers can be recovered from few packets, with more and more enhancement layers being recovered as more packets are received.

Interestingly, the unequal error protection principle can be easily extended to NC. In particular, in [21] it is proposed to implement priority encoding transmission in a distributed way, exploiting NC packet recombinations to generate the FEC symbols in a distributed way. Thus, relatively few linearly independent packets are sufficient to recover the base layer during the NC decoding process, while more packets are needed to recover the enhancement layers. A similar approach

has been proposed in [33]. Given  $P$  quality layers,  $P$  different “types” of packets can be created, where a packet of type  $i$  contains linear combinations of source packets from layers 1 to  $i$ , but not packets from layers  $i + 1$  to  $P$ . In this way, packets of type  $i$  can be used to decode any layer from 1 to  $i$ . The result is similar to [21], in that the base layer can be recovered from a limited number of packets. The number of packets of each type can be modulated in order to reach a desired probability of successful decoding for a given layer.

The approach proposed in [34] is also similar in spirit to the above unequal error protection schemes. Multimedia sources encode data with scalable coding principles. Hence, the first part of the compressed file is more important, as it contains the base layer. Then a NC scheme is designed in such a way as to achieve higher probability of successful decoding for the first part of a media segment. This is done by dividing the media into layers and creating NC packets that are linear combinations of packets belonging to the first  $i$  out of  $P$  layers. The authors in [34] investigate the problem of designing distributions of packet types that can lead to optimal quality. They provide an analytical evaluation of the decoding probability for each layer, enabling accurate control of quality of experience through the design of a suitable distribution. In [35], the multi-generation mixing approach has been proposed. With this technique, coding can be performed over different generations, which facilitates decoding in case of incomplete generations. Decoding of a generation can be performed independently if sufficiently many packets have been received, and jointly with other generations otherwise. Note that multiple generations with inter-generation decoding as in [35] can also be interpreted as representing the media as one single generation divided into layers, with inter-layer combinations and joint decoding as in [34].

The problem of delivering scalable content has also been addressed in [36]. In scalable coding with NC, the receiver has to wait until the complete segment has been received before starting the decoding process. The authors of [36] have designed a delay-mitigating code that can be applied to a layered source in such a way that the first and most important layers are decoded earlier and forwarded to the application layer without any delay. This is achieved through the concatenation of a short-length delay-mitigating code and a network code. In general, the ability to receive and decode the layers in order comes at the expense of a larger overall overhead.

Finally, the unequal error protection problem has been addressed from a packet scheduling perspective in [37]. Unlike previous approaches that are based on the design of codes yielding unequal protection, the authors in [37] have defined coding decisions that are adapted to the capabilities of different receivers. The receiving peers request packets from different layers and prioritized transmission is achieved by varying the number of packets from each layer that are employed in the NC combinations. The authors propose a distributed optimization algorithm that minimizes the expected distortion in the overlay network.

As an alternative to hierarchical video layers, multiple description coding (MDC) [38] can also generate multiple video streams, where the “descriptions” are independently decodable and hence do not require any unequal error protection. The combination of NC and MDC has been given

comparatively less attention than SVC has been. In [39], the authors have proposed to use multiple description wavelet-based video coding based on FEC codes in the framework of priority encoding transmission [38]. The multiple description scheme employs random codes as in [21]. A similar approach has been developed in [40]. In this case, the objective is to optimize the redundancy of each layer in an interleaved packet-based priority encoding transmission scheme. The authors develop redundancy allocation algorithms and finally apply their scheme to H.264/SVC.

### C. Delay and complexity constraints

We describe now NC techniques that specifically address the delay and complexity constraints in multimedia applications. In general, NC can reduce delay as the reduced number of transmission opportunities employed to deliver the content often translates into a reduced delay experienced by the receiver. At the same time, NC is a block-coding operation where a block represents a generation; hence the encoder has to wait for a given number of symbols before these symbols can be processed and transmitted. This introduces a “minimum” delay, which may even be an unbounded quantity in the case where rateless codes are used, although the delay can be bounded with very high probability. Since NC is essentially a distributed FEC code, the trade-off between performance, delay and complexity is somewhat similar to that for regular non-distributed block coding. High-performance coding for short block lengths (and hence low delay) is possible, but it generally requires to employ “dense” linear combinations, *i.e.*, combinations such that most of the coefficients  $\alpha_i$  are nonzero. This leads to a code whose encoding and decoding complexity is large, and may be undesirable for applications in wireless networks and with battery-powered computing devices.

Low-complexity codes can be designed based on random coding theory, *e.g.*, low-density parity-check codes [41] or digital fountain codes [12], [11]. However, these codes typically require large block lengths to operate close to capacity, which leads to large delay. It is possible to employ a random code over a short block, but generally this yields a less efficient code. As a consequence, the receiver will have to wait for a possibly large number of packets before decoding, as some of the received packets are likely to be linearly dependent. Another influential factor is the size of the Galois field that the code is constructed on. In general, small field sizes lead to lower complexity codes, and are amenable to precomputation of multiplications so that the encoding only consists of table look-up operations. However, it is known that the smaller the field size, the larger the probability of receiving linearly dependent combinations; hence, a larger bandwidth overhead is needed to perform successful decoding. In short, there are several trade-offs to determine for achieving bandwidth efficiency, complexity and delay.

A few specific solutions have been proposed to lower the complexity of NC while still achieving good performance. In [42], two modifications have been proposed. First, the linear combinations are picked directly from the partial decoding results generated during the Gaussian elimination process. Second, the degree of the linear combinations is kept low by combining only a limited number of packets at a time. In [43], band codes have been proposed, which permit fine

tuning of the complexity of NC schemes with very little performance penalty. A similar problem has been addressed in [44]. The authors propose to employ modified degree distributions at the NC encoders, calculated in such a way that a desired distribution is obtained at the decoders for low-complexity decoding. Finally, the complexity problem can also be addressed at a higher level. In [45], it has been proposed that only a limited number of appropriately-selected nodes of an overlay network perform linear combinations while the other nodes simply relay their incoming packets. This minimizes the transmission delay incurred by NC.

Recent implementations of network coding libraries, such as NCUtils [46], Tenor [47] and KoDo [48] have demonstrated that it is possible to achieve low delay and high encoding/decoding rates on commercial platforms, including resource-constrained smartphones. For example, the work in [49] implements a cooperative video streaming system on Android phones, using the NCUtils library [46]. Experiments demonstrate that, for a field size of 8 and generation size of 25, encoding and decoding rates are in the order of 5Mbps and 25Mbps; this is sufficient for video streaming purposes in practice. This was achieved through a combination of optimizations such as progressive encoding/decoding, selection of the generation size and field size, table-lookups for multiplications and XOR for additions, random selection of only a subset of the coefficients, implementation in Java and native C++ on Android phones.

In summary, there are different ways to leverage NC and improve media streaming performance, as summarized in Tab. I. A first class of techniques are designed to improve networking by properly designing linear combinations and packet scheduling policies in order to optimize decoding performance. Another class of NC techniques exploit specific media features such as scalable and multiple description coding in order to maximize the quality of experience. Overall, several papers have demonstrated their usefulness in ad-hoc scenarios, but in-network techniques still lack a unified and comprehensive framework. Moreover, although there is a good understanding of the basic principles of NC for multimedia streaming, optimal solutions have yet to be found. For example, NC for SVC and multiple description coding is very challenging, as it involves two aspects at the same time, *i.e.*, designing an NC scheme that requires a small overhead and designing suitable packet scheduling policies for the different substreams. None of these problems has been fully solved, and there is still a lot of room for research in these areas. As NC is making its move towards mobile battery-powered devices, the topic of low-complexity NC schemes is also very timely and relevant.

We provide in the next sections more details about specific algorithms in two of the most popular frameworks for multimedia NC, namely peer-to-peer systems and wireless scenarios.

## IV. PEER-TO-PEER MULTIMEDIA APPLICATIONS

The requirements of P2P live multimedia streaming applications have marked a significant departure from P2P file sharing. In *P2P streaming*, like PPLive [50], a peer plays the video while receiving the content from the source, which requires consistent and sustainable throughput over time in order to maintain a smooth playback. The streaming content is

TABLE I  
NC TECHNIQUES FOR MULTIMEDIA APPLICATIONS

Classes of Proposal	Section	Key Benefits	References
In-network error control	III-A	Increased goodput, reduced delay, increased error resilience	[27], [28], [29]
Scalable video coding	III-B	Improved quality of experience under packet losses (requires unequal error protection), handling of heterogeneous clients (bit-rate/quality, display resolution, temporal resolution)	[21], [33], [34], [35], [36], [37]
Multiple description coding	III-B	Improved quality of experience under packet losses (does not require unequal error protection)	[39], [40]
Low-complexity network coding	III-C	Improved battery life, reduced computational delay, ability to handle computation-heterogeneous clients	[42], [43], [44]

made available by one or more servers, known as the *streaming sources*, and is partitioned into *groups of frames (GOFs)* representing  $t$  seconds of the playback. The smallest unit of data that is being transmitted from the server to a client is commonly referred to as a *segment*, which encompasses  $n > 0$  GOFs. As participating peers, end hosts contribute their upload bandwidth capacities to serve other peers. Consequently, the load on dedicated streaming servers is significantly reduced. Thus, each peer can potentially be a server for the content it has received. When peer A receives a segment from peer B, peer A is peer B's *downstream* peer, and peer B is the *seed* of this segment for peer A. The successful deployments of PPLive [50] and CoolStreaming [51] have demonstrated the feasibility of P2P multimedia streaming over the Internet. The salient advantage of P2P streaming is the *scalability* of a streaming session since the upload capacities on streaming sources are no longer the bottleneck.

In the above context, NC has the advantages of imposing less bandwidth demand on servers and offering better playback quality. It also leads to shorter initial delay as well as more robustness to network dynamics [52]. The equal importance of all NC packets naturally balances the bandwidth demand on each peer according to its upload capacity. Furthermore, NC transmits small blocks of segments rather than segments in their entirety, which leads to better utilization of peer upload capacity and smaller waste of bandwidth when discarding blocks of obsolete segments. The effective bandwidth utilization naturally leads to very short initial buffering delay, especially during the flash-crowd scenario. In addition, it significantly reduces the bandwidth demand on the streaming server. Ultimately, the bandwidth saving enables a better scaling of the network. The feasibility of NC is based on a special protocol design in which the random coding coefficients are either embedded in each of the transmitted coded blocks or can be reproduced using the random generator seed used in the segment. In this section, we first review the P2P infrastructure for multimedia streaming since NC operates on top of a P2P streaming protocol. We then discuss the applications of NC in P2P live streaming, followed by the applications of NC in P2P Video-on-Demand (VoD). We conclude this section with a discussion of new research directions in applying NC for multimedia streaming.

#### A. P2P approaches for multimedia streaming

Stemming from the success of P2P file sharing, a few state-of-the-art P2P streaming algorithms have been proposed to alleviate bandwidth demands on the streaming sources. There

are mainly two structures in P2P streaming systems: push-based and pull-based. The push-based solutions, also known as the tree-based approaches [53], [54], [55], [56], are based on the philosophy of IP multicast. In such a paradigm, peers are organized into one or more multicast trees rooted at the source. The source “pushes” *segments* to all descendants among the trees. Although the push-based approaches lead to short delays in distributing the content, it is not generally employed in real-world streaming applications, mainly due to the complexity and difficulty in maintaining the structured network topology in the presence of peer dynamics.

In sharp contrast, the pull-based approaches, also known as the mesh-based approaches, do not enforce any rigid structure among the peers [57], [51], [58], [59], [60], [61]. Instead, connections are established dynamically based on the content availability at each peer. The content exchanged in this approach is best described as a “data-driven” or “swarming” style of multicast. In data swarming, each peer advertises to its neighbours the availability of segments in its buffer, and the neighbours explicitly request segments as needed. The primary advantages here are simplicity in maintaining peer connectivities and robustness in dynamic networks. Nonetheless, the delay in delivering the live content to each participating peer is inevitably increased due to the periodical exchange of segment availability among peers.

Regardless of the actual algorithm and protocol in use, the P2P infrastructure poses unique challenges in designing a scalable and high performance multimedia streaming systems. First, peers may arrive at and depart from a session in unpredictable ways. Second, peers must communicate with each other in order to avoid receiving redundant content. This is commonly referred to as *data reconciliation* and often results in excessive communication overhead and a lack of adaptivity to network dynamics. Third, the heterogeneity in peer upload capacities makes it challenging to *balance the load* among peers without a central administration. Last, but not least, the diverse network delays and jitters require peers to buffer a sufficient number of segments before the start of the playback in order to maintain a smooth rendering. The time required for this buffering is commonly referred to as *initial delay* or *playback delay*. In the next two sections, we discuss how NC can help to address these challenges.

#### B. Network Coding for P2P Live Streaming

NC has been one of the key enabling technologies that marks a significant design shift in P2P multimedia streaming. The highly visible *Avalanche* project [62] has demonstrated the

first practical use of NC in P2P file sharing systems. It showed that all pieces of information are treated equally with NC. Without the need to identify and distribute the “rarest piece” first, the control protocols are greatly simplified since the need for data reconciliation is eliminated. The simplified protocol along with the coded data swarming concept lead to a faster download rate with a minimal coding operation overhead. It has been shown that the performance benefits provided by NC correspond to a 2-3 times higher throughput compared to a system that does not use NC at all [62]. In addition, the residual bandwidth at peers can be utilized to transmit small encoded blocks.

Due to the great performance gain brought by NC in P2P file sharing systems, network researchers and developers are extending its application to P2P live multimedia streaming systems. The benefits and trade-offs of NC in P2P live streaming have been studied in [63], [64]. These studies show that the use of NC leads to better bandwidth utilization and better resiliency to network dynamics. Furthermore, under limited bandwidth, NC-enabled streaming systems offer better performance than conventional streaming systems do.

We analyze now in more details the benefits of NC in P2P live streaming. With NC, video segments are divided into blocks and then encoded, as shown in Figure 6. Peers exchange small coded blocks rather than the large raw segments. Hence, a peer may download coded blocks of a segment from multiple seeds simultaneously without using any protocol to coordinate the seeds. Once a peer completely decodes the segment, it informs all its seeds by sending short messages to terminate the transmission of the segment. Without using NC, a peer has to explicitly request individual segments from the seeds.




Fig. 6. Network coding in P2P streaming systems. Each segment is divided into small blocks that are coded using NC. Small coded blocks are being exchanged among peers.

As mentioned in Section III, the delay introduced by NC operations can increase the delivery time of video segments, which is critical in multimedia streaming sessions. In order to minimize this overhead, progressive decoding has been introduced in [63], [64]. With progressive decoding, as illustrated in Figure 7, a peer can start decoding as soon as the first coded block is received. Then, it *progressively* decodes the new coded blocks as soon as they are received. In this process, the decoding time overlaps with the time required to receive the coded blocks, thus mitigating the coding delay within the transmission time of a segment.

The application of NC fundamentally changes the way segments are shared among peers, and the uniform importance




Fig. 7. Progressive decoding for P2P streaming

of each coded block within a segment greatly simplifies the data reconciliation process. A peer no longer relies on a single seed for a given segment. It can simultaneously receive different blocks of a segment from multiple seeds. Consequently, the system is more resilient to network dynamics since the departure of one seed only affects a small portion of a segment, which can be quickly recovered with data from other seeds. The delivery of small coded blocks also makes good use of upload capacity, even for peers with very small residual upload capacity. This effectively leads to faster delivery of segments and better playback quality.

These fundamental changes encourage a re-design of the P2P live streaming system to take full advantage of NC. To this end, the authors in [65] have redesigned the P2P streaming protocol,  $R^2$ , which incorporates random NC with a randomized push algorithm. Unlike the “static” push-based design using predetermined trees in [58], a peer in  $R^2$  randomly chooses a downstream peer and pushes coded blocks for a segment that is found missing without the need for any explicit request. We finally note that the  $R^2$  design has been adapted by UUSee [66], hence it represents the first real-world deployment of NC.

### C. Network coding for P2P Video-on-Demand

*Video-on-Demand (VoD)* is a special case of live streaming, where the constraint of synchronized playback among peers is relaxed. VoD users enjoy the flexibility of watching arbitrary video segments at any time, including DVD-like playback operations: play, pause, chapter selection, fast forward, and rewind. P2P VoD has been widely deployed [66], [50], [67], [68], but it has received less attention in the research community compared to P2P live streaming services. Many works have focused on the ability to support asynchronous playback but not the full set of VCR/DVD-like features. RedCarpet [69] is the first work incorporating NC into a P2P VoD system that achieves a better playback quality with a simple protocol. Annapureddy *et al.* [70] have then addressed the challenge of providing VoD using P2P mesh-based network. They have also shown that it is possible to provide high quality VoD using an algorithm combining NC, optimized resource allocation and overlay topology management. SonicVoD [71] and UUSee [66] are the two latest implementations of NC in real P2P streaming applications. Measurements from UUSee [66] confirm that NC can significantly reduce the initial delay and server bandwidth cost in the streaming architecture. They also show that, when multiple seeds proactively push coded blocks to neighbouring peers, more blocks than necessary for decoding may be transmitted, resulting in a waste of resources. This calls for an early breaking mechanism, proposed in [66], so that a peer can effectively stop the seeds from sending coded

blocks when it is about to receive sufficiently many blocks for decoding.

Despite the success of NC, the performance gain provided by NC has yet to be quantified. SonicVoD [71] has provided a comparison study to this end, but the evaluation results are questionable. NC enabled VoD applications cannot achieve smooth playback until the bandwidth provision is equivalent to at least twice the streaming rate, and the baseline VoD applications can never achieve smooth playback. In reality, the streaming protocol cannot be that inefficient in its bandwidth utilization. Therefore, the comparison results are yet to be confirmed. More in-depth work on NC for P2P VoD is to be performed.

#### D. What's Next?

Although the application of NC in P2P multimedia streaming has received a lot of attention, there are still several issues to be investigated. Such research is certainly encouraged by the growth of P2P traffic. This growth raises many concerns for ISPs and content providers, and it opens new research directions towards system scalability and ISP traffic localization. In this section, we briefly review ongoing work and future research directions in NC for P2P multimedia streaming.

1) *Multimedia-based optimization*: An important research direction deals with the heterogeneity of the peers in P2P systems, and the adaptation of video quality to the capabilities of each client. It therefore becomes important to optimize NC for better video quality and better network resource utilization. In order to accommodate the heterogeneity in peer upload capacity, in [72] the P2P streaming systems have been modelled as a multi-rate multicast problem, and the optimal linear NC assignment is computed using linear programming optimization. This solution leads to the maximum aggregate rate among all participating peers in a streaming session.

One of the distinct characteristics of multimedia content is that it can be received in different forms and with different qualities depending on the bandwidth availability. For example, scalable coding and multiple description coding organize the content into multiple layers that can be decoded in a flexible way, as has been shown in the previous section. The quality of the playback then typically depends on the number of layers that have been received by individual peers. The feasibility of combining NC with SVC has been explored in [73], [74]. In [73], the proposed system, *Chameleon*, groups the network abstraction layer (NAL) units of SVC that have the same quality into a single packet. With NC, each packet is divided into smaller blocks, just like the way segments are divided in both P2P live streaming and VoD systems. Instead of transmitting raw packets, coded blocks of each packet are shared among peers. Such a design extends the benefits that have been identified in live streaming to the SVC-based streaming services. *Chameleon* shows up to 2.5% of improvement in playback skips and better resilience to peer dynamics. In [74], the proposed system utilizes both NC and SVC to better support heterogeneous bandwidth among peers and to allow quick adaptation to network churns.

Recently, a P2P multimedia streaming system has been proposed that utilizes prioritized, randomized NC [37]. The original video content is divided into classes of video frames and NC is applied differently in each class. An optimal rate

is then determined for each class on each network link. For practicality, a greedy algorithm is proposed for computing the rate allocation independently at each node. Using the video scalability property, hierarchical NC [33] has been proposed to ensure that the base layer of a layered bitstream is received with high probability. In addition, a network coding algorithm has been proposed to solve the problem for quality requirements of the receivers in multi-layered video streaming [75]. In summary, optimization can further be performed at all levels of the system, and the joint design of NC along with effective rate allocation in the peers can lead to optimized delivery in heterogeneous P2P environments.

2) *Scalability*: The second important open issue in P2P multimedia streaming is scalability, that is, the ability of the system to serve many users. It has recently been predicted that the number of online video viewers will grow to more than 940 millions by 2013. This clearly requires important scalability properties, which calls for a redesign of video codecs, P2P protocols, hardware provisioning, and P2P traffic management. In general, cooperation at all levels, from peers to ISPs to content providers, is necessary in order to build a scalable multimedia streaming system.

Based on existing deployments and research results, it is clear that P2P is a promising approach for improving the scalability of multimedia streaming systems. Furthermore, since P2P traffic constitutes 92% of the cross-ISP traffic, improving the multimedia streaming applications will not only save resources to ISPs, but it will also reduce the redundant traffic across ISPs. To this end, the work in [76] examines the inter-ISP traffic incurred by P2P streaming applications. It points out that fully localizing P2P streaming traffic significantly degrades the overall streaming quality due to the lack of diverse content among the peers. The solution to effective P2P streaming relies on identifying the maximum level of traffic localization and on the design of an ISP-friendly P2P streaming approach.

Interestingly enough, NC can help in localizing P2P traffic too. A locality-aware network coding (LANC) P2P streaming system has been proposed in [77]. It uses locality information in both the topology construction and the segment scheduling. LANC shows that the random property of randomized NC increases the chance of finding useful data in nearby peers, which in turn reduces the inter-ISP traffic. The simulation results show that LANC can effectively reduce the inter-ISP traffic by 50%.

Finally, unlike cable and satellite services, multimedia streaming services over the Internet is best-effort. The current Internet-based streaming are still not comparable to the services offered by cable and satellite networks, especially for HD TV and channel surfing experience. The potential of NC has still to be unveiled. For example, the authors in [78] have proposed a layered network coding solution for building collaboration incentives among peers and improving content availability in P2P live streaming systems. They utilize layered coding as a tool to generate incentives and combine it with a specific network coding scheme to achieve efficient scheduling and delay minimization. Such solutions might permit to get the best of the best-effort services, and to improve the quality of P2P streaming applications.

In summary, regardless of the internal design of the multimedia streaming service, NC clearly improves bandwidth

utilization and reduces the overhead in the communication protocol. These benefits consequently lead to smoother playback and higher video fidelity. The work on NC applications in P2P multimedia systems are recapped in Table II. Nonetheless, there remain many open problems, unaddressed issues, and unexplored potentials in incorporating NC into diverse systems for effective P2P multimedia streaming.

## V. WIRELESS MULTIMEDIA APPLICATIONS

Wireless environments lend themselves naturally to network coding, thanks to the inherent overhearing and superposition capabilities of the wireless medium. The former (overhearing) provides side information to each next-hop node, which can then be used for decoding coded packets. The latter (superposition) can be viewed as physical-layer network coding [79], [80], [81], where coding is not introduced by nodes but rather by the wireless medium itself [82], [83]. In this section, we focus on overhearing, which is better understood today and already used for multimedia applications.

We review wireless coded systems that have been proposed for different traffic scenarios, network topologies and coding schemes, as summarized in Table III. Although this taxonomy can be applied to both data and media traffic, we focus here on issues specific to media traffic. Given the large literature on wireless network coding, this review does not attempt to be exhaustive but tries only to highlight some representative schemes.

### A. Single Unicast

First, let us consider a single unicast flow with intra-session coding. Intra-session coding can be implemented at the end points and potentially also at selected nodes (*e.g.*, access points or mobile devices) within the network. Coding at the source requires neither changes in the network nor cooperations with other flows. Random network coding is the simplest form of network coding to implement at intermediate nodes.

In [30], the authors have considered a single TCP flow transmitted over a single path with one or more lossy links. The lossy links are typically wireless links but they can potentially be wired links as well. The authors have proposed a thin coding layer under TCP. At the source, this layer sends linear combinations of packets within a TCP-like window; the size of this window is adjusted based on feedback from the receiver. At the receiving end, this layer collects, decodes and delivers the packets to the TCP receiver; it also sends acknowledgements back to the source. The difference with TCP is that, instead of acknowledging individual packet sequence numbers, the receiver reports the dimensions of the subspace spanned by the vectors received so far, and the sender accordingly decides how many coded packets to retransmit. The goal of this network coding layer is to make the flow resilient to packet loss in a way that is transparent to TCP, thus avoiding retransmissions. The key contribution of [30] is the incorporation of network coding with minimal changes to the protocol stack.

Interestingly, these ideas are applicable not only to data but also to media flows. For example, the method in [30] is directly applicable to HTTP streaming, which represents the majority of video streaming traffic today. In [84], a strategy for network coding in wireless video transmission has been

presented, which uses a variety of coding approaches and adds feedback and device discovery to tailor the coding to the receivers.

The idea has also been applied to wireless video streaming over multiple paths. In [85], several connections to the same phone have been considered, *e.g.*, WiFi (which is considered free but unreliable) and LTE (which is considered expensive but reliable), and coding has been performed across these heterogeneous networks. The authors propose to use the more expensive network only when there is a risk of interruption in viewing video. This way, the scheme incurs the cost of the cheaper network, while at the same time achieving the performance of the best network. Approaches based on combining heterogeneous networks without NC suffer from the difficulty of having to coordinate across separate flows, which may require retransmission of specific packets across one or more networks. Coding approaches offer the flexibility of combining data across different networks.

We would like to note that applying coding only at the end-points is a very restricted version of network coding, essentially similar to classic channel coding. However, some of these ideas gracefully generalize to allowing coding at intermediate nodes. For example, consider a single flow going over a multi-hop network with lossy links (an example, for a tandem network of three nodes, has been discussed in detail in Section II and illustrated in Fig.3). Allowing random network coding at intermediate nodes is known to achieve the optimal rate with minimum delay [96], [97]. This is in contrast to alternatives, such as end-to-end FEC (which adjusts the redundancy to the end-to-end loss rate, and thus cannot achieve the optimal rate), ARQ schemes (which achieve the optimal rate but with increased delay), or even schemes where intermediate nodes can decode and re-encode (which also achieve the optimal rate at the cost of additional delay).

### B. Multiple Unicasts

Second, let us consider multiple unicast flows over multihop wireless networks, such as wireless mesh networks. One could still use per-flow intra-session network coding as described before, but higher benefit can be achieved using NC at all intermediate nodes and/or with inter-session coding.

Given that optimal inter-session network coding is an open problem, constructive approaches have been proposed [98], [20], [99], [9], [100]. One of the first and most influential practical wireless network coding systems is COPE [20] - a coding layer between the IP and MAC layers that performs one-hop, opportunistic network coding for multihop wireless networks. In COPE, each node combines packets from incoming unicast flows using simple (bitwise XOR) coding operations. Each node then broadcasts the coded packet and the next hop nodes are able to decode using overheard packets from previous transmissions. This way, COPE effectively forwards multiple packets in a single transmission to improve throughput. The scheme has been implemented in a WiFi testbed consisting of laptops with madWiFi drivers; it has been shown to significantly improve throughput in a range of scenarios, especially for UDP traffic [20].

COPE was designed to support any type of unicast flows. Next, we describe modifications and extensions of COPE proposed specifically for media flows. The core design question in this setting is the *coding scheme*: which packets to

TABLE II  
NC APPLICATIONS IN P2P MULTIMEDIA SYSTEMS

Classes of Proposal	Section	Key Benefits	References
NC for live streaming protocol	IV-B	Simplified protocol design, smoother playback, efficient bandwidth utilizes, shorter initial delay, and resilient to dynamics	[63], [64], [65], [66]
NC for VoD protocol	IV-C	Same as in live streaming, plus more responsive to seek operations	[69], [70], [71], [66]
Combining NC and SVC	IV-D1	Smoother playback, resilient to dynamics, and better support for heterogeneous systems	[73], [74]
Combining NC and layered coding	IV-D1	Better adaptability and diverse viewing experience	[37], [33], [75]
New uses	IV-D1 IV-D2	Maximized system throughput ISP traffic localization Incentive building and content availability boosting	[72] [76], [77] [78]

TABLE III  
REPRESENTATIVE WIRELESS NETWORK CODING SCENARIOS

Traffic Scenario	Section	Wireless Topology	Coding Scheme	Example Application	References
Single Unicast Session	V.A	Multihop	source [+other nodes], intra-session	TCP over wireless	[30], [84], [85]
Multiple Unicast Sessions	V.B	multihop	in the middle, inter-session (e.g. COPE)	Wireless mesh networks	[20], [86], [87], [88]
Single Multicast Session	V.C	one-hop downlink	at BS or AP, intra-session	Video Broadcast	[89], [90], [91], [92]
Multicast Session(s)	V.D	device-to-device links	all nodes, intra [and inter-] session	Cooperative Mobile Devices	[49], [93], [94], [95]

select and code together from all possible subsets of packets at an intermediate node's queue? In COPE, a node always transmits the head-of-line packet and then greedily considers each subsequent packet, so as to ensure that the largest number of receivers can decode. This policy increases the information per packet transmission and thus the throughput. However, when the transmitted flows are media streams, this FIFO greedy policy is not necessarily the best choice. In particular, when coding packets together, one should take into account not only the decodability by as many neighbors as possible, but also the contribution of the packets to video quality. In other words, when media streams are transmitted, it is not only the number but also the content of the packets that should be taken into account by the network coding scheme.

The unequal importance of media packets and the need for prioritization in transport mechanisms are well-understood in the media streaming community. Incorporating this idea into network coding schemes was first described for intra-session network coding [21] along the lines of priority encoding transmission [32], as described in Section III-B. This idea of prioritization among media packets was applied specifically in the context of COPE [86]. The algorithms build on top of COPE and combine several packets from different streams, thus increasing throughput. However, they also select which video packets to code by taking into account their importance in terms of video distortion and playout deadlines. Simulations for various topologies and traffic patterns have shown that the combined approach greatly improves video quality for the same throughput. Three algorithms (NCV, NCVD and NC-RaDiO) have been proposed in [86], which employ different coding subsets of packets of different size, in order of increasing complexity and performance. NCV ("Network Coding for Video") adopts the greedy selection of COPE but considers a metric that captures distortion as opposed to the number of packets. NCVD is similar but is not greedy: it considers all possible subsets of packets in the queue, which is a NP-hard problem. Finally, NC-RaDiO achieves the optimal performance within the rate-distortion optimized (RaDiO) packet

scheduling framework [101]. Realistic simulations have shown that NCVD is able to achieve near-optimal performance with reasonable computational complexity for the small queue sizes that are typical of real-time media traffic.

Independently, in [87], the RaDiO framework [101] has also been applied to the transmission of multicast and unicast traffic over a single broadcast wireless link when XOR network coding is allowed at the access point. The authors use a Markov Decision Process framework to optimize the policy at the access point, *i.e.*, to decide whether to send a new packet, retransmit a lost packet, or transmit an XOR-ed packet.

In [88], inter-session network coding across two unicast sessions over an unreliable wireless channel has been studied. Each unicast session transmits a stored video file, whose packets have hard sequential deadline constraints. The authors characterize the capacity region for the transmission rates of the two unicast sessions under heterogeneous channel conditions and heterogeneous deadline constraints. Then, they develop "immediately-decodable network coding" (IDNC) schemes for controlling packet transmissions for the unicast sessions. They show the asymptotic optimality of the proposed IDNC scheme within the deadline constraints, when the file sizes are sufficiently large. In general, establishing the optimality of inter-session network coding is non-trivial. An additional difficulty in the analysis of [88] stems from the heterogeneity of channel conditions and deadline constraints.

A scheme that combines *intra-session and inter-session network coding* for unicast flows over multi-hop wireless networks,  $I^2NC$ , has been proposed in [102].  $I^2NC$  builds on and extends COPE: it allows intermediate nodes to perform not only one-hop opportunistic inter-session network coding as in COPE but also to add per flow redundancy using intra-session network coding. The combined approach has two benefits compared to COPE. First,  $I^2NC$  is resilient to high loss rates, which are typical in wireless links. Second,  $I^2NC$  is sequence-agnostic in the sense that intermediate nodes can operate using information only about the loss rates on the downstream links, as opposed to detailed reports about which

packets have been received (as implemented in COPE). The scheme is also applicable to media flows and can be further optimized to take into account the loss resilience of media flows.

There is also a significant body of work on *cross-layer optimization* of rate-control, routing, scheduling and network coding, typically formulated within the network utility maximization framework. This general framework is applicable to multimedia flows as well if utilities and constraints are appropriately defined to capture multimedia-specific considerations such as distortion and delay. Next, we describe a few representative examples, which have focused specifically on video and on the interaction between video rate control and inter-session network coding.

The rate of multimedia flows typically varies over time, depending on the content and on the rate control. Bursty traffic patterns are well-known to not fully exploit the underlying coding opportunities because packets from different flows must be present at the same node and at the same time in order for them to be coded together. This was originally noticed in the context of TCP but arises also in inter-session coding of media streams with time-varying rates. Two approaches have been proposed to deal with this problem.

The first approach [103], [104] proposes to delay packets at intermediate nodes in order to create more network coding opportunities; it faces an inherent tradeoff between delay and throughput. Intermediate nodes have control over how long to wait before coding or forwarding packets from different flows. At one extreme if they forward packets immediately, they minimize delay but may also miss coding opportunities, thus reducing throughput. At the other extreme, they can delay packets from one flow until packets from another flow arrive and code them together. The relation between delay and throughput has been analyzed based on random arrivals [103], [104], [105], and assumptions on game [106] or adversarial [107] settings.

The second approach [108] proposes a cross-layer optimization of rate control at the higher layer and network coding at the underlying layer in order to maximize the total utility (e.g., the overall expected video quality in the wireless streaming session). The authors of [108] exploit the observation that utility varies over time depending on the video content. As a result, two or more video streams can have different rates over a short-time scale even though they may have similar rates over longer time scales. Additional delay is introduced in some video scenes and rate allocation is optimized over longer time intervals in order to increase the NC opportunities and eventually maximize the total utility.

### C. One-Hop Broadcast

Many media applications are based on broadcast transmission, which perfectly matches the broadcast nature of the wireless medium. There is a significant body of work on wireless video broadcast where a single node broadcasts to several receivers. (The broadcasting node can be thought of as the access point, base station, or video proxy, as depicted in Figure 8). Coding over a broadcast link makes each transmission useful to multiple receivers at the same time.

The work in [109], [110] considers real-time streaming of stored video using broadcast over the downlink of a single

cell. The capacity of the system, subject to hard deadline constraints, is derived for both uncoded and coded wireless broadcast schemes. In [110], it is shown that network coding is asymptotically throughput-optimal, subject to the deadline constraints, when there are no more than three users and the file size is sufficiently large. Furthermore, numerical results show that IDNC schemes strictly outperform non-coding schemes not only in the asymptotic regime of large files but also for small files. One advantage of the immediately decodable network coding (IDNC) schemes is that they do not suffer from the decoding delay that is inherent to generation-based network coding protocols.

In [89], [90], the goal is to achieve synchronized multimedia streaming to multiple iPhone devices. Broadcast transmissions and re-transmissions from the base station are used. In [92] and [91], broadcast has been used on the downlink and ad-hoc links have been used for error recovery. In [92], a group of smartphone users are connected to the Internet via LTE links and packets are broadcast from the base stations using the Multimedia Broadcast Multicast Services (MBMS). We note, however, that although MSMS is standardized within LTE, it is not currently implemented. In [111] it is proposed to integrate NC in the LTE/LTE-A radio access network protocol stack; the authors propose a MAC layer solution alternative to hybrid ARQ, which is particularly well suited to multimedia applications.

We further note that coding over a broadcast link with erasures is a well studied problem for which many coding schemes, such as Fountain codes, have been previously proposed. The similarities of such schemes with linear network coding can potentially be exploited and lead to combined or novel solutions for one-hop wireless broadcast. For example, a new code called BATS (“Batched Sparse”) has recently been proposed in [112]. BATS enables a matrix generalization of fountain-like codes to be combined efficiently with random linear NC. A prototype has been built with a notebook computer broadcasting network-coded packets to iPod/iPad mobile devices. In ongoing work, the authors investigate the performance of BATS in different systems, including P2P and wireless systems. Finally, we recall that, as discussed in Section III-C, coding for broadcast may increase the delay due to the block-coding or rateless coding operations; the delay may become unbounded, which is clearly undesirable for multimedia applications.

### D. Cooperative Mobile Devices

Smart mobile devices, such as smartphones, tablets, and portable media players, are widely used today. They are equipped with ever increasing computational, storage and networking capabilities. For example, smartphones today have several network connections (cellular, WiFi and most recently WiFiDirect and BlueTooth), which are used to connect to each other and to the Internet. Of interest here is media traffic to these devices, whether the content is generated/stored externally (on the cloud) or locally (on one of the devices).

One example application is streaming video from YouTube or Netflix to mobile devices. Although the demand for such streaming services is exponentially increasing [113], the downlink cellular connection typically faces problems such as low or time varying rate, loss, and occasional outages.




Fig. 8. Overview of cooperative video streaming to mobile devices. A group of smartphone users, within proximity of each other, are interested in viewing the same video at the same time. Each smartphone has Internet connection via cellular or WiFi connection. When a user is interested in viewing a video, it connects to the video source (e.g., YouTube or Netflix) via its base station, which may be the same or different for different users, depending on the provider their use. The proxy, in our system, is responsible for selecting the video rate and performing network coding. Each smartphone can receive packets from the source as well as from other smartphones in the neighborhood, through device-to-device (Bluetooth or WiFi) links. Network coding can be used on the downlink (by the source or proxy) and/or on the local links (by the phones).

When a group of smartphones are within proximity of each other, they can potentially cooperate to deal with these problems, by establishing device-to-device connections via WiFi or Bluetooth. Cooperation between mobile devices is also motivated by the increasingly social aspect of mobile-to-mobile communication; mobile social networks are emerging as a field on its own [114], [115], [116], [117], [118], [119] and media content is routinely exchanged over these networks.

Cooperative mobile devices combine two orthogonal characteristics, namely cooperation and wireless transmission. First, as discussed in Section IV, network coding offers benefits in cooperative content distribution: the intuition is that transmitting linear combinations, as opposed to original packets, makes distributed scheduling easier. Second, as discussed earlier in Section V, network coding works well with wireless broadcast: the intuition is that a coded packet broadcast over wireless is simultaneously useful to multiple receivers. Applications involving cooperative mobile devices combine these two features, cooperation and wireless transmission, and thus provide an ideal setting for harvesting the benefits of network coding.

Fortunately, network coding is feasible in today's mobile phones, thanks to the increased computational and storage capabilities. For example, the practicality of random network coding on iPhones has been discussed in [120]; the Tenor toolkit for network coding has been proposed for devices from servers to smartphones [47]; PictureViewer has demonstrated the feasibility of network coding on Nokia N95–8GB mobile phones [94]; NCUtils [46] is a C and Java library to implement network coding in various applications, and has recently been used as part of the Microcast [49] and MicroPlay [93] frameworks on Android Nexus phones.

Due to both the need and opportunities for network coding

on cooperative mobile devices, there have been a number of recent research efforts that build such wireless systems primarily for media applications. Next, we highlight some of these efforts, grouped according to their objective.

1) *Network coding for error recovery*: Downloading content, e.g., through cellular or WiFi, typically suffers from packet loss, due to noise and interference, on the downlink. One possible solution is to have several devices, in close proximity of each other, cooperating for error recovery: they establish device-to-device connections and retransmit lost packets (or linear combinations of lost and original packets). A rate-distortion optimized strategy for cooperative video system repair using network coding in wireless peer-to-peer networks has been studied in [121]. Wireless video broadcasting with peer-to-peer error recovery has been proposed in [122] and an efficient scheduling approach to network coding for wireless local repair has been introduced in [123]. The authors in [124] further propose a cooperative IPTV system with pseudo-broadcast to improve reliability. In [91], [92], base stations broadcast packets and smartphones establish device-to-device connections to help each other with error recovery.

2) *Network coding for delay*: Network coding can also help to reduce delay in wireless settings. In [95], the scenario of multiple users interacting through their smartphones using multi-touch gestures has been considered. A gesture broadcast protocol, called *GestureFlow*, is designed for concurrent gesture streams in multiple broadcast sessions using inter-session network coding. The goal of *GestureFlow* is to minimize the delay in recognizing a gesture in each session, which is critical for interactive applications. An example application, called *Music Score*, has been developed to allow multiple users, communicating over a wide-area-network (WAN), to compose music together. It has been used for demonstration and evaluation of *GestureFlow* on iPads and iPods. However, the gesture streaming protocol itself is not specific to *MusicScore* and can work well with any application that requires intensive user interaction with multi-touch gestures. The scenario differs from traditional multimedia streaming in that gestures are very low rate, the communication scenario is all-to-all, and the gestures must be recovered with 100% reliability and with very low delay and delay jitter. The design of *GestureFlow* is based on the following key features: adapting the coding window, employing inter-session coding and using multiple paths.

In an ongoing work [93], the authors consider local multiplayer games on android phones. Similarly to *GestureFlow*, the communication scenario is all-to-all and the metric to minimize is the delay in rendering all players' moves. Different from *GestureFlow*, however, all players are within proximity of each other. Current multiplayer games do not typically exploit the locality of the players. The authors in [93] develop a cooperative system using network coding, called *MicroPlay* that exploits WiFi broadcast and network coding to reduce game latency and eliminate the need for input prediction by exploiting overheard packets.

3) *Network coding for throughput*: The authors in [49], [125] consider a group of smartphone users, within proximity of each other, who are interested in simultaneously viewing a video. The video can be stored either at a remote server or locally on one of the phones; an overview of this scenario is shown on Figure 8. A system, called *MicroCast*, has been

designed using cooperation and network coding to maximize the common throughput to all users. Key ingredients of the MicroCast design include the following. First, a scheduling algorithm, MicroDownload, decides what parts of the video each phone should download from the server, based on the download rates and the congestion in the local network. Second, a novel all-to-all local dissemination scheme, MicroNC-P2, is used for sharing content among group members. MicroNC-P2 is specifically designed to exploit WiFi overhearing and network coding, based on a local high-rate WiFi broadcast mechanism, MicroBroadcast; it has been developed specifically for Android phones. MicroCast allows users to view the video simultaneously, while each user is able to stream video at a higher, and less varying, rate than if it would use only its single cellular connection or even state-of-the-art peer-to-peer schemes. Although the current application used to demonstrate MicroCast is cooperative video streaming on mobile devices [49], the framework itself can be used for any application that requires high common throughput to a group of cooperative devices within proximity of each other.

## VI. CONCLUSIONS

We have reviewed in this paper the potentials and benefits of the network coding paradigm in multimedia applications. NC offers great advantages due to its ability to increase throughput as well as error resiliency, and to simplify the design of distributed architectures. These benefits perfectly match the growing demand for multimedia communications services over networks with sources, paths and clients diversity. We have discussed the adaptation of the NC principles to practical multimedia systems. An in-depth review of the recent NC research in peer-to-peer and wireless streaming systems has also been presented. NC offers important performance benefits in such popular settings where it increases the quality of service by effective exploitation of the network resources. In general, NC principles rely on the idea that in-network processing with actions close to bottlenecks or points of failures is key to the optimization of multimedia communication systems.

A few aspects have been omitted in our review of multimedia systems based on NC. In particular, this paper has not discussed the security issues posed by NC. NC security is an important topic on its own right and would deserve its own review paper. On the one hand, NC is more vulnerable than routing to byzantine modification attacks. Solutions to this vulnerability have been proposed with either error correction (following a typical communications and information theory approach) or novel cryptographic primitives (mainly from the cryptographic community). For example, a more detailed discussion can be found in [5]. On the other hand, NC is more robust to eavesdropping attacks than a non-coded communication system. Quite a few research efforts have addressed these problems lately, although the proposed methods are not specific to multimedia systems. In general, NC security methods are independent of the type of content shared through the NC system, *i.e.*, whether it is data or video, and thus outside the scope of this paper. The most relevant aspect to this review paper is the fact that, in video applications, pollution detection can be performed by the receivers at the video application layer [126]. In addition, we have not considered the problem of distributed data storage where NC brings important

benefits too. However, most of the research in this area is not focused on multimedia applications.

In summary, the most important research questions in the design of NC systems consider the effective control of delays and computational complexity in large scale distributed systems with multiple concurrent sessions. NC shares some similarity with channel coding and, in particular, rateless codes (which also use randomized coding strategies that are prone to distribution); it further complements distributed coding theory (which deals with distributed systems using a source coding approach). The development of both a unified theory and a solid practical framework in this area will certainly be of great benefit to the next generation of multimedia applications.

## REFERENCES

- [1] R. Ahlswede, C. Ning, S. Li, and R. Yeung, "Network Information Flow," *IEEE Transactions on Information Theory*, vol. 46, no. 4, pp. 1204–1216, Jul. 2000.
- [2] E. Magli and P. Frossard, "An Overview of Network Coding for Multimedia Streaming," in *Proc. of IEEE International Conference on Multimedia and Expo*, 2009.
- [3] A. Markopoulou and H. Seferoglu, "Network coding meets multimedia: Opportunities and challenges," in *IEEE MMTC E-Letter*, Feb. 2009.
- [4] T. Mehta and Z. Narmawala, "Survey on multimedia transmission using network coding over wireless networks," in *Proc. of NUiCONE*, 2011.
- [5] A. Le, "Defense Against Pollution Attacks in Network Coding," Ph.D. dissertation, University of California, Irvine, June 2012.
- [6] S. Y. R. Li, R. W. Yeung, and C. Ning, "Linear Network Coding," *IEEE Transactions on Information Theory*, vol. 49, no. 2, pp. 371–381, February 2003.
- [7] R. Koetter and M. Médard, "An Algebraic Approach to Network Coding," *IEEE/ACM Transactions on Networking*, vol. 11, no. 5, pp. 782–795, Oct. 2003.
- [8] T. Ho and D. S. Lun, *Network Coding: An introduction*. Cambridge Univ Press, 2008.
- [9] D. Traskov, N. Ratnakar, D. S. Lun, R. Koetter, and M. Medard, "Network Coding for Multiple Unicasts: An Approach based on Linear Optimization," in *Proc. of IEEE International Symposium on Information Theory*, Seattle, WA, July 2006, pp. 1758–1762, inter-session network coding.
- [10] D. S. Lun, "Efficient Operation of Wireless Packet Networks," Ph.D. dissertation, MIT, Cambridge, MA, June 2006.
- [11] A. Shokrollahi, "Raptor Codes," *IEEE Transactions on Information Theory*, vol. 52, no. 6, pp. 2551–2567, June 2006.
- [12] M. Luby, "LT Codes," in *Proc. of the 43rd Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, 2002, pp. 271–282.
- [13] R. W. Yeung, *Information Theory and Network Coding*, ser. Information Technology: Transmission, Processing and Storage. Springer-Verlag, 2008.
- [14] R. W. Yeung, "Network Coding Theory: An introduction," *Frontiers of Electrical and Electronic Engineering in China*, vol. 5, no. 3, pp. 363–390, 2010.
- [15] C. Fragouli, "Network Coding: Beyond Throughput Benefits," in *Proceedings of the IEEE*, 2011, pp. 461–475.
- [16] C. Fragouli, J.-Y. L. Boudec, and J. Widmer, "Network Coding," *Computer Communication Review*, vol. 36, no. 1, pp. 63–68, Jan. 2006.
- [17] S. Li, Q. Sun, and Z. Shao, "Linear Network Coding: Theory and Algorithms," *Proceedings of the IEEE*, vol. 99, no. 3, pp. 372–387, 2011.
- [18] S. Jaggi, P. Sanders, P. A. Chou, M. Effros, S. Egner, K. Jain, and L. M. G. M. Tolhuizen, "Polynomial Time Algorithms for Multicast Network Code Construction," *IEEE Transactions on Information Theory*, vol. 51, no. 6, pp. 1973–1982, June 2005.
- [19] T. Ho, M. Médard, R. Koetter, D. R. Karger, M. Effros, S. Jun, and B. Leong, "A Random Linear Network Coding Approach to Multicast," *IEEE Transactions on Information Theory*, vol. 52, no. 10, pp. 4413–4430, Oct. 2006.
- [20] S. Katti, H. Rahul, W. Hu, D. Katabi, M. Medard, and J. Crowcroft, "XORs in the Air: Practical Network Coding," in *Proc. of ACM SIGCOMM*, Pisa, Italy, September 2006.
- [21] P. A. Chou, Y. Wu, and K. Jain, "Practical Network Coding," in *Proc. of the 41st Allerton Conference*, 2003.
- [22] R. Yeung and N. Cai, "Network Error Correction, Part I: Basic Concepts and Upper Bounds," *Communications in Information and Systems*, vol. 6, no. 1, pp. 19–36, 2006.

- [23] N. Cai and R. W. Yeung, "Network Error Correction, Part II: Lower Bounds," *Communications in Information and Systems*, vol. 6, no. 1, pp. 37–54, 2006.
- [24] F. Silva, F. R. Kschischang, and R. Koetter, "A Rank-Metric Approach to Error Control in Random Network Coding," *IEEE Transactions on Information Theory*, vol. 54, no. 9, pp. 3951–3967, Sep. 2008.
- [25] E. M. Gabidulin, "Theory of Codes with Maximum Rank Distance," *Probl. Peredachi Inf.*, vol. 21, no. 1, pp. 3–16, 1985.
- [26] R. M. Roth, "Maximum-Rank Array Codes and their Application to Crisscross Error Correction," *IEEE Transactions on Information Theory*, vol. 37, no. 2, pp. 328–336, Mar. 1991.
- [27] M. Wu, S. Karande, and H. Radha, "Network Embedded FEC for Optimum Throughput of Multicast Packet Video," *EURASIP Journal on Advances in Signal Processing*, vol. 20, no. 8, pp. 728–742, September 2005.
- [28] N. Thomos and P. Frossard, "Raptor Network Video Coding," in *Proc. of the 1st ACM International Workshop on Mobile video (in conjunction with ACM Multimedia 2007)*, Augsburg, Germany, Sep. 2007.
- [29] N. Thomos and P. Frossard, "Network Coding of Rateless Video in Streaming Overlays," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 20, no. 12, pp. 1834–1847, December 2010.
- [30] J. K. Sundararajan, D. Shahand, M. Médard, S. Jakubczak, M. Mitzenmacher, and J. Barros, "Network Coding Meets TCP: Theory and Implementation," *Proceedings of the IEEE*, vol. 99, no. 3, pp. 490–512, Mar. 2011.
- [31] H. Schwarz, D. Marpe, and T. Wiegand, "Overview of the scalable video coding extension of the H.264/AVC standard," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 17, no. 9, pp. 1103–1120, Sep. 2007.
- [32] A. Albanese, J. Blömer, J. Edmonds, M. Luby, and M. Sudan, "Priority Encoding Transmission," *IEEE Transactions on Information Theory*, vol. 42, pp. 1737–1744, Nov. 1996.
- [33] K. Nguyen, T. Nguyen, and S. Cheung, "Peer-To-Peer Streaming with Hierarchical Network Coding," in *Proc. of IEEE International Conference on Multimedia and Expo (ICME)*, 2007.
- [34] D. Vukobratović and V. Stanković, "Unequal Error Protection Random Linear Coding for Multimedia Communications," in *Proc. of IEEE International Workshop on Multimedia Signal Processing (MMSp)*, 2010.
- [35] M. Hallouh and H. Radha, "Network Coding with Multi-Generation Mixing: A Generalized Framework for Practical Network Coding," *IEEE Transactions on Wireless Communications*, vol. 10, no. 2, pp. 466–473, Feb. 2011.
- [36] J. M. Walsh and S. Weber, "A Concatenated Network Coding Scheme for Multimedia Transmission," in *Proc. of the 4th Workshop on Network Coding, Theory, and Applications (NetCod)*, 2008.
- [37] N. Thomos, J. Chakareski, and P. Frossard, "Prioritized Video Streaming Through Randomized Network Coding," *IEEE Transactions on Multimedia*, vol. 13, no. 4, pp. 776–787, Aug. 2011.
- [38] R. Puri and K. Ramchandran, "Multiple Description Source Coding through Forward Error Correction Codes," in *Proc. of 33rd Asilomar Conference on Signals, Systems, and Computers*, 1999.
- [39] A. K. Ramasubramoniana and J. W. Woods, "Video Multicast using Network Coding," in *Proc. of Visual Communications and Image Processing (VCIP)*, 2009.
- [40] H. Wang and C.-C. J. Kuo, "Robust Video Multicast in Erasure Networks with Joint Network Coding and Video Interleaving," *Journal of Visual Communication and Image Representation*, vol. 21, no. 2, pp. 77–88, Feb. 2010.
- [41] R.G. Gallager, "Low-Density Parity-Check codes," Ph.D. dissertation, MIT Press, 1963.
- [42] A. Fiandrotti, S. Zezza, and E. Magli, "Complexity-Adaptive Random Network Coding for Peer-to-Peer Video Streaming," in *Proc. of IEEE International Workshop on Multimedia Signal Processing*, 2011.
- [43] A. Fiandrotti, V. Bioglio, M. Grangetto, R. Gaeta, and E. Magli, "Band Codes: Controlled Complexity Network Coding for Peer-to-Peer Video Streaming," in *Proc. of IEEE International Conference on Multimedia and Expo*, 2012.
- [44] N. Thomos and P. Frossard, "Degree Distribution Optimization in Raptor Network Coding," in *Proc. of International Symposium on Information Theory (ISIT)*, 2011.
- [45] N. Cleju, N. Thomos, and P. Frossard, "Selection of Network Coding Nodes for Minimal Playback Delay in Streaming Overlays," *IEEE Transactions on Multimedia*, vol. 13, no. 5, pp. 1103–1115, Oct. 2011.
- [46] "NCutils: Network Coding Utilities," <http://arni.epfl.ch/software>, [Available Online].
- [47] H. Shojania and B. Li, "Tenor: Making Coding Practical from Servers to Smartphones," in *Proc. of ACM Multimedia*, Firenze, Italy, October 2010.
- [48] M. V. Pedersen, J. Heide, and F. H. P. Fitzek, "Kodo: An Open and Research Oriented Network Coding Library," in *Proc. of Network Coding Applications and Protocols Workshop (NC-Pro)*, IFIP Networking, Valencia, Spain, May 9–13 2011.
- [49] L. Keller, A. Le, B. Cici, H. Seferoglu, C. Fragouli, and A. Markopoulou, "Microcast: Cooperative Video Streaming on Smartphones," in *Proc. of ACM MobiSys*, Low Wood Bay, Lake District, United Kingdom, June 2012.
- [50] <http://www.pplive.com/en/index.html>, PPLive. [Online]. Available: <http://www.pplive.com/en/index.html>
- [51] X. Zhang, J. Liu, B. Li, and T.-S. P. Yum, "CoolStreaming/DONet: A Data-Driven Overlay Network for Peer-to-Peer Live Media Streaming," in *Proc. of the 24th Conference of the IEEE Communications Society (INFOCOM 2005)*, March 2005.
- [52] C. Feng and B. Li, "On Large-Scale Peer-to-Peer Streaming Systems with Network Coding," in *Proc. of ACM Multimedia*, October 2008.
- [53] M. Castro, P. Druschel, A.-M. Kermarrec, A. Nandi, A. Rowstron, and A. Singh, "SplitStream: High-Bandwidth Multicast in Cooperative Environments," in *Proc. of the 19th ACM Symposium on Operating Systems Principles (SOSP 2003)*, October 2003.
- [54] J. Li, P. Chou, and C. Zhang, "Mutualcast: An Efficient Mechanism for One-to-Many Content Distribution," in *Proc. of the 1st ACM SIGCOMM Asia Workshop (SIGCOMM ASIA 2005)*, April 2005.
- [55] V. Padmanabhan, H. Wang, P. Chou, and K. Sripanidkulchai, "Distributing Streaming Media Content Using Cooperative Networking," in *Proc. of the 12th International Workshop on Network and Operating Systems Support for Digital Audio and Video (NOSSDAV 2002)*, May 2002.
- [56] V. N. Padmanabhan, H. J. Wang, and P. A. Chou, "Resilient Peer-to-Peer Streaming," in *Proc. of the 11th IEEE International Conference on Network Protocols (ICNP)*, November 2003.
- [57] D. Kostic, A. Rodriguez, J. Albrecht, and A. Vahdat, "Bullet: High Bandwidth Data Dissemination Using an Overlay Mesh," in *Proc. of the 19th ACM Symposium on Operating Systems Principles (SOSP 2003)*, October 2003.
- [58] M. Zhang, Y. Xiong, Q. Zhang, and S. Yang, "A Peer-to-Peer Network for Live Media Streaming: Using a Push-Pull Approach," in *Proc. of ACM Multimedia*, November 2005.
- [59] V. Venkataraman, K. Yoshida, and P. Francis, "Chunkspread: Heterogeneous Unstructured Tree-based Peer to Peer Multicast," in *Proc. of the 14th IEEE International Conference on Network Protocols (ICNP 2006)*, November 2006.
- [60] V. Venkataraman, P. Francis, and J. Calandrino, "Chunkspread: Multitree Unstructured Peer-to-Peer Multicast," in *Proc. of the 5th International Workshop on Peer-to-Peer Systems (IPTPS 2006)*, November 2006.
- [61] T. Moscibroda and R. Rejaie, "PRIME: Peer-to-Peer Receiver-driven Mesh-Based Streaming," in *Proc. of the 26th Conference of the IEEE Communications Society (INFOCOM 2007)*, May 2007.
- [62] C. Gkantsidis and P. Rodriguez, "Network Coding for Large Scale Content Distribution," in *Proc. of the 24th Conference of the IEEE Communications Society (INFOCOM 2005)*, March 2005.
- [63] M. Wang and B. Li, "Lava: A Reality Check of Network Coding in Peer-to-Peer Live Streaming," in *Proc. of the 26th Conference of the IEEE Communications Society (INFOCOM 2007)*, May 2007.
- [64] M. Wang and B. Li, "Network Coding in Live Peer-to-Peer Streaming," *IEEE Transactions on Multimedia, Special Issue on Content Storage and Delivery in Peer-to-Peer Network*, vol. 9, no. 8, pp. 1554–1567, December 2007.
- [65] M. Wang and B. Li, " $R^2$ : Random Push with Random Network Coding in Live Peer-to-Peer Streaming," *IEEE Journal on Selected Areas in Communications, Special Issue on Advances in Peer-to-Peer Streaming Systems*, vol. 25, no. 9, pp. 1655–1666, December 2007.
- [66] Z. Liu, C. Wu, B. Li, and S. Zhao, "UUSEE: Large-Scale Operational On-Demand Streaming with Random Network Coding," in *Proc. of IEEE INFOCOM*, March 2010.
- [67] X. Yang, M. Gjoka, P. Chhabra, A. Markopoulou, and P. Rodriguez, "Kangaroo: Video Seeking in P2P Systems," in *Proc. of the 8th International Workshop on Peer-to-Peer Systems (IPTPS 2009)*, April 21 2009.
- [68] <http://www.bbc.co.uk/iplayer/radio>, iplayer. [Online]. Available: <http://www.bbc.co.uk/iplayer/radio>
- [69] S. Annapureddy, C. Gkantsidis, and P. Rodriguez, "Providing Video-on-Demand using Peer-to-Peer Networks," in *Proc. of Internet Protocol Television (IPTV) workshop in conjunction with WWW '06*, May 2006.
- [70] S. Annapureddy, S. Guha, C. Gkantsidis, D. Gunawardena, and P. Rodriguez, "Is High-Quality VoD Feasible Using P2P Swarming?" in *Proc. of the 16th International World Wide Web Conference (WWW)*, 2007.

- [71] L. Yu, L. Gao, J. Zhao, and X. Wang, "SonicVoD: A VCR-Supported P2P-VoD System with Network Coding," *IEEE Transactions on Consumer Electronics*, vol. 55, no. 2, pp. 576–582, May 2009.
- [72] N. Sundaram, P. Ramanathan, and S. Banerjee, "Multirate Media Streaming using Network Coding," in *Proc. of 43rd Annual Allerton Conference on Communication, Control, and Computing*, 2003.
- [73] A. T. Nguyen, B. Li, and F. Eliassen, "Chameleon: Adaptive Peer-to-Peer Streaming with Network Coding," in *Proc. of IEEE INFOCOM*, March 2010.
- [74] S. Mirshokraie and M. Hefeeda, "Live Peer-to-Peer Streaming with Scalable Video Coding and Networking Coding," in *Proc. of the 1st ACM Multimedia Systems (MMSys)*, Scottsdale, Arizona, February 22–23 2010.
- [75] Z. Király and E. R. Kovács, "A Network Coding Algorithm for Multi-Layered Video Streaming," in *Proc. of the International Symposium on Network Coding (NETCOD 2011)*, Beijing, China, July 25–27 2011.
- [76] N. Magharei and R. Rejaie, "ISP-Friendly P2P Streaming," in *Proc. of IEEE Multimedia Communications Technical Committee E-Letter*, October 2009.
- [77] G. Zhang, G. Zhang, and S. Cheng, "LANC: Locality-Aware Network Coding for Better P2P Traffic Localization," *Elsevier Journal of Computer Networks*, vol. 55, no. 6, pp. 1242–1256, December 2010.
- [78] S. Gheorghiu, L. Lima, A. L. Toledo, and J. Barros, "A Layered Network Coding Solution for Incentives in Peer-to-Peer Live Streaming," in *Proc. of the International Symposium on Network Coding (NETCOD 2011)*, Beijing, China, July 25–27 2011.
- [79] S. Zhang, S.-C. Liew, and P. P. Lam, "Hot Topic: Physical Layer Network Coding," in *Proc. of ACM International Conference on Mobile Computing and Networking*, Los Angeles, CA, Sept. 2006, pp. 358–365.
- [80] Popovski and H. Yomo, "The Anti-Packets Can Increase the Achievable Throughput of a Wireless Multi-Hop Network," in *Proc. of IEEE International Conference on Communications (ICC)*, Istanbul, Turkey, June 2006, pp. 3885–3890.
- [81] B. Nazer and M. Gastpar, "Computing Over Multiple-Access Channels with Connections to Wireless Network Coding," in *Proc. of IEEE International Symposium on Information Theory*, Seattle, USA, July 2006, pp. 1354–1358.
- [82] S. Avestimehr, S. Diggavi, and D. Tse, "Wireless Network Information Flow: A Deterministic Approach," *IEEE Transactions on Information Theory*, vol. 57, no. 4, pp. 1872–1905, April 2011.
- [83] J. Ebrahimi and C. Fragouli, "Combinatorial Algorithms for Wireless Information Flow," *ACM Transactions in Algorithms*, 2011.
- [84] M.-J. Montpetit and M. Medard, "Video-Centric Network Coding Strategies for 4G Wireless Networks: An Overview," in *Proc. of IEEE Consumer Communications and Networking Conference*, 2010.
- [85] A. ParandehGheibi, M. Medard, A. Ozdaglar, S. Shakkottai, A. Kulkarni, D. Traskov, and M. Heindlmaier, "On Coding Across Networks," in *Proc. of Annual International Titanium Association (ITA) Conference*, UCSD, 2011.
- [86] H. Seferoglu and A. Markopoulou, "Video-Aware Opportunistic Network Coding over Wireless Networks," *Journal of Selected Areas in Telecommunications (JSAT)*, vol. 27, no. 5, pp. 713–728, June 2009.
- [87] D. Nguyen, T. Nguyen, and X. Yang, "Multimedia Wireless Transmission with Network Coding," in *Proc. of Packet Video*, Lausanne, Switzerland, November 2007.
- [88] X. Li, C.-C. Wang, and X. Lin, "Optimal Immediately-Decodable Inter-Session Network Coding (IDNC) Schemes for Two Unicast Sessions with Hard Deadline Constraints," in *Proc. of the Allerton Conference*, Allerton Park, Monticello, IL, Sept. 2011.
- [89] P. Vingelmann, M. Pedersen, F. Fitzek, and J. Heide, "Multimedia Distribution using Network Coding on the iPhone Platform," in *Proc. of ACM Multimedia 2010 Workshop - Mobile Cloud Media Computing*, Florence, Italy, 2010.
- [90] P. Vingelmann, F. Fitzek, M. Pedersen, J. Heide, and H. Charaf, "Synchronized Multimedia Streaming on the iPhone Platform with Network Coding," in *Proc. of IEEE Consumer Communications and Networking Conference - Multimedia & Entertainment Networking and Services Track (CCNC)*, Las Vegas, NV, USA, 2011.
- [91] S. Hua, Y. Guo, Y. Liu, H. Liu, and S. Panwar, "Scalable Video Multicast in Hybrid 3G/Ad-Hoc Networks," *IEEE Transactions on Multimedia*, vol. 13, no. 2, pp. 402–413, April 2011.
- [92] P. Vingelmann, M. V. Pedersen, F. H. P. Fitzek, and J. Heide, "On-the-Fly Packet Error Recovery in a Cooperative Cluster of Mobile Devices," in *Proc. of Globecom*, Houston, TX, Dec. 2011.
- [93] A. Le, L. Keller, C. Fragouli, and A. Markopoulou, "MicroPlay: A Networking Framework for Local Multiplayer Games," in *SIGCOMM MOBIGAMES Workshop*, under submission, 2012.
- [94] M. W. Pedersen, J. Heide, and F. Fitzek, "PictureViewer - A Mobile Application using Network Coding," in *Proc. of the 15th European Wireless Conference (EW)*, Aalborg, DK, 2009.
- [95] Y. Feng, Z. Liu, and B. Li, "GestureFlow: Streaming Gestures to an Audience," in *Proc. of IEEE INFOCOM*, Shanghai, China, April 2011.
- [96] D. Lun, M. Medard, and M. Effros, "On Coding For Reliable Communication Over Packet Networks," in *Proc. of the 42nd Annual Allerton Conference on Communication, Control, and Computing*, Monticello, Illinois, Sept. 29 - Oct. 1 2004.
- [97] P. Pakzad, C. Fragouli, and A. Shokrollahi, "On Low Complexity Coding for Line Networks," in *Proc. of IEEE International Symposium on Information Theory (ISIT)*, Adelaide, Australia, Sept. 4 - 9 2005.
- [98] Y. Wu, P. A. Chou, and S. Y. Kung, "Information Exchange in Wireless Network Coding and Physical Layer Broadcast," in *Proc. of IEEE Conference on Information Sciences and Systems (CISS)*, Baltimore, MD, March 2005.
- [99] M. Effros, T. Ho, and S. Kim, "A Tiling Approach to Network Code Design for Wireless Networks," in *Proc. of IEEE Information Theory Workshop (ITW)*, Punta del Este, Uruguay, March 2006.
- [100] S. Omiwade, R. Zheng, , and C. Hua, "ButterFlies in the Mesh: Lightweight Localized Wireless Network Coding," in *Proc. of NetCod*, Hong Kong, January 2008.
- [101] P. P. A. Chou and Z. Miao, "Rate-Distortion Optimized Streaming of Packetized Media," *IEEE Transactions on Multimedia*, vol. 8, no. 2, pp. 390–404, April 2006.
- [102] H. Seferoglu, A. Markopoulou, and K. K. Ramakrishnan, "I2NC: Intra- and Inter-Session Network Coding for Unicast Flows in Wireless Networks," in *Proc. of IEEE INFOCOM*, Shanghai, China, April 2011.
- [103] T. Huang, M. Ghaderi, D. Towsley, and W. Gong, "TCP Performance in Coded Wireless Mesh Networks," in *Proc. of 5th Annual IEEE Communications Society Conference on Sensor, Mesh and Ad Hoc Communications and Networks (SECON)*, San Francisco, CA, June 16 - 20 2008.
- [104] H. Seferoglu, A. Markopoulou, and U. C. Kozat, "Network Coding-Aware Rate Control and Scheduling in Wireless Networks," in *Proc. of International Conference on Multimedia and Expo (ICME)*, New York, NY, June 2009.
- [105] Y.-P. Hsu, N. Abedini, S. Ramasamy, N. Gautam, A. Sprintson, and S. Shakkottai, "Opportunities for Network Coding: To Wait or Not to Wait," in *Proc. of the IEEE International Symposium on Information Theory (ISIT)*, St. Petersburg, Russia, July 31 - Aug 5 2011.
- [106] V. Reddy, S. Shakkottai, A. Sprintson, and N. Gautam, "Multipath Wireless Network Coding: A Population Game Perspective," in *Proc. of IEEE INFOCOM*, San Diego, CA, March 15–19 2010.
- [107] Y.-P. Hsu and A. Sprintson, "Opportunistic Network Coding: Competitive Analysis," in *Proc. of NetCod*, Boston, MA, June 29–30 2012.
- [108] H. Seferoglu and A. Markopoulou, "Distributed Rate Control for Video Streaming over Wireless Networks with Inter-session Network Coding," in *Proc. of Packet Video*, Seattle, WA, May 2009.
- [109] X. Li, C.-C. Wang, and X. Lin, "Throughput and Delay Analysis on Uncoded and Coded Wireless Broadcast with Hard Deadline Constraints," in *Proc. of INFOCOM*, 2010.
- [110] X. Li, C. Wang, and X. Lin, "On The Capacity of Immediately-Decodable Coding Schemes for Wireless Stored-video Broadcast with Hard Deadline Constraints," *IEEE Journals on Selected Areas of Communication*, vol. 29, no. 5, pp. 1094–1105, May 2011.
- [111] D. Vukobratović, C. Khirallah, V. Stanković, and J. Thompson, "Random Network Coding for Multimedia Delivery over LTE-Advanced," in *Proc. of IEEE International Conference on Multimedia and Expo*, 2012.
- [112] S. Yang and R. W. Yeung, "Coding for a Network Coded Fountain," in *Proc. of IEEE International Symposium on Information Theory*, Aug. 2011, pp. 2647 – 2651.
- [113] "Cisco Visual Networking Index: Global Mobile Data Traffic Forecast Update," 2010–2015.
- [114] S. Scellato, C. Mascolo, M. Musolesi, and V. Latora, "Distance Matters: Geo-Social Metrics for Online Social Networks," in *Proc. of Workshop on Online Social Networks (WOSN)*, 2010.
- [115] P. Hui, J. Crowcroft, and E. Yoneki, "Bubble Rap: Social-Based Forwarding in Delay Tolerant Networks," *IEEE Transactions on Mobile Computing*, vol. 10, no. 11, pp. 1576–1589, November 2011.
- [116] C. Boldrini, M. Conti, and A. Passarella, "ContentPlace: social-aware data dissemination in opportunistic networks," in *Proc. of ACM International Conference on Modeling, Analysis and Simulation of Wireless and Mobile Systems (MSWiM)*, 2008.
- [117] E. Yoneki, P. Hui, S. Chan, and J. Crowcroft, "A Socio-Aware Overlay for Publish/Subscribe Communication in Delay Tolerant Networks," in *Proc. of ACM International Conference on Modeling, Analysis and Simulation of Wireless and Mobile Systems (MSWiM)*, 2007.
- [118] E. Jaho and I. Stavrakakis, "Joint interest- and locality-aware content dissemination in social networks," in *Proc. of IEEE/IFIP Conference on Wireless On-demand Network Systems and Services*, Feb. 2009.

- [119] A. J. Mashhadi, S. B. Mokhtar, and L. Capra, "Habit: Leveraging Human Mobility and Social Network for Efficient Content Dissemination in Delay Tolerant Networks," in *Proc. of IEEE International Symposium on a World of Wireless Mobile and Multimedia Networks (WoWMoM)*, Jun. 2009.
- [120] H. Shojania and B. Li, "Random Network Coding on the iPhone: Fact or Fiction?" in *Proc. of ACM Network and Operating System Support for Digital Audio and Video (NOSSDAV)*, Williamsburg, VI, June 2009.
- [121] X. Liu, G. Cheung, and C. N. Chuah, "Rate-Distortion Optimized Network Coding for Cooperative Video System Repair in Wireless Peer-to-Peer Networks," in *Proc. of IEEE Workshop on Mobile Video (MoViD)*, June 2008.
- [122] S. Li and S. H. G. Chan, "Bopper: Wireless Video Broadcasting with Peer-to-Peer Error Recovery," in *Proc. of IEEE International Conference on Multimedia and Expo (ICME)*, Aug. 2007.
- [123] J. B. Saleh, D. Qiu, and A. K. Elhakeem, "Performance of an Efficient Scheduling Approach to Network Coding for Wireless Local Repair," *Journal of Selected Areas in Telecommunications (JSAT)*, January 2011.
- [124] Y. Park, C. Jo, S. Yun, and H. Kim, "Multi-Room IPTV Delivery Through Pseudo-Broadcast over IEEE 802.11 Links," in *Proc. of IEEE Vehicular Technology Conference*, Taipei, Taiwan, May 2010.
- [125] H. Seferoglu, L. Keller, B. Cici, A. Le, and A. Markopoulou, "Cooperative Video Streaming on Smartphones," in *Proc. of Allerton Conference*, Allerton Park, Montivello, IL, Sept. 2011.
- [126] Q. Wang, L. Vu, K. Nahrstedt, and H. Khurana, "Identifying Malicious Nodes in Network-Coding-Based Peer-to-Peer Streaming Networks," in *Proc. of IEEE INFOCOM Mini-Conference*, 2010.

**Athina Markopoulou** (SM'98, M'02, S'12) is an Associate Professor in the EECS Dept. at the University of California, Irvine. She received a Diploma degree in Electrical and Computer Engineering from the National Technical University of Athens, Greece, in 1996, and M.S. and Ph.D. degrees, both in Electrical Engineering, from Stanford University in 1998 and 2003, respectively. She has been a postdoctoral fellow at Sprint Labs (2003) and at Stanford University (2004-2005), and a member of the technical staff at Arastra Inc. (2005). Her research interests include network coding, online social networks, network measurement and security. She received the NSF CAREER award in 2008.

**Enrico Magli** (SM'97, M'01) is currently an Associate Professor at Politecnico di Torino (Italy). He received the M.Sc. and Ph.D. degrees from the same university in 1997 and 2001, respectively. His research interests are in the field of error-resilient image and video coding for wireless applications, network coding, P2P video streaming, compressive sensing, and distributed source coding. He is an associate editor of the *IEEE Transactions on Circuits and Systems for Video Technology*, and a co-recipient of the IEEE Geoscience and Remote Sensing Society 2011 Transactions Prize Paper Award.

**Mea Wang** Dr. Mea Wang is currently an Assistant Professor in the Department of Computer Science at the University of Calgary. She received her Bachelor of Computer Science (Honours) degree from the Department of Computer Science, University of Manitoba, Canada, in 2002. She received her Master of Applied Science and Ph.D. degrees from the Department of Electrical and Computer Engineering at the University of Toronto, Canada, in 2004 and 2008, respectively. Her research interests include Peer-to-Peer networking, multimedia networking, cloud computing and networking system design and development.

**Pascal Frossard** Pascal Frossard (S96,M01,SM04) received the M.S. and Ph.D. degrees, both in electrical engineering, from the Swiss Federal Institute of Technology (EPFL), Lausanne, Switzerland, in 1997 and 2000, respectively. Between 2001 and 2003, he was a member of the research staff at the IBM T. J. Watson Research Center, Yorktown Heights, NY, where he worked on media coding and streaming technologies. Since 2003, he has been a faculty at EPFL, where he heads the Signal Processing Laboratory (LTS4). His research interests include image representation and coding, visual information analysis, distributed image processing and communications, and media streaming systems. Dr. Frossard has been an Associate Editor of the IEEE TRANSACTIONS ON MULTIMEDIA (2004-), the IEEE TRANSACTIONS ON IMAGE PROCESSING (2010-) and the IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY (2006-2011). He received the Swiss NSF Professorship Award in 2003, the IBM Faculty Award in 2005, the IBM Exploratory Stream Analytics Innovation Award in 2008 and the IEEE Transactions on Multimedia Best Paper Award in 2011.