

A dynamic homogenization approach for modelling hybrid piezoelectric nanogenerators

Original

A dynamic homogenization approach for modelling hybrid piezoelectric nanogenerators / De Bellis, MI; Bacigalupo, A; Zavarise, G. - CD-ROM. - (2019). (AIMETA 2019 Roma Settembre 2019).

Availability:

This version is available at: 11583/2787315 since: 2020-01-30T16:50:52Z

Publisher:

AIMETA

Published

DOI:

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

A dynamic homogenization approach for modelling hybrid piezoelectric nanogenerators

Maria Laura De Bellis¹, Andrea Bacigalupo², Giorgio Zavarise³

¹ *University of Chieti-Pescara, INGEO, Viale Pindaro 42, Pescara, Italy*

E-mail:maria.laura.debellis@hotmail.it

² *IMT School for Advanced Studies, Piazza S. Francesco 19, 55100 Lucca, Italy*

E-mail:andrea.bacigalupo@imtlucca.it

³ *Polytechnic University of Turin, DISEG, Corso Duca degli Abruzzi 24, Torino 10129, Italy*

E-mail:giorgio.zavarise@polito.it

Keywords: Energy scavenging; ZnO nanorods; Multi-field homogenization

Energy scavenging, from green and sustainable energy resources, is increasingly attracting the attention of researchers and industries in several engineering fields. The main aim is capturing the energy, naturally available in the environment, and converting it into electrical energy. Emerging applications, such as in flexible/stretchable micro and nano electronics, biomedical monitoring, wearable technology, micro and nano robotics and extreme technology, require devices of smaller and smaller size and high performances.

In this framework, we investigate hybrid piezoelectric nanogenerators, made up with Zinc oxide nanorods [1], embedded in a polymeric matrix, and grown on a flexible polymeric support. The ZnO nanorods are arranged in clusters, forming nearly regular distributions, so that periodic topologies can be realistically assumed. It is well established that, in the context of multi-field problems involving complex composite topologies, a very valuable tool is resorting to generalized homogenization approaches [2-4]. Thus, we propose a dynamic multi-field asymptotic homogenization approach, for the static and dynamic characterization of such microstructured periodic devices, [5]. A set of applications is proposed considering nanogenerators based on three different working principles. Both extension and bending nanogenerators are, indeed, analysed, considering either extension along the nanorods axis, or orthogonally to it. The study of the wave propagation is, also, exploited to comprehend the main features of such piezoelectric devices in the dynamic regime.

References

- [1] Wang, Z. L., Song, J., "Piezoelectric nanogenerators based on zinc oxide nanowire arrays". *Science*, **312**(5771), 242–246 (2006).
- [2] Francfort, G. A., "Homogenization and linear thermoelasticity". *SIAM Journal on Mathematical Analysis*, **14**(4), 696-708 (1983)
- [3] Abdessamad, Z., Kostin, I., Panasenko, G., Smyshlyaev, V. P., "Homogenization of thermo-viscoelastic KelvinVoigt model". *Comptes Rendus Mcanique*, **335**(8), 423-429 (2007).
- [4] Fantoni, F. Bacigalupo, A., Paggi, M., "Multi-field asymptotic homogenization of thermo-piezoelectric materials with periodic microstructure". *International Journal of Solids and Structures*, **120**, 31-56 (2017).
- [5] De Bellis M. L., Bacigalupo A., Zavarise G., "Characterization of hybrid piezoelectric nanogenerators through dynamic asymptotic homogenization", submitted, <http://arxiv.org/abs/1902.04010>, 2019