

Design of active debris flow mitigation measures: a comprehensive analysis of existing impact models

Original

Design of active debris flow mitigation measures: a comprehensive analysis of existing impact models / Vagnon, F.. - In: LANDSLIDES. - ISSN 1612-510X. - 17:(2020), pp. 313-3j3. [10.1007/s10346-019-01278-5]

Availability:

This version is available at: 11583/2957379 since: 2024-12-12T08:47:59Z

Publisher:

Springer-Verlag GmbH

Published

DOI:10.1007/s10346-019-01278-5

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

Springer postprint/Author's Accepted Manuscript

This version of the article has been accepted for publication, after peer review (when applicable) and is subject to Springer Nature's AM terms of use, but is not the Version of Record and does not reflect post-acceptance improvements, or any corrections. The Version of Record is available online at: <http://dx.doi.org/10.1007/s10346-019-01278-5>

(Article begins on next page)

Reliability design optimisation of classic composite plates using a CUF-based layerwise approach

A.R. Sanchez-Majano, A. Pagani

Politecnico di Torino, Corso Duca degli Abruzzi 24, Torino. alberto.racionero@polito.it

Politecnico di Torino, Corso Duca degli Abruzzi 24, Torino. alfonso.pagani@polito.it

Keywords: Straight fibre composites, classic composites, uncertainty, surrogate modelling, Carrera unified formulation

Uncertainties in the manufacturing process of structures may arise at any moment of the fabrication chain. In the case of composite structures, such uncertainties may appear in the material elastic properties as a result of the microscale features of such material or even from manufacturing flaws, such as misalignments, fibre waviness, etc. [1] when assembling the final product. As a result of these defects, the structural response of the final structure might be compromised. Therefore, a reliability analysis is needed. In this work, a reliability-based design optimization (RBDO) [2] regarding the linearized buckling behavior of a straight-fibre composite laminate is carried out concerning homogeneous material elastic properties variation. In order to perform such analyses, Carrera Unified Formulation (CUF) [3] is used, according to which structural theories with low-order accuracy to layerwise models can be implemented in a hierarchical and unified manner. These analyses are then used to build a surrogate model based on Polynomial Chaos Kriging (PCK) [4], which substitutes the finite element model and thus accelerates the optimization process. The final scope of the work is to show that layerwise models can help to broaden the design space that other structural approaches may have shrunk, while subjected to the manufacturing constraints that the industry has imposed through the years [5].

References

- [1] A. Pagani, A.R. Sanchez-Majano. *Influence of fibre misalignments on buckling performance of variable stiffness composites using layerwise models and random fields*. Mechanics of Advanced Materials and Structures 2020. DOI: <https://doi.org/10.1080/15376494.2020.1771485>
- [2] M. Moustapha, B. Sudret. *Surrogate-assisted reliability-based design optimization: a survey and a unified modular framework*. Structural and Multidisciplinary Optimization 60, 2157–2176 (2019). DOI: 10.1007/s00158-019-02290-y
- [3] E. Carrera, M. Cinefra, M. Petrolo, E. Zappino. *Finite Element Analysis of Structures through Unified Formulation*. Wiley & Sons. 2014. ISBN: 978-1-119-94121-7.
- [4] R. Schobi, S. Marelli, B. Sudret, UQLab user manual – Polynomial chaos Kriging, Report # UQLab-V1.3-109, Chair of Risk, Safety and Uncertainty Quantification, ETH Zurich, Switzerland, 2019
- [5] G.H.C. Silva, A.P. do Prado, P.H. Cabral, R. De Breuker, J.K.S. Dillinger. *Tailoring of a Composite Regional Jet Wing Using the Slice and Swap Method*. Journal of Aircraft, 1–15. (2019) DOI:10.2514/1.c035094