

Identification of energy-efficient solutions for broiler house envelopes through a primary energy approach

Original

Identification of energy-efficient solutions for broiler house envelopes through a primary energy approach / Costantino, Andrea; Calvet, Salvador; Fabrizio, Enrico. - In: JOURNAL OF CLEANER PRODUCTION. - ISSN 0959-6526. - STAMPA. - 312:(2021), p. 127639. [10.1016/j.jclepro.2021.127639]

Availability:

This version is available at: 11583/2920368 since: 2021-10-08T22:46:27Z

Publisher:

Elsevier Ltd

Published

DOI:10.1016/j.jclepro.2021.127639

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

Elsevier postprint/Author's Accepted Manuscript

© 2021. This manuscript version is made available under the CC-BY-NC-ND 4.0 license
<http://creativecommons.org/licenses/by-nc-nd/4.0/>. The final authenticated version is available online at:
<http://dx.doi.org/10.1016/j.jclepro.2021.127639>

(Article begins on next page)

1 Identification of energy-efficient solutions for broiler house envelopes 2 through a primary energy approach

3
4 Andrea Costantino^{1,2*}, Salvador Calvet², Enrico Fabrizio¹

5 ¹*DENERG, Politecnico di Torino, TEBE Research Group, Corso Duca degli Abruzzi 24, 10129 Torino, Italy*

6 ²*Institute of Animal Science and Technology, Universitat Politècnica de València, Camino de Vera s/n, 46022,*
7 *València, Spain*

8 *Corresponding author. Tel: +39 0110904552

9 E-mail address: andrea.costantino@polito.it

10 Abstract


11 One of the main concerns regarding intensive broiler production is the high use of energy for
12 climate control. An improved design of broiler house envelopes could decrease this energy
13 consumption. Current evaluation methods only consider the delivered energy, which is
14 misleading because it does not consider the entire energy supply chain. By contrast, primary
15 energy encompasses all forms of direct energy, e.g. thermal and electrical, that are supplied to
16 the broiler house, including the energy losses along the energy supply chain. In this work,
17 delivered energy and primary energy approaches are adopted to identify the most energy-
18 efficient solution for envelopes in typical European broiler houses. This work evaluates 18
19 scenarios characterized by three different envelope types and six different outdoor weather
20 conditions. Financial aspects are evaluated through global cost analysis. The results of this
21 study show that a high-insulated envelope is suitable in the considered outdoor weather
22 conditions, but it is not sustainable from a financial point of view. By contrast, a medium
23 insulated envelope shows a favourable energy performance and its global cost is similar to
24 that of a non-insulated envelope. A comparison of the results reveals that the delivered energy
25 approach considerably underestimates the broiler house energy consumption compared to the
26 primary energy approach. These results strongly suggest that a primary energy approach is
27 well-suited for the assessment of the energy performance of broiler houses and livestock
28 houses. This is because it accounts for the total direct energy supplied to the broiler house
29 considering the specificity of the energy mix of the analysed country and the considered
30 energy carrier. The proposed approach lays the groundwork for future research regarding the
31 assessment of the energy performance of livestock houses.

32

33 **Keywords:** energy analysis; energy benchmarks; dynamic energy simulation model; poultry
34 farming; global cost analysis; livestock sustainability

35
36

37 **Graphical abstract**



40 Nomenclature

A	Area of opaque envelope element
C_a	Annual cost [€ m^{-2}]
C_{el}	Electrical energy cost [€ kWh_{el}^{-1}]
C_m	Total building fabric heat capacity [kJ K^{-1}]
C_G	Global cost [€ m^{-2}]
C_I	Investment cost [€ m^{-2}]
C_{th}	Thermal energy cost [€ kWh_{th}^{-1}]
DE	Germany
$E_{cycle_p_el}$	Primary energy consumption of a production cycle (electrical energy share) [$\text{kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$]
$E_{cycle_p_glob}$	Global primary energy consumption of a production cycle [$\text{kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$]
$E_{cycle_p_th}$	Primary energy consumption of a production cycle (thermal energy share) [$\text{kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$]
E_{p_el}	Electrical share of primary energy consumption [$\text{kWh}_p \text{ m}^{-2} \text{ y}^{-1}$]
E_{p_glob}	Global primary energy consumption [$\text{kWh}_p \text{ m}^{-2} \text{ y}^{-1}$]
E_{p_th}	Thermal share of primary energy consumption [$\text{kWh}_p \text{ m}^{-2} \text{ y}^{-1}$]
E_{el}	Total electrical energy consumption [$\text{kWh}_{el} \text{ m}^{-2} \text{ y}^{-1}$]
E_{el_ec}	Electrical energy consumption for evaporative cooling [$\text{kWh}_{el} \text{ m}^{-2} \text{ y}^{-1}$]
E_{el_ven}	Electrical energy consumption for ventilation [$\text{kWh}_{el} \text{ m}^{-2} \text{ y}^{-1}$]
E_{meat_el}	Electrical energy consumption for unit of mass of produced meat [$\text{Wh}_{el} \text{ kg}_{meat}^{-1}$]
$E_{meat_p_glob}$	Primary energy consumption for unit of mass of produced meat [$\text{kWh}_p \text{ kg}_{meat}^{-1}$]
E_{meat_th}	Thermal energy consumption for unit of mass of produced meat [$\text{Wh}_{th} \text{ kg}_{meat}^{-1}$]
E_{th}	Thermal energy consumption for heating [$\text{kWh}_{th} \text{ m}^{-2} \text{ y}^{-1}$]
ES	Spain
$f_{p_el_tot}$	Total primary energy conversion factor for electrical energy [$\text{kWh}_p \text{ kWh}_{el}^{-1}$]
$f_{p_th_tot}$	Total primary energy conversion factor for thermal energy [$\text{kWh}_p \text{ kWh}_{th}^{-1}$]
FR	France
g_{gl}	Solar factor of the glazed surface [-]
H_{sol_hor}	Annual total solar radiation on horizontal surface [GJ m^{-2}]
IAQ	Indoor Air Quality
IT	Italy
j	j -th opaque element of the envelope
k	k -th time step
l	l -th component of cost
n_{comp}	Number of opaque envelope elements
n_{step}	Number of time steps
PL	Poland
q	q -th year of broiler house lifespan
\mathcal{R}^+	Set of positive real numbers
R_d	Discount rate [%]
R_R	Real interest rate [%]
RH_i	Indoor air relative humidity [%]

U -value	Stationary thermal transmittance of a generic envelope component [$\text{W m}^{-2} \text{K}^{-1}$]
\bar{U} -value	Average stationary thermal transmittance of the entire building envelope [$\text{W m}^{-2} \text{K}^{-1}$]
UK	United Kingdom
V_f	Final value [€ m^{-2}]
α_{sol}	Solar absorption coefficient [–]
γ_{PLI}	Cost conversion factor [–]
Δp_{st}	Static pressure difference between inside and outside [Pa]
$\Delta\tau$	Time interval [h]
θ_{air_i}	Indoor air temperature [$^{\circ}\text{C}$]
θ_{air_o}	Outdoor air temperature [$^{\circ}\text{C}$]
$\bar{\theta}_{\text{air}_o}$	Average annual outdoor air temperature [$^{\circ}\text{C}$]
$\theta_{\text{air}_\text{sup}}$	Supply air temperature [$^{\circ}\text{C}$]
θ_{set_C}	Cooling set point temperature [$^{\circ}\text{C}$]
θ_{set_H}	Heating set point temperature [$^{\circ}\text{C}$]
κ_i	Internal heat capacity [$\text{kJ m}^{-2} \text{K}^{-1}$]
τ_{Is}	Broiler house lifespan [y]
Ω_{OH}	Overheating index [$^{\circ}\text{C h}$]

42 **1 Introduction**

43 Intensive livestock production systems are expanding to cover the increasing world food
44 demand (Firfiris et al., 2019). Poultry meat consumption is estimated to increase by 125%
45 before 2050 compared to 2010 (FAO, 2011a). Currently, more than 70% of the globally
46 produced poultry derives from intensive production systems (FAO, 2011b). Poultry
47 production is often considered the most environmentally efficient type of livestock production
48 (Roma et al., 2015). However, increasing environmental concerns have raised questions about
49 the sustainability of livestock production systems (Costantini et al., 2020).

50 One of the main concerns regarding broiler production is the high use of energy required to
51 farm the animals, e.g. thermal and electrical energy, or to provide the inputs, e.g. machinery
52 and feed. According to Heidari et al. (2011), the highest indirect energy input of poultry
53 production is feed, that represents around 32% of the total energy inputs. Other energy inputs,
54 e.g. for machinery and human labour, are negligible. The importance of feed as an energy
55 input for broiler production has been underlined in literature by energy analyses, which are
56 analyses that assess the overall energy inputs of broiler production as units of equivalent solar
57 energy (Odum, 1995). Castellini et al. (2006), for example, compared conventional and
58 organic broiler farming in terms of energy inputs. Allegretti et al. (2018) performed an
59 energy assessment to show the potentialities of insect-based feed for broiler production.

60 The highest direct energy inputs in broiler production are fuel and electrical energy needed in
61 broiler houses, that represent around 59% and 9% of the total (direct *plus* indirect) energy
62 inputs, respectively (Heidari et al., 2011). Fuel and electrical energy are mainly used on farms
63 for climate control, that is by far the highest share of on-farm energy consumption. According
64 to Costantino et al. (2016), in fact, around 96% of thermal energy and around 76% of
65 electrical energy are used for maintaining adequate indoor climate conditions. Such high
66 shares of energy consumption highlight how an energy-efficient climate control of livestock
67 houses could contribute to improving the environmental sustainability of livestock sector with
68 a view to climate change (Izar-Tenorio et al., 2020). In literature, several works have
69 investigated solutions to decrease the energy consumption for climate control of broiler
70 houses. Most of these works focus on the improvement of the climate control system
71 performance through the use of aerothermal heat pumps (Manolakos et al., 2019), geothermal
72 heat pumps (Choi et al., 2012), solar systems (Gad et al., 2020) including those based on
73 experimental parabolic concentrators (El Mogharbel et al., 2014), and heat recovery systems
74 (Coulombe et al., 2020).


75 Whilst some research has been carried out on the improvement of the energy performance of
76 climate control systems, there have been few investigations into the improvement of the
77 energy performance of broiler house envelopes (Axaopoulos et al., 2014). The envelope is
78 composed of the outer elements of a broiler house, i.e. walls, roof, floor and windows. It
79 constitutes the boundary of thermodynamic system of the broiler house that modulates the
80 exchange of energy - e.g. heat and solar irradiation - and mass - e.g. ventilation air and
81 moisture - between the indoor environment - the enclosure - and the outdoor. The design of
82 the envelope, hence, should aim at improving the energy performance for climate control
83 through the decrease of the overall consumption of thermal and electrical energy. By contrast,
84 in current practice, the envelope design of a broiler house is often a shallow process that
85 provides standardized solutions for contexts that are considerably different. Therefore, there is
86 a strong need for a design process targeted at improving the energy performance of the broiler
87 house envelope. Energy analysis (Pimentel et al., 1973) is a powerful method to evaluate
88 improvements of the energy performance, but research has pointed out that the robustness of
89 this method may need to be improved (Vigne et al., 2012). Most of the energy analyses
90 described above, in fact, evaluated the energy performance of broiler houses focusing only on
91 thermal and electrical energy delivered on farms. Thus, the current state of the art adopts a
92 delivered energy approach that focuses only on the very last stages of the energy supply
93 chain, neglecting the energy consumption that occurs in the previous stages. A new approach
94 based on primary energy could encompass all the stages of the energy supply chain. Primary
95 energy assessment, in fact, is a single metric for assessing all forms of direct energy, e.g.
96 thermal and electrical, that are supplied to the broiler house. Primary energy accounts for the
97 energy losses - e.g. due to conversion and transportation - and for the energy embedded in the
98 infrastructures - e.g. in turbines and pipes - along the energy supply chain in addition to the
99 on-farm energy consumption. Furthermore, primary energy focuses on the adopted energy
100 carrier, e.g. natural gas or electricity from grid, and on the considered country (ISO, 2017a).
101 The importance of primary energy is testified by its adoption as major metric by the Energy
102 Performance of Buildings Directive of European Union (European Commission, 2018) and it
103 is becoming widely adopted in the energy assessment of residential (Bilardo et al., 2020) and
104 office (Krstić-Furundžić et al., 2019) buildings and industrial processes (Dunkelberg et al.,
105 2018). By contrast, there are few primary energy analyses of broiler houses in literature and
106 they focus on very specific case studies and geographical contexts. Costantino et al. (2020),
107 for example, estimated the variation of the primary energy consumption due to different
108 ventilation strategies in a Spanish broiler house. Baxevanou et al. (2017) used the primary

109 energy approach to evaluate the energy consumption of eight broiler houses in different Greek
110 climate contexts. Thus, improving the energy performance of broiler house envelopes through
111 the assessment of primary energy could contribute to decreasing the energy consumption of
112 this production system and of the entire livestock sector.

113 In this work, delivered energy and primary energy approaches are adopted to identify the
114 most energy-efficient solution for envelopes in typical European broiler houses. For this
115 purpose, 18 different scenarios characterized by three different envelope types and six
116 different outdoor weather conditions are simulated. The results of the simulations are
117 evaluated from the financial point of view and considering the heat stress risk.

118 2 Materials and methods

119 This work is based on the methodology workflow schematized in Fig. 1. The pre-processing
120 stage lies in two different tasks. The first one is the identification of the adequate case study
121 for the purpose of this work (section 2.1). The identified case study is then used to calibrate a
122 previously developed dynamic energy simulation model (section 2.2). In the pre-processing
123 stage the simulation scenarios are set by defining different envelope types (section 2.3) and
124 different outdoor weather conditions (section 2.4).



125

126

Fig. 1. Schematization of the methodology workflow.

127 After the pre-processing stage, a calibrated simulation of a typical year of broiler production
128 is performed per each considered scenario. The following results are obtained:

- 129 • energy consumptions for climate control, namely
 - 130 ▪ thermal energy for supplemental heating
 - 131 ▪ electrical energy for ventilation and evaporative cooling

- 132 • indoor climate conditions, namely
133 ▪ indoor air temperature
134 ▪ indoor air relative humidity.

135 The obtained energy consumptions are analysed adopting both the delivered and the primary
136 energy approaches and the results are presented in section 3.1 and 3.2, respectively, where,
137 additionally, reference values of energy consumption are provided. The main difference
138 between delivered and primary energy approach is conceptualized in Fig. 2. As shown in the
139 figure, the delivered energy approach accounts exclusively for the energy that is converted
140 and used on farm. In this work, the delivered energy consumption of the analysed broiler
141 house is provided directly by the energy simulation model. By contrast, the primary energy
142 approach encompasses all the stages of the energy supply chain, from the resource extraction
143 to the final on-farm use, as visible in Fig. 2. The primary energy consumption of the analysed
144 scenarios is calculated from the simulation results through *ad-hoc* conversion factors. The
145 global primary energy consumption E_{p_glob} , is calculated as the sum of primary energy
146 consumption due to thermal E_{p_th} and electrical energy E_{p_el} , as


$$E_{p_glob} = E_{p_th} + E_{p_el} \quad [\text{kWh}_p] \quad (1)$$

147 where

$$E_{p_th} = E_{th} \cdot f_{p_th_tot} \quad [\text{kWh}_p] \quad (2)$$

$$E_{p_el} = (E_{el_ven} + E_{el_ec}) \cdot f_{p_el_tot} \quad [\text{kWh}_p] \quad (3)$$

148 where $f_{p_th_tot}$ is the total primary energy conversion factor for thermal energy and $f_{p_el_tot}$ is
149 the total primary energy conversion factor for electrical energy. These factors depend on the
150 considered energy carrier since the overheads for extracting, refining, converting, and
151 transporting energy change significantly depending on it. The primary energy factors are
152 calculated at a national level since each country should consider its own energy mix. The
153 terms $f_{p_th_tot}$ and $f_{p_el_tot}$ are “total” conversion factors since they account for the renewable
154 and non-renewable primary energy shares.



155

156

Fig. 2. Conceptualization of the differences between the delivered and the primary energy approach.

157

As shown in Fig. 1, the scenarios are analysed from a financial point of view according to the methodology provided in section 2.5. The financial evaluation estimates how the considered types of envelope affect the global cost of the broiler house over its lifespan and the results are presented in section 3.3.

158

159

160

161

162

163

164

165

Finally, a comparison of the scenarios regarding the indoor climate conditions to assess the potential heat stress risk for broilers is performed. For this purpose, the overheating index Ω_{OH} is assessed, as similarly done in previous works (Fabrizio et al., 2014). The overheating index indicates the extent to which indoor air temperature $\theta_{air,i}$ exceeds the set point temperature $\theta_{set,C}$ during a considered time interval $\Delta\tau$ and reads

$$\Omega_{OH} = \sum_{k=1}^{n_{step}} (\Omega_{OH,k} \cdot \Delta\tau) \quad [^{\circ}\text{C h}] \quad (4)$$

166 with

$$\Omega_{OH,k} \in \mathcal{R}^+ \quad (5)$$

167 where

$$\Omega_{OH,k} = \theta_{air,i,k} - \theta_{set,C,k} \quad [^{\circ}\text{C}] \quad (6)$$

168

169

170

171


172

173

where \mathcal{R}^+ is the set of positive real numbers, $\Omega_{OH,k}$ is the overheating index calculated at the k -th hour and n_{step} is the number of hours in which broilers are present inside the house. The value of n_{step} in this work is 7,200 h (the total hours of the years *minus* the hours of sanitary empty periods) and $\Delta\tau$ is equal to one hour (the simulation time step). The terms $\theta_{air,i,k}$ and $\theta_{set,C,k}$ are the indoor air temperature and the cooling set point temperature at the k -th hour, respectively. The results of this analysis are presented in section 3.4.

174 *2.1 Description of the case study*

175 The broiler house selected for this work is located in Italy, has a useful floor area of 1,200 m²
176 (120 m long and 10 m wide) and is schematized in Fig. 3. The considered broiler house has a
177 gable roof which height is 4.4 m of at the ridge level and 2.1 m at the eave level. The useful
178 volume is around 3,900 m³ and the largest walls of the house face east and west.
179 The walls and the roof are made of sandwich panels, while the windows are made of
180 polycarbonate alveolar panels. The floor is a reinforced concrete screed above a
181 waterproofing sheet in direct contact with the ground.



182

183

Fig. 3. Schematization of the typical European broiler house selected as case study.

184 The considered broiler house is mechanically ventilated through a tunnel ventilation
185 configuration, one of the most common strategy adopted in broiler house design. On the south
186 wall, ten exhaust fans deal with both Indoor Air Quality (IAQ) control and tunnel ventilation.
187 The mechanical power of the installed fan model is 0.75 kW (1 hp) and the diameter of the
188 propeller (six blades) is 1.27 m. The maximum flow rate of the fan in free air delivery
189 conditions (static pressure difference between inside and outside the house Δp_{st} equal to 0 Pa)
190 is around 42,000 m³ h⁻¹. The climate control system manages the window opening to
191 maintain Δp_{st} constant at 20 Pa during the production cycle.

192 When cooling ventilation cannot maintain the cooling set point temperature $\theta_{set,C}$,
193 evaporative cooling is activated, and the supply air temperature $\theta_{air,sup}$ is decreased through
194 the adiabatic saturation performed by the evaporative pads installed in the north part of the
195 longest walls. Climate control system activates the evaporative cooling when the difference

196 between θ_{set_C} and outdoor air temperature θ_{air_o} is lower than 3 °C. The evaporative pads are
197 150 mm thick and are made of impregnated and corrugated cellulose paper sheets. The direct
198 saturation effectiveness of the pads (as defined by ASHRAE, 2012) is equal to 87%, as
199 reported in the technical datasheet provided by the manufacturer. Two submersible pumps are
200 used to pump the water from the tanks at the basis of the pads to the top of them. The
201 electrical motor of each pump is estimated to deliver 0.55 kW (0.75 hp) of mechanical power
202 and to absorb 0.85 kW of electrical power.

203 In the monitored broiler house, four gas air heaters provide the supplemental heating to
204 maintain the heating set point temperature θ_{set_H} . Each gas heater has 36 kW of heating
205 capacity and their heating efficiency is estimated to be 100%, since they are placed directly
206 inside the enclosure.

207 When broiler chicks are present inside the house, the climate control system maintains θ_{air_i}
208 at 32 °C and provides $2.3 \text{ m}^3 \text{ h}^{-1} \text{ kg}^{-1}$ of minimum ventilation to control the IAQ. At the end
209 of the cycle, θ_{air_i} is maintained at 17 °C and the minimum ventilation flow rate is
210 $0.4 \text{ m}^3 \text{ h}^{-1} \text{ kg}^{-1}$. More details about the adopted θ_{set_H} , θ_{set_C} and minimum ventilation flow
211 rates can be found in Cobb (2008). Please note that inside the broiler house, the only climate
212 parameter that is controlled by climate control with a feedback loop is θ_{air_i} . Indoor air
213 relative humidity RH_i is not controlled in a feedback loop.

214 In the analysed case study, broilers are reared to reach a final live weight of around 3.6 kg in a
215 production cycle that lasts 50 days. After each production cycle, a sanitary empty period of 11
216 days is considered for sanitization tasks. Six production cycles are completed each year.

217 *2.2 Model calibration*

218 The energy consumption in the different scenarios is estimated using the previously validated
219 energy simulation model of Costantino et al. (2018). The adopted model relies on an *ad hoc*
220 customization of the simple hourly method in compliance with ISO 13790 standard (European
221 Committee for Standardisation and EN ISO, 2008). The reliability of this model was proved
222 by Costantino et al. (2018) through a validation against real monitored data in compliance
223 with ASHRAE Guideline 14 (ANSI/ASHRAE, 2002). The adoption of a numerical model is
224 essential for the aim of this work since enhances the comparison of the scenarios in the same
225 standardized boundary conditions, e.g. animal stocking density and heating system efficiency,
226 varying only the envelope thermo-physical properties and the outdoor weather conditions.

227 The adopted energy simulation model was *ad hoc* calibrated to improve the reliability of the
 228 results of this work through an optimization-based calibration (Fabrizio and Monetti, 2015)
 229 based on real monitored data. To do so, a long-term monitoring campaign was carried out in
 230 the case study presented in section 2.1.

231 2.3 Types of broiler house envelopes

232 Three types of building envelope that are commonly used in typical European broiler houses
 233 are considered in this work and they are presented in Table 1. The considered envelopes are
 234 characterized by different values of average stationary thermal transmittance \bar{U} -value and
 235 total building fabric heat capacity C_m . The term \bar{U} -value reported in Table 1 represents the
 236 averaged stationary thermal transmittance of the entire building envelope and is calculated as

$$\bar{U} - \text{value} = \frac{\sum_{j=1}^{n_{\text{comp}}} (U - \text{value}_j \cdot A_j)}{\sum_{j=1}^{n_{\text{comp}}} A_j} \left[\frac{\text{W}}{\text{m}^2\text{K}} \right] \quad (7)$$

237 where U -value is the stationary thermal transmittance of the j -th element of the building
 238 envelope ($\text{W m}^{-2} \text{K}^{-1}$) and A_j is its area (m^2). The term n_{comp} is the number of building
 239 components of the envelope.

240 The total building fabric heat capacity C_m reported in Table 1 is calculated as

$$C_m = \sum_{j=1}^{n_{\text{comp}}} (\kappa_{i,j} \cdot A_j) \left[\frac{\text{kJ}}{\text{K}} \right] \quad (8)$$

241 where $\kappa_{i,j}$ ($\text{kJ m}^{-2} \text{K}^{-1}$) is the internal heat capacity of the j -th opaque element -calculated
 242 according to EN ISO 13786 standard (European Committee for Standardisation, 2018)- and
 243 A_j is its area. The internal heat capacity is the amount of heat to be supplied to a unit of area
 244 of the building component to produce a unitary change in its temperature. This parameter is
 245 needed since describes the capacity of the building component to buffer heat during a diurnal
 246 cycle. The term n_{comp} is the number of building components that are considered in the
 247 calculation of C_m . In this work, κ_i of the transparent elements is considerably lower than the
 248 one of the opaque ones, thus it was neglected in the simulations.

249 **Table 1** – The average stationary thermal transmittance of the entire envelope \bar{U} -value and total building fabric
 250 heat capacity C_m of the considered envelope types.

Envelope	Envelope features	Use	\bar{U} -value [W m ⁻² K ⁻¹]	C_m [kJ K ⁻¹]
----------	-------------------	-----	--	--------------------------------


Type-A	Medium insulation and low mass	Modern broiler houses	0.69	24,231
Type-B	High insulation and low mass	Modern broiler houses	0.36	24,045
Type-C	Low insulated and high mass	Older broiler houses	1.15	49,322

251 The U -values (Eq. (7)) and the values of κ_i (Eq. (8)) for each considered envelope that are
 252 used in this work are reported in Fig. 4 together with the solar factors of the glazed surfaces
 253 g_{gl} . All the adopted thermo-physical properties were calculated from the values reported in
 254 international standards (ISO, 2017b), technical handbooks (ASHRAE, 2017) or technical
 255 datasheets of commercial products.

256 The walls of type-A and type-B envelopes and all the rooves are sandwich panels made of a
 257 double pre-painted steel sheet with the thermal insulation layer interposed (high density
 258 spread polyurethane). The panel thickness changes according to the envelope type. The walls
 259 of type-C envelope are made up of hollow concrete blocks. The outdoor surface of all the
 260 walls is painted of a light colour (solar absorption coefficient α_{sol} equal to 0.3), while the roof
 261 has an intermediate colour ($\alpha_{sol} = 0.6$).

262 The floors of the three envelopes are made by a reinforced concrete screed with litter of wood
 263 shavings above. The thermo-physical properties of the litter are the ones calculated by Ahn,
 264 Sauer, Richard, & Glanville (2009). A thermal insulation layer of cellular glass granules is
 265 considered below the concrete screed in type-A and type-B envelopes (with different
 266 thickness), while the floor of type-C envelope has no thermal insulation.

267 The windows of the broiler house (114 m^2 of the envelope) have metal frames and
 268 polycarbonate alveolar panels of different thicknesses. The value of g_{gl} is considered equal to
 269 0.75 for all the envelopes.



270

271

272

273

Fig. 4. Details of the building components (walls, rooves, floors and windows) of the three analysed envelope types (A, B and C). In the figure, the stationary thermal transmittances U -value, the internal aerial heat capacities κ_i and the solar factors of the glazed surfaces g_{gl} are shown.

274 2.4 Outdoor weather conditions

275 The energy performance of the analysed broiler house was assessed considering different
 276 outdoor weather conditions of the European context. The chosen weather conditions are
 277 proper of geographical locations characterized by the highest poultry production in Europe
 278 and are Poland (PL), France (FR), United Kingdom (UK), Germany (DE), Spain (ES), and
 279 Italy (IT). In these six countries more than 70% of the European poultry meat is produced
 280 (Van Horne, 2018). For each country, the region with the highest poultry production at a
 281 national level was individuated to perform the simulations. A reference city representative of
 282 each one of these regions was selected for obtaining the Typical Meteorological Year (TMY),
 283 needed for the simulation inputs. In Table 2, the six selected locations with their countries and
 284 geographical regions are presented. In addition, the main parameters useful to characterize
 285 their weather conditions are shown. The reference locations are characterized by different
 286 values of average annual outdoor air temperature $\bar{\theta}_{\text{air,o}}$ and annual total solar radiation on
 287 horizontal surface $H_{\text{sol,hor}}$. In the framework of the present work, $\bar{\theta}_{\text{air,o}}$ is the arithmetic
 288 mean of the hourly $\theta_{\text{air,o}}$ values over the entire year, while $H_{\text{sol,hor}}$ is the integral of the
 289 hourly values of solar irradiance over the entire year. From Table 2, it stands out that
 290 Barcelona is characterized by the highest value of $\bar{\theta}_{\text{air,o}}$ (15.7 °C) and the highest $H_{\text{sol,hor}}$
 291 (5.2 GJ m⁻² y⁻¹). Warsaw results the location with the lowest $\bar{\theta}_{\text{air,o}}$ (8.4 °C), while
 292 Finninglay and Bremen are the ones characterized by the lowest $H_{\text{sol,hor}}$ (3.4 GJ m⁻² y⁻¹).

293 **Table 2** – The locations used in this work with the reference cities, acronyms, and geographical regions. For
 294 each location, the average annual outdoor air temperature $\bar{\theta}_{\text{air,o}}$ and the annual total solar radiation on horizontal
 295 surface $H_{\text{sol,hor}}$ are shown.

Location (reference city)	Acronym	Geographical region	$\bar{\theta}_{\text{air,o}}$ [°C]	$H_{\text{sol,hor}}$ [GJ m ⁻² y ⁻¹]
Poland (Warsaw)	PL	Central Europe	8.4	3.6
France (Brest)	FR	Western Europe	11.2	3.9
United Kingdom (Finninglay)	UK	Western Europe	9.5	3.4
Germany (Bremen)	DE	Central Europe	8.9	3.4
Spain (Barcelona)	ES	Southwest Europe	15.7	5.2
Italy (Verona)	IT	Southern Europe	12.3	3.9

296 Considering the six different locations and the three envelope types (A, B and C), 18
 297 simulation scenarios are formulated. Each scenario is identified by a code in which the first

298 two characters indicate the reference country (acronyms from Table 2), while the last one
299 (separated by a dash) indicates the considered envelope type (A, B or C, Fig. 4).

300 2.5 Financial evaluation: global cost methodology

301 After the delivered and primary energy analyses, the scenarios are analysed from a financial
302 point of view to estimate how the considered types of envelope affect the global cost of the
303 broiler house over its lifespan. This analysis is performed in compliance with the EN 15459
304 international standard (CEN, 2007). The global cost C_G , here referred to the unit of useful
305 floor area, is the sum of the present value of all the costs estimated during the lifespan τ_{ls} of
306 the broiler house and reads

$$C_G(\tau_{ls}) = C_I + \sum_{l=1}^{n_{com}} \left[\sum_{q=1}^{\tau_{ls}} (C_{a,q,l} \cdot R_{d,q}) - V_{f,\tau_{ls},l} \right] \quad [\text{€ m}^{-2}] \quad (9)$$

307 where C_I is the initial investment cost (€ m^{-2}), $C_{a,q,l}$ is the annual cost regarding the l -th
308 component of cost calculated at the q -th year (€ m^{-2}) of broiler house lifespan while $V_{f,\tau_{ls},l}$ is
309 the final value of the l -th component at the end of its lifespan τ_{ls} (€ m^{-2}). The term $R_{d,q}$ is
310 the discount rate (%) introduced to refer the value of money of the q -th year at the present. It
311 reads

$$R_d(q) = \left(\frac{1}{1 + R_R} \right)^q \cdot 100 \quad [\%] \quad (10)$$

312 where R_R is the real interest rate (%) that considers the market and inflation rates.
313 In this work, The global cost C_G of each proposed solution is evaluated considering 30 years
314 of broiler house lifespan τ_{ls} and a real interest rate R_R of 3.5% (Hermelink and de Jager,
315 2015).

316 The initial investment cost C_I for IT-A, IT-B, and IT-C scenarios was estimated through an
317 analysis on the Italian market aimed at finding the final costs (product *plus* installation *plus*
318 taxes) of each considered element of the envelope and climate control system of the broiler
319 house. These costs are presented in Table 3 referring to the unit of useful floor area. Other
320 costs, such as feeders and lighting system, are not considered since they negligibly affect the
321 energy performance of the broiler house.

322 **Table 3** – Costs of envelope and the climate control system elements and initial investment cost C_I referred to
323 unit of useful floor area.

Element	IT-A [€ m ⁻²]	IT-B [€ m ⁻²]	IT-C [€ m ⁻²]
Walls	17.49	32.07	21.60

Roof	45.25	76.95	45.25
Floor	107.93	208.43	53.72
Windows	4.03	5.03	3.39
Fans	4.37	4.37	4.37
Gas air heaters	6.51	6.51	7.81
Evaporative pads	3.30	3.30	3.30
Pad pumps and pipelines	4.55	4.55	4.55
C_I	193.43	341.21	143.99

324 The C_I values for the other considered countries can be estimated assuming that the difference
 325 between the C_I values of two countries depends on the difference between their purchasing
 326 powers due to the fluctuations in currency exchange rates, as reported in Eurostat (2019).
 327 Hence, the C_I values for the other considered countries are obtained by multiplying the C_I
 328 values for the Italian context -last row of Table 3- by the dimensionless cost conversion factor
 329 γ_{PLI} . This factor is the ratio between the construction price level of the considered European
 330 country and the Italian one. In this work, γ_{PLI} values are obtained by elaborating the Price
 331 Level Indices for non-residential buildings construction provided by Eurostat (2019). The
 332 considered γ_{PLI} values are presented in Table 4.

333 The considered annual costs C_a over the broiler house lifespan are due to energy and due to
 334 the replacement of the elements of climate control system. Other annual costs, such as
 335 insurances and ordinary maintenance, are considered out of the scope of this work. The
 336 annual cost of energy is estimated multiplying the yearly thermal and electrical energy
 337 consumptions obtained from the simulations by the cost of thermal C_{th} and electrical C_{el}
 338 energy for the considered country. The costs of energy adopted in this work were obtained
 339 from Eurostat (2020a, 2020b) and are reported in Table 4. The annual cost of element
 340 replacement for climate control system is estimated considering the initial costs presented in
 341 Table 3 and estimating a lifespan of 15 years for fans, gas air heaters and pumps and pipeline
 342 of the evaporative cooling system. The lifespan of the evaporative pads was estimated equal
 343 to 5 years. At the end of the broiler house lifespan, no final value V_f (Eq. (9)) is considered for
 344 envelope and climate control system elements.

345 **Table 4** – Considered cost conversion factor γ_{PLI} and costs of thermal C_{th} and electrical C_{el} energy (including
 346 taxes).

Country	γ_{PLI} [–]	C_{th} [€ kWh _{th} ⁻¹]	C_{el} [€ kWh _{el} ⁻¹]
PL	0.78	0.04	0.15
FR	1.23	0.08	0.19

UK	1.38	0.05	0.22
DE	1.67	0.06	0.30
ES	0.95	0.07	0.22
IT	1.00	0.07	0.22

347 **3 Results and discussion**

348 Each one of the 18 considered scenarios is simulated in standardized conditions using the
 349 calibrated energy model. The results of the simulations are analysed to identify the best
 350 envelope solution in terms of delivered and the primary energy performance. In addition, the
 351 results are compared in terms of global cost and overheating index.

352 *3.1 Delivered energy approach*

353 The delivered energy consumption is evaluated considering the thermal energy consumption
 354 for heating E_{th} , the electrical energy consumption for ventilation E_{el_ven} and for evaporative
 355 cooling E_{el_ec} . The values of E_{th} and E_{el_ven} are calculated by the model considering the
 356 efficiency of the heating system and the features of the ventilation system. The value of E_{el_ec}
 357 is calculated by the model considering the electrical energy consumption of the circulation
 358 pumps.

359 *3.1.1 Thermal and electrical energy consumption*

360 In the bar charts of Fig. 5, E_{th} , E_{el_ven} and E_{el_ec} are presented normalized per unit of floor
 361 area. The graph shows that important differences in terms of E_{th} (Fig. 5a) stand out among the
 362 analysed scenarios. The highest E_{th} values are from PL-C ($163.7 \text{ kWh}_{th} \text{ m}^{-2} \text{ y}^{-1}$), DE-C
 363 ($142.7 \text{ kWh}_{th} \text{ m}^{-2} \text{ y}^{-1}$) and UK-C ($119.0 \text{ kWh}_{th} \text{ m}^{-2} \text{ y}^{-1}$) scenarios, respectively. The
 364 lowest values of E_{th} result from ES-B ($19.6 \text{ kWh}_{th} \text{ m}^{-2} \text{ y}^{-1}$), FR-B ($29.3 \text{ kWh}_{th} \text{ m}^{-2} \text{ y}^{-1}$)
 365 and ES-A ($36.3 \text{ kWh}_{th} \text{ m}^{-2} \text{ y}^{-1}$). The lowest values of E_{th} (ES-B scenario) is 88% lower
 366 than the highest E_{th} (PL-C scenario) highlighting the effects that outdoor weather conditions
 367 and envelope type have in terms of thermal energy consumption of broiler houses.

368 Looking at the values of $\bar{\theta}_{air_o}$ presented in Table 2, it stands out that the highest E_{th} values
 369 come from the outdoor weather conditions characterized by the lowest $\bar{\theta}_{air_o}$. Solar radiation
 370 seems to not have the same influence of θ_{air_o} on E_{th} because, even though PL-C is
 371 characterized by a slightly higher value of H_{sol_hor} than DE-C, its E_{th} is considerably higher
 372 than the one of DE-C. An interesting analysis in this sense is the comparison between the

373 sensible heat load from broilers with the heat load from solar radiation. Considering the last
374 day of the production cycle in August, the maximum solar heat load that should be removed
375 from the enclosure per unit of useful floor area is 47 W in scenario ES-C. At the same
376 moment, the sensible heat load due to the animals is 176 W m^{-2} of useful floor area, a value
377 that is nearly four times higher the one of the solar heat load. This difference means that
378 sensible heat load from animals represents the major issue for cooling ventilation broiler
379 houses, even in mild climates such as the one of ES-C scenario. Please note that in this work,
380 the total solar radiation on any surface was calculated from the hourly values of direct normal
381 radiation and diffuse horizontal solar radiation reported in the TMY adopting the transposition
382 model of ASHRAE (2017). The calculation of the solar gains from the solar irradiance on
383 opaque and transparent envelope components was performed in compliance with EN ISO
384 13790 standard (European Committee for Standardisation and EN ISO, 2008).


385 The results of the simulations show that, from the delivered energy point of view, the
386 adoption of the high-insulation and low-massive building envelope (type-B) represents an
387 interesting strategy to reduce E_{th} in all the considered weather conditions, because the type-B
388 envelope entails the lowest E_{th} . The relative differences between the thermal energy
389 performance of the considered envelopes in the same weather conditions are important. The
390 choice of a high-insulation building envelope (type-B) reduces E_{th} between 63 and 67% if
391 compared to a non-insulated envelope (type-C). The increase of the thermal insulation layer
392 (from type-A to type-B envelope) entails a decrease of E_{th} between 41 and 46%.

393 High-insulation building envelope (type-B) resulted the best option for decreasing E_{th} , but the
394 better thermal insulation properties favour the overheating of the enclosure. Consequently,
395 higher electrical energy consumptions for ventilation $E_{\text{el_ven}}$ and evaporative cooling $E_{\text{el_ec}}$
396 are expected compared to the other envelope types. In Fig. 5b, the electrical energy
397 consumptions $E_{\text{el_ven}}$ and $E_{\text{el_ec}}$ are presented and the bar chart indicates that, actually, $E_{\text{el_ven}}$
398 is higher when type-B envelope is considered. The highest value of $E_{\text{el_ven}}$ come from Spain
399 (ES-B, $15.5 \text{ kWh}_{\text{el}} \text{ m}^{-2} \text{ y}^{-1}$) while the lowest one from United Kingdom (UK-C,
400 $5.8 \text{ kWh}_{\text{el}} \text{ m}^{-2} \text{ y}^{-1}$). Even in this case, the higher $E_{\text{el_ven}}$ values come from the weather
401 conditions characterized by the higher $\bar{\theta}_{\text{air}_o}$, namely Spain ($15.7 \text{ }^\circ\text{C}$) and Italy ($12.3 \text{ }^\circ\text{C}$).

402 The $E_{\text{el_ec}}$ values presented in Fig. 5b are the same for each considered geographical location
403 regardless of the analysed envelope type. This is because the adopted energy model simulates
404 the activation of the evaporative cooling only depending on the temperature difference
405 between θ_{set_C} and θ_{air_o} . The bar chart of Fig. 5b shows greater $E_{\text{el_ec}}$ for those scenarios

406 where the E_{el_ven} is higher, such as Spain and Italy. The estimated E_{el_ec} values are
 407 considerably smaller than E_{el_ven} , being $2.5 \text{ kWh}_{el} \text{ m}^{-2} \text{ y}^{-1}$, or lower, for all the considered
 408 scenarios.

409 The total electrical energy consumption E_{el} (sum of E_{el_ven} and E_{el_ec}) ranges between
 410 $18.0 \text{ kWh}_{el} \text{ m}^{-2} \text{ y}^{-1}$ and $6.4 \text{ kWh}_{el} \text{ m}^{-2} \text{ y}^{-1}$. The adoption of a low insulated envelope
 411 (type-C) decreases it from 6 to 13% if compared to a high-insulation envelope (type-B).



412
 413 **Fig. 5.** Thermal (E_{th} , figure a), and electrical energy consumption (figure b) both for ventilation (E_{el_ven}) and
 414 evaporative cooling (E_{el_ec}) from the 18 scenarios.

415 3.1.2 Reference values of delivered energy consumption

416 The delivered energy consumption values are now used to provide reference values about the
 417 use of energy in broiler houses. Similar values are interesting from the scientific point of view
 418 with a perspective on the improvement of the energy efficiency of broiler production, but very
 419 few of them are present in literature, as highlighted by Costantino et al. (2016). Most of the
 420 existing reference values, in fact, refers to specific case studies or geographical contexts, as
 421 done by Hörndahl (2008) for the Swedish context, the Technical Institute of Poultry (2010)
 422 for the France and Rossi et al. (2013) for Italy. In addition, those reference values were not
 423 assessed in standardized conditions, a feature that may jeopardize their reliability. By
 424 contrast, the reference values present in this section were calculated in standardized
 425 conditions, refer to different European context and consider different types of building
 426 envelope. Nevertheless, more accurate results would be obtained performing simulations


427 using Monte Carlo method to consider a higher variations of boundary conditions and
428 sensitivity analysis can better investigate the influence of each parameter on the final results.
429 The results obtained from the simulated scenarios are normalized on the kg_{meat} and grouped
430 to obtain ranges of delivered energy consumption for climate control. This normalization is
431 necessary to make the results independent from the assumptions made for this work, such as
432 the farming features. Furthermore, the adopted unit of measure ($\text{Wh kg}_{\text{meat}}^{-1}$) is useful for
433 engineers and farmers since they can refer production costs and revenues to the unit of final
434 product. The saleable meat from each broiler is calculated considering a carcass yield,
435 percentage of the saleable meat over the final live weight, of 73% (Costantino et al., 2016).
436 Consequently, a meat production of $2.60 \text{ kg}_{\text{meat}}$ per harvested broiler is estimated. The main
437 limitation in the formulation of these reference values is the estimation of the broiler final live
438 weight that does not consider eventual decrease of weight gain due to, for example, heat
439 stress. This issue could be considered in future works using the formulations provided by St-
440 Pierre, Cobanov, & Schnitkey (2003).

441 In Fig. 6, the ranges of the specific thermal $E_{\text{meat_th}}$ (Fig. 6a) and electrical energy
442 consumption $E_{\text{meat_el}}$ (Fig. 6b) referred to the selected countries are presented. The values of
443 $E_{\text{meat_th}}$ and $E_{\text{meat_el}}$ were calculated dividing the yearly thermal and electrical energy
444 consumption by the meat production over the entire year. The presented ranges consider the
445 minimum and the maximum values of $E_{\text{meat_th}}$ and $E_{\text{meat_el}}$ (sum of electrical energy
446 consumption for ventilation and evaporative cooling) of each country considering the three
447 envelope types.

448 The range of $E_{\text{meat_th}}$ goes from $628 \text{ Wh}_{\text{th}} \text{ kg}_{\text{meat}}^{-1}$ (Spain) to $5,245 \text{ Wh}_{\text{th}} \text{ kg}_{\text{meat}}^{-1}$ (Poland).
449 Three countries (France, United Kingdom, and Italy) are in the range from 940 to
450 $3,812 \text{ Wh}_{\text{th}} \text{ kg}_{\text{meat}}^{-1}$, while the $E_{\text{meat_th}}$ of Germany and Poland is between the range $1,711 -$
451 $5,245 \text{ Wh}_{\text{th}} \text{ kg}_{\text{meat}}^{-1}$. Spain is the country with the narrower range of $E_{\text{meat_th}}$ that goes from
452 628 to $1,901 \text{ Wh}_{\text{th}} \text{ kg}_{\text{meat}}^{-1}$.

453 The ranges presented in Fig. 6b are narrower and of an order of magnitude lower than the
454 ones of Fig. 6a. The difference between the highest and the lowest value of each country
455 presented in Fig. 6b is between 26 and $33 \text{ Wh}_{\text{el}} \text{ kg}_{\text{meat}}^{-1}$. The lowest $E_{\text{meat_el}}$ is the one from
456 Great Britain ($205 \text{ Wh}_{\text{el}} \text{ kg}_{\text{meat}}^{-1}$) while the greatest one is from Spain ($577 \text{ Wh}_{\text{el}} \text{ kg}_{\text{meat}}^{-1}$).
457 $E_{\text{meat_el}}$ of four countries (Poland, France, United Kingdom, and Germany) is between 205

458 and $299 \text{ Wh}_{\text{el}} \text{ kg}_{\text{meat}}^{-1}$. The $E_{\text{meat}_{\text{el}}}$ value from Italy is between 417 and $447 \text{ Wh}_{\text{el}} \text{ kg}_{\text{meat}}^{-1}$,
 459 while Spain has the wider $E_{\text{meat}_{\text{el}}}$ range ($543 - 577 \text{ Wh}_{\text{el}} \text{ kg}_{\text{meat}}^{-1}$).



460
 461 **Fig. 6.** Ranges of specific thermal ($E_{\text{meat}_{\text{th}}}$, figure a) and electrical energy consumption ($E_{\text{meat}_{\text{el}}}$, figure b) for
 462 the considered locations.

463 3.2 Primary energy approach

464 The previous analysis assessed the delivered energy consumption. Type-B envelope resulted
 465 the best solution to decrease E_{th} , while type-C envelope was the worst one by far in all the
 466 considered locations. On the contrary, type-C envelope was characterized by the best
 467 performance considering the electrical energy consumption for ventilation and evaporative
 468 cooling. Type-A envelope is the intermediate solution for both thermal and electrical energy
 469 consumption.

470 To identify the best global solution, the primary energy performance is assessed for the 18
 471 scenarios. In this way, the thermal and electrical energy consumption can be correctly
 472 weighted considering their respective energy overheads for extracting, refining, converting,
 473 and transporting energy.

474 3.2.1 Primary energy consumption

475 The conversion from delivered energy to primary energy can be performed according to Eqs.
 476 (1)-(3) using the total (renewable and non-renewable) primary energy consumption factors
 477 $f_{\text{p}_{\text{th}_{\text{tot}}}}$ and $f_{\text{p}_{\text{el}_{\text{tot}}}}$ reported in Table 5. The energy carriers that are considered are natural

478 gas and electrical energy from the national grid. From Table 5, two main aspects can be
 479 highlighted. The first aspect is that $f_{p_el_tot}$ is always higher than $f_{p_th_tot}$. This difference is
 480 since the production and transport of electrical energy is characterized by higher energy
 481 overheads than the thermal one. The second aspect is that quite important differences stand
 482 out among the considered countries especially concerning $f_{p_el_tot}$. These differences could be
 483 attributable to the different energy mixes proper of each country and, consequently, different
 484 energy overheads.

485 **Table 5** – Total (renewable and non-renewable) primary energy factors for thermal $f_{p_th_tot}$ and electrical
 486 $f_{p_el_tot}$ energy.


Country	$f_{p_th_tot}$ (natural gas) [kWh _p kWh _{th} ⁻¹]	$f_{p_el_tot}$ (electrical grid) [kWh _p kWh _{el} ⁻¹]	Source
Poland	1.10	3.03	Polish Ministry of Economy (2014)
France	1.00	2.58	French Ministry of Territorial Equality and Housing (2011)
United Kingdom	1.02	2.92	E. Molenbroek, E. Stricker (2011)
Germany	1.10	2.80	German Association of Energy and Water Industries (BDEW) (2015)
Spain	1.195	2.368 ^a	Spanish Ministry of Industry Energy and Tourism (2016)
Italy	1.05	2.42	Italian Ministry of Economic Development (2015)

^a $f_{p_el_tot}$ referred to Peninsular Spain; the national values is 2.403 kWh_p kWh_{el}⁻¹.

487 In Fig. 7, E_{p_glob} and its shares E_{p_th} and E_{p_el} from the analysed scenarios are presented. The
 488 graph shows that PL-C is characterized by the highest E_{p_glob} (205.9 kWh_p m⁻² y⁻¹). This is
 489 since the considered Polish weather conditions entail a considerable high E_{th} that represents
 490 around 87% of E_{p_glob} .

491 In all the considered weather conditions, type-B envelope provides the best global primary
 492 energy performance entailing the minimum E_{p_glob} . In particular, the scenario characterized
 493 by the lowest value of E_{p_glob} is FR-B (51.9 kWh_p m⁻² y⁻¹). This scenario, in fact, is
 494 characterized by a quite low E_{th} (the lowest one after ES-B) that is not increased by $f_{p_th_tot}$
 495 that, for France, is equal to 1 kWh_p kWh_{el}⁻¹. Furthermore, $\bar{\theta}_{air_o}$ (the highest one after ES and

IT), entails a reduced E_{el_vent} ($8.1 \text{ kWh}_{el} \text{ m}^{-2} \text{ y}^{-1}$) that, converted in E_{p_el} , represents 43% of E_{p_glob} .
 The analysis of the primary energy consumption highlights that type-B envelope is the actual best solution to decrease the energy consumption for climate control of the analysed broiler house in all the outdoor weather conditions. The thermal energy analysis showed that type-B envelope can reduce E_{th} between 63 and 67% if compared to type-C envelope. This result is quite misleading since the actual decrease of that energy consumption (evaluated through the primary energy consumption) is lower, being between 41 and 55%.



504 **Fig. 7.** Primary energy consumption E_{p_glob} of each scenario. In addition, the energy shares due to electrical (E_{p_el}) and thermal (E_{p_th}) energy consumptions are shown.


507 The values of E_{p_glob} presented in Fig. 7 refer to the entire year but each production cycle
 508 could be characterized by considerably different values of primary energy consumption, if
 509 compared to the other cycles, depending on the period of the year in which is carried out.
 510 To analyse these differences, the global primary energy consumption of each production cycle
 511 $E_{cycle_p_glob}$ ($\text{kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$) from PL-C and ES-B scenarios are shown in Fig. 8. The
 512 comparison between PL-C and ES-B is interesting since these scenarios are characterized by
 513 the highest E_{p_th} and E_{p_el} , respectively. The sum of $E_{cycle_p_glob}$ of each production cycle is
 514 equal to E_{p_glob} reported in Fig. 7. In Fig. 8, the primary energy shares due to thermal
 515 $E_{cycle_p_th}$ and electrical $E_{cycle_p_el}$ energy are reported. In addition, the average $E_{cycle_p_glob}$
 516 calculated over the six production cycles is provided for both the considered scenarios.
 517 The bar chart of Fig. 8 shows that the average $E_{cycle_p_glob}$ values of the considered scenarios
 518 are different, being $E_{cycle_p_glob}$ of PL-C scenario around $19.8 \text{ kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$ (around

519 87% due to $E_{\text{cycle,p,th}}$ and 13% due to $E_{\text{cycle,p,el}}$), while $E_{\text{cycle,p,glob}}$ of the ES-B scenario is
520 $6.4 \text{ kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$ (35% due to $E_{\text{cycle,p,th}}$ and 65% due to $E_{\text{cycle,p,el}}$).

521 From Fig. 8, important differences between the production cycles of the warm and the cool
522 seasons can be highlighted. Analysing the Polish scenario, it stands out that the production
523 cycles of the cool season (1st, 2nd, and 6th) are characterized by $E_{\text{cycle,p,tot}}$ values that are
524 higher than $23.0 \text{ kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$. This energy consumption is greater than the one from
525 the 3rd, 4th, and 5th production cycles, that is always lower than $10.0 \text{ kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$.

526 Looking at the shares of $E_{\text{cycle,p,glob}}$, in 1st, 2nd, 5th and 6th production cycles in PL-C
527 scenario, $E_{\text{cycle,p,th}}$ is always higher than 80% of the total, with a maximum value of 98%
528 during the 1st production cycle. In 3rd and 4th production cycles (during the warm season),
529 $E_{\text{cycle,p,th}}$ is lower, being around 60% and 40%, respectively.

530 In PL-C scenario, great differences stand out between the production cycles that are carried
531 out during the warm and the cool season, while in ES-B scenario this difference is negligible.
532 In ES-B scenario, in fact, $E_{\text{cycle,p,glob}}$ is quite constant during all the year being the minimum
533 and the maximum values 3.9 and $8.7 \text{ kWh}_p \text{ m}^{-2} \text{ cycle}^{-1}$, respectively. Another difference
534 between the PL-C and ES-B scenarios concerns the shares of $E_{\text{cycle,p,th}}$ and $E_{\text{cycle,p,el}}$. In PL-
535 C scenario $E_{\text{cycle,p,el}}$ is the lowest one in all the production cycles with the only exception of
536 the 4th one. In ES-B scenario, $E_{\text{cycle,p,el}}$ is the highest share during warm season production
537 cycles (3rd, 4th, and 5th), reaching the maximum relative value of 97% during the 4th
538 production cycle.



539

540

Fig. 8. Primary energy consumption for each production cycle ($E_{\text{cycle}_p_{\text{glob}}}$) and shares due and electrical ($E_{\text{cycle}_p_{\text{el}}}$) and thermal ($E_{\text{cycle}_p_{\text{th}}}$) energy from PL-C and ES-B scenario.

541

542

3.2.2 Reference values of primary energy consumption

543

Reference values are provided for primary energy consumption, considering the global energy

544

performance of the broiler houses. In Table 6, the primary energy consumption for climate

545

control needed to produce a unit of mass of broiler meat ($E_{\text{meat}_p_{\text{glob}}}$) is presented with the

546

shares due to heating, ventilation, and evaporative cooling. The results show that the range of

547

$E_{\text{meat}_p_{\text{glob}}}$ values goes from 1.7 to 6.6 kWh_p kg⁻¹_{meat}. Heating represents the highest share of

548

$E_{\text{meat}_p_{\text{glob}}}$ in almost all the scenarios (the only exceptions is ES-B) being between 51 and

549

87% of the total. Ventilation goes from 11 to 55% of $E_{\text{meat}_p_{\text{glob}}}$. Evaporative cooling is

550

equal or lower than 6% in all the scenario except for ES-A and ES-B where it represents 7%

551

and 9%, respectively. This result proves that in the assessment of the energy performance of a

552

broiler house, the energy consumption for evaporative cooling can be neglected due to its

553

minor relevance, especially in cool climate conditions and in presence of low-insulated

554

envelopes.

555

Table 6 – Primary energy consumption embedded in a unit of mass (kg) of broiler meat ($E_{\text{meat}_p_{\text{glob}}}$) and shares due to heating, ventilation, and evaporative cooling.

556

Scenario	$E_{\text{meat}_p_{\text{glob}}}$ [kWh _p kg ⁻¹ _{meat}]	Heating [%]	Ventilation [%]	Evaporative cooling [%]
PL-A	4.5	81%	17%	2%
PL-B	3.1	71%	26%	3%

PL-C	6.6	87%	11%	2%
FR-A	2.4	72%	26%	2%
FR-B	1.7	57%	40%	3%
FR-C	3.5	82%	17%	1%
UK-A	3.1	79%	19%	2%
UK-B	2.0	66%	31%	3%
UK-C	4.5	87%	12%	1%
DE-A	4.0	80%	18%	2%
DE-B	2.7	70%	27%	3%
DE-C	5.8	87%	12%	1%
ES-A	2.7	51%	42%	7%
ES-B	2.1	36%	55%	9%
ES-C	3.6	64%	31%	5%
IT-A	3.4	70%	26%	4%
IT-B	2.5	56%	38%	6%
IT-C	4.8	79%	18%	3%


557 3.3 Financial evaluation

558 The previously presented scenarios are analysed from the financial point of view to
 559 understand the differences in terms of cost-benefit analysis. The global cost C_G of each
 560 scenario was estimated according to the methodology described in section 2.5.

561 In Fig. 9, the shares of C_G due to envelope, climate control system and energy of each
 562 considered scenario are presented in a stacked bar chart. The graph shows that the highest
 563 overall C_G is 714 € m^{-2} of DE-B scenario, while the lowest one is 272 € m^{-2} of PL-A
 564 scenario. These absolute values can be explained with a view on Table 4 since γ_{PLI} , C_{th} and
 565 C_{el} considerably affects the difference between countries. Germany, in fact, is characterized
 566 by the highest γ_{PLI} (1.67) that entails considerably higher C_I and C_a (due to climate control
 567 system replacement) than the other countries, especially, Poland where γ_{PLI} is only 0.78. A
 568 similar difference can be found analysing C_{th} and C_{el} that are the lowest ones for Poland
 569 ($0.04 \text{ € kWh}_{th}^{-1}$ and $0.15 \text{ € kWh}_{el}^{-1}$, respectively), while Germany is characterized by the
 570 highest C_{el} .

571 The results of the global cost analysis presented in Fig. 9 show that, in all the considered
 572 countries, type-B envelope is characterized by the highest C_G , while type-A and type-C
 573 envelopes are characterized approximatively by the same C_G , with a maximum relative
 574 difference of 8% (UK-A and UK-C scenarios). The relative difference between type-B

575 envelope and the other two types is considerable, being between 29% (IT-C) and 58% (UK-
 576 C). The stacks of the bar chart explain why type-B envelope is characterized by a
 577 considerably high C_G although it was characterized by the best primary energy performance,
 578 as previously showed in Fig. 7. The costs related to the building envelope, in fact, represent
 579 between 68% and 79% of C_G in the considered countries. The good energy performance of
 580 type-B envelope reflects on very low shares of C_G for energy (between 12% and 21%) but it
 581 is not enough to make type-B envelope a good option from the financial point of view. In this
 582 sense, type-A envelope could represent a good compromise since it is a solution that
 583 guarantee a favourable primary energy performance (considerably better than the one of type-
 584 C, as visible in Fig. 7) and a C_G similar to the one of type-C envelope, with a good impact
 585 form the financial sustainability point of view.




586
 587 **Fig. 9.** Global cost C_G and shares due to envelope, climate control system and energy for each of the analysed
 588 scenarios.

589 3.4 Comparison of indoor climate conditions

590 The free cooling systems with which broiler houses are usually equipped could be not able to
 591 maintain the required $\theta_{set,C}$ especially in warm season and broilers can be exposed to heat
 592 stress especially in presence of thermal insulated envelopes. For this reason, it is important to
 593 evaluate the envelope considering the indoor climate conditions to assure that low energy
 594 consumptions are not related to excessively poor indoor climate conditions.

595 For this purpose, the overheating index Ω_{OH} is calculated according to Eq. (4) for the
 596 considered scenarios and the results are presented in the bar chart of Fig. 10. From the bar

597 chart, it stands out that overheating problems are evident in the scenarios with the outdoor
598 weather conditions of Spain and Italy, while the other scenarios are characterized by low Ω_{oH} .
599 The minimum Ω_{oH} value is from UK-C scenario.
600 Through the bar chart of Fig. 10, the differences between the three types of envelope in the
601 same outdoor weather conditions in terms of Ω_{oH} can be assessed. In the same outdoor
602 weather conditions, the maximum Ω_{oH} come from the scenarios with type-B envelope, while
603 the minimum Ω_{oH} comes from the scenario with type-C envelope. The higher thermal
604 insulation of the type-B envelope, in fact, decreases the energy need for heating but does not
605 foster the heat losses through transmission, increasing the cooling need. During the warm
606 season (or in presence of high thermal load from the animals) these transmission heat losses
607 would decrease $\theta_{air,i}$ mitigating the overheating of the enclosure. In the scenarios
608 characterized by milder weather conditions (Spain and Italy), the relative difference between
609 the type-B envelope (with the maximum Ω_{oH}) and type-A and type-C envelopes (with the
610 minimum Ω_{oH}) is equal or less than 6%. In the scenarios with cooler outdoor weather
611 conditions, those differences are higher. The greatest difference is from United Kingdom
612 scenarios where the maximum relative difference between type-C and type-B is around 30%.
613 In all the other weather conditions this difference is always lower than 20%, but in absolute
614 terms, Ω_{oH} is low.



615
616

Fig. 10. Overheating index (Ω_{oH}) of the analysed scenarios.

617 **4 Conclusions**

618 In the present work, the best energy-efficient solution in terms of envelope for a typical
619 broiler house in the European context was identified in different scenarios. This identification
620 was performed through the assessment of the delivered energy consumption (state of the art)
621 and the primary energy consumption (new proposed approach). The results highlight that,
622 from the delivered and the primary energy points of view, a high-insulated envelope is
623 strongly recommended for all the analysed outdoor weather conditions, but it is not
624 sustainable from a financial point of view. This is because the financial savings due to the
625 reduction of energy consumption enhanced by the improved energy performance do not pay
626 back the high initial investment cost of the envelope. By contrast, a medium insulated
627 envelope could be interesting since is a compromise between a good energy performance and
628 a sustainable cost without increasing considerably the overheating of the enclosure.

629 The previous analyses lay the groundwork for future research into the energy efficiency of
630 livestock house through two main contributions. First, this work shows the importance of a
631 case-by-case design of the building envelope in improving the energy performance of broiler
632 houses, while in literature most of the works are focused on the improvement of climate
633 control systems. The second contribution relies in the methodology that is adopted in this
634 paper to evaluate the energy performance. The performed energy analyses are not limited to
635 the delivered energy consumed on farm, but they encompass the entire energy supply chain
636 adopting an approach based on primary energy. In this way, important issues can be
637 considered such as the energy losses along the energy supply chain of the considered energy
638 carrier and different energy mixes proper of the country. This last aspect is essential to
639 evaluate how the transition toward cleaner energy mixes undertaken by several countries
640 affects the sustainability of the livestock production. To do so, future works could further
641 deepen the energy analysis based on the primary energy approach to assess the share of
642 primary energy from renewable and non-renewable sources. That distinction would
643 considerably improve the assessment of the environmental sustainability of livestock
644 production. In addition, primary energy approach could represent the core of a new energy
645 certification scheme *ad-hoc* developed for livestock houses. It would represent the first step of
646 new legislation frameworks that, establishing minimum energy performances and incentive
647 systems, could boost to a cleaner livestock production through a top-down approach.

648

649 **Funding**

650 This research did not receive any specific grant from funding agencies in the public,
651 commercial or not-for-profit sectors.

652 **References**

- 653 Ahn, H.K., Sauer, T.J., Richard, T.L., Glanville, T.D., 2009. Determination of thermal properties of composting
654 bulking materials. *Bioresour. Technol.* 100, 3974–3981. <https://doi.org/10.1016/j.biortech.2008.11.056>
- 655 Allegretti, G., Talamini, E., Schmidt, V., Bogorni, P.C., Ortega, E., 2018. Insect as feed: An emergy assessment
656 of insect meal as a sustainable protein source for the Brazilian poultry industry. *J. Clean. Prod.* 171, 403–
657 412. <https://doi.org/https://doi.org/10.1016/j.jclepro.2017.09.244>
- 658 ANSI/ASHRAE, 2002. ASHRAE Guideline 14-2002 Measurement of Energy and Demand Savings. Ashrae.
659 ASHRAE, 2017. ASHRAE Handbook - Fundamentals (SI Edition), ASHRAE. Atlanta.
- 660 ASHRAE, 2012. 2012 ASHRAE Handbook: HVAC Systems and Equipment, ASHRAE. ASHRAE, Atlanta,
661 GA.
- 662 Axaopoulos, P., Panagakis, P., Axaopoulos, I., 2014. Effect of wall orientation on the optimum insulation
663 thickness of a growing-finishing piggery building. *Energy Build.* 84, 403–411.
664 <https://doi.org/10.1016/j.enbuild.2014.07.091>
- 665 Baxevanou, C., Fidaros, D., Bartzanas, T., Kittas, C., 2017. Energy Consumption and Energy Saving Measures
666 in Poultry. *Environ. Eng.* 5, 29–36. <https://doi.org/10.13189/eee.2017.050201>
- 667 Bilardo, M., Ferrara, M., Fabrizio, E., 2020. Performance assessment and optimization of a solar cooling system
668 to satisfy renewable energy ratio (RER) requirements in multi-family buildings. *Renew. Energy* 155, 990–
669 1008. <https://doi.org/https://doi.org/10.1016/j.renene.2020.03.044>
- 670 Castellini, C., Bastianoni, S., Granai, C., Bosco, A.D., Brunetti, M., 2006. Sustainability of poultry production
671 using the emergy approach: Comparison of conventional and organic rearing systems. *Agric. Ecosyst.*
672 *Environ.* 114, 343–350. <https://doi.org/https://doi.org/10.1016/j.agee.2005.11.014>
- 673 CEN, 2007. EN 15459:2007 - Energy performance of buildings - Economic evaluation procedure for energy
674 systems in buildings.
- 675 Choi, H.C., Salim, H.M., Akter, N., Na, J.C., Kang, H.K., Kim, M.J., Kim, D.W., Bang, H.T., Chae, H.S., Suh,
676 O.S., 2012. Effect of heating system using a geothermal heat pump on the production performance and
677 housing environment of broiler chickens. *Poult. Sci.* 91, 275–281. <https://doi.org/10.3382/ps.2011-01666>
- 678 Cobb, 2008. *Broiler Management Guide*. Siloam Springs, Arkansas (USA).
- 679 Costantini, M., Lovarelli, D., Orsi, L., Ganzaroli, A., Ferrante, V., Febo, P., Guarino, M., Bacenetti, J., 2020.
680 Investigating on the environmental sustainability of organic animal products? The case of organic eggs. *J.*
681 *Clean. Prod.* 123046. <https://doi.org/https://doi.org/10.1016/j.jclepro.2020.123046>
- 682 Costantino, A., Fabrizio, E., Biglia, A., Cornale, P., Battaglini, L., 2016. Energy Use for Climate Control of
683 Animal Houses: The State of the Art in Europe. *Energy Procedia* 101, 184–191.
684 <https://doi.org/10.1016/j.egypro.2016.11.024>
- 685 Costantino, A., Fabrizio, E., Ghiggini, A., Bariani, M., 2018. Climate control in broiler houses: A thermal model
686 for the calculation of the energy use and indoor environmental conditions. *Energy Build.* 169, 110–126.
687 <https://doi.org/10.1016/j.enbuild.2018.03.056>

- 688 Costantino, A., Fabrizio, E., Villagrà, A., Estellés, F., Calvet, S., 2020. The reduction of gas concentrations in
689 broiler houses through ventilation: Assessment of the thermal and electrical energy consumption. *Biosyst.*
690 *Eng.* <https://doi.org/10.1016/j.biosystemseng.2020.01.002>
- 691 Coulombe, F., Rousse, D.R., Paradis, P.-L., 2020. CFD simulations to improve air distribution inside cold
692 climate broiler houses involving heat exchangers. *Biosyst. Eng.* 198, 105–118.
693 <https://doi.org/https://doi.org/10.1016/j.biosystemseng.2020.07.015>
- 694 Dunkelberg, H., Wagner, J., Hannen, C., Schlüter, B.A., Phan, L., Hesselbach, J., Lin, C.-X., 2018. Optimization
695 of the energy supply in the plastics industry to reduce the primary energy demand. *J. Clean. Prod.* 192,
696 790–800. <https://doi.org/https://doi.org/10.1016/j.jclepro.2018.04.254>
- 697 E. Molenbroek, E. Stricker, T.B., 2011. Primary energy factors for electricity in buildings - Toward a flexible
698 electricity supply. Utrecht.
- 699 El Mogharbel, O., Ghali, K., Ghaddar, N., Abiad, M.G., 2014. Simulation of a localized heating system for
700 broiler brooding to improve energy performance. *Int. J. Energy Res.* 38, 125–138.
701 <https://doi.org/10.1002/er.3023>
- 702 European Commission, 2018. EPBD - Energy performance of buildings and Directive (EU) 2018/844. Off. J.
703 Eur. Union.
- 704 European Committee for Standardisation, 2018. EN ISO 13786: Thermal performance of building components --
705 Dynamic thermal characteristics -- Calculation methods, CEN.
- 706 European Committee for Standardisation, EN ISO, 2008. EN ISO 13790: Energy performance of buildings--
707 Calculation of energy use for space heating and cooling, CEN.
- 708 Eurostat, 2020a. Natural gas price statistics [WWW Document]. URL [https://ec.europa.eu/eurostat/statistics-](https://ec.europa.eu/eurostat/statistics-explained/index.php?title=Natural_gas_price_statistics)
709 [explained/index.php?title=Natural_gas_price_statistics](https://ec.europa.eu/eurostat/statistics-explained/index.php?title=Natural_gas_price_statistics) (accessed 2.16.21).
- 710 Eurostat, 2020b. Electricity price statistics [WWW Document]. URL [https://ec.europa.eu/eurostat/statistics-](https://ec.europa.eu/eurostat/statistics-explained/index.php/Electricity_price_statistics)
711 [explained/index.php/Electricity_price_statistics](https://ec.europa.eu/eurostat/statistics-explained/index.php/Electricity_price_statistics) (accessed 2.17.21).
- 712 Eurostat, 2019. Price level indices for construction and its components, 2019 [WWW Document]. URL
713 [https://ec.europa.eu/eurostat/statistics-](https://ec.europa.eu/eurostat/statistics-explained/index.php?title=File:Price_level_indices_for_construction_and_its_components,_2019_(EU-27%3D100)_update_December.png)
714 [explained/index.php?title=File:Price_level_indices_for_construction_and_its_components,_2019_\(EU-](https://ec.europa.eu/eurostat/statistics-explained/index.php?title=File:Price_level_indices_for_construction_and_its_components,_2019_(EU-27%3D100)_update_December.png)
715 [27%3D100\)_update_December.png](https://ec.europa.eu/eurostat/statistics-explained/index.php?title=File:Price_level_indices_for_construction_and_its_components,_2019_(EU-27%3D100)_update_December.png) (accessed 2.14.21).
- 716 Fabrizio, E., Airoidi, G., Chiabrando, R., 2014. Study of the environmental control of sow farrowing rooms by
717 means of dynamic simulation. *Lect. Notes Electr. Eng.* 263, 3–11. [https://doi.org/10.1007/978-3-642-](https://doi.org/10.1007/978-3-642-39578-9_1)
718 [39578-9_1](https://doi.org/10.1007/978-3-642-39578-9_1)
- 719 Fabrizio, E., Monetti, V., 2015. Methodologies and advancements in the calibration of building energy models.
720 *Energies* 8, 2548–2574. <https://doi.org/10.3390/en8042548>
- 721 FAO, 2011a. World Livestock 2011 - Livestock in food security, World. FAO, Rome.
- 722 FAO, 2011b. Energy-smart food for people and climate – Issue Paper. Rome.
- 723 Firfiris, V.K., Martzopoulou, A.G., Kotsopoulos, T.A., 2019. Passive cooling systems in livestock buildings
724 towards energy saving: A critical review. *Energy Build.* <https://doi.org/10.1016/j.enbuild.2019.109368>
- 725 French Ministry of Territorial Equality and Housing, 2011. Thermal regulation 2012: an energy leap for new
726 buildings (Réglementation thermique 2012: un saut énergétique pour les bâtiments neufs, French), *Journal*
727 *officiel de la République française.*

- 728 Gad, S., El-Shazly, M.A., Wasfy, K.I., Awany, A., 2020. Utilization of solar energy and climate control systems
729 for enhancing poultry houses productivity. *Renew. Energy* 154, 278–289.
730 <https://doi.org/https://doi.org/10.1016/j.renene.2020.02.088>
- 731 German Association of Energy and Water Industries (BDEW), 2015. Primary energy factors - the relationship
732 between primary energy and final energy in the energy evaluation (Primärenergiefaktoren - Der
733 Zusammenhang von Primärenergie und Endenergie in der energetischen Bewertung, in German). Berlin.
- 734 Heidari, M.D., Omid, M., Akram, A., 2011. Energy efficiency and econometric analysis of broiler production
735 farms. *Energy* 36, 6536–6541. <https://doi.org/https://doi.org/10.1016/j.energy.2011.09.011>
- 736 Hermelink, A.H., de Jager, D., 2015. Evaluating our future - The crucial role of discount rates in European
737 Commission energy system modelling.
- 738 Hörndahl, T., 2008. *Energy Use in Farm Buildings – A study of 16 farms with different enterprises Revised and*
739 *translated second edition*. Alnarp.
- 740 ISO, 2017a. ISO 52000-1:2017 Energy performance of buildings — Overarching EPB assessment — Part 1:
741 General framework and procedures. ISO.
- 742 ISO, 2017b. *Building components and building elements - Thermal resistance and thermal transmittance-*
743 *Calculation methods (ISO 6946:2017)*.
- 744 Italian Ministry of Economic Development, 2015. Interministerial Decree of 26 June 2015 - Application of the
745 methodologies for calculating energy performance and defining the prescriptions and minimum
746 requirements for buildings (Decreto interministeriale 26 giugno 2015 - Applicazione delle metodologie .
747 Italy.
- 748 Izar-Tenorio, J., Jaramillo, P., Griffin, W.M., Small, M., 2020. Impacts of projected climate change scenarios on
749 heating and cooling demand for industrial broiler chicken farming in the Eastern U.S. *J. Clean. Prod.* 255,
750 120306. <https://doi.org/https://doi.org/10.1016/j.jclepro.2020.120306>
- 751 Krstić-Furundžić, A., Vujošević, M., Petrovski, A., 2019. Energy and environmental performance of the office
752 building facade scenarios. *Energy* 183, 437–447.
753 <https://doi.org/https://doi.org/10.1016/j.energy.2019.05.231>
- 754 Manolakos, D., Panagakis, P., Bartzanas, T., Bouzianas, K., 2019. Use of heat pumps in HVAC systems for
755 precise environment control in broiler houses: System’s modeling and calculation of the basic design
756 parameters. *Comput. Electron. Agric.* 163. <https://doi.org/10.1016/j.compag.2019.104876>
- 757 Odum, H.T., 1995. *Environmental Accounting: Emery and Environmental Decision Making*. Wiley, New York
758 (USA).
- 759 Pimentel, D., Hurd, L.E., Bellotti, A.C., Forster, M.J., Oka, I.N., Sholes, O.D., Whitman, R.J., 1973. Food
760 production and the energy crisis. *Science* (80-). <https://doi.org/10.1126/science.182.4111.443>
- 761 Polish Ministry of Economy, 2014. *National Energy Efficiency Action Plan for Poland 2014*. Warsaw.
- 762 Roma, R., Corrado, S., De Boni, A., Forleo, M.B., Fantin, V., Moretti, M., Palmieri, N., Vitali, A., Camillo,
763 D.C., 2015. Life Cycle Assessment in the Livestock and Derived Edible Products Sector, in: *Life Cycle*
764 *Assessment in the Agri-Food Sector*. Springer International Publishing, pp. 251–332.
765 https://doi.org/10.1007/978-3-319-11940-3_5
- 766 Rossi, P., Gastaldo, A., Riva, G., de Carolis, C., 2013. *Re Sole Projet - Guidelines for the energy saving and*
767 *solar energy production in livestock facilities (Progetto Re Sole - Linee guida per il risparmio energetico e*

768 per la produzione di energia da fonte solare negli allevamenti zootecnici, in Italian). Reggio Emilia.
769 Spanish Ministry of Industry Energy and Tourism, 2016. CO2 emission factors and primary energy factors of
770 different energy sources used in the Spanish building sector (Factores de emisión de CO2 y coeficientes de
771 paso a energía primaria de diferentes fuentes de energía final consumidas en el sector de edifici,
772 Documento Reconocido del Reglamento de Instalaciones Térmicas en los Edificios (RITE).
773 <https://doi.org/10.1017/CBO9781107415324.004>
774 St-Pierre, N.R., Cobanov, B., Schnitkey, G., 2003. Economic Losses from Heat Stress by US Livestock
775 Industries. *J. Dairy Sci.* 86, E52–E77. [https://doi.org/10.3168/jds.s0022-0302\(03\)74040-5](https://doi.org/10.3168/jds.s0022-0302(03)74040-5)
776 Technical Institute of Poultry, 2010. Summary of propane and electricity consumption in poultry farming
777 (Synthèse des consommations de propane et d'électricité en aviculture, in French).
778 Van Horne, P.L.M., 2018. Competitiveness of the EU poultry meat sector, base year 2017 : international
779 comparison of production costs, Wageningen Economic Research REPORT.
780 <https://doi.org/10.18174/404949>
781 Vigne, M., Vayssières, J., Lecomte, P., Peyraud, J.-L., 2012. Evaluating the ability of current energy use
782 assessment methods to study contrasting livestock production systems. *J. Environ. Manage.* 112, 199–212.
783 <https://doi.org/https://doi.org/10.1016/j.jenvman.2012.07.017>
784