

Erratum: Integrated design strategy for EU-DEMO first wall protection from plasma transients (Fusion Engineering and Design (2022) 177, (113067) (S0920379622000679),

*Original*

Erratum: Integrated design strategy for EU-DEMO first wall protection from plasma transients (Fusion Engineering and Design (2022) 177, (113067) (S0920379622000679), (10.1016/j.fusengdes.2022.113067)) / Maviglia, F., Bachmann, C., Federici, G., Franke, T., Siccino, M., Albanese, R., Ambrosino, R., Arter, W., Bonifetto, R., Calabro, G., De Luca, R., Di Grazia, L.E., Fable, E., Fanelli, P., Fanni, A., Firdaouss, M., Gerardin, J., Lombroni, R., Mattei, M., Moscheni, M., et al.. - In: FUSION ENGINEERING AND DESIGN. - ISSN 0920-3796. - ELETTRONICO. - 178:(2022), p. 113125.

[10.1016/j.fusengdes.2022.113125]

*Availability:*

This version is available at: 11583/2964840 since: 2022-05-27T18:57:32Z

*Publisher:*

Elsevier Ltd

*Published*

DOI:10.1016/j.fusengdes.2022.113125

*Terms of use:*

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

*Publisher copyright*

(Article begins on next page)

Contents lists available at [ScienceDirect](https://www.sciencedirect.com)

## Fusion Engineering and Design

journal homepage: [www.elsevier.com/locate/fusengdes](http://www.elsevier.com/locate/fusengdes)

## Integrated design strategy for EU-DEMO first wall protection from plasma transients Fusion Engineering and Design 177 (2022) 113067

Francesco Maviglia<sup>a,b,\*</sup>, Christian Bachmann<sup>a,n</sup>, Gianfranco Federici<sup>a</sup>, Thomas Franke<sup>a,c</sup>, Mattia Siccinio<sup>a,c</sup>, Raffaele Albanese<sup>d</sup>, Roberto Ambrosino<sup>d</sup>, Wayne Arter<sup>m</sup>, Roberto Bonifetto<sup>e</sup>, Giuseppe Calabrò<sup>f</sup>, Riccardo De Luca<sup>f</sup>, Luigi E. Di Grazia<sup>o</sup>, Emiliano Fable<sup>c</sup>, Pierluigi Fanelli<sup>f</sup>, Alessandra Fanni<sup>g</sup>, Mehdi Firdaouss<sup>h</sup>, Jonathan Gerardin<sup>i</sup>, Riccardo Lombroni<sup>f</sup>, Massimiliano Mattei<sup>d</sup>, Matteo Moscheni<sup>e</sup>, William Morris<sup>m</sup>, Gabriella Pautasso<sup>c</sup>, Sergey Pestchanyi<sup>l</sup>, Giuseppe Ramogida<sup>b</sup>, Maria Lorena Richiusa<sup>m</sup>, Giuliana Sias<sup>g</sup>, Fabio Subba<sup>e</sup>, Fabio Villone<sup>d</sup>, Jeong-Ha You<sup>c</sup>, Zsolt Vizvary<sup>m</sup>

<sup>a</sup> EUROfusion – Programme Management Unit, Boltzmannstrasse 2, 85748 Garching, Germany

<sup>b</sup> Associazione EURATOM-ENEA sulla Fusione, C.R. Frascati, C.P. 65-00044 Frascati, Rome, Italy

<sup>c</sup> Max-Planck-Institut für Plasmaphysik, Garching, Germany

<sup>d</sup> Consorzio CREATE, Univ. Napoli Federico II - DIETI, 80125 Napoli, Italy

<sup>e</sup> NEMO Group, Dip. Energia, Politecnico di Torino, C.so Duca degli Abruzzi24, Torino 10129, Italy

<sup>f</sup> DEIm Department, University of Tuscia, Largo dell'Università, 01100 Viterbo, Italy

<sup>g</sup> Electrical and Electronic Engin. Dept.-University of Cagliari, Piazza D'Armi, 09123, Cagliari, Italy

<sup>h</sup> CEA, F-13108 St Paul-Lez-Durance, France

<sup>i</sup> Institute of Plasma Physics, Czech Academy of Sciences, Prague, Czech Republic

<sup>l</sup> KIT, Hermann-von-Helmholtz-Platz 1, Eggenstein-Leopoldshafen, Germany

<sup>m</sup> CCFE, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK

<sup>n</sup> Technical University of Denmark, Lyngby, Denmark

<sup>o</sup> Consorzio CREATE, Univ. della Campania L. Vanvitelli, Dip. Ingegneria, 80131 Aversa, Italy

The publisher regrets that [Table 1](#) has the wrong formatting. The correct version of the table is hereafter reported:

DOI of original article: <https://doi.org/10.1016/j.fusengdes.2022.113067>.

\* Corresponding author.

E-mail address: [francesco.maviglia@euro-fusion.org](mailto:francesco.maviglia@euro-fusion.org) (F. Maviglia).

<https://doi.org/10.1016/j.fusengdes.2022.113125>

Available online 2 April 2022

0920-3796/© 2022 The Author(s). Published by Elsevier B.V. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).

**Table 1**

Summary of all the plasma steady state and transient cases analyzed. The results, in the Output columns, show the HF due to charged particles (in MW/m<sup>2</sup>, while in **bold** are indicated in GW/m<sup>2</sup>), evaluated with 3D field-line tracing codes (except the mitigated disruption where, instead, the photonic radiation, including toroidal and poloidal peaking factors, is reported). For the SOF and EOF are indicated in brackets, in *italic*, the HF including the radiation. \*represents a D-VDE with the plasma shifted downwards (conservative). A subset of critical cases, in the output columns, is indicated with a superscript number within brackets

Inputs					Outputs: max HF (MW/m <sup>2</sup> ) <i>(Italic): with radiation, Bold: GW/m<sup>2</sup></i>				
Scenario	Case	P <sub>SOL</sub> (MW) +(P <sub>RAD</sub> )	λ <sub>q</sub> (mm)	Deposition time	OML	UL	OLL	IML	FW
<a href="#">SOF</a>	Diverted	69 +(300 core + 130 SOL)	50	Steady state	0.53 <i>(0.65)</i>	0.82 <i>(1.10)</i>	0.09 <i>(0.33)</i>	0 <i>(0.19)</i>	0.40 <i>(0.59)</i>
<a href="#">EOF</a>	Diverted	69 +(300 core + 130 SOL)	50	Steady state	0.54 <i>(0.74)</i>	1.25 <i>(1.42)</i>	0.1 <i>(0.36)</i>	0.9 <i>(1.11)</i>	0.48 <i>(0.67)</i>
Min disr	Diverted	69	50	15-50ms	<0.01	0.13	0.01	3.06	0.69
ELM	Diverted	69	50	15-50ms	1.40	0.56	0	0	1.48
<a href="#">Ramp-Up</a>	Limited	3.5	6	17.5-35s	2.37	0	0	0	0.29
<a href="#">Ramp-Down</a>	Limited	5	6	25-50s	<0.01	<0.01	<0.01	0.02	0.01
		5	50	25-50s	<0.01	<0.01	<0.01	1.39	0.60
U-VDE	<a href="#">First touch</a>	69	1	20-35ms	<0.01	114 <sup>(2)</sup>	<0.01	0	0
		69	5	20-35ms	<0.01	15.6	<0.01	0	0.02
	<a href="#">TQ</a>	325·10 <sup>3</sup>	7	1-4ms	<0.01	<b>63</b> <sup>(3)</sup>	0	<0.01	138 <sup>(8)</sup>
	<a href="#">Current Quench</a>	10	10	74-200ms	<0.01	2.52	0	<0.01	0.01
		10	30	74-200ms	<0.01	1.53	0	<0.01	0.11
D-VDE	<a href="#">First touch</a>	10 (*69)	10 (*1)	15-35ms	<0.01 <i>(*0.01)</i>	0 <i>(*0)</i>	<0.01 <i>(*24.8)</i>	<0.01 <i>(*&lt;0.01)</i>	<0.01 <i>(*&lt;0.01)</i>
		10 (*69)	30 (*5)	15-35ms	<0.01 <i>(*0.01)</i>	0 <i>(*0)</i>	<0.01 <i>(*7.83)</i>	<0.01 <i>(*&lt;0.01)</i>	0.08 <i>(*0.01)</i>
	<a href="#">TQ</a>	325·10 <sup>3</sup>	7	1-4ms	0.77 <i>(*182)</i> <sup>(1)</sup>	0 <i>(*0)</i>	<b>4.4</b> <i>(*306)</i> <sup>(4)</sup>	0.84 <i>(*11.3)</i>	8.11 <i>(*292)</i> <sup>(9)</sup>
	<a href="#">Current quench</a>	10	10	74-200ms	<0.01	<0.01	<0.01	<0.01	<0.01
		10	30	74-200ms	<0.01	<0.01	<0.01	<0.01	<0.01
H-L transition	<a href="#">Limited (inboard)</a>	30	2	1-5s	<0.01	<0.01	<0.01	64 <sup>(5)</sup>	1.06
		30	4	1-5s	<0.01	<0.01	<0.01	44.5 <sup>(6)</sup>	5.48
Major Disruption (MD)	<a href="#">TQ</a>	325·10 <sup>3</sup>	7	1-4ms	0.61	1.46	0.84	<b>1.44</b> <sup>(7)</sup>	333 <sup>(10)</sup>
	<a href="#">CQ</a>	10	10	74-200ms	<0.01	<0.01	<0.01	0.01	<0.01
		10	30	74-200ms	<0.01	<0.01	<0.01	0.21	0.05
Mitig. disr.	TQ	P <sub>RAD.</sub> : 2.2 GW		1ms	<b>2</b> <sup>(11)</sup>	<b>1.8</b> <sup>(11)</sup>	<b>1.8</b>	<b>1.5</b>	<b>2</b> <sup>(11)</sup>

The publisher would like to apologise for any inconvenience caused.