

Performance study of a thin cation exchange membrane for water based supercapacitor applications

Original

Performance study of a thin cation exchange membrane for water based supercapacitor applications / Molino, D., Pedico, A., Zaccagnini, P., Lamberti, A., Bocchini, S.. - (2023). (IWES 2023 - Second Italian Workshop on Energy Storage Bressanone (ITA) 25/01/2023 - 27/01/2023).

Availability:

This version is available at: 11583/2975480 since: 2023-02-01T10:32:26Z

Publisher:

MDPI

Published

DOI:

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)



Performance study of a thin cation exchange membrane for water based supercapacitor applications

Davide Molino,^a Alessandro Pedico,^a Pietro Zaccagnini,^{a,b} Andrea Lamberti,^{a,b} Sergio Bocchini^b

^a DISAT Dipartimento di Scienza Applicata e Tecnologia, Politecnico di Torino, corso Duca degli Abruzzi 24, 10129, Torino, Italy

^b Istituto Italiano di Tecnologia, Center for Sustainable Future Technologies, Via Livorno 60, 10144, Torino, Italy

davide.molino@polito.it



Politecnico di Torino

Background

A novel method to modify **activated carbon electrodes** through addition of **selective ion exchange polymers (IEM)** is presented. Nowadays the preferred method to self-polarize an electrode in an EDLC is to place a stand-alone membrane in proximity of the electrode itself [1, 2]. This technique produces some drawbacks brought about the dimension of the device: an increase of the internal series resistance and reduction of overall capacitance. With the proposed methods, it is possible to use the IEM **directly in the production** of the slurry (instead of traditional binders) or in a **conformal contact** with the electrode.

Electrode fabrication




Negative electrode:

- SPEEK binder
- Melted SPEEK casted over AC, dried under vacuum


Positive electrode:

- PVDF binder
- No infiltrated IEM


3 Electrodes measurements




Device measurements



IEM as binder



IEM as conformal coating



Conclusions

- Newly proposed coating procedure to obtain thin membrane over carbon based materials
- Substitution of standard binder and improvement of the adhesion performances for supercapacitor electrode application
- Use of CEM in thin film over a carbon based electrode resulting in an enlargement in operating voltage window, increase in coulombic efficiency and reduction of ESR

Future outlooks

- Combination of SPEEK modified electrode with a AEM modified electrode
- Test the device inside a Capmix or RED cell

ACKNOWLEDGEMENT: This result is part of a project that has received funding from the European Research Council (ERC) under the European Union's ERC Starting Grant. Grant agreement "CO2CAP" No. 949916

Bibliography:

- [1] Sales, Bruno B., et al. <<Electrochemical characterization of a supercapacitor flow cell for power production from salinity gradients>> *Electrochimica acta*, 86 (2012) 298-304
- [2] Wang, Xingfeng, et al. <<A 1.8 V aqueous supercapacitor with a bipolar assembly of ion-exchange membranes as separator>> *Journal of The Electrochemical Society*, 163.9 (2016): A1853