

New and Emerging Directions in the Fields of Antennas and Propagation

Original

New and Emerging Directions in the Fields of Antennas and Propagation / Pichot, Christian; Huff, Gregory H.; Yang, Yang; Jiang, Zhi Hao; Tong, Xuanfeng; Loh, Tian Hong; Alemaryeen, Ala; Wagih, Mahmoud; Noghanian, Sima; Paryani, Rajesh C.; Huang, Yi; Sakakibara, Kunio; Vipiana, Francesca; Fear, Elise; Bakshi, Saikat Ch.; Waterhouse, Rod; Urbina, Julio; Meinrath, Sascha D.; Shih, Bono Po-Jen; Sharma, Rohit; Manohar, Vignesh; Dagefu, Fikadu T.; Ito, Koichi. - In: IEEE TRANSACTIONS ON ANTENNAS AND PROPAGATION. - ISSN 0018-926X. - 73:1(2025), pp. 566-581.

[10.1109/tap.2024.3514092]

Availability:

This version is available at: 11583/3009274 since: 2026-03-27T08:16:21Z

Publisher:

IEEE

Published

DOI:10.1109/tap.2024.3514092

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

IEEE postprint/Author's Accepted Manuscript

©2025 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collecting works, for resale or lists, or reuse of any copyrighted component of this work in other works.

(Article begins on next page)

New and Emerging Directions in the Fields of Antennas and Propagation

Ch. Pichot, *Life Fellow, IEEE*, G. H. Huff, *Senior Member, IEEE*, Y. Yang, *Senior Member, IEEE*, Z. H. Jiang, *Member, IEEE*, X. Tong, *Graduate Student Member, IEEE*, T. H. Loh, *Senior Member, IEEE*, A. Alemarween, M. Wagih, *Member, IEEE*, S. Noghianian, *Senior Member, IEEE*, R. C. Paryani, *Member, IEEE*, Y. Huang, *Fellow, IEEE*, K. Sakakibara, *Senior Member, IEEE*, F. Vipiana, *Senior Member, IEEE*, E. Fear, *Senior Member IEEE*, S. C. Bakshi, *Senior Member, IEEE*, R. Waterhouse, *Fellow, IEEE*, J. Urbina, *Senior Member, IEEE*, S. Meinrath, B. P-J. Shih, *Member, IEEE*, R. Sharma, *Senior Member, IEEE*, V. Manohar, *Member, IEEE*, F. T. Dagefu, *Senior Member, IEEE*, and K. Ito, *Life Fellow, IEEE*

Abstract— In this invited paper, the New Technology Directions Committee (NTDC) of the IEEE Antennas and Propagation Society (AP-S) presents new and emerging research directions to commemorate the 70th anniversary of the *IEEE Transactions on Antennas and Propagation*. The NTDC consists of three Working Groups (WGs); members and collaborators of these groups provide their perspectives on topics related to WG themes in this paper. WG-1 focuses on advancement of materials and manufacturing processes for future antenna applications. WG-2 focuses on advances in communications, sensing and imaging. WG-3 focuses on maximizing the societal impact of wireless connectivity. The discussion in this paper ranges from additive manufacturing techniques and system integration to advanced communications and quantum-based sensing technologies. Numerous applications are explored and a perspective on the digital divide is offered.

Index Terms— Additive manufacturing, circuits/antennas integration, intelligent surfaces, wearable/implanted antennas, mobile communications, sub-THz antennas, microwave medical imaging, quantum sensing, wireless connectivity, digital divide, heterogeneous integration, wireless network security

Manuscript received January **, 2024.

Christian Pichot is with the Electronics, Antennas, and Telecommunications Laboratory, Université Côte d'Azur, France (e-mail: christian.pichot@univ-cotedazur.fr).

Gregory H. Huff, Julio Urbina, and Rohit Sharma are with the Department of Electrical Engineering at Pennsylvania State University, PA 16802 USA (e-mail: ghuff@psu.edu, juv1@psu.edu, and rys5498@psu.edu).

Yang Yang is with School of Electrical and Data Engineering, University of Technology Sydney, Australia (e-mail: yang.yang.au@ieee.org).

Zhi Hao Jiang, and Xuanfeng Tong are with the State Key Laboratory of Millimeter Waves, Southeast University, China (e-mail: zhihao.jiang@seu.edu.cn, and xuanfengtong@seu.edu.cn).

Tian Hong Loh is with the National Physical Laboratory, Teddington, UK (e-mail: tian.loh@npl.co.uk).

Ala Alemarween is with the Department of Communication and Computer Engineering, Tafila Technical University, Jordan (e-mail: ala.alemareween@ttu.edu.jo).

Mahmoud Wagih is with the James Watt School of Engineering, University of Glasgow, UK (e-mail: mahmoud.wagih@glasgow.ac.uk).

Rajesh C. Paryani is with Northrop Grumman Mission Systems, MD 21240 USA (e-mail: Rajesh.Paryani@ngc.com).

Yi Huang is with the Department of Electrical Engineering & Electronics, University of Liverpool, UK (e-mail: yi.Huang@liverpool.ac.uk).

I. INTRODUCTION

IN celebration of the 70th anniversary of the *IEEE Transactions on Antennas and Propagation (T-AP)*, the Editor-in-Chief invited the New Technology Directions Committee (NTDC) of AP-S to contribute this article highlighting potential future directions and emerging technologies. In 2022, the NTDC Chair, Koichi Ito, established three Working Groups (WGs) within the committee related to new and upcoming areas/fields within AP-S.

Advancement of materials and manufacturing processes for future antenna applications is the focus of WG-1 (Lead: Katherine Duncan). This area can be broadly categorized into six themes, namely (1) Additive manufacturing for radio frequency (RF) and microwave applications, (2) Antenna and microwave circuit design/integration, (3) Intelligent surfaces, (4) Nano-optical antennas, (5) New materials for antennas, and (6) Wearable/implantable devices, as discussed below:

- *Additive manufacturing (AM) technologies* have attracted a

Kunio Sakakibara is with the Graduate School of Engineering, Electrical and Mechanical Engineering, Nagoya Institute of Technology, Japan (e-mail: sakaki@nitech.ac.jp).

Francesca Vipiana is with the Department of Electronics and Telecommunications, Politecnico di Torino, Italy (e-mail: francesca.vipiana@polito.it).

Elise Fear is with the Department of Electrical and Software Engineering, University of Calgary, Canada (e-mail: fear@ucalgary.ca).

Saikat C. Bakshi is with the National Institute of Technology Calicut, India (e-mail: saikatbakshi@nitc.ac.in).

Rod Waterhouse is with Octane Wireless, Hanover, MD 21076 USA (e-mail: rwaterhouse@octanewireless.com).

Bono Po-Jen Shih is with the Rock Ethics Institute and Leonhard Center for Enhancement of Engineering Education at Pennsylvania State University, PA 16802 USA (e-mail: bps5848@psu.edu).

Sima Noghianian is with CommScope Ruckus Networks, CA 94089 USA (e-mail: sima_noghianian@ieee.org).

Vignesh Manohar is with Delart Technologies Corp., Mississauga, Ontario, Canada (e-mail: vignesh@delartech.com).

Sascha Meinrath is with the Department of Telecommunications at Pennsylvania State University, PA 16802 USA (e-mail: sascha@psu.edu).

Fikadu T. Dagefu is with the U.S. DEVCOM Army Research Laboratory, MD 20783 USA (e-mail: fikadu.t.dagefu.civ@army.mil).

Koichi Ito is with the Center for Frontier Medical Engineering, Chiba University, Japan (e-mail: ito.koichi@faculty.chiba-u.jp)

surge of interest for their potential to achieve antenna devices with performance beyond what is possible with conventional processes, along with reduced cost and time required for fabrication.

- *Increased degrees of integration* have been required of wireless systems to address both growing demands on system functionality and required reductions in form factor. Example techniques include combining RF/microwave devices, and the reduction or elimination of standalone interconnects by use of fabrication or packaging processes that enable the co-location of sensors and processing components.
- *Reconfigurable intelligent surfaces (RIS)*, also known as intelligent reflecting surfaces, can enable improved control of RF signals between a transmitter and a receiver. RIS have been proposed for dynamic operation while meeting specified goals and maintaining this performance in complex and varying wireless channels.
- *Wearable/implanted devices* are an enabling technology that can provide better health care, seamless communication, enhanced performance in sports, and new and improved products in defense and consumer electronics.

Advances in communications, sensing and imaging is the focus of WG-2 (Lead: Christian Pichot). WG-2 focuses on 5 themes: (1) Mobile communications systems, (2) Sub-THz and mm-wave technologies, (3) Microwave systems and technologies for medical applications, (4) Application of machine learning to inverse problems, and (5) Quantum-based electromagnetic sensing technologies, as discussed below:

- The evolution of *mobile communications* has been tremendous since the first-generation (1G) mobile network was introduced. Communications systems continue rapid advancement with the development of the sixth-generation (6G) and beyond. Recent trends such as joint communication and sensing demand innovation in antenna designs.
- *Millimeter-wave (mm-wave) and terahertz (THz) technologies* are expected to play a role in the development of high-bit-rate wireless communication systems and high-resolution sensing systems. Challenges extend from antenna design to material selection and implementation.
- *Microwaves for medical diagnostic radiology* have been the subject of numerous R&D efforts for many years, including the advancements exploiting magnetic nanoparticles and magnetic fluids. After three decades of promising proofs-of-concept supported by numerical simulations and laboratory experiments on phantoms, microwave diagnostics for medical applications have finally entered a translational era, thanks to a handful of spin-off companies from academia that have succeeded in developing advanced prototypes.
- *Machine Learning (ML) and Artificial Intelligence (AI)* are expected to continue to advance techniques for addressing inverse problems.
- *The area of quantum antennas (q-antennas)* is actively researched for possible implementation in quantum communications, quantum imaging and sensing, which could revolutionize communications and sensing.

Maximizing the societal impact of wireless connectivity is the focus of WG-3 (Lead: Gregory Huff). Guided by the notion that new antenna technologies and systems are critical for

maximizing the societal impact of wireless connectivity, the goals of WG-3 are to: (1) Investigate strategies and collaborative opportunities that enable insight into current and emerging societal needs for wireless connectivity, (2) Identify both technical and societal challenges that may impact the development, deployment, and adoption of new technologies for wireless connectivity, and (3) Enhance the current landscape of outreach opportunities (e.g. conferences, workshops, etc.) with new activities that seek to operationalize societal-driven initiatives that promote the advancement, socialization, and dissemination of new technologies for wireless connectivity.

These goals bring stakeholders from public policy and social science together with communities pioneering new antenna technologies for the Internet of Space (IoS), energy-efficient antenna systems, Next-G Technologies, spectrum access and utilization techniques, and wireless power transfer and energy harvesting systems.

In this paper, Section II highlights new technologies related to WG-1, Section III presents WG-2's views on emerging directions related to communications, sensing and imaging, and Section IV summarizes important aspects of the impact of wireless connectivity on our community at large. Finally, Section V summarizes the discussion.

II. ADVANCEMENT OF MATERIALS AND MANUFACTURING PROCESSES FOR FUTURE ANTENNA APPLICATIONS

A. Additive Manufacturing for Antennas

AM antennas can be categorized into three groups in terms of fabrication materials: metal-only, [1], [2], dielectric-only [3], and conductive and dielectric multi-material antennas [4].




Fig. 1. Additively manufactured metasurfaces with seven metal layers in a single substrate. Blind vias are 3D printed for interconnecting phase delay lines among the transmitting/receiving antennas at the top/bottom surfaces [10].

1) Additively Manufactured Metal-Only Antennas

Popular metal printing techniques used for antenna prototyping include Direct Metal Laser Sintering (DMLS) and Selective Laser Melting (SLM), which can prototype complex antenna structures using metal powders melted by lasers. Metal printers can be used to prototype entire microwave devices without the need to assemble components, thus potentially avoiding interconnection loss. Metal printing also enables the prototyping of increasingly complex three-dimensional (3D) structures that were previously unrealizable, such as metamaterials [5], power combiners [1], and antennas [2].

2) Additively Manufactured Dielectric-Only Antennas

Dielectric-only 3D printing plays a dominant role in consumer electronics, where state-of-the-art techniques

including fused deposition modeling (FDM), continuous liquid interface production (CLIP), aerosol jet printing, and piezoelectric inkjet. Each of these techniques have their specific advantages. As a cost-effective solution, FDM has been widely adopted for prototyping low-cost, high-performance reflectarrays, polarizers, lens antennas, and transmitarrays. Dielectric-only printing techniques have also been applied to design metallic waveguides/antennas with the addition of post-metalizing operations [6].

3) Additively Manufactured Multi-Material Antennas

Conductive and dielectric multi-material 3D printing is an emerging process and presents vast potential for innovative new antenna designs. Multi-material AM techniques use more than one printing head for conductive and dielectric inks. Multi-material printers can seamlessly sinter conductive and dielectric inks for prototyping PCB-like circuit boards. This process enables multiple metallic layers to be printed in a single substrate while offering unique design capabilities, such as flexible/dynamic spacing between metal layers, printable vias and through holes, conformal/non-planar surfaces, and vertically designed circuit/antenna elements. This approach is ideal for antenna-in-package (AiP) manufacture, as well as large and complex antenna arrays/metasurfaces that can offer exceptional beam-shaping performance [7]. Demonstrated designs include circuit components [8], patch arrays [9], a dual-band Fresnel Zone plate lens antenna [4], and the metasurfaces [10] which are highlighted in Fig. 1.

B. Integration of Microwave Circuits and Antennas

Wireless systems for beyond fifth-generation (B5G) and sixth-generation (6G) communications require considerable increases in levels of integration. Some of the B5G operation will occur at much shorter wavelengths than the sub-6 GHz predecessors, so conventional connection solutions between antennas and front-end circuits are no longer suitable. The border between the antennas and circuit topologies are increasingly blurred as the entire front-end sub-system must be considered to improve the impedance matching, minimize the footprint, and enhance the overall performance [11]. This presents a major shift for microwave researchers who have traditionally been committed to designing single-packaged devices, e.g., antenna-in-package, filter-in-package, *etc.* A growing number of researchers in the community have been devoted to the integration and co-design of multiple components as a single module. For example, filters and antennas [12], as well as filters and amplifiers [13], can be seamlessly combined to realize performance improvements compared to direct cascading of these components. Increasing levels of co-design will become necessary for B5G systems.

One primary area of interest is the integration of antennas and passive circuits located at the system's front end. A common example is the *filtenna* [14], formed by merging a radiator and frequency-selective circuit into a single component. This not only eliminates the mismatch between the radiator and filter but also improves the frequency selectivity and reduces the overall footprint. More recently, new methods for realizing filtennas

have been proposed, including exploiting reverse-phase currents on the radiator [15] and engineering transmission zeros of the antenna from the equivalent circuit perspective [16], which facilitates further miniaturization. The co-design of antennas and other types of circuits, such as diplexers [17] have also been carried out for satellite and space applications.

Another emerging technology trend with increased focus is the co-design and integration of antennas with silicon-based transceiver/beamforming chips. This is largely in response to enabling beam scanning functionalities required in B5G applications with a technology that is consistent with mass product electronics development [18]. Integrated phased array modules are evolving towards low-cost and high performance at a faster pace than ever, with characteristics adapted to platforms ranging from base stations [19], small satellites [20] and mobile terminals [21]. Moreover, highly integrated systems have also been developed for radars [21] and biomedical sensing [22]. These innovations suggest a major shift in antenna research towards systems-centric, multi-disciplinary exploration of antenna-integrated components and systems.

C. Intelligent Surfaces

RIS can be broadly categorized as engineered materials with configurable electromagnetic properties due to the inclusion of integrated electronic circuits and/or software that enables control of the wireless environment, where the latter aspect is known as software-controlled metasurfaces [23]. The principle of operation is based on the generalization of Snell's law. Specifically, energy from a plane wave incident onto the RIS is scattered with spatially inhomogeneous phase shifts that are tailored to produce the desired reflection characteristics. RIS present the potential to manipulate the electromagnetic properties of a wireless propagation environment. This may enable wireless channels to be optimized to maximize the overall system performance, including channel capacity, coverage, positioning, security, and sustainability.

A summary of concepts and realizations for a smart radio environment has been presented in [24]. This includes diverse application scenarios from media-sharing Wi-Fi systems to mm-wave, THz, and even optical communications. Recent examples of RIS prototypes have been presented covering a wide range of frequencies [24], [25]. Several papers have discussed the challenges and relevant research opportunities, as well as future perspectives for RIS [24], [26]-[32].

D. Wearable and Implanted Antennas and Sensors

Wearable and implanted antennas/sensors have experienced a revolution in applications, fabrication techniques, and design methodologies (Fig. 2). In general, implanted antennas and sensors refer to a system that is located inside the human body. The system may be injected [33], placed via surgery [34], or swallowed as an ingestible system [35].

1) Applications

New and emerging applications for wearable antennas and sensors include biomedical sensing and monitoring [42], human-centric Internet of Things and Wi-Fi devices [43], wearable connectivity [44], environmental monitoring and

tracking [45], and wireless power transmission (WPT) [38]. Implantable antennas have found widespread applications in biomedical sensing and monitoring [46], WPT [47], body-centric communications [48], pacemakers [49], RF identification (RFID) [50], wireless capsule endoscopy [51], drug delivery [52], and biotelemetry [53].

2) Wireless Power Harvesting and Transfer

Flexible, conformable, and textile-based wearables cannot rely on rigid batteries. RF wireless power has an inherent advantage over other energy harvesting technologies, as exotic materials are not required. Instead, conductors are used to realize the rectennas or coils [54]. Wearable rectennas closely followed the development of textile antennas, with rectifiers first implemented on flexible textile substrates in [55]. It has been demonstrated that textiles, despite being lossy ($\tan \delta > 0.01$), can still achieve best-in-class RF to DC conversion efficiencies, outperforming or matching those provided by rigid systems [54]. As materials for RF power transfer and harvesting continue to develop, ecological sustainability needs to be considered from a life cycle assessment perspective [56].

Implants need to be maintenance-free or remain reliable via a wireless approach in circumstances where intermittent energy harvesting sources are not available [57]. Wirelessly powered implants enable minimally invasive optogenetics [34] and closed-loop stimulation [58]. In systems using radiative sources, body-matched antennas are key components for both implantable power transfer and communication [59].




Fig. 2. Wearable and implanted antenna research topics: (a-b) Flexible conformal antennas [36],[71], (c-d) All-textile wireless power transfer [37], (e) Bio-based substrate material [38], (f) Breast phantom [39], (g) Breast tissue measurement [69], (h) Embroidery of E-threads [40], (i) Human body electromagnetic modeling [36], (j) Specific absorption rate analysis [36], [41].

3) Materials and Fabrication Technologies

Emerging materials are crucial for retaining the flexibility, reliability, stretchability, mechanical stability, and energy efficiency of wearable antennas. Examples include smart textile [60], flexible [61], biodegradable [62]-[63], and polymer-based materials [64]. Fabrication technologies are key drivers impacting the manufacturability and achievable performance of low-cost wearable antenna prototypes. Several fabrication techniques have been reported for the realization of wearable antennas, including substrate integrated waveguide (SIW) based technology [65], embroidery [66], inkjet printing [67], screen printing [68], and adhesive [36] methods.

Implanted antennas face additional stringent requirements such as biocompatibility, patient safety, and miniaturization, posing challenges for practical antenna fabrication and implementation [70]. Several techniques have been explored for this application, including using biocompatible materials for antenna fabrication such as Kapton [71], coating the antenna with a thin layer of a biocompatible material such as silicon [72], and encapsulating the antenna with a layer of a biocompatible material such as Ceramic Alumina [73].

In addition, agile-tunable materials such as ferrites, ferroelectrics, and multiferroics hold great potential for future intelligent antenna and medical applications. Their unique properties and dynamic tunability make them ideal for smart antennas used in biomedical and sensing applications. Ongoing research and innovation in this field is expected to lead to the development of new, high-performance antennas that will significantly impact future intelligent wireless devices.

E. Future Perspectives and Challenges

Future directions for additively manufactured antenna applications involve designing antennas using multi-material 3D printing processes. Currently, commercially available 3D printing systems are restricted to specific materials and face significant challenges, such as multi-material adhesion and heteromaterial integration. Despite these obstacles, integrating the printing of both conductive and dielectric materials within the same processing system offers a promising solution for microwave circuits and antenna integration.

Future technological advancements in RIS include sustainable and low-cost hardware implementation, compensating for possible performance degradation due to limited-precision RIS elements, integrating renewable energy sources to reduce power consumption, developing low-complexity RIS architectures for practical deployment, AI-based designs, and hybrid transceivers for RIS-assisted systems.

For wearable antennas, future challenges in integrating antennas within clothing include identifying cost-effective manufacturing techniques and materials suitable for both antennas and everyday objects. Other considerations include durability and ease of integration with other electronic systems. Future directions encompass the development of multifunctional and reconfigurable antennas [74], fabrication reliability [75], washability [76], testing standards, safety and regulations, security, and ML approaches to design antennas that interact with the body. Future research and development directions for implantable antenna systems include miniaturization [72], the use of metasurfaces/metamaterials [77], biocompatible/biodegradable materials [63], integration [52], and establishing safety and standards [78].

III. ADVANCES IN COMMUNICATIONS, MICROWAVE SYSTEMS FOR MEDICAL APPLICATIONS AND QUANTUM SENSING TECHNOLOGIES

A. Mobile Communications

Mobile communications have undergone rapid development over the past 30 years. Cellular radio systems have evolved from 2G to 5G, and smartphones have become an essential part of our daily lives. This is partially due to the

significant progress in antennas: here are now at least 10 antennas inside a standard smartphone. This is still a very exciting and energetic area, with new functions and applications are emerging more rapidly than expected. For example, the latest Huawei Mate-60-pro smartphone can directly communicate with the geostationary satellite Tiantong 1 which is 36,000 km above the Earth [79], representing a significant development in mobile antennas. In addition, Starlink has been working with mobile service providers (such as T-Mobile) to provide mobile satellite service directly to smartphone users from 2024 [80]. The era of developing 6G could provide even more advanced capabilities, such as terabit-per-second data speeds, ubiquitous connectivity, and reduced energy consumption. While the details are yet to be defined, emerging trends and possibilities are summarized below and highlighted in Fig. 3 [81-84].

1) **AI Integration:** to optimize network performance, personalize services, and improve security.

2) **Satellite Integration:** to extend to remote areas (including oceans) and enhance global coverage through low Earth orbit (LEO) satellites, High Altitude Platforms (HAPs) and geostationary satellites; aka Non-Terrestrial Networks.

3) **Joint Communication and Sensing:** to enable simultaneous data sensing and transmission at a relatively low cost, which has significant potential for applications including healthcare, environmental monitoring, and transportation.

4) **Edge Computing:** to enable faster data processing and reduce latency. This is crucial for applications like autonomous vehicles, augmented reality, and virtual reality.

5) **Augmented and Virtual Reality (AR/VR):** may lead to new applications in gaming, education, healthcare, and more. Cellular phones are the gateway for AR/VR systems.

6) **Sustainable and Green Communications:** to reduce the environmental impact of communication networks, more energy-efficient networks are required, including incorporation of renewable energy sources, and reduction of electronic waste.

7) **Holographic Communication:** to provide 3D holographic calls and interactions via mobile devices.

8) **Digital Twins:** to enable real-time monitoring, analysis, and simulation.

9) **IoT and M2M Communications:** to lead to more seamless machine-to-machine (M2M) communications, enabling smart cities and industrial automation.

10) **Security and Privacy:** will be required to improve authentication methods, encryption, and privacy-preserving technologies.

These new technology areas will bring new challenges to antenna designs which include:

- *Compact/broadband, high-gain circularly-polarized antennas.*
- *Efficient higher frequency antennas (THz antennas & mm-waves).*
- *Reconfigurable antennas.*
- *Integration of antennas with RF front ends.*
- *Antenna measurements, especially over-the-air (OTA).*

B. Sub-THz Antennas and Channel Characterizations

In the development of sub-THz antennas, not only the antenna design techniques but also the material technologies for lens antennas and substrates, and manufacturing techniques are important. High-gain, beam-scanning and low-loss feeding are key features of the development of sub-THz antennas. Lens antennas shown in Fig. 4 (a) are advantageous in a sub-THz band. Beam scanning is achieved by shifting the primary radiator from the focal point. When the focal length is short for low profile configurations, the lens thickness is large for large refraction. To reduce the thickness, high permittivity material is desired. However, high permittivity material has a high loss tangent. Uniformity of the permittivity distribution is also important in lens production.

Planar arrays on substrates shown in Fig. 4 (b) are popular. However, the transmission loss of planar transmission lines is significant in the sub-THz band. Dielectric loss increases as a function of frequency, as does conductor loss due to the surface roughness of the copper foil adhered to the dielectric sheet. New dielectric materials to adhere to the copper without surface roughness are expected for high-gain planar antennas. As fine pitch patterns are necessary, the modified semi-additive process (MSAP) is becoming popular [85].

As is well known, phased arrays are comprised of antenna elements fed independently from RF circuits [86]. To reduce the feeding loss, on-chip antennas and antenna-in-package (AiP) techniques have been developed for the integration of these modules [87].





Fig. 3. Trends in next generation mobile systems.



(a) 10-mm lens with matching corrugation. (b) Planar comb-line antenna.
Fig. 4. Sub-THz antennas.

Operating emerging wireless technologies at a higher RF, such as mm-wave and quasi-THz, is a route to achieving higher data bandwidths and supporting the growth at the network edge for Terabit transmission. In particular, a single-input single-output (SISO) system at 237.5 GHz for transmitting data over 20 m at a rate of 100 Gbit/s illustrates the promise that the sub-THz band offers in delivery of 6G [88]. However, there is

currently a lack of real-world empirical measurement data to support the R&D advances towards 6G definitions and new product development. As sub-THz wide bandwidth propagation channel characterizations have not been extensively studied, nor experimentally verified in the open literature, this frequency band has not been incorporated in the standardization efforts that are led globally by ITU-R, 3GPP, ETSI, and IEEE. Furthermore, practical and traceable sub-THz propagation channel characterization presents new measurement challenges in a real-world environment. These challenges arise from the high signal transmission loss, limited equipment dynamic range, limited availability of commercial RF components, the need for high-gain and beam steerable antennas, and the requirement for extreme data rates [89].

Propagation channel models for sub-THz in city deployment are an active research topic and work has been reported at 90 GHz and 200 GHz [90, 91]. However, this work is only from a numerical and analytical modelling perspective with limited variables in both environmental settings and parametric studies. In [92], two vector network analyzer (VNA)-based frequency-domain sub-THz channel sounder systems were developed for operating at the frequency ranges of 75 GHz – 110 GHz and 220 GHz – 330 GHz. In [93], an instrument-based time-domain sub-THz channel sounder was developed for the frequency range between 280 GHz and 330 GHz. The overall propagation path of these sounding systems between transmitter and receiver is limited to about 10 m for [92] and 3.85 m for [93]. In practice, coaxial cable losses restrict the practical measurement range and therefore, the use of an optical-fiber based phase-compensated sounder to mitigate the coaxial cable loss issue and extend the measurement range has been investigated [94]. This addresses the issue relevant to optical fiber cables being inherently sensitive to phase changes due to bending and temperature and extends the measurement range from meters to tens of meters for mm-wave and sub-THz bands. Furthermore, there is currently on-going work developing long-range phase-compensated VNA-based frequency-domain sub-THz channel sounder systems for operating at frequency ranges of 330 GHz – 500 GHz and 500 GHz – 750 GHz [95].

C. Microwave Systems and Technologies for Medical Applications

Medical technologies using microwaves are established for treatment and have been proposed for a variety of imaging and sensing applications. To support patient care and home-based safety, radar-based approaches for monitoring vital signs and detecting falls have been introduced [96]. Radio frequency and microwave ablation have been developed to treat liver, lung, and kidney cancers, as well as cardiac arrhythmias, maturing into clinical product offerings [97-99]. Key imaging and sensing applications that involve bulk tissues at microwave frequencies are the detection of breast cancer [100], differentiation of ischemic and hemorrhagic stroke [101,102] and assessment of lung water content [103-105]. Moreover, microwave tumor detection and imaging can be enhanced by exploiting magnetic nanoparticles as modulated contrast agents selectively delivered to the tumor [106,107]. Solutions for these

applications have advanced beyond initial feasibility studies into physical systems capable of scanning human subjects. Recently, testing with human subjects has commenced and several start-up companies are pursuing commercialization of these technologies [100]. Emerging applications include colon health using microwave sensors incorporated into endoscopes for [108], as well as hydration monitoring [109]. For smaller samples and single cells, microwave biosensors have been developed for applications such as monitoring blood glucose levels and gaining insight into the effects of chemoelectrotherapy on single cells [110,111]. Interest in utilizing mm-waves is growing. However, the limited penetration of these signals suggests that analysis of small samples and assessment of skin cancers will only be the potential applications [112].

Several important general technology improvements may enable advances in medical applications. Firstly, enhanced computational power and speed have enabled the development of detailed models to support the design of complex components and systems, feasibility analysis and performance assessment. For imaging applications, this also accelerates iterative reconstruction algorithms that require multiple forward solutions. Secondly, the reduction in the cost of hardware has enabled prototypes to be developed and tested. This testing is key for unravelling assumptions that reduce efficacy in real-world scenarios. Rapid manufacturing, such as 3D printing, also allows for the development of prototypes with less overhead, as well as phantoms to support this testing.

Recently, testing in realistic scenarios has increased, corresponding to the availability of prototype systems capable of scanning human subjects or samples. For example, a microwave stethoscope for monitoring heart and respiration rates has been tested in small-scale studies [105]. Differentiation of ischemic and hemorrhagic stroke has been tested with groups of 20 patients, as well as a second group of 25 patients and 65 volunteers [101]. As recently reviewed in [100], the growing number of studies with human subjects is pointing towards breast imaging as the first clinical application of this technology.

As microwave technologies become increasingly established for medical applications, several key trends are anticipated. First, improvements in imaging technologies are expected with the incorporation of multi-modality information. This may be in the form of prior information available from other clinical methods, or through the collection of information with a co-located system (e.g. ultrasound). The growth in commercialization activity is also expected to increase the availability of devices and help establish collaborations with clinicians. This is also expected to refine clinical use cases for microwave imaging technologies. Utilization of machine and deep learning methods to elucidate trends data will improve images or enable detection of anomalies with the expansion of datasets [113]. Microwave technologies are also anticipated to be incorporated into wearables used for monitoring via IoT technologies [52].

D. Application of Machine Learning to Inverse Problems

Microwave imaging (MI) is a non-destructive testing (NDT) technique employing electromagnetic waves with a frequency range of 300 MHz to 300 GHz. The main goal of MI is to reconstruct the permittivity of unknown scatterers by measuring the scattered data, which is often described as an electromagnetic inverse scattering problem (ISP). Although rigorous and demanding in terms of mathematical skill, solving inverse problems is a significant technological achievement in the field of satellite-based remote sensing, biomedical imaging, geophysics exploration and several defense applications.

ISPs are typically non-linear and ill-posed in nature. Thus, the legacy practice was to deal with them either with non-iterative methods (Born or Rytov approximations) or with iterative methods e.g. Born and Distorted Born iterative methods, constant source inversion and subspace-based optimization methods). The limited accuracy of non-iterative methods restricts their wide acceptance, whereas more accurate iterative methods come with a huge computational load.

Recently, machine learning (ML), a widely accepted tool for signal and image processing, have demonstrated potential to transform the solution of ISPs. More specifically, deep learning (DL) techniques that mimic the learning process of the human brain using a convolution neural network (CNN) can offer unprecedented improvement in speed and accuracy of solving ISPs. The general framework for these recipes is to use a forward solver to generate a training dataset which then can be used to train the CNN. Legacy techniques like support vector machine (SVM) were initially adapted to solve ISPs [114], followed by CNN-based approaches. In the literature, deep neural networks were combined with traditional iterative methods [115] to improve the computational load. It is quite straightforward to predict that the choice and efficacy of the neural network (NN) plays a crucial role in improving the accuracy, and thus, a three-layer CNN [116] following the U-net [117] architecture was also explored. However, one drawback of this approach is that a custom built and dedicated neural network is necessary for solving each ISP; thus, the versatility of such a method remains restricted. This challenge motivated the application of DL into well-described existing techniques. An excellent solution is using such a CNN, which is trained to learn the underlying signal patterns. Chang *et al.* [118] proposed a NN that can solve any arbitrary linear ISP. Improved magnetic resonance image reconstruction was achieved using the alternating direction method of multipliers (ADMM) [119].

The future research scope for embedding AI/ML techniques into ISPs is exciting. Various research groups around the globe are striving to improve the speed and accuracy of ISPs and new advancements are frequently being reported. To name a few, Lianlin *et al.* proposed a more realistic model of DNN [120] termed DeepNIS. Sanghvi *et al.* [121] developed an excellent CNN network that can learn the noise space components of the radiation operator. To consider the effect of system noise, a physics-assisted ML approach has also been examined [122]. A more advanced approach of using the physics-informed supervised residual learning (PhiSRL) method following the

traditional Born iterative method has very recently come into the picture [123]. Incorporation of AI/ML is important when developing algorithms for larger size electrical objects. Large electrical objects typically possess intricate geometries and diverse material composition, necessitating computationally intensive simulations. Thus, the use of AI/ML is necessary to tackle these problems. Future research directions and the interests of the AP-S community are expected not only to focus on the popular such as medical imaging and non-destructive testing, but expand to geophysical exploration, extraction of cosmological parameters, and space weather prediction.

E. Quantum-based Electromagnetic Sensing Technologies

The traditional metallic antenna can cause invasive perturbation to the original electromagnetic (EM) field generated by an antenna under test (AUT) due to the presence of conductive surfaces which may possess surface charges [124]. Photonic electro-optical methods for electric field (E-field) sensing have redefined in situ non-invasive near-field characterization in harsh thermal environments, exhibiting wide frequency bandwidths spanning from near direct current to the edge of the THz regime [125]. These sensors operate on the principle of optical intensity varying bulk parameters, including the electro-absorption effect [126], the electro-chromatic effect [127]), the linear Pockel's effect [128] and the non-linear Kerr effect [129]. Two mature Pockel's based designs, namely the Mach-Zehnder interferometer and whispering gallery mode sensor, have dominated the field, due to their simplicity and superior figures of merit. The first is the standard Mach-Zehnder Interferometer, where the optical length inside the measurement arm varies with respect to the applied EM field. The other is a whispering gallery mode sensor which possesses a resonant cavity whose frequency may be modulated by the changing refractive index induced by the E-field. However, these sensors have fundamental operational limitations, such as bandwidth-sensitivity trade-offs, the requirement of complex calibrated digital signal post-processing and expensive costs.

Atom-based non-invasive measurements of EM fields are receiving increasing attention due to the advantage of a predictable response directly tied to fundamental concepts (resulting in traceable self-calibrated measurement [130]). The operation is based on quantum interference by means of a coupling/probe laser [131] incident on a vapor cell containing alkali atoms (potassium, rubidium & cesium). The enclosed atoms could be excited to high-energy Rydberg states (where the principal quantum number n typically takes values between 10 and 100) [132]. These Rydberg atoms are identical quantum particles exhibiting large polarizability and sensitivity [133], ($<1 \mu\text{V cm}^{-1}\text{Hz}^{-1/2}$ [134]) in the presence of the EM field generated by the AUT; change in probe transmission through the vapor cell is detected with a photodetector. The atom in this atomic state acts as a dipole due to the separation of charge between the valence electron and remaining positively charged ion. A variety of laser configurations/techniques have been used to induce this excitation, including electro-magnetically induced transparency (EIT), and Autler-Townes splitting,




Fig. 5. Example of growth in the number of devices using telecommunication services (from [139]).

allowing Rydberg atoms to be used as high-sensitivity non-invasive tunable sensors/antennas [129] within electrometry up to the THz regime [134]-[136]. Such atomic E-field sensors have predicted applications in RF telecommunications, electromagnetic sensing, imaging, and metrology [137]. However, at present this technology is still in the very early stages of development. Various research challenges such as equipment miniaturization, finding the optimum RF modulation and signal processing will need to be addressed to enable its wider uptakes [138].

IV. MAXIMIZING THE SOCIETAL IMPACT OF WIRELESS CONNECTIVITY

Wireless connectivity is set to play a key role in addressing a growing number of societal challenges related to digital equity, climate change, and public health. New antenna technologies will serve at the forefront of these efforts by enabling persistent and ubiquitous access to the electromagnetic spectrum and the Internet. Their role will be largely unseen, when successful, as they facilitate the exchange of information and energy amongst people, machines, and infrastructure. Fig. 5 summarizes expected growth in this area. It will be critical for new antenna technologies to enhance access to this connectivity and lower or even remove many of the barriers to information, tools, and opportunities on the Internet. These are essential to the empowerment of digitally underserved communities, and to link all people to the advanced distributed data storage and computing resources at the network edge and its backend linkage of high-speed fiber, satellites, and other networks.

A. The Digital Divide

It is constructive to first examine a global view of digital equity to gain a better understanding of the importance of new antenna technologies. For this, we look to September of 2015 when more than 190 members of the United Nations (UN) committed to 17 Sustainable Development Goals (SDGs) [140] for bringing equality across the world, both in the present and for generations to come. These goals represent a call to action for every nation, irrespective of its development status, to engage in a unified global partnership. These goals also underscore the critical need to simultaneously address poverty

and various forms of deprivation alongside endeavors to enhance healthcare and education, diminish inequality, stimulate economic advancement, and confront the challenges of climate change.

The UN has recognized Internet access as a basic human right, emphasizing the need for social workers to advocate for policies that address this digital divide [141-142]. The critical role of high-speed broadband access was especially evident during the COVID-19 pandemic for social, educational, financial, health, and other needs. Even in the US, a significant portion of the population, particularly low-income individuals, people of color, older adults, Native Americans, and rural residents, lack home access to high-speed Internet, exacerbating social, economic, and political disparities.

Wireless systems have the potential to help bridge the digital divide and promote digital equity by providing reliable internet access to underserved and remote areas. The discussion in [143-144] outlines key challenges and solutions to providing Internet and wireless systems worldwide. However, access to wireless systems alone is not enough. People also need digital literacy skills to effectively use online resources. Lack of digital literacy can perpetuate the digital divide, and initiatives to address the digital divide in the US frame it as a social justice and human rights issue, where advocacy tools can be aimed at reducing the digital divide at the state and local levels.

B. Connecting Policy to Practice

The societal impact of major advancements in new antenna technologies is contingent on the allowances made for the actual use of allocated bands. Substantial new investments in digital infrastructure are necessary, but public policy also substantially lags technological realities that span from increasingly “smart” transceivers to distributed networking. Innovations in antenna design are often ignored in current decision-making, with many of the shared spectrum proceedings lagging decades behind the state-of-the-art. In turn, bringing high-speed connectivity to underserved communities is often hampered by the limited spectrum assets allocated for the implementation of innovative solutions, including next-generation antenna deployment.

Recent initiatives in the U.S. may be examined as a bellwether for global efforts. The many federal broadband grant and loan

programs to increase connectivity across the US are predicated on the creation of a meaningful impact from public investment in critical infrastructure, including \$42.45 billion for NTIA's BEAD initiative, \$10 billion from the US Treasury's Capital Project Fund, roughly \$14 billion from the FCC's RDOF Phase II, and billions from additional USDA, DOE, and other agencies' programs.

Unfortunately, accurate baseline measures of connectivity across the US still do not exist. The FCC's Broadband Fabric and National Broadband Map advertise availability [145], but these self-reported measures by internet service providers often substantially overstate speed and coverage (especially regarding wireless connectivity). To date, no scientifically rigorous analysis of actual broadband speeds has documented household-level realities. Poor, rural, and communities of color often show the greatest discrepancies between "advertised" availability and "on-the-ground reality." When metrics contain measurement artifacts, it then becomes all-the-more difficult to target federal funding to the communities most in need. Limitations in network architecture have compounded these problems. One example is hub-and-spoke wireless implementations in areas with substantial topology and/or trees. Meanwhile, distributed and software defined networking (and the concomitant internetworking of antennas across arrays of transceivers) remains almost entirely unexplored, given current spectrum allocations.

Digital equity efforts face a major hurdle. Areas may be declared "served" when they are, in reality, un-or under-served (e.g., receive broadband speeds of less than 25/3 Mbps or 100/20Mbps, respectively, as of Fall 2023). These same areas may then be declared ineligible for funding that aims to address the digital divide. Furthermore, key metrics like overall network and link reliability over time, and pricing (as well as latency, bufferbloat, etc.) are all currently missing from national data collection efforts. A real-world example is the rural Alaskan Tribes, experiencing challenges such as satellite broadband that regularly experiences 2000-3000 ms latency, and often goes entirely offline 4-6 times/day during longitudinal data collection efforts. This connectivity is too often unusable for any real-time application (e.g., telehealth and other video conferencing needs), as well as for any critical communications. Thus, a substantial and immediate documentation effort is both timely and essential to bridge the digital divide more efficaciously, spanning both innovative network implementations (especially distributed and shared spectrum implementations) and far more nuanced data collection that captures the quality of service faced within marginal connectivity areas and among underserved constituencies.

Opportunistic spectrum access (e.g. FCC Docket 04-186) has also long languished; while enabling technologies for opportunistic and shared spectrum access have radically improved, no new spectrum licensure has been introduced in over 20 years. This does not leverage the possibilities from advancements in Software Defined Radio (SDR) and Software Defined Networking (SDN) technologies. A potential starting point for approaching this oversight would be to conduct audits of actual spectrum utilization to determine the magnitude of the discrepancy between spectrum allocation and assignment, as well as the actual utilization of those same bands. Prior analyses

conducted by McHenry et al. in the 2004-2007 timeframe as a part of the NSF Spectrum Occupancy Measurements Project documented widespread underutilization of the public airwaves, often with less than 10% utilization. In the 20 years since these studies, many spectrum license holders have shifted from analog to digital, which may lead to even lower spectrum utilization in many areas of the country. An updated analysis would prove incredibly enlightening, helping to spur a new generation of more efficient spectrum allocation, assignment, and overall utilization, and simultaneously alleviating the "spectrum crunch" lamented by many contemporary spectrum users and license holders.

In the US, this issue is particularly important to Tribal authorities who, under their current treaty rights, retain control over any natural resources not explicitly given away during their treaty-signing. As such, electromagnetic spectrum should be available for use by Tribes, yet is currently often assigned to non-Tribal license-holders. License-holders may not be using the licensed spectrum in Tribal areas, yet Tribes are forbidden to utilize this spectrum because it is officially in use by non-Tribal entities. Tribal areas are often "spectrum green fields" with close to zero actual spectrum use across wide spectral bands; they are the natural location for prototyping next-generation wireless technologies and cost-effective broadband implementations. Tribes should be the vanguard for pushing the R&D envelope and, with the \$3 billion in Tribal Broadband funding being made available over the next two years, are perfectly situated to partner on everything from basic R&D to real-world proof-of-concept implementation of solutions to bridge the digital divide.

C. Extending Socio-Economic Benefits of Cellular

In addition to investments in infrastructure and the impact of public policy, it is also instructive to highlight the impact of wireless connectivity in society and examine the challenges faced when socializing and adopting new technologies. This can be observed by first examining the well-known generational (e.g., "Next G") upgrades in telecommunication technology. While performance metrics representing improvements in system performance can be identified, deployment is complicated by a combination of regulatory bodies, private companies, and end-user device makers. Under this scheme, digital equity is sometimes undermined despite a technological upgrade.

One example is the technology standard for cellular networks. Wireless companies and technology news media often depict Next G upgrades in bandwidth and transmission speed [146-147]. While upgrades from 3G to 5G have increased the number of frequency bands, their availability still depends on a nation's radio spectrum allocation and compatibility of a mobile device's radios and antennas. Even in the same country, such as the U.S., device makers often manufacture carrier-specific phones that support only a subset of available frequency bands. While 3G has a clear divide between UMTS and CDMA2000, a phone's compatibility with a specific mobile network operator (MNO) has become less straightforward and lacked transparency in later generations [148]. This leads to premature obsolescence of an older mobile device, which creates e-waste and an additional economic burden on many underserved communities. There is also the problem of spectrum

fragmentation; in each frequency band, contiguous spectrum blocks theoretically available for more efficient usage are divided by several MNOs, each of which may in the end utilize a collection of scattered spectrums based on their acquired licenses [149].

At the current state of 5G deployment, the GSM Association (GSMA) maintains its position that without sufficient low-band (<1 GHz) spectrum, “the digital divide is likely to widen, and those living in rural areas will be excluded from the latest digital technologies.” The same report, however, discovers that low-band spectrum has not been used at all for 5G in more than a half of the surveyed countries [150]. Considering that there are usually several MNOs in a country and that MNOs may prioritize the provision of mid-band (1-7 GHz) and high-band (or mmWave) spectrum, even if low spectrum is deployed, it remains uncertain whether 5G will fulfil its potential to deliver what the report considers needed to achieve “digital equality.”

A lesson learned for the engineering communities is that, while there is never a shortage of new technological ways to solve a challenge, there are always several larger sociotechnical systems that surround a technology. As a society, it is necessary to approach these entanglements with both engineering and non-engineering perspectives. To illustrate this, in communication system engineering, “spectrum allocation” represents innovative ways to dynamically allocate scarce spectrum resources based on temporal usage, price, and other factors [151-152]. However, in the context of technology policy and management, the same term means an international or national spectrum planning process to optimize overall system efficiency and to maintain fairness and equity for all stakeholders [153-154]. Accommodating different perspectives and drawing from cross-disciplinary approaches (e.g. [155]) is key to extending our technology’s socio-economic benefits to a broader (often socially-disadvantaged) population.

D. WiFi and Bridging the Gap in the Digital Divide

Given the challenges surrounding the deployment of new and existing antenna technologies for wireless connectivity, it is crucial to grasp society’s reliance on Internet access. The absence of such access can deprive nearly 34% of the world’s population of services like ride-sharing, map navigation, and accessing restaurant menus. According to [156], as of 2022, there were 5.3 billion Internet users worldwide, representing 66% of the global population. As Internet usage grows, the digital divide widens, posing a gap between those with access and those without.

While alternatives like Device-to-Device (D2D) communication offer solutions, challenges persist. Antennas must ensure sufficient coverage without causing interference, necessitating strong beamforming capabilities. This, in turn, requires miniaturization and coupling reduction within limited volumes. Careful planning for power consumption and spectrum management is imperative.

Bridging the digital divide is about more than Internet availability; it is also about equipping individuals with the skills and resources to use it effectively. WiFi plays a pivotal role in developing digital literacy and is affordable, showcasing the impact of standardized services. Efforts to expand outdoor and free WiFi access, particularly to underserved communities, are underway globally, leveraging cost-effective hotspot setups.

Initiatives like New York’s LinkNYC repurpose payphone kiosks into multifunctional WiFi hotspots, offering free Internet access, calls, and device charging.

The study in [157] examined the effects of providing wireless connectivity, such as free WiFi, to digitally underserved communities through municipal-university partnerships. Three services, namely work opportunities, education via massive open online courses and communication, were found to significantly impact economic metrics. This highlights the importance of comprehensive research on the economic, societal and educational implications of accessible and affordable wireless connectivity. Bridging the digital gap goes beyond providing free Internet; it involves empowerment, education, and economic advancement, fostering a more connected and inclusive global community.

As technology advances to offer wider bandwidth and access, device costs are likely to rise. The challenge that the Antennas and Propagation Society faces lies in developing low-cost solutions such as higher-efficiency antennas, ensuring affordability and accessibility for all.

E. Drones/Unmanned Aerial Vehicles

Low Earth Orbit (LEO) satellite networks have recently been used to develop the Internet of Space (IoS) and even space-based WiFi-like services for wireless connectivity. The role of these space-based systems will continue to play an increasingly important role in maximizing the societal impact of wireless connectivity. In a synergistic effort, drones, unmanned ariel vehicles (UAVs), and other autonomous vehicles and systems are also being used to reshape the landscape of wireless communications. Several industries such as agriculture, real estate, infrastructure inspections and package delivery are already employing drones to enable quick, affordable, and safe operations. In the Antennas and Propagation realm, drones have garnered interest in characterizing large antennas where size precludes the use of conventional anechoic chambers [158-161].

A major limitation of the current use of drones for wireless communication is the line of sight (LOS) requirements between the operator and the drone. This severely limits the scale at which drones can be deployed, and the ability to bring wireless connectivity and/or services. Investments in Beyond Visual Line of Sight (BVLOS) operations with drones, where cellular base stations can be used for control via cellular networks [162], may help alleviate the challenges. This allows drones to fly unseen by operators, but results in unique challenges for engineers as existing base station antenna technologies are typically oriented to serve users on the ground. In contrast, drones fly at an altitude above the base station and thus communicate to the base stations exclusively through sidelobes of the base station antenna [163]. Assuming that the drone antenna patterns are quasi-omnidirectional implies that they can transition rapidly from a zone of good signal to a zone of no signal without excessive base station handovers.

On the other hand, the communication link between drones and base stations is relatively free of multi-path and obstructions. This can cause increased interference levels at base stations that the drone does not intend to communicate with, thus impacting the network performance. These issues can

be alleviated by a directional antenna onboard the drone. This ensures that the main beam of the drone antenna stays aligned with the sidelobe of the base station antenna if the drone enters regions where the signal levels are changing rapidly. The directional antenna also minimizes radiation towards the base stations with which the drone does not intend to communicate. The key challenge for antennas onboard aerial vehicles, thus, is the necessity of a reconfigurable directional antenna that can adhere to the SWAP-C constraints posed by the drone, especially in the sub-6 GHz spectrum. For higher frequencies (mmWave and beyond), such antennas might be more feasible.

F. Heterogeneous Integration and Packaging

The transition to SDR and SDN, key enabling technologies for wireless communication networks, has been driven in part by advancements in high-speed digitizers, field programmable gate arrays (FPGAs), and ultimately radio frequency system-on-chip (RFSoc). The at-scale development and transition of mmWave systems is also growing, with fieldable links now being deployed beyond 100 GHz. This consolidation of the RF front-end for wireless communication has created a unique relationship between semiconductor, packaging, antenna, and networking communities, as all are now interlinked in their societal impact. The deployment of low-cost wireless communication technologies resides at the forefront of this discussion, but costs of semiconductor device fabrication are increasing due to rising capital costs.

Heterogeneous integration and higher-level assembly (e.g., system-in-package) are emerging as a key mechanism to mitigate rising costs and address the inequitable economic impact this creates amongst users. The disaggregation and reaggregation of large dies from advanced technology nodes into smaller dies connected in a package shorten design times. Savings can also be gained using smaller dies from legacy and advanced technology nodes that are combined on high-density packages. This can also lead to enhanced functionality with improved electrical, thermal, and mechanical performance [164-165], where the systems range from a microelectromechanical system to an assembled package for high-bandwidth memory or active and passive components interconnected as part of a logic-memory-RF block. A more-than-Moore system can thus help integrate logic, memory, sensors, and antennas from various front-end manufacturing nodes into a single package. The main challenges for the advanced packaging industry relate to the required process, tooling, and metrological improvements [166]. These challenges include developing technologies for power delivery, thermal management, and selection of appropriate materials for densely integrated systems.

Heterogeneously integrated advanced packages are also seen as the performance drivers for several wireless communication technologies including Next-G, autonomous vehicles and IoTs, and AR/VR with the design of these packages primarily driven by end-user applications [167]. However, given the complex and capital-intensive nature of running semiconductor fabs, there are several challenges that need to be addressed [168]. These include workforce development, reduced emissions

along supply chains, and, critically, effective material sourcing with minimal environmental impact to ensure a vibrant semiconductor ecosystem that can support the deployment of low-cost wireless communication.

G. Physical Layer and Wireless Network Security

Expanding access and coverage is a key aspect of tackling the digital divide, but these are complicated by challenges in network security from physically complex, infrastructure-poor, and contested or unregulated environments. This challenge is further exacerbated by the fact that nearly 70% of the world's population is expected to live in dense urban environments by 2050 [169], and that there is a growing presence of sophisticated bad actors that may exploit networking technologies to cause significant damages and loss (e.g., ransomware attacks).

This poses major threats to user privacy and security in addition to the direct impact such actions may cause on private and public entities (e.g., ransomware attacks, spoofing, wireless sniffing, attacks on public infrastructure). It may also lead users to lose trust and may delay the adoption of networking technologies globally, especially in developing countries where a significant portion of the population has very limited digital literacy [170]. The lack of infrastructure makes this even more challenging as it limits the deployment of network security technologies that rely on extensive and reliable infrastructure. As part of the overarching efforts to close the gap due to the digital divide, novel physical layer technologies will play a significant role in helping expand access while providing robust wireless network security features.

Emerging networking technologies that could help to deliver robust wireless network security while expanding access and coverage include intelligent and opportunistic heterogeneous networks. These can enhance security by adaptively exploiting multiple communications technologies operating at different parts of the electromagnetic spectrum [171-172]. The expanded utilization of spectrum comes with additional security requirements. Another future direction is the development of novel antenna technologies that enable a new layer of wireless security capability at the physical layer. For example, compact antenna diversity systems, in addition to enabling MIMO-based wireless networking technologies, can be used to create protection against signal energy and feature detection schemes especially when combined with advanced coding and signal processing techniques [173-174]. Such techniques provide novel protection schemes against eavesdroppers that attempt to detect and intercept communications signals among legitimate users.

Additionally, Reconfigurable Intelligent Surfaces (RIS) (described in Section II.C), can enable novel security features by reducing the probability of detection (LPD) by adversaries [175]. Directional networking enabled by antennas with directional modulation capabilities, as well as phased arrays and adaptive beamforming approaches, also show promise for more resilient and secure communications among legitimate users [176].

V. CONCLUSION

In this invited paper, members from the three working groups in the IEEE AP-S NTDC have presented recent and emerging research directions in the fields of antennas and propagation. WG-1 focused on materials and manufacturing processes for novel antenna applications, covering several emerging areas of research that could fundamentally shape the future of antenna and sensor system technologies. WG-2 focused on advances in communications, sensing and imaging. For mobile communications, recent research focuses on the development of 6G, sub-THz antennas and propagation. For microwave medical imaging systems, advances in computational power and speed combined with machine learning techniques will provide more accurate results and offer more potential benefits. The advent of quantum technologies for sensing systems could revolutionize the domain. The primary goal of WG-3 is to examine the new technology directions that intersect with the overarching goal of maximizing the social impact of wireless connectivity. This WG brings attention to the considerations that social science, economics, and public policy have. To this end, the challenge of new technologies does not just reside within the technical community, but rather the entirety of the problem space.

REFERENCES

- [1] G. Huang, C. Han, W. Xu, T. Yuan, and X. Zhang, "A compact 16-way high-power combiner implemented via 3-D metal printing technique for advanced radio-frequency electronics system applications," *IEEE Trans. Ind. Electron.*, vol. 66, no. 6, pp. 4767–4776, Jun. 2019.
- [2] G. L. Huang, S. G. Zhou, and T. H. Chio, "Highly-efficient self-compact monopulse antenna system with integrated comparator network for RF industrial applications," *IEEE Trans. Ind. Electron.*, vol. 64, no. 1, pp. 674–681, Jan. 2017.
- [3] J. Zhu, et. al., "3-D printed all-dielectric dual-band broadband reflectarray with a large frequency-ratio," *IEEE Transactions on Antennas and Propagation*, vol. 69, no. 10, pp. 7035-7040, Oct. 2021.
- [4] J. Zhu, et. al., "Additively manufactured millimeter-wave dual-Band single-polarization shared aperture Fresnel zone plate metalens antenna," *IEEE Transactions on Antennas and Propagation*, vol. 69, no. 10, pp. 6261-6272, Oct. 2021.
- [5] A. Plessis, N. Razavi, M. Benedetti, S. Murchio, M. Leary, M. Watson, D. Bhate, F. Berto, "Properties and applications of additively manufactured metallic cellular materials: A review", *Progress in Materials Science*, vol. 125, pp. 100918, Apr. 2022.
- [6] S. Moscato et al., "Infill-dependent 3-D-printed material based on ninjaFlex filament for antenna applications," *IEEE Antennas Wireless Propagation Letters*, vol. 15, pp. 1506–1509, Jan. 2016.
- [7] J. Zhu, et. al, "3-D printed noninterleaved reflective metasurfaces supporting dual-band spin-decoupled quadruplex channel independent beam-shaping with controllable energy distribution", *IEEE Trans. on Micro. Theo. and Tech.*, vol. 72, no. 2, pp.1196-1205, Feb. 2024.
- [8] D. Sokol, M. Yamada and J. Nulman, "Design and performance of additively manufactured in-circuit board planar capacitors", *IEEE Trans. Electron. Devices*, vol. 68, no. 11, pp. 5747-5752, Nov. 2021.
- [9] M. Li, et. al., "3D-printed low-profile single-substrate multi-metal layer antennas and array with bandwidth enhancement", *IEEE Access*, vol. 8, pp. 217370-217379, 2020.
- [10] J. Zhu, Y. Yang, J. Lai and J. Nulman, "Additively manufactured polarisation insensitive broadband transmissive metasurfaces for arbitrary polarisation conversion and wavefront shaping," *Advance Optical Materials*, vol. 10, pp. 2200928, Nov. 2022.
- [11] X. Gu, D. Liu, and B. Sadhu, "Packaging and antenna integration for silicon-based millimeter-wave phased arrays: 5G and beyond," *IEEE J.Microw.*, vol. 1, no. 1, pp. 123–134, Jan. 2021.
- [12] C. X. Mao, et. al., "Filtering antennas: design methods and recent developments," *IEEE Microw. Mag.*, vol. 22, no. 11, pp. 52-63, Nov. 2021.
- [13] Y. Gao, et. al., "Integrated filter–amplifiers: a comprehensive review," *IEEE Microw. Mag.*, vol. 23, no. 6, pp. 57-75, Jun. 2022.
- [14] G. Q. Luo et al., "Filtenna consisting of horn antenna and substrate integrated waveguide cavity FSS," *IEEE Trans. Antennas Propag.*, vol. 55, no. 1, pp. 92-98, Jan. 2007.
- [15] X. Y. Zhang, W. Duan, and Y. -M. Pan, "High-gain filtering patch antenna without extra circuit," *IEEE Trans. Antennas Propag.*, vol. 63, no. 12, pp. 5883-5888, Dec. 2015.
- [16] K. Huang and Y. Zhang, "Analysis and design of dual-polarized millimeter-wave filtering magneto-electric dipole antenna," *IEEE Trans. Antennas Propag.*, vol. 71, no. 8, pp. 6947-6952, Aug. 2023.
- [17] A. Vosoogh, et. al., "An integrated ka-band diplexer-antenna array module based on gap waveguide technology with simple mechanical assembly and no electrical contact requirements," *IEEE Trans. Microw. Theory Technol.*, vol. 66, no. 2, pp. 962-972, Feb. 2018.
- [18] W. Hong et al., "The role of millimeter-wave technologies in 5G/6G wireless communications," *IEEE J. Microw.*, vol. 1, no. 1, pp. 101-122, Jan. 2021.
- [19] K. Kibaroglu, M. Sayginer, T. Phelps and G. M. Rebeiz, "A 64-element 28-GHz phased-array transceiver with 52-dBm EIRP and 8–12-Gb/s 5G link at 300 meters without any calibration," *IEEE Trans. Microw. Theory Technol.*, vol. 66, no. 12, pp. 5796-5811, Dec. 2018.
- [20] X. Fu et al., "A low-power 256-element Ka-band CMOS phased-array receiver with on-chip distributed radiation sensors for small satellite constellations," *IEEE J. Solid-State Circuits*.
- [21] B. -H. Ku, O. Inac, M. Chang, H. -H. Yang and G. M. Rebeiz, "A high-linearity 76–85-GHz 16-element 8-transmit/8-receive phased-array chip with high isolation and flip-chip packaging," *IEEE Trans. Microw. Theory Technol.*, vol. 62, no. 10, pp. 2337-2356, Oct. 2014.
- [22] Y. -J. Huang et al., "A self-powered CMOS reconfigurable multi-sensor soc for biomedical applications," *IEEE J. Solid-State Circuits*, vol. 49, no. 4, pp. 851-866, Apr. 2014.
- [23] RF Wireless World, Advantages of Reconfigurable Intelligent Surface | Disadvantages of Reconfigurable Intelligent Surface [Online]. <https://www.rfwireless-world.com/Terminology/Advantages-and-Disadvantages-of-Reconfigurable-Intelligent-Surface.html>
- [24] S. Gong, X. Lu, D. T. Hoang, D. Niyato, L. Shu, D. I. Kim, and Y.-C. Liang, "Toward smart wireless communications via intelligent reflecting surfaces: a contemporary survey," *IEEE Communications Surveys & Tutorials*, Vol. 22, no. 4, pp. 2283–2314, Fourth quarter 2020.
- [25] B. Rana, S.-S. Cho, and I.-P. Hong, "Parameters and measurement techniques of reconfigurable intelligent surfaces," *Micromachines*, Vol. 13, no. 11, p. 1841, Oct. 2022.
- [26] C. Pan, H. Ren, K. Wang, et al., "Reconfigurable intelligent surfaces for 6g systems: principles, applications, and research directions," *IEEE Communications Magazine*, vol. 59, no. 6, pp. 14 - 20, June 2021.
- [27] X. Yuan, et. al., "Reconfigurable-intelligent-surface empowered wireless communications: challenges and opportunities," *IEEE Wireless Communications*, vol. 28, no. 2, pp. 136–143, April 2021.
- [28] S. Hu, F. Rusek, and O. Edfors, "Beyond massive mimo: the potential of data transmission with large intelligent surfaces," *IEEE Transactions on Signal Processing*, vol. 66, no. 10, pp. 2746 - 2758, May 2018.
- [29] W. Tang, et. al., "Wireless communications with programmable metasurface: new paradigms, opportunities, and challenges on transceiver design," *IEEE Wire. Comm.*, vol. 27, no. 2, pp. 180 - 187, April 2020.
- [30] D. Pérez-Adán, et. al., "Intelligent reflective surfaces for wireless networks: an overview of applications, approached issues, and open problems," *Electronics*, vol. 10, no. 19, p. 2345, Sep. 2021.
- [31] I.-P. Hong, "Reviews based on the reconfigurable intelligent surface technical issues". *Electronics*, vol. 12, no. 21, pp. 4489, 2023.
- [32] W. Khalid, et al., "Simultaneous transmitting and reflecting-reconfigurable intelligent surface in 6G: design guidelines and future perspectives," *IEEE Network*, vol. 37, no. 5, pp. 173-181, Sept. 2023.
- [33] A. Kiourti and K. S. Nikita, "A review of in-body biotelemetry devices: Implantables, ingestibles, and injectables," *IEEE Trans Biomed Eng.* vol. 64, no. 7, pp. 1422–1430, 2017, doi: 10.1109/TBME.2017.2668612.
- [34] K. L. Montgomery et al., "Wirelessly powered, fully internal optogenetics for brain, spinal and peripheral circuits in mice," *Nat Methods*, vol. 12, no. 10, pp. 969–974, 2015, doi: 10.1038/nmeth.3536.
- [35] M. Zada and H. Yoo, "A miniaturized triple-band implantable antenna system for bio-telemetry applications," *IEEE Trans Antennas Propag.* vol. 66, no. 12, pp. 7378–7382, Dec. 2018.

- [36] A. Alemarween and S. Noghianian, "On-body low-profile textile antenna," *IEEE Trans. Antenna. Propag.*, vol. 67, no. 6, pp. 3649–3656, 2019, doi: 10.1109/TAP.2019.2902632.
- [37] M. Wagih, A. Komolafe, I. Ullah, A. S. Weddell, and S. Beeby, "A wearable all-printed textile-based 6.78 MHz 15 W-output wireless power transfer system and its screen-printed joule heater application," *IEEE Transactions on Industrial Electronics*, 2023.
- [38] A. Tesser, et. al., "Synthesis and use of bio-based dielectric substrate for implanted radio frequency antennas," *IEEE Access*, vol. 7, 2019.
- [39] C. Hahn and S. Noghianian, "Heterogeneous breast phantom development for microwave imaging using regression models," *Int J Biomed Imaging*, vol. 2012, 2012.
- [40] A. Kiourti, C. Lee, and J. L. Volakis, "Fabrication of textile antennas and circuits with 0.1 mm precision," *IEEE Antennas Wirel Propag Lett*, vol. 15, pp. 151–153, 2016.
- [41] R. Shadid, M. Haerinia, S. Roy, and S. Noghianian, "Hybrid inductive power transfer and wireless antenna system for biomedical implanted devices," *Progress In Electromagnetics Research C*, vol. 88, 2018.
- [42] A. Kiourti, et. al., "A broadband implantable and a dual-band on-body repeater antenna: Design and transmission performance," *IEEE Trans Antennas Propag*, vol. 62, no. 6, pp. 2899–2908, 2014.
- [43] S. Agnessens and H. Rogier, "Compact half diamond dual-band textile HMSIW on-body antenna," *IEEE Trans Antennas Propag*, vol. 62, no. 5, pp. 2374–2381, 2014, doi: 10.1109/TAP.2014.2308526.
- [44] A. Ejaz et al., "A high-performance all-textile wearable antenna for wristband application," *Micromachines*, vol. 14, no. 6, pp. 1–15, 2023.
- [45] D. Le, S. Ahmed, L. Ukkonen, and T. Bjorninen, "A small all-corners-truncated circularly polarized microstrip patch antenna on textile substrate for wearable passive UHF RFID tags," *IEEE Journal of Radio Frequency Identification*, vol. 5, no. 2, pp. 106–112, Jun. 2021.
- [46] C. W. L. Lee, et. al., "A high-sensitivity fully passive neurosensing system for wireless brain signal monitoring," *IEEE Trans Microw Theory Tech*, vol. 63, no. 6, pp. 2060–2068, Jun. 2015.
- [47] R. Shadid and S. Noghianian, "A literature survey on wireless power transfer for biomedical devices," *Int J Antennas Propag*, vol. 2018, 2018.
- [48] R. Noormohammadi, A. Khaleghi, and I. Balasingham, "Galvanic impulse wireless communication for biomedical implants," *IEEE Access*, vol. 9, pp. 38602–38610, 2021, doi: 10.1109/ACCESS.2021.3064206.
- [49] P. Bose, A. Khaleghi, and I. Balasingham, "In-body and off-body channel modeling for future leadless cardiac pacemakers based on phantom and animal experiments," *IEEE Antennas Wirel Propag Lett*, vol. 17, no. 12, pp. 2484–2488, Dec. 2018, doi: 10.1109/LAWP.2018.2878950.
- [50] A. Kiourti, "RFID Antennas for Body-Area Applications: From Wearables to Implants," *IEEE Antennas Propag Mag*, vol. 60, no. 5, pp. 14–25, Oct. 2018, doi: 10.1109/MAP.2018.2859167.
- [51] A. Basir and H. Yoo, "Efficient wireless power transfer system with a miniaturized quad-band implantable antenna for deep-body multitasking implants," *IEEE Trans Microw Theory Tech*, vol. 68, no. 5, pp. 1943–1953, May 2020, doi: 10.1109/TMTT.2020.2965938.
- [52] M. Wagih et al., "Microwave-enabled wearables: underpinning technologies, integration platforms, and next-generation roadmap," *IEEE Journal of Microwaves*, vol. 3, no. 1, pp. 193–226, Dec. 2022, doi: 10.1109/jmw.2022.3223254.
- [53] I. Gani and H. Yoo, "Multi-band antenna system for skin implant," *IEEE Microwave and Wireless Components Letters*, vol. 26, no. 4, pp. 294–296, Apr. 2016, doi: 10.1109/LMWC.2016.2538470.
- [54] M. Wagih, et. al., "Dual-band dual-mode textile antenna/rectenna for simultaneous wireless information and power transfer (swipt)," *IEEE Trans Antennas Propag*, vol. 69, no. 10, pp. 6322–6332, 2021.
- [55] G. Monti, L. Corchia, and L. Tarricone, "UHF wearable rectenna on textile materials," *IEEE Trans Antennas Propag*, vol. 61, no. 7, pp. 3869–3873, 2013, doi: 10.1109/TAP.2013.2254693.
- [56] H. Rahmani et al., "Next-generation IoT devices: sustainable eco-friendly manufacturing, energy harvesting, and wireless connectivity," *IEEE Journal of Microwaves*, vol. 3, no. 1, pp. 237–255, 2023.
- [57] S. Roy, A. N. M. Wasekul Azad, S. Baidya, M. K. Alam, and F. Khan, "Powering solutions for biomedical sensors and implants inside the human body: a comprehensive review on energy harvesting units, energy storage, and wireless power transfer techniques," *IEEE Trans Power Electron*, vol. 37, no. 10, pp. 12237–12263, 2022.
- [58] A. Mickle et al., "A wireless closed-loop system for optogenetic peripheral neuromodulation," *Nature*, vol. 565, no. 7739, pp. 361–365, 2019.
- [59] J. Blauert and A. Kiourti, "Theoretical modeling and design guidelines for a new class of wearable bio-matched antennas," *IEEE Trans Antennas Propag*, vol. 68, no. 3, pp. 2040–2049, Mar. 2020.
- [60] M. Wagih, A. Komolafe, and N. Hillier, "Screen-printable flexible textile-based ultra-broadband millimeter-wave DC-blocking transmission lines based on microstrip-embedded printed capacitors," *IEEE Journal of Microwaves*, vol. 2, no. 1, 2021, doi: 10.1109/jmw.2021.3126927.
- [61] J. Bito, et. al., "Ambient RF energy harvesting from a two-way talk radio for flexible wearable wireless sensor devices utilizing inkjet printing technologies," *IEEE Trans Microw Theory Tech*, vol. 63, no. 12, 2015.
- [62] A. Nemet, S. Alkaraki, Q. H. Abassi, and S. F. Jilani, "A biodegradable textile-based graphene antenna for 5g wearable applications," *2021 IEEE International Symposium on Antennas and Propagation and North American Radio Science Meeting, APS/URSI 2021 - Proceedings*, 2021.
- [63] Hwang, S.-W., Huang, X., Seo, J.-H., Song, J.-K., Kim, S., Hage-Ali, S., Chung, H.-J., Tao, H., Omenetto, F.G., Ma, Z. and Rogers, J.A. (2013), Materials for Bioresorbable Radio Frequency Electronics. *Adv. Mater.*, 25: 3526-3531
- [64] R. B. V. B. Simorangkir, et. al., "Polydimethylsiloxane-embedded conductive fabric: characterization and application for realization of robust passive and active flexible wearable antennas," *IEEE Access*, vol. 6, pp. 48102–48112, Aug. 2018.
- [65] F. Ghanem, R. Langley, and L. Ford, "Propagation control using SIW technology," *2010 IEEE International Symposium on Antennas and Propagation and CNC-USNC/URSI Radio Science Meeting - Leading the Wave, AP-S/URSI 2010*, 2010, doi: 10.1109/APS.2010.5562333.
- [66] S. Shao, A. Kiourti, R. J. Burkholder, and J. L. Volakis, "Broadband textile-based passive UHF RFID tag antenna for elastic material," *IEEE Antennas Wirel Propag Lett*, vol. 14, pp. 1385–1388, 2015.
- [67] W. G. Whittow, et. al., "Inkjet-printed microstrip patch antennas realized on textile for wearable applications," *IEEE Ant. Wirel Propag Lett*, vol. 13, 2014.
- [68] M. L. Scarpello, I. Kazani, C. Hertleer, H. Rogier, and D. Vande Ginste, "Stability and efficiency of screen-printed wearable and washable antennas," *IEEE Antennas Wirel Propag Lett*, vol. 11, 2012.
- [69] A. Sabouni, C. Hahn, S. Noghianian, E. Sauter, and T. Weiland, "Study of the Effects of Changing Physiological Conditions on Dielectric Properties of Breast Tissues," *ISRN Biomed. Imaging*, 2013, doi: 10.1155/2013/894153.
- [70] N. A. Malik, et. al., "Implantable antennas for bio-medical applications," *IEEE J Electromagn RF Microw Med Biol*, vol. 5, no. 1, 2021.
- [71] A. Alemarween, "Compact wideband antenna for wireless capsule endoscopy system," *Appl Phys A Mater Sci Process*, vol. 127, no. 4, p. 271, Apr. 2021.
- [72] S. Hout, et. al., "Design and characterization of a miniaturized implantable antenna in a seven-layer brain phantom," *IEEE Access*, vol. 7, 2019.
- [73] M. Zada, I. A. Shah, A. Basir, and H. Yoo, "Ultra-compact implantable antenna with enhanced performance for leadless cardiac pacemaker system," *IEEE Trans Antennas Propag*, vol. 69, no. 2, 2021.
- [74] Q. H. Dang, et. al., "Multifunctional reconfigurable wearable textile antennas using coplanar reconfiguration modules," *IEEE Trans Antennas Propag*, vol. 71, no. 5, pp. 3806–3815, May 2023.
- [75] M. L. Scarpello, I. Kazani, C. Hertleer, H. Rogier, and D. Vande Ginste, "Stability and efficiency of screen-printed wearable and washable antennas," *IEEE Antennas Wirel Propag Lett*, vol. 11, 2012.
- [76] R. B. V. B. Simorangkir, et. al., "Washing durability of PDMS-conductive fabric composite: realizing washable UHF RFID tags," *IEEE Antennas Wirel Propag Lett*, vol. 18, no. 12, pp. 2572–2576, Dec. 2019.
- [77] P. K. Nunna, P. Kuchhal, and A. Varshney, "Wearables and implantables in MICS- A review," *Alexandria Engineering Journal*, vol. 79. Elsevier B.V., pp. 73–80, Sep. 15, 2023, doi: 10.1016/j.aej.2023.07.060.
- [78] V. De Santis, M. Feliziani, and F. Maradei, "Safety assessment of uwb radio systems for body area network by the FD 2 TD method," *IEEE Trans Magn*, vol. 46, no. 8, pp. 3245–3248, 2010.
- [79] HUAWEI Mate 60 Pro launched. This phone can make satellite class. <https://www.androidauthority.com/huawei-mate-60-pro-3358902/>
- [80] Starlink Direct to Cell [Online]. <https://direct.starlink.com/>
- [81] 6G spectrum-enabling the future mobile life beyond 2030 [Online]. <https://www.ericsson.com/en/reports-and-papers/white-papers/6g-spectrum-enabling-the-future-mobile-life-beyond-2030>.
- [82] Q. Wu, et al., "A comprehensive overview on 5G-and-beyond networks with UAVs: From communications to sensing and intelligence," *IEEE Jour. on Sel. Areas in Comm.*, vol. 39, no. 10, pp. 2912-2945, Oct. 2021.

- [83] K. B. Letaief, et. al., "The roadmap to 6G: AI empowered wireless networks," *IEEE Comm. Mag.*, vol. 57, no. 8, pp. 84-90, August 2019.
- [84] T. Chaloun et al., "Electronically steerable antennas for future heterogeneous communication networks: review and perspectives," *IEEE Journal of Microwaves*, vol. 2, no. 4, pp. 545-581, Oct. 2022.
- [85] S. Acharya, S. S. Chouhan, and J. Delsing, "An additive production approach for microvias and multilayered polymer substrate patterning of 2.5 μm feature sizes," *2020 IEEE 70th Electronic Components and Technology Conference*, Orlando, FL, USA, 2020, pp. 1304-1308.
- [86] B. Sadhu, X. Gu and A. Valdes-Garcia, "The more (antennas), the merrier: a survey of silicon-based mm-Wave phased arrays using multi-IC scaling," in *IEEE Micro. Mag.*, vol. 20, no. 12, pp. 32-50, Dec. 2019.
- [87] T. Zwick, et. al., "Pea-sized mmW transceivers: QFN-? based packaging concepts for millimeter-wave transceivers," *IEEE Micro. Mag.*, vol. 18, no. 6, pp. 79-89, Sept.-Oct. 2017.
- [88] S. Koenig, et al., "Wireless sub-THz communication system with high data rate", *Nature Photonics*, Vol. 7, pp. 977-981, 2013.
- [89] F. Zhang, M. F. Bengtson, P. Kyösti, J. Kyröläinen and W. Fan, "Dynamic sub-THz radio channel emulation: principle, challenges, and experimental validation," *IEEE Wirel. Commun.*, Vol. 31, No. 1, pp. 10-16, Feb. 2024.
- [90] G. Gougeon, Y. Corre, and M. Z. Aslam, "Ray-based deterministic channel modelling for sub-THz band," *IEEE 30th Int. Sym. on Person., Ind. and Mob. Radio Communications*, Istanbul, Turkey, 2019, pp. 1-6.
- [91] Y. Corre, et. al., "Sub-THz spectrum as enabler for 6G wireless communications up to 1 Tbit/s," *6G Wirel. Sum.*, Levi, Finland, Mar. 2019.
- [92] Y. Lyu, P. Kyösti, and W. Fan, "Sub-THz VNA-based channel sounder structure and channel measurements at 100 and 300 GHz", *2021 IEEE 32nd Annual International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC 2021)*, Helsinki, Finland, 2021, pp. 1-5.
- [93] M. Schmieder, W. Keusgen, M. Peter, et al., "THz channel sounding: design and validation of a high performance channel sounder at 300 GHz," *2020 IEEE Wireless Communications and Networking Conference Workshops (WCNCW)*, Seoul, Korea, 2020, pp. 1-6.
- [94] Y. Lyu, A. W. Mbugua, K. Olesen, P. Kyösti, and W. Fan, "Design and validation of the phase-compensated long-range sub-THz VNA-based channel sounder", *IEEE Antennas and Wireless Propagation Letters*, vol. 20, no. 12, pp. 2461-2465, Dec. 2021.
- [95] T. H. Loh, W. Fan, D. Allal, A. Alomainy, F. Pythoud, and E. Tas, "Recent activities of a European union joint research project on metrology for emerging wireless standards", *the 45th Annual Meeting & Symposium of the Antenna Measurement Techniques Association (AMTA 2023)*, Seattle, WA, USA, 8 - 13 Oct. 2023.
- [96] E. Cippitelli, F. Fioranelli, E. Gambi, and S. Spinsante, "Radar and RGB-depth sensors for fall detection: a review," *IEEE Sensors Journal*, vol. 17, no. 12, pp. 3585-3604, 2017, doi: 10.1109/JSEN.2017.2697077.
- [97] J. Han, Y.-C. Fan, and K. Wang, "Radiofrequency ablation versus microwave ablation for early stage hepatocellular carcinoma: A PRISMA-compliant systematic review and meta-analysis," *Medicine (Baltimore)*, vol. 99, no. 43, pp. e22703-e22703, 2020.
- [98] V. Ravi et al., "A systematic review and meta-analysis comparing radiofrequency catheter ablation with medical therapy for ventricular tachycardia in patients with ischemic and non-ischemic cardiomyopathies," *Journal of interventional cardiac electrophysiology*, vol. 66, no. 1, pp. 161-175, 2023.
- [99] S. J. S. Ruiters, W. J. Heerink, and K. P. de Jong, "Liver microwave ablation: a systematic review of various FDA-approved systems," *European Radiology*, vol. 29, no. 8, pp. 4026-4035, 2019.
- [100] E. Porter and D. O'Loughlin, "Pathway to demonstrating clinical efficacy of microwave breast imaging: qualitative and quantitative performance assessment," *IEEE Journal of Electromagnetics, RF and Microwaves in Medicine and Biology*, vol. 6, no. 4, pp. 439-448, 2022.
- [101] M. Persson et al., "Microwave-based stroke diagnosis making global prehospital thrombolytic treatment possible," *IEEE Transactions on Biomedical Engineering*, vol. 61, no. 11, pp. 2806-2817, 2014, doi: 10.1109/TBME.2014.2330554.
- [102] D. O. Rodriguez-Duarte et al., "Experimental validation of a microwave system for brain stroke 3-D imaging," *Diag.*, vol. 11, no. 7, p. 1232, 2021.
- [103] A. Fedeli, et. al., "Nonlinear S-parameters inversion for stroke imaging," *IEEE Trans. Micro. Theo. and Tech.*, vol. 69, no. 3, pp. 1760-1771, 2021.
- [104] S. Ahdi Rezaeieh, et. al., "Novel microwave Torso scanner for thoracic fluid accumulation diagnosis and monitoring," *Scientific Reports*, vol. 7, no. 1, pp. 304-304, 2017.
- [105] M. F. Iskander, T. B. Seto, R. R. G. Perron, E. Lim, and F. Qazi, "Cardio-pulmonary stethoscope: clinical validation with heart failure and hemodialysis patients," *IEEE Transactions on Biomedical Engineering*, vol. 65, no. 5, pp. 1176-1180, 2018, doi: 10.1109/TBME.2017.2739695.
- [106] N.K. Nikolova, "Microwave imaging for breast cancer", *IEEE Microw. Mag.* vol. 12, no. 7, pp. 78-94, Dec. 2011.
- [107] G. Bellizzi, O.M. Bucci, I. Catapano, "Microwave cancer imaging exploiting magnetic nanoparticles as contrast agent", *IEEE Trans. Biomed. Eng.*, vol. 58, no. 9, pp. 2528-2536, Sept. 2011.
- [108] M. Guardiola et al., "MiWEndo: evaluation of a microwave colonoscopy algorithm for early colorectal cancer detection in ex vivo human colon models," *Sensors (Basel, Switzerland)*, vol. 22, no. 13, p. 4902, 2022, doi: 10.3390/s22134902.
- [109] D. C. Garrett, et. al., "Feasibility study of hydration monitoring using microwaves-part 2: measurements of athletes," *IEEE Journal of Elec. RF and Micro. in Medicine and Biology*, vol. 3, no. 4, pp. 300-307, 2019.
- [110] S. Guha, F. I. Jamal, and C. Wenger, "A review on passive and integrated near-field microwave biosensors," *Biosensors*, vol. 7, no. 4, p. 42, 2017.
- [111] A. Tamra, et. al., "Single cell microwave biosensor for monitoring cellular response to electrochemotherapy," *IEEE Transactions on Biomedical Engineering*, vol. PP, no. 11, pp. 1-1, 2022.
- [112] D. Kissinger, M. Kaynak, and A. Mai, "Integrated millimeter-wave and terahertz analyzers for biomedical applications," *IEEE Transactions on Microwave Theory and Techniques*, vol. 70, no. 11, pp. 1-18, 2022.
- [113] P. Mojabi, M. Hughson, V. Khoshdel, I. Jeffrey, and J. LoVetri, "CNN for compressibility to permittivity mapping for combined ultrasound-microwave breast imaging," *IEEE Journal on Multiscale and Multiphysics Computational Techniques*, vol. 6, pp. 62-72, 2021.
- [114] A. Randazzo and M. Pastorino, "Microwave detection of unknown targets by using support vector machines," *IEEE Int. Workshop Imag. Syst. Tech.*, 2009, pp. 141-146.
- [115] L. Li, et al., "Deepnis: deep neural network for nonlinear electromagnetic inverse scattering," *IEEE Trans. on Ant. and Propag.*, vol. 67, no. 3, pp. 1819-1825, 2019.
- [116] Z. Wei and X. Chen, "Deep-learning schemes for full-wave nonlinear inverse scattering problems," *IEEE Trans. Geosci. Remote Sens.*, vol. 57, no. 4, pp. 1849-1860, Apr. 2019.
- [117] O. Ronneberger, P. Fischer, and T. Brox, "U-net: Convolutional networks for biomedical image segmentation," *Int. Conf. Med. Image Comput. Comput. Assisted Intervention*, Springer, 2015, pp. 234-241.
- [118] J.-H. R. Chang, et. al., "One network to solve them all-solving linear inverse problems using deep projection models," *Int. Conf. Comput. Vis.*, 2017, pp. 5889-5898.
- [119] J. Sun et al., "Deep ADMM-net for compressive sensing MRI," *Adv. Neural Inf. Process. Syst.*, 2016, pp. 10-18.
- [120] L. Li, et. al. "DeepNIS: Deep neural network for nonlinear electromagnetic inverse scattering," *IEEE Transactions on Antennas and Propagation*, vol. 67, no. 3, pp. 1819-1825, Mar. 2019.
- [121] Y. Sanghvi, et. al., "Embedding deep learning in inverse scattering problems," *IEEE Trans. Comp. Imag.*, vol. 6, pp. 46-56, 2020.
- [122] J. Wang et al., "A machine learning-assisted inversion method for solving biomedical imaging based on semi-experimental data," *Electronics*, vol. 12, no. 12, p. 2623, 2023.
- [123] T. Shan, Z. Lin, X. Song, M. Li, F. Yang, and S. Xu, "Neural born iterative method for solving inverse scattering problems: 2D cases," *IEEE Trans. on Antennas and Propagation*, vol. 71, no. 1, pp. 818-829, Jan. 2023.
- [124] J. Zhang, L. Yang, and Y. Li, "Non-invasive measurement of intensive power-frequency electric field using a linbo3-integrated optical waveguide sensor," *IET Science, Measurement & Technology*, vol. 15, no. 1, pp. 101-108, 2021.
- [125] A. J. Mercante, S. Shi, P. Yao, L. Xie, R. M. Weikle, and D. W. Prather, "Thin film lithium niobate electro-optic modulator with terahertz operating bandwidth," *Opt. Express*, vol. 26, pp. 14810-14816, 2018.
- [126] R. Heinzlmann, et. al., "Optically powered remote optical field sensor system using an electroabsorption-modulator," *1998 IEEE MTT-S International Microwave Symposium Digest (Cat. No.98CH36192)*, vol. 3, pp. 1225-1228, 1998.
- [127] C. Fernandez-Valdivielso, I. Matias, M. Gorraiz, F. Arregui, C. Barriain, and M. Lopez-Amo, "Low cost electric field optical fiber detector," *15th Optical Fiber Sensors Conference Technical Digest (OFS 2002) (Cat. No.02EX533)*, vol. 1, pp. 499-502, 2002.
- [128] A. A. Savchenkov, W. Liang, V. S. Ilchenko, E. Dale, E. A. Savchenkova, A. B. Matsko, D. Seidel, and L. Maleki, "Photonic E-field sensor," *AIP Advances*, vol. 4, no. 12, p. 122901, 2014.
- [129] R. Shimizu, M. Matsuoka, K. Kato, N. Hayakawa, M. Hikita, and H. Okubo, "Development of Kerr electro-optic 3-d electric field measuring

- technique and its experimental verification," *IEEE Transactions on Dielectrics and Electrical Insulation*, vol. 3, no. 2, pp. 191–196, 1996.
- [130] C. L. Holloway, J. A. Gordon, S. Jefferts, A. Schwarzkopf, D. A. Anderson, S. A. Miller, N. Thacharoen, and G. Raithel, "Broadband Rydberg atom-based electric-field probe for SI-traceable, self-calibrated measurements," *IEEE Transactions on Antennas and Propagation*, vol. 62, no. 12, pp. 6169–6182, 2014.
- [131] N. Lehrter, *High Sensitivity Detection of Low Levels of Electromagnetic Fields: MPhil Thesis*. Downing College, University of Cambridge, 2021.
- [132] C. Foot and D. Foot, *Atomic Physics*. Oxford Master Series in Physics, OUP Oxford, 2005.
- [133] D. H. Meyer, Z. A. Castillo, K. C. Cox, and P. D. Kunz, "Assessment of Rydberg atoms for wideband electric field sensing," *Journal of Physics B: Atomic, Molecular and Optical Physics*, vol. 53, p. 034001, 2020.
- [134] H. Fan, et al., "Atom based RF electric field sensing," *Journal of Phy. B: Atomic, Molecular and Optical Physics*, vol. 48, no. 20, p. 202001, 2015.
- [135] Z. Song, et al., "Rydberg-atom-based digital communication using a continuously tunable radio-frequency carrier," *Optics Express*, vol. 27, no. 6, pp. 8848–8857, 2019.
- [136] J. A. Gordon, et al., "Weak electric-field detection with sub-1 Hz resolution at radio frequencies using a Rydberg atom-based mixer," *AIP Advances*, vol. 9, no. 4, p. 045030, 2019.
- [137] C. T. Fancher, D. R. Scherer, M. C. S. John, and B. L. S. Marlow, "Rydberg atom electric field sensors for communications and sensing," *IEEE Transactions on Quantum Engineering*, Vol. 2, pp. 1–13, 2021.
- [138] BT Trials Quantum Radios to Boost Future UK 5G Mobile Cover. Online: <https://www.ispreview.co.uk/index.php/2022/05/bt-trials-quantum-radios-to-boost-future-uk-5g-mobile-cover.html>
- [139] "Cisco Annual Internet Report (2018–2023) White Paper," Cisco, [Online], <https://www.cisco.com/c/en/us/solutions/collateral/executive-perspectives/annual-internet-report/white-paper-c11-741490.html>
- [140] "The 17 goals | sustainable development," United Nations, <https://sdgs.un.org/goals> (accessed Nov. 29, 2023).
- [141] C. K. Sanders and E. Scanlon, "The digital divide is a human rights issue: Advancing Social Inclusion Through Social Work Advocacy," *Journal of Human Rights and Social Work*, vol. 6, no. 2, pp. 130–143, 2021.
- [142] P. Vassilakopoulou and E. Hustad, "Bridging digital divides: A literature review and research agenda for information systems research," *Information Systems Frontiers*, vol. 25, no. 3, pp. 955–969, 2021.
- [143] "Digital inclusion of all," ITU, <https://www.itu.int/en/mediacentre/backgrounders/Pages/digital-inclusion-of-all.aspx>.
- [144] "How to close the digital divide in the U.S.," Harvard Business Review, <https://hbr.org/2021/07/how-to-close-the-digital-divide-in-the-u-s>.
- [145] T. Whipple, "State officials highlight discrepancies between updated FCC map and Ground Truth" [Online], Broadband Breakfast, <https://broadbandbreakfast.com/2023/06/state-officials-highlight-discrepancies-between-updated-fcc-map-and-ground-truth/>.
- [146] "Difference between 3G, 4G and 5G?" [Online], Verizon, <https://www.verizon.com/about/our-company/5g/difference-between-3g-4g-5g> (accessed Nov. 29, 2023).
- [147] A. Fendelman, "An introduction to 1G, 2G, 3G, 4G & 5G wireless," Lifewire, [Online], <https://www.lifewire.com/1g-vs-2g-vs-2-5g-vs-3g-vs-4g-578681> (accessed Nov. 29, 2023).
- [148] M. Jansen, "Will that unlocked phone work with your wireless carrier?" [Online], Digital Trends, <https://www.digitaltrends.com/mobile/smartphone-bands-explained>
- [149] Y. Kwon et al., "Spectrum fragmentation: Causes, measures and applications," *Telecom. Policy*, vol. 41, no. 5–6, pp. 447–459, 2017.
- [150] The socio-economic benefits of 5G services - GSMA, [Online], <https://www.gsma.com/spectrum/wp-content/uploads/2023/07/Socio-Economic-Benefits-of-Low-Band-5G-Spectrum.pdf>.
- [151] F. Hu, B. Chen and K. Zhu, "Full spectrum sharing in cognitive radio networks toward 5g: a survey," *IEEE Access*, vol. 6, pp. 15754–15776, 2018.
- [152] N. Tadayon and S. Aïssa, "Radio resource allocation and pricing: auction-based design and applications," *IEEE Transactions on Signal Processing*, vol. 66, no. 20, pp. 5240–5254, 2018.
- [153] R. Frieden, "The evolving 5G case study in spectrum management and industrial policy," *Telecom. Policy*, vol. 43, no. 6, pp. 549–562, 2019.
- [154] A. Kuš and M. Massaro, "Analysing the C-Band spectrum auctions for 5G in Europe: Achieving efficiency and fair decisions in radio spectrum management," *Telecommunications Policy*, vol. 46, no. 4, 2022.
- [155] M. Matinmikko-Blue, S. Yrjölä and P. Ahokangas, "Spectrum Management in the 6G Era: The Role of Regulation and Spectrum Sharing," 2020 2nd 6G Wireless Summit, Levi, Finland, 2020, pp. 1–5.
- [156] "Number of internet users worldwide 2022," Statista, [Online], <https://www.statista.com/statistics/273018/number-of-internet-users-worldwide> (accessed Nov. 29, 2023).
- [157] N. J. Rensburg, A. N. Matheri, and J. Meyer, "Bridging the digital divide in an African smart city," *2019 IEEE International Smart Cities Conference (ISC2)*, 2019.
- [158] R. A. M. Mauermayer and J. Kornprobst, "A Cost-effective tethered-uav-based coherent near-field antenna measurement system," *IEEE Open J. of Antennas and Propagation*, vol. 3, pp. 984–1002, 2022.
- [159] L. Ciorba et al., "Large horizontal near-field scanner based on a non-tethered unmanned aerial vehicle," *IEEE Open J. of Antennas and Propagation*, vol. 3, pp. 568–582, 2022.
- [160] S. Henault, "Antenna measurement drone for over-the-horizon radar," *15th Eur. Conf. Ant. and Propag.*, Dusseldorf, Germany, 2021, pp. 1–5.
- [161] C. Culotta-López et al., "On the uncertainty sources of drone-based outdoor far-field antenna measurements," *2021 Antenna Measurement Techniques Association Symp.*, Daytona Beach, FL, USA, 2021, pp. 1–6.
- [162] "Valmont records longest BVLOS flight on the wings of T-mobile 5G," T-mobile newsroom, <https://www.t-mobile.com/news/network/valmont-t-mobile-5g-industry-first-bvlos-flight>.
- [163] "LTE cellular connectivity for UAS," [Online], <https://www.elsight.com/blog/lte-cellular-connectivity-for-uas-command-control/> (accessed Nov. 29, 2023).
- [164] S. Ravichandran & M. Swaminathan, Heterogeneous Integration for AI Applications: Status & Future Needs, Chip Scale Review, 2022.
- [165] "Heterogeneous integration roadmap," *IEEE Electron. Packaging Soc.* [Online], <https://eps.ieee.org/technology/heterogeneous-integration-roadmap.html> (accessed Nov. 29, 2023).
- [166] G. Kenyon, "Heterogeneous integration and IC Packaging," EE Times Europe [Online], <https://www.eetimes.eu/heterogeneous-integration-and-the-evolution-of-ic-packaging/> (accessed Nov. 29, 2023).
- [167] O. Burkacky et al., "Advanced Chip Packaging: How manufacturers can play to win" [Online], McKinsey, <https://www.mckinsey.com/industries/semiconductors/our-insights/advanced-chip-packaging-how-manufacturers-can-play-to-win#> (acc. Nov. 29, 2023).
- [168] P. Patel, "U.S. universities are building a new semiconductor workforce," *IEEE Spectrum* [Online], <https://spectrum.ieee.org/chips-act-workforce-development#toggle-gdpr> (accessed Nov. 29, 2023).
- [169] 68% of the world population projected to live in urban areas by 2050 [Online], <https://www.un.org/development/desa/en/news/population/2018-revision-of-world-urbanization-prospects.html> (accessed 29 Oct 2023).
- [170] "Digital Literacy: The Great Divide," "GDC-submission_digital-national-alliance-bulgaria.pdf (un.org)" (accessed 29 Oct 2023).
- [171] D. Fang, Y. Qian and R. Q. Hu, "Security for 5G mobile wireless networks," *IEEE Access*, vol. 6, pp. 4850–4874, 2018.
- [172] J. Kong, F. T. Dagefu, J. Choi, P. Spasojevic and C. Koumpouzi, "Covert communications in low-VHF/microwave heterogeneous networks," *2022 IEEE Wireless Communications and Networking Conference*, 2022.
- [173] J. Choi and F. T. Dagefu, "A compact three-port antenna with enhanced inter-port isolation for polarization and pattern diversity," *IEEE Access*, vol. 11, pp. 111402 – 111409, 2023.
- [174] C. Koumpouzi et al., "Exploiting polarization diversity to improve cyclostationary-based LPD properties of CDMA," *IEEE Wireless Comm. Lett.*, vol. 12, no. 1, pp. 6–10, Jan. 2023.
- [175] J. Kong, et al., "Covert communication in intelligent reflecting surface assisted networks with a friendly jammer," *IEEE Transactions on Vehicular Technology*, vol. 73, no. 1, pp. 1467 – 1472, Jan. 2024.
- [176] J. Kong, F. T. Dagefu and B. M. Sadler, "Distributed beamforming in the presence of adversaries," *IEEE Trans. on Vehicular Technology*, vol. 69, no. 9, pp. 9682 – 9696, Sep. 2020.

Christian Pichot (IEEE Life Fellow) is a Director of Research Emeritus CNRS (French National Center for Scientific Research), Université Côte d'Azur and CNRS, LEAT Laboratory, Sophia Antipolis, France.

Gregory H. Huff (IEEE Senior Member) was born in Oklahoma City, OK, in 1975. He received the Ph.D. degree in electrical engineering from the University of Illinois, Urbana, IL, in 2006.

Yang Yang (IEEE Senior Member) was born in Inner Mongolia, China. He received the Ph.D. degree from Monash University, Melbourne, Australia, in 2013. He is currently an Associate Professor at the University of Technology Sydney.

Zhi Hao Jiang (IEEE Member) was born in Nanjing, China. He received the Ph.D. degree from The Pennsylvania State University, USA, in 2013. He is currently a Professor at SKLMMW, Southeast University.

Xuanfeng Tong (IEEE Graduate Student Member) was born in Taizhou, Jiangsu, China, in 1993. He received the Ph.D. degree from Southeast University, China, in 2023.

Tian Hong Loh (IEEE Senior Member) received the Ph.D. degree from Warwick University, UK, in 2005. He is currently a Principal Scientist at the UK National Physical Laboratory and a Visiting Professor with Surrey University, UK.

Ala Alemaryeen received her M.Sc. and Ph.D. degrees both in Electrical Engineering from the University of North Dakota, USA, in 2015 and 2019, respectively. She has been an Assistant Professor at Tafila Technical University, Jordan since 2019.

Mahmoud Wagih (IEEE Member) leads the Green RF-Enabled Electronics Lab at the University of Glasgow. He is an IEEE AP-S and MTT-S member, Speaker's Bureau for MTT-S, and has received 20+ research awards.

Sima Noghianian (IEEE Senior Member) received the Ph.D. degree in Electrical Engineering from the University of Manitoba, Canada. She is currently a Distinguished Antenna Design Engineer at CommScope Ruckus Networks, Sunnyvale, USA.

Rajesh C. Paryani (IEEE Member) is a Senior Staff Engineer and Technical Fellow at Northrop Grumman Mission Systems in Baltimore, MD. He received a PhD in Electrical Engineering from the University of Central Florida, Orlando, FL in 2008.

Yi Huang (IEEE Fellow) received a DPhil degree from Oxford University in 1994 and worked in industry and universities. He is at present a Professor in Wireless Engineering at the University of Liverpool, United Kingdom.

Kunio Sakakibara (IEEE Senior Member) was born in Aichi, Japan, in 1968. He received M.S. and D.E. degrees in Electrical

and Electronic Engineering from Tokyo Institute of Technology, Tokyo, Japan, in 1993 and 1996, respectively.

Francesca Vipiana (IEEE Senior Member) received the Ph.D. degree in Electronics and Communications Engineering in 2004 and currently is a Full Professor of Electromagnetic Fields at the Politecnico di Torino, Torino, Italy.

Elise Fear (IEEE Senior Member) received the Ph.D. degree in Electrical Engineering from the University of Victoria in 2001. She is currently a Professor at the University of Calgary, Canada and co-founded Wave View Imaging in 2020.

Saikat C. Bakshi (IEEE Senior Member) received Ph.D. from IEST, Shibpur, India. He did Post-Doctoral research at NUS Singapore for around two years. He is currently Assistant Professor at NIT Calicut, India.

Rod Waterhouse (IEEE Fellow) was born in Lower Hutt, New Zealand, in 1966. He received the Ph.D. degree in Electrical Engineering from the University of Queensland, Brisbane, Australia, in 1994.

Julio Urbina (IEEE Senior Member) received the Ph.D. degree from University of Illinois at Urbana-Champaign, IL, in 2002. He is currently a Professor in the School of Electrical Engineering and Computer Science at the Pennsylvania State University.

Sascha Meinrath (IEEE Member) is the Palmer Chair in Telecommunications at Penn State University, and director of the X-Lab, a DC-based technology policy institute.

Bono Po-Jen Shih (IEEE Member) received his Ph.D. in Science and Technology Studies from Virginia Tech in 2022. He is a Postdoctoral Scholar in Engineering Ethics with Penn State University's Rock Ethics Institute and Leonhard Center.

Rohit Sharma (IEEE Senior Member) is a Professor of Electrical Engineering at the Indian Institute of Technology Ropar, India. He was a Research Professor in the Department of Electrical Engineering at the Pennsylvania State University. His research interest is in the area of electronic packaging.

Vignesh Manohar (IEEE Member) was born in Maharashtra, India, in 1992. He received the Ph.D. degree in Electrical Engineering with focus on antenna design from University of California Los Angeles (UCLA) in 2020.

Fikadu T. Dagefu (IEEE Senior Member) received the Ph.D. degree from the University of Michigan, Ann Arbor. He is currently a Research Scientist at the US DEVCOM Army Research Laboratory in Adelphi, MD, USA.

Koichi Ito (IEEE Life Fellow) received the Ph.D. degree from Tokyo Institute of Technology, Japan. He is currently a Professor Emeritus and Visiting Professor at the Center for Frontier Medical Engineering, Chiba University, Japan.