POLITECNICO DI TORINO Repository ISTITUZIONALE

The Air-Water Interface of Water Microdroplets Formed by Ultrasonication or Condensation Does Not Produce H2O2

Original

The Air-Water Interface of Water Microdroplets Formed by Ultrasonication or Condensation Does Not Produce H2O2 / Musskopf, Nayara H; Gallo Jr, Adair; Zhang, Peng; Petry, Jeferson; Mishra, Himanshu. - In: THE JOURNAL OF PHYSICAL CHEMISTRY LETTERS. - ISSN 1948-7185. - ELETTRONICO. - 12:46(2021), pp. 11422-11429. [10.1021/acs.jpclett.1c02953]

Availability: This version is available at: 11583/2995205 since: 2024-12-12T08:29:43Z

Publisher: ACS

Published DOI:10.1021/acs.jpclett.1c02953

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)



pubs.acs.org/JPCL

The Air–Water Interface of Water Microdroplets Formed by Ultrasonication or Condensation Does Not Produce H₂O₂

Nayara H. Musskopf,[†] Adair Gallo, Jr.,[†] Peng Zhang,[†] Jeferson Petry, and Himanshu Mishra*

Cite This: J. Phys. Chem. Lett. 2021, 12, 11422–11429

III Metrics & More



Article Recommendations

Λ /	ጉሰ	NC C	20	
ΑI		. – .	5.0	
				1

ABSTRACT: Recent reports on the production of hydrogen peroxide (H_2O_2) on the surface of condensed water microdroplets without the addition of catalysts or additives have sparked significant interest. The underlying mechanism is thought to be ultrahigh electric fields at the air-water interface; smaller droplets present larger interfacial areas and produce higher (detectable) H_2O_2 yields. To gain insights into this phenomenon, we performed condensation experiments and quantified H_2O_2 formation as a function of the vapor source. Specifically, we compared the H_2O_2 concentration in water microdroplets condensed from the vapor realized via (i) heating water in the range of 50-70 °C and (ii) ultrasonic humidification (as exploited in the original report). Experimental results revealed that the H_2O_2 level inside water microdroplets condensed via heating water was below our detection limit ($\geq 0.25 \ \mu M$), regardless of the droplet size or the substrate wettability. In contrast, water droplets condensed via ultrasonic humidification contained significantly higher ($\sim 1 \ \mu M$) H_2O_2 concentrations. We conclude that the ultrasonic humidifiers contribute to H_2O_2 production, not droplet interfacial effects.



SI Supporting Information

Recent studies reporting on the spontaneous production of $\leq 115 \ \mu M \ H_2O_2$ in condensed water microdroplets with diameters of $\leq 10 \ \mu m$ on common substrates have sparked considerable interest.¹ Elucidation of the breakage of water O-H covalent bonds under normal temperature and pressure (NTP, 293 K and 1 atm) without the use of a catalyst, energy (electrical or mechanical), or other chemicals poses a challenge to our current understanding of water. These findings could advance our understanding of environmental processes, such as the oxidation of S(IV) species by H_2O_2 in the presence or absence of Fe^{2+} or Cu^{2+} ions, leading to the acidification of clouds, dew, fog, etc.²⁻⁴ Greener approaches for H_2O_2 synthesis⁵ and the rational development of hydrogen peroxide-based automated room disinfection in hospitals,⁶ water treatment,⁷ oral care,⁸ etc., are other exciting avenues. The mechanism suggested for H₂O₂ production in water microdroplets is based on the presence an an ultrahigh electric field at the air–water interface ($\sim 10^7 \text{ V/cm}$), which drives the formation of \bullet OH radicals from OH⁻ ions; these \bullet OH radicals combine to form H₂O₂.^{1,9} Currently, there is no theoretical explanation available for this intriguing phenomenon. We note that probing the air-water interface of <1 nm dimensions is a daunting task and sometimes fraught with interpretational ambiguities and/or experimental artifacts.¹⁰⁻¹⁹

Let us begin by briefly discussing the significance of the microscale of water droplets implicated in this phenomenon. Microscale enhances the air–water surface area; the larger the droplet surface area, the higher the level of H_2O_2 production due to the putative surface electrical field.¹ For example, the surface area of a 1 mL water droplet at normal temperature and

pressure (NTP, 293 K and 1 atm) with a diameter D of 1.24 cm, if transformed into microdroplets with a diameter d of 5 μ m, increases by a factor of D/d = 2480. In summary, the claim essentially is that H₂O₂ is produced even on the surface of a pail of water but remains undetected owing to the small airwater surface area and large volume of water, yielding ultralow concentrations.¹ The maximum reported H_2O_2 concentration in the water microdroplets condensed from the vapor within the relative humidity (RH) range of 40-70% and at substrate (silica) temperature 3.5 °C is ~115 μ M, when the droplet mean size is $\leq 10 \ \mu m$.¹ This concentration translates to ~ 1 H_2O_2 molecule per ~483092 water molecules, which renders standard spectroscopic fingerprinting techniques ineffective. As the condensed droplets grow over time, their surface-tovolume ratios decrease, which reduces H₂O₂ production and lowers measurable H_2O_2 concentration.¹ Thus, it is crucial to utilize ultrasensitive detection methods to investigate the factors and mechanisms underlying this phenomenon. Herein, we investigate H₂O₂ in condensed water microdroplets via an ultrasensitive method and put forth an alternate explanation for H_2O_2 formation in condensed water microdroplets.

Received: September 7, 2021 Accepted: November 1, 2021 Published: November 18, 2021





pubs.acs.org/JPCL



Figure 1. Comparison of representative calibration curves for H_2O_2 quantification assays: (A) potassium titanium oxalate (PTO) assay, (B) 2hydroxyterephthalic acid (HTA) assay, and (C) hydrogen peroxide assay kit (HPAK). The HPAK can detect H_2O_2 concentrations down to ~250 nM, while the PTO and HTA assays fail to resolve at 10 and 5 μ M, respectively. In the range of $0-1 \mu$ M, (D) PTO and (E) HTA assays cannot afford linearity in quantification, whereas (F) the HPAK affords it reliably for ≥250 nM H_2O_2 .

To utilize the most sensitive analytical method for quantifying trace amounts of H2O2 in water, we compared the efficacy of several known methods.³ For instance, titration with 0.1 M potassium titanium oxalate [PTO, $K_2 TiO(C_2O_4)_2$] is the most common method that was also exploited in the original report.¹ It entails the measurement of the absorbance at 400 nm of samples that also contain PTO (Figure S1A). However, this method can at best detect ~10 μ M H₂O₂ (or ~ 0.34 ppm) (Figure 1A). We also tested the efficacy of titration with terephthalic acid that yields 2-hydroxyterephthalic acid (HTA) on reaction with •OH radicals furnished by H₂O₂.²⁰ However, this method also fails to resolve dissolved H_2O_2 concentrations below 5 μ M (or ~0.17 ppm) (Figure 1B and Figure S1B). Either method would, for instance, prove to be inadequate in providing high-resolution insight into the time-dependent decline in the H2O2 concentration in condensing drops as they grow larger. In response, we utilized the Hydrogen Peroxide Assay Kit (HPAK, ab138886, Abcam PLC, Cambridge, U.K.). This fluorometric kit contains (i) a proprietary peroxide indicator that upon oxidation with H₂O₂ produces fluorescence in the near-infrared region (674 nm wavelength) and (ii) the horseradish peroxidase (HRP) enzyme that catalyzes the oxidation reaction. The HRP's catalytic activity enhances the fluorescence signal significantly, facilitating a linear detection range for H₂O₂ from ~250 nM (or 8.5 ppb) to 10 μ M (0.3 ppm) and rendering HPAK one of the most sensitive quantification methods for H_2O_2 .^{3,21} Panels A–C of Figure 1 compare the calibration plots for H_2O_2 titrations with PTO, terephthalic acid, and HPAK methods, respectively. With an approximately 40 times lower limit of detection than the PTO method, the HPAK assay would be able to pinpoint H_2O_2 concentrations inside condensing water droplets as their volumes increase with time (despite the dilution).

Equipped with the HPAK assay, we investigated H_2O_2 production in condensed water microdroplets as a function of different (i) methods for producing water vapor, (ii) substrates for condensation, and (iii) droplet sizes. Experiments were conducted inside a clean glovebox equipped with a N₂ flow to control the relative humidity of air. Water vapor was produced inside the glovebox via (i) a commercial ultrasonic humidifier (15 W output power) equipped with a megahertz range piezoelectric transducer or (ii) a hot plate to heat water in the range of 50-70 °C (Materials and Methods). N.B. an ultrasonic humidifier is a common household appliance; it produces tiny droplets at the air-water interface that rapidly evaporate to increase the relative humidity; a similar instrument was exploited in the original report.¹ In both cases, the relative humidity was adjusted to 92-96% at \sim 21-23 °C by a moisture controller by flowing N2 gas into the glovebox whenever the humidity was above the set point. Single-crystal SiO₂/Si wafers with the following surface

pubs.acs.org/JPCL

Letter



Figure 2. Representative time-dependent size distributions of condensed water droplets on FDTS-coated silica surfaces maintained at 3-4 °C and 92–96% RH realized via an ultrasonic humidifier: (A) 10 s, (B) 30 s, (C) 1 min, (D) 1.5 min, (E) 2.0 min, (F) 3.0 min, (G) 5 min, and (H) 40 min (bimodal distribution). Note that scale bars are in micrometers.



Figure 3. Representative image analysis (with ImageJ²⁴) of condensed water droplets on FDTS-coated silica surfaces at 3–4 °C and 92–96% RH realized via an ultrasonic humidifier. (A) Diameter distribution of the condensed droplets as a function of time [note that blue stars correspond to the mean value; the *x*-axis scale is not linear, and the right-hand-side *y*-axis is droplet diameter (micrometers) for t = 1200 s only]. (B) Mean droplet diameters as a function of time. Error bars signify one standard deviation. (C) Estimated cumulative volume of the condensate over time. The estimated average condensation rate is 0.31 μ L/s. Note the bimodal droplet distribution at t = 1200 s; this happens because larger droplets merge and numerous $\leq 10 \ \mu$ m droplets emerge in the spaces between them.

treatment (wettability) served as the substrates for the condensation of water vapor: (i) oxygen plasma treatment (hydrophilic) and (ii) silanization with perfluorodecyltrichlorosilane (FDTS) using a molecular vapor deposition technique²² (hydrophobic; details in the Materials and Methods and wetting characterization in section S1 of the Supporting Information). Substrates were cooled below the dew point by placing them on a water-ice bag; the surface temperatures were measured using an infrared probe (Materials and Methods) and found to be in the range of 3-4 °C. A significant distance (~40 cm) between the location of the substrates inside the glovebox and the vapor source ensured that any airborne droplets and/or clusters would evaporate first to form vapor and then condense, as observed by the gradual increase in the size of the droplets (Figure 2 and Figure S2). Note that hydrophobic FDTS-coated SiO₂/Si

wafers (hereafter termed FDTS-coated silica) were utilized as the substrate for condensation in most of this work because they facilitated easier removal of the condensed water for further analysis than did hydrophilic plasma-treated silica.

With the water vapor supplied from the ultrasonic humidifier, size distributions (mean \pm standard deviation) of the condensed microdroplets on FDTS-coated silica shifted their peak positions from 10.3 \pm 3.2 μ m at 10 s to 103 \pm 98 μ m (bimodal distribution) at 20 min (Figures 2 and 3 and details in Materials and Methods). Similarly, with the vapor supplied from the heated water (60 °C), size distributions shifted their peak positions from 8.4 \pm 2.7 μ m at 10 s to 144 \pm 134 μ m (bimodal distribution) at 40 min (Figures S2 and S3).

We were also able to estimate the condensation rates via image analysis. To do this, we assumed the condensed microdroplets to be truncated spheres with the contact angles

at the solid–liquid–vapor interface equal to the measured apparent contact angles on FDTS-coated silica $[\theta_r \approx 105^{\circ} (\text{section S1})]$. This is a reasonable assumption because the capillary length of water, defined as the length scale at which capillary forces dominate over inertia, at NTP is $\lambda_c = 2.7 \text{ mm}$, which is much larger than the size of the condensed water microdroplets. N.B. λ_c is given by the formula, $\lambda_c = \sqrt{\frac{\gamma_{LV}}{\rho g}}$, where, γ_{LV} is the surface tension of water, ρ is the density, and g is the acceleration due to gravity.²³ With this approach, we estimated the condensation rates to be 0.31 and 0.23 μ L/s for the ultrasonic humidifier and the heating plate (at 60 °C), respectively (Figure 3 and Figure S3). Out of curiosity, we also quantified the condensation behavior of water from the ambient laboratory air at 59% RH and 21.4 °C and found it to be 0.35 μ L/s (Figures S4 and S5).

Next, H₂O₂ concentrations were quantified in the condensates formed on FDTS-coated silica and plasma-treated silica with the vapor formed via heating water or ultrasonic humidification (Figure 3). In a typical experiment, we stopped water condensation when the condensate was enough for us to collect ~400-600 μ L, which took ~40 min for heating and \sim 20 min for the ultrasonic humidifier. See Figure 3A and Figure S3A to notice the size distribution of droplets in those instances. Subsequently, the substrates were tilted to pour condensed water (drops or films) into clean glassware for H₂O₂ quantification via the HPAK. When water was heated to 60 °C to produce the vapor, we found no significant differences (with a p value of >0.01) in the H₂O₂ concentrations of the condensed water and the bulk water; i.e., both were below our detection limit (0.25 μ M) (Figure 4, group c, and Figure S8). Also, when the vapor was formed via heating water, the hydrophilicity or hydrophobicity of the substrates had no effect on the H2O2 concentration. These trends were consistent at 50 and 70 °C, as well (Figure S6).

In contrast, when ultrasonic humidification was exploited to produce the vapor, there was a significant enhancement in the H_2O_2 concentration (~1 μ M) in the condensed water (Figure 4); the condensates on the plasma-treated surfaces had H_2O_2 concentrations slightly higher than those on the FDTS-coated surfaces (groups **a** and **b** in Figure 4).

We wondered if the absence of H_2O_2 in the condensates derived from the heating experiments and the ~1 μ M H_2O_2 concentration measured in the condensates derived from the ultrasonic humidifier were so low due to the fact that (i) we collected microdroplets largely with diameters of $\geq 10 \ \mu$ m, which caused a dramatic dilution of the H_2O_2 concentration, or (ii) H_2O_2 is produced exclusively when ultrasonic humidification is applied.

To pinpoint the correct answer, first, we tried to measure the H_2O_2 concentration in water microdroplets with diameters of strictly $\leq 10 \ \mu$ m. Under our experimental conditions, condensed water microdroplets with diameters of $\leq 10 \ \mu$ m appeared during the first 10 s for the ultrasonic humidifier (Figures 2 and 3) and during the first 20 s for the heating plate at 60 °C (Figures S2 and S3) and ambient moisture condensation (Figures S4 and S5). Very quickly, we realized that due to their size being significantly smaller than the capillary length of water, pinning forces were so high compared to inertia that it was not possible to detach them via tilting (90° or 180°) from the FDTS-coated silica substrates.²⁵ Microdroplets also evaporated rapidly when exposed to a lower-relative humidity environment, which prevented us from



Figure 4. Comparison of H₂O₂ concentrations in the water microdroplets that accumulated on hydrophobic (Phob.) and hydrophilic (Phil.) substrates after the condensation of vapor produced via (i) heating water in the temperature range of 50-70 °C (Heat.) and (ii) an ultrasonic humidifier (Hum.). There were no statistically significant differences in the H2O2 concentration of the bulk water and the water droplets collected after the condensation of vapor generated by heating water at 60 °C. Note that experimental results for heating at 50 and 70 °C (Figure S6) yield results similar to those of the 60 °C case presented here. The chemical makeup of the substrates had no significant effects on the H2O2 concentration. In contrast, the H₂O₂ concentration in the water condensed from the ultrasonic humidifier was $\sim 1 \,\mu$ M. In this case, the chemical makeup of the substrates also had a significant effect on the H₂O₂ concentration. Bold letters (a-c) under the labels refer to the statistically different groups analyzed with one-way ANOVA and Tukey's test for comparison of the means (p < 0.01); a blue star indicates the mean value. Note that the detection limit of the HPAK assay in our experiments was 0.25 µM.

using ultracentrifugation for sliding and collecting them. Furthermore, the volume of the droplets after condensation for only 10–20 s was so low that the HPAK could not be utilized because the minimum sample volume, considering evaporative losses during handling, is 400–600 μ L. Therefore, we resorted to commercial peroxide test strips with a detection limit of 29.4 μ M for aqueous H₂O₂; similar strips were also utilized in the original report¹ (details in Materials and Methods). However, when peroxide test strips were swiped over water microdroplets with diameters of \leq 10 μ m that condensed from vapor generated by the ultrasonic humidifier, heating (60 °C), and ambient air, they did not undergo any change in their color. As a check, we tested the test strips with standard H₂O₂ solutions and confirmed that they reliably detect H₂O₂ at concentrations of \geq 30 μ M.

We wondered if this outcome was due to the fact that the lifetime of the microdroplets was too short to produce a detectable H_2O_2 concentration. After the first few seconds (7–10 s) of condensation from the three sources listed above, we cut off the vapor from condensing further by placing a lid on top. This simple method allowed us to maintain the desirable size distribution for a longer time (2–5 min). Using peroxide test strips again, we found no evidence of aqueous H_2O_2 regardless of the waiting time.

Next, we studied the effects of the output power of ultrasonic humidifiers on the H_2O_2 concentration in condensed water microdroplets. We compared the perform-

ance of our 15 W ultrasonic humidifier with that of another commercial 20 W device (details in Materials and Methods). We broadened the investigation by probing H₂O₂ concentrations not only in the condensed microdroplets but also in the mist formed at the humidifier outlet as well as the water reservoirs inside the humidifiers. Because the volumes of the mist and the water reservoirs were large, we could track them from inception via the HPAK, while we had to wait for ~ 20 min to collect adequate condensate (also explained above). Experimental results revealed that for either device, the H_2O_2 concentration was below the detection limit before it was turned on; after mist formation started, the H2O2 concentration in the mist increased with time and reached ~ 2 and ~ 3 μ M for the 15 and 20 W devices, respectively (Figure 5). The H₂O₂ concentrations in the reservoir also followed the same trend.



Figure 5. Ultrasonic humidifier mist and H_2O_2 formation. H_2O_2 formation over time in the mist and in the water reservoir (in contact with the piezo element) in ultrasonic humidifier models 1 and 2 with output powers of 15 and 20 W, respectively. The yellow box represents the H_2O_2 concentrations in water microdroplets that accumulated on FDTS-coated silica (from Figure 4). Note that humidifier model 1 was used in most of the condensation experiments reported in this work and humidifier model 2 was used to compare the effect of output power on H_2O_2 production.

We also tested the effects of a 500 W microtip ultrasonication device (20000 Hz) on H_2O_2 concentration in bulk water (Materials and Methods). Analysis with the HPAK revealed that while the bulk water had an initial H_2O_2 concentration below the detection limit, it increased linearly with time to 3 μ M in 3 h (Figure S7).

As illustrated in Figure 6, our experiments with heating, ultrasonic humidifiers, and ambient air condensation demonstrate that detectable H_2O_2 is produced in condensed water microdroplets exclusively when ultrasonic humidifiers are exploited. In section S2, we explain why condensed microdroplets with diameters of $\leq 10 \ \mu$ m produced via heating, ultrasonics, and ambient air could not have had H_2O_2 concentrations of $\geq 60 \ \mu$ M in our experiments, or else the HPAK would have detected them. Furthermore, during ultrasonic humidification studies, we noticed that most of the generated mist fell back into the water reservoir, which caused the time-dependent increase in the H_2O_2 concentration in the mist. This is expected to increase the H_2O_2 concentration in the condensate for some time, a trend also observed in the

original report.¹ For further insight into H_2O_2 production in ultrasonic humidifiers, it is crucial to investigate the effects of output power, operational frequency, structural design, water level, etc. How H_2O_2 partitions between the mist and the bulk water considering its ultrahigh solubility in water is also worth exploring. Next, we list two crucial questions pertaining to H_2O_2 formation that still remain unaddressed. (i) Why do we not observe H_2O_2 concentration in the range of $30-115 \ \mu$ M in our condensed microdroplets as in the original report?¹ (ii) What factors and mechanisms underlie the formation of H_2O_2 (~30 $\ \mu$ M) in water microdroplets generated via pneumatic spraying²⁶ (which does not utilize ultrasonication for droplet generation)? We are currently investigating these unanswered questions via a combination of experiment and theory.

Significantly different outcomes manifest when a bulk liquid is exposed to ultrasonication or gently heated on a hot plate (below its boiling point and with a stirrer). The latter method distributes the energy uniformly within the bulk, while the former entails energy localization leading to hot spots.²⁷ The ultrasonication of water causes the formation of numerous tiny pulsating bubbles, cavitation, that eventually implode to produce ultrahigh pressure (shock waves) and temperature and drive chemical reactions (including H_2O_2 formation).^{28–30} On one hand, cavitation erosion of surfaces poses an engineering challenge to fluid machinery; 31,32 on the other hand, it has been utilized for wastewater treatment, 33,7,34,35 surface cleaning,³⁶ and synthesis of materials.³⁷ Similarly, ultrasonic humidifiers exploit megahertz-frequency piezoelectric transducers that convert electrical energy into vibrational energy to produce the mist. Our experimental results demonstrate that this process produces H₂O₂ in the mist and, consequently, in the condensed droplets (Figure 5). In contrast, mild heating does not lead to H2O2 formation (Figure 4). Therefore, we submit that the recently reported H_2O_2 production in condensed water droplets could be in part due to experimental artifacts arising from ultrasonication.¹ We hope that this report will stimulate further research to address the pending questions.

MATERIALS AND METHODS

Chemicals. A Milli-Q Advantage 10 setup was utilized for deionized water used in this study. The water purification unit consisted of a Q-Gard pretreatment pack, an ultraviolet lamp, a Quantum cartridge (activated carbon and ion exchange resins), and a Q-Pod dispenser for the final polishing.³⁸ The electrical resistivity of the water was 18.2 M Ω cm. Standard hydrogen peroxide (H₂O₂) solutions (30%) were purchased from VWR Chemicals (catalog no. 23622.298) and used as is.

Substrates for Condensation. Silicon wafers (p-doped, $\langle 100 \rangle$ orientation, 4 in. diameter, with a 500 μ m thickness and with a thermally grown 2 μ m thick oxide layer) were purchased from Silicon Valley Microelectronics (catalog no. SV010).

Functionalization of SiO_2/Si Wafers. Oxygen Plasma Treatment for Hydrophilic Substrates. A Diener electronic machine (Atto model, 200 W) was supplied with ultrapure (99.999%) O_2 gas at a flow rate of 16.5 sccm for 10 min, to create oxygen plasma.

Silanization with Perfluorodecyltrichlorosilane (FDTS). Treatment of silica surfaces with an oxygen plasma for 2 min removed organic contaminants and hydroxylated the surface. These surfaces were then grafted with FDTS using a molecular vapor deposition process (Applied Microstructures



Figure 6. Scientific illustration of the condensation of water vapor generated via (A) heating water on a hot plate and (B) an ultrasonic humidifier. Condensed water droplets formed on hydrophilic and hydrophobic substrates and then were collected and analyzed for H_2O_2 concentration. Our experimental results reveal that ultrasonic humidifiers can produce significant quantities of H_2O_2 in their mist (and also in the water reservoir), which then appears in the condensed water droplets. On the contrary, heating water to form vapor and condensing it does not produce H_2O_2 within our detection limits ($\geq 0.25 \ \mu$ M) (image credit, Ivan Gromicho, KAUST).

MVD100E) using protocols that we have reported previously.³⁹

Characterizing Wetting of Substrates via Apparent Contact Angles. Apparent contact angles of water droplets were measured on the substrates using the Kruss Drop Shape Analyzer (DSA100E), and the data were analyzed with the Advance software.

Glovebox Experiments. Condensation experiments were performed inside a portable isolation glovebox (Cleatech, catalog no. 2200-2-B) as a controlled-environment chamber. It was equipped with a digital humidity control system (Cleatech, A21-HM-HDS) that purged nitrogen gas flow to dehumidify the air. SiO₂/Si wafers with the surface treatments mentioned above were used as substrates. The substrates were cooled by placing them onto an ice-water bag, i.e., ice mixed with water such that the temperature of the bag is constant in every region. We allowed the samples to reach thermal equilibrium with the ice-water bath. The temperature of the surfaces was measured via a noncontact digital infrared thermometer (Lasergrip 774) during the experiment. The relative humidity inside the chamber was kept in the range of 92-96%, and the laboratory temperature was in the range of 21-23 °C. To collect the samples after condensation, we poured the droplets into clean glassware and transferred it into a 15 mL centrifuge tube (VWR International).

Water Vapor Generation via an Ultrasonic Humidifier. The following two ultrasonic humidifiers were used in this work: (i) Proton PHC 9UH (15 W) and (ii) Beurer LB 44 (20 W). Both of them contain a piezoelectric disk that vibrates creating ultrasonic waves that lead to the formation of mist from bulk water. The former humidifier was used in most of our experiments. To prevent the direct deposition of the mist (before its evaporation) onto the substrates, we positioned them 40 cm apart. These humidifiers enabled us to pinpoint the effect of output power on H_2O_2 production in the mist, the water reservoirs, and the condensates.

Water Vapor Generation via a Heating Plate. Deionized water was heated in the range of 50-70 °C using an IKA RCT heating plate (catalog no. 3810000). The plate was located ~30 cm from the substrates. To control the temperature, the coupled temperature sensor (PT 1000.60) was inserted inside the water.

Quantification of H₂O₂ in Water. Hydrogen Peroxide Assay Kit (HPAK) Assay. The H₂O₂ concentration inside condensed water microdroplets was quantified using the HPAK (fluorometric-near infrared, catalog no. ab138886). It contains its unique AbIR Peroxidase Indicator that produces fluorescence independent of the solution pH in the range of 4-10. Its maximum excitation wavelength is at 647 nm, and its maximum emission at 674 nm. Horseradish peroxidase catalyzes the reaction between H_2O_2 and the indicator and enhances the fluorescence signal. This facilitates the linear range of detection from 250 nM to 10 μ M. The calibration curve (Figure 1C) was realized by adding 50 μ L of an H₂O₂ standard solution from a concentration of 50 nM to 10 μ M to 50 μ L of the H₂O₂ reaction mixture. The analysis was performed in a 96-well black/clear bottom microtiter plate with the SpectraMax M3 microplate reader (Molecular Devices LLC). The analysis software used was SoftMax Pro 7. The water microdroplets were analyzed in the same way by mixing 50 μ L of each sample with the H₂O₂ reaction mixture, thus obtaining the respective concentration by the calibration curve.

Peroxide Test Strips for Semiquantitative Analysis. Peroxide test strips (Baker Test Strips, VWR International) with a detection limit of 1–100 mg/L were used to analyze the H_2O_2 concentration when we could not collect adequate sample volumes (100 μ L) for HPAK analysis. These strips contain a

colorimetric reagent that turns blue when brought into contact with H_2O_2 in the specified concentration range.

Characterization of the Size of Microdroplets. After microdroplet condensation inside the chamber, the samples were quickly (<10 s) moved to a Leica DVM6 optical microscope for imaging. Next, ImageJ²⁴ was used to estimate the size distribution. To estimate the size distributions of microdroplets condensed from the ambient laboratory air, substrates were already positioned in the microscope.

Probe Sonication. A 500 W ultrasonic processor (Sonics & Materials, model VC 505) with a stepped microtip was used to ultrasonicate 30 mL of water at 20 kHz at its 40% amplitude for different durations from 10 to 180 min. The beaker was kept in an ice bath to prevent sample evaporation.

ASSOCIATED CONTENT

Supporting Information

The Supporting Information is available free of charge at https://pubs.acs.org/doi/10.1021/acs.jpclett.1c02953.

Comparative spectra for the H_2O_2 detection methods, wetting characterization of the treated SiO₂/Si wafers, time-dependent size distribution images and analysis of condensed water droplets on FDTS-coated silica surfaces with RH realized via heating water to 60 °C in ambient air, comparison of H_2O_2 concentrations in the water droplets that accumulated on the substrates after the condensation of vapor produced via heating water in the temperature range of 50–70 °C, H_2O_2 production in a bulk water sample using probe sonication, and assessment of H_2O_2 detection with HPAK from diluted condensed microdroplets (PDF)

AUTHOR INFORMATION

Corresponding Author

Himanshu Mishra – Interfacial Lab (iLab), King Abdullah University of Science and Technology (KAUST), Biological and Environmental Science and Engineering (BESE) Division, Water Desalination and Reuse Center (WDRC), Thuwal 23955-6900, Saudi Arabia; orcid.org/0000-0001-8759-7812; Email: Himanshu.Mishra@kaust.edu.sa

Authors

- Nayara H. Musskopf Interfacial Lab (iLab), King Abdullah University of Science and Technology (KAUST), Biological and Environmental Science and Engineering (BESE) Division, Water Desalination and Reuse Center (WDRC), Thuwal 23955-6900, Saudi Arabia
- Adair Gallo, Jr. Interfacial Lab (iLab), King Abdullah University of Science and Technology (KAUST), Biological and Environmental Science and Engineering (BESE) Division, Water Desalination and Reuse Center (WDRC), Thuwal 23955-6900, Saudi Arabia; © orcid.org/0000-0001-5015-8111
- Peng Zhang Interfacial Lab (iLab), King Abdullah University of Science and Technology (KAUST), Biological and Environmental Science and Engineering (BESE) Division, Water Desalination and Reuse Center (WDRC), Thuwal 23955-6900, Saudi Arabia
- Jeferson Petry Interfacial Lab (iLab), King Abdullah University of Science and Technology (KAUST), Biological and Environmental Science and Engineering (BESE)

Division, Water Desalination and Reuse Center (WDRC), Thuwal 23955-6900, Saudi Arabia

Complete contact information is available at: https://pubs.acs.org/10.1021/acs.jpclett.1c02953

Author Contributions

^TN.H.M., A.G., and P.Z. contributed equally to this work.

Notes

The authors declare no competing financial interest.

ACKNOWLEDGMENTS

The authors acknowledge research funding from King Abdullah University of Science and Technology via Grant BAS/1/1070-01-01. The illustration for Figure 6 was created by Ivan Gromicho, Scientific Illustrator, Research Communication and Publication Services, Office of the Vice President for Research, King Abdullah University of Science and Technology.

REFERENCES

(1) Lee, J. K.; Han, H. S.; Chaikasetsin, S.; Marron, D. P.; Waymouth, R. M.; Prinz, F. B.; Zare, R. N. Condensing water vapor to droplets generates hydrogen peroxide. *Proc. Natl. Acad. Sci. U. S. A.* **2020**, *117* (49), 30934–30941.

(2) Seinfeld, J. H.; Pandis, S. N. Atmospheric Chemistry and Physics: From Air Pollution to Climate Change, 2nd ed.; Wiley-Interscience, 1998.

(3) Gunz, D. W.; Hoffmann, M. R. Atmospheric chemistry of peroxides: a review. Atmos. Environ., Part A 1990, 24 (7), 1601–1633. (4) He, S. Z.; Chen, Z. M.; Zhang, X.; Zhao, Y.; Huang, D. M.; Zhao, J. N.; Zhu, T.; Hu, M.; Zeng, L. M. Measurement of atmospheric hydrogen peroxide and organic peroxides in Beijing before and during the 2008 Olympic Games: Chemical and physical factors influencing their concentrations. J. Geophys. Res. 2010, 115 (D17), n/a.

(5) Zhu, C.; Francisco, J. S. Production of hydrogen peroxide enabled by microdroplets. *Proc. Natl. Acad. Sci. U. S. A.* **2019**, *116* (39), 19222.

(6) Otter, J. A.; Yezli, S.; Barbut, F.; Perl, T. M. An overview of automated room disinfection systems: When to use them and how to choose them. *Decontamination in Hospitals and Healthcare* **2020**, 323–369.

(7) Hoffmann, M.; Hua, I.; Hoechemer, R. Application of Ultrasonic Irradiation for the Degradation of Chemical Contaminants in Water. *Ultrason. Sonochem.* **1996**, *3*, 168–172.

(8) Marshall, M.; Cancro, L.; Fischman, S. Hydrogen Peroxide: A Review of Its Use in Dentistry. J. Periodontol. **1995**, 66, 786–96.

(9) Dulay, M. T.; Huerta-Aguilar, C. A.; Chamberlayne, C. F.; Zare, R. N.; Davidse, A.; Vukovic, S. Effect of relative humidity on hydrogen peroxide production in water droplets. *QRB Discovery* **2021**, *2*, e8.

(10) Mishra, H.; Enami, S.; Nielsen, R. J.; Stewart, L. A.; Hoffmann, M. R.; Goddard, W. A.; Colussi, A. J. Bronsted basicity of the airwater interface. *Proc. Natl. Acad. Sci. U. S. A.* **2012**, *109* (46), 18679–18683.

(11) Saykally, R. J. Air/water interface: Two sides of the acid-base story. *Nat. Chem.* **2013**, *5* (2), 82–84.

(12) Gallo, A.; Farinha, A. S. F.; Dinis, M.; Emwas, A.-H.; Santana, A.; Nielsen, R. J.; Goddard, W. A.; Mishra, H. The chemical reactions in electrosprays of water do not always correspond to those at the pristine air-water interface. *Chemical Science* **2019**, *10* (9), 2566–2577.

(13) Colussi, A. J.; Enami, S. Comment on "The chemical reactions in electrosprays of water do not always correspond to those at the pristine air-water interface" by A. Gallo Jr, A. S. F. Farinha, M. Dinis, A.-H. Emwas, A. Santana, R. J. Nielsen, W. A. Goddard III and H. Mishra, Chem. Sci., 2019, 10, 2566. *Chem. Sci.* 2019, 10, 8253.

(14) Gallo, A.; Farinha, A. S. F.; Emwas, A.-H.; Santana, A.; Nielsen, R. J.; Goddard, W. A.; Mishra, H. Reply to the 'Comment on "The chemical reactions in electrosprays of water do not always correspond to those at the pristine air-water interface" by A. J. Colussi and S. Enami, Chem. Sci., 2019, 10, DOI: 10.1039/c9sc00991d. Chem. Sci. 2019, 10, 8256.

(15) Nauruzbayeva, J.; Sun, Z.; Gallo, A.; Ibrahim, M.; Santamarina, J. C.; Mishra, H. Electrification at water-hydrophobe interfaces. *Nat. Commun.* **2020**, *11* (1), 5285.

(16) Uematsu, Y.; Bonthuis, D. J.; Netz, R. R. Charged Surface-Active Impurities at Nanomolar Concentration Induce Jones-Ray Effect. J. Phys. Chem. Lett. 2018, 9 (1), 189–193.

(17) Byrnes, S. J.; Geissler, P. L.; Shen, Y. R. Ambiguities in surface nonlinear spectroscopy calculations. *Chem. Phys. Lett.* **2011**, *516* (4–6), 115–124.

(18) Agmon, N.; Bakker, H. J.; Campen, R. K.; Henchman, R. H.; Pohl, P.; Roke, S.; Thämer, M.; Hassanali, A. Protons and Hydroxide Ions in Aqueous Systems. *Chem. Rev.* **2016**, *116* (13), 7642–7672.

(19) Ruiz-Lopez, M. F.; Francisco, J. S.; Martins-Costa, M. T. C.; Anglada, J. M. Molecular reactions at aqueous interfaces. *Nature Reviews Chemistry* **2020**, *4* (9), 459–475.

(20) Barreto, J. C.; Smith, G. S.; Strobel, N. H.; McQuillin, P. A.; Miller, T. A. Terephthalic acid: a dosimeter for the detection of hydroxyl radicals in vitro. *Life Sci.* **1994**, *56* (4), PL89–PL96.

(21) Kim, G.; Lee, Y.-E. K.; Kopelman, R. Hydrogen Peroxide (H_2O_2) Detection with Nanoprobes for Biological Applications: A Mini-review. In *Oxidative Stress and Nanotechnology: Methods and Protocols;* Armstrong, D., Bharali, D. J., Eds.; Humana Press: Totowa, NJ, 2013; pp 101–114.

(22) Pillai, S.; Santana, A.; Das, R.; Shrestha, B. R.; Manalastas, E.; Mishra, H. A molecular to macro level assessment of direct contact membrane distillation for separating organics from water. *J. Membr. Sci.* **2020**, *608*, 118140.

(23) Adamson, A. W.; Gast, A. P. Physical Chemistry of Surfaces; Wiley-Interscience, 1997.

(24) Schneider, C. A.; Rasband, W. S.; Eliceiri, K. W. NIH Image to ImageJ: 25 years of image analysis. *Nat. Methods* **2012**, *9* (7), 671–675.

(25) Gao, N.; Geyer, F.; Pilat, D.; Wooh, S.; Vollmer, D.; Butt, H.-J.; Berger, R. How drops start sliding over solid surfaces. *Nat. Phys.* **2018**, *14*, 191.

(26) Lee, J. K.; Walker, K. L.; Han, H. S.; Kang, J.; Prinz, F. B.; Waymouth, R. M.; Nam, H. G.; Zare, R. N. Spontaneous generation of hydrogen peroxide from aqueous microdroplets. *Proc. Natl. Acad. Sci. U. S. A.* **2019**, *116* (39), 19294–19298.

(27) Suslick, K. S. Sonochemistry. Science 1990, 247 (4949), 1439–45.

(28) Riesz, P.; Berdahl, D.; Christman, C. L. Free radical generation by ultrasound in aqueous and nonaqueous solutions. *Environ. Health Perspect.* **1985**, *64*, 233–252.

(29) Suslick, K. S. Ultrasound: its chemical, physical, and biological effects; VCH Publishers, 1988.

(30) Fang, X.; Mark, G.; von Sonntag, C. OH radical formation by ultrasound in aqueous solutions Part I: the chemistry underlying the terephthalate dosimeter. *Ultrason. Sonochem.* **1996**, 3 (1), 57–63.

(31) Gonzalez-Avila, S. R.; Nguyen, D. M.; Arunachalam, S.; Domingues, E. M.; Mishra, H.; Ohl, C.-D. Mitigating cavitation erosion using biomimetic gas-entrapping microtextured surfaces (GEMS). *Sci. Adv.* **2020**, *6* (13), eaax6192.

(32) Singh, R.; Tiwari, S.; Mishra, S. Cavitation Erosion in Hydraulic Turbine Components and Mitigation by Coatings: Current Status and Future Needs. J. Mater. Eng. Perform. **2012**, 21, 1539.

(33) Gogate, P.; Tayal, R. K.; Pandit, A. Cavitation: A technology on the horizon. *Current Science* **2006**, *91*, 35–46.

(34) Petrier, C.; Lamy, M.-F.; Francony, A.; Benahcene, A.; David, B.; Renaudin, V.; Gondrexon, N. Sonochemical Degradation of Phenol in Dilute Aqueous Solutions: Comparison of the Reaction Rates at 20 and 487 kHz. *J. Phys. Chem.* **1994**, *98* (41), 10514–10520.

(35) Hoffmann, M. R.; Hua, I.; Höchemer, R. Application of ultrasonic irradiation for the degradation of chemical contaminants in water. *Ultrason. Sonochem.* **1996**, 3 (3), S163–S172.

(36) Ohl, C.-D.; Arora, M.; Dijkink, R.; Janve, V.; Lohse, D. Surface cleaning from laser-induced cavitation bubbles. *Appl. Phys. Lett.* **2006**, 89 (7), 074102.

(37) Bang, J. H.; Suslick, K. S. Applications of Ultrasound to the Synthesis of Nanostructured Materials. *Adv. Mater.* **2010**, *22* (10), 1039–1059.

(38) Milli-Q® Advantage A10® Water Purification Systems. Useradapted ultrapure water. EMD Millipore Corp.: Billerica, MA, 2013. (39) Shrestha, B. R.; Pillai, S.; Santana, A.; Donaldson, S. H., Jr; Pascal, T. A.; Mishra, H. Nuclear Quantum Effects in Hydrophobic Nanoconfinement. J. Phys. Chem. Lett. **2019**, *10* (18), 5530–5535.