

A kinetic perspective on k-epsilon turbulence model and corresponding entropy production

Original

A kinetic perspective on k-epsilon turbulence model and corresponding entropy production / Asinari, Pietro; Fasano, Matteo; Chiavazzo, Eliodoro. - In: ENTROPY. - ISSN 1099-4300. - ELETTRONICO. - 18:4(2016), pp. 121-134. [10.3390/e18040121]

Availability:

This version is available at: 11583/2638624 since: 2016-03-31T15:14:05Z

Publisher:

MDPI

Published

DOI:10.3390/e18040121

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Article

A kinetic perspective on $k - \epsilon$ turbulence model and corresponding entropy production

Pietro Asinari ^{1,*}, Matteo Fasano ¹ and Eliodoro Chiavazzo ¹

¹ Department of Energy, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy

* Correspondence: pietro.asinari@polito.it; Tel.: +39-011-090-4434

Version March 23, 2016 submitted to Entropy; Typeset by L^AT_EX using class file mdpi.cls

Abstract: In this paper, we present an alternative derivation of the entropy production in turbulent flows, based on a formal analogy with the kinetic theory of rarefied gas. This analogy allows proving that the celebrated $k - \epsilon$ model for turbulent flows is nothing more than a set of coupled BGK-like equations with a proper forcing. This opens a novel perspective on this model, which may help in sorting out the heuristic assumptions essential for its derivation, such as the balance between turbulent kinetic energy production and dissipation. The entropy production is an essential condition for the design and optimization of devices where turbulent flows are involved.

Keywords: Thermodynamics of Irreversible Processes (TIP); turbulence modeling; Reynolds averaging; entropy production; second law

1. Introduction and motivation

Even though it is omnipresent around us, turbulence remains one of the last unsolved problems in classical physics. We can find turbulent flows in astrophysical plasmas, atmospheric winds, ocean currents, planetary boundary layers, rivers, fluid dynamics around all kind of vehicles, internal combustion engines, heat exchangers and, even, blood flows. Turbulence indicates certain complex and unpredictable motions of a fluid with an entire hierarchy of structures called eddies. An overview of this topic is too broad to be reported here, and it can be found in Ref. [1]. Interesting historical notes can be found in Ref. [2]. In spite of the tremendous work done in the last century and the new possibilities offered by direct numerical simulation of turbulent flows, the theoretical progress in understanding turbulence are proceeding slowly. One of the reasons may be that turbulence is deeply rooted in fluid mechanics, [while fluid dynamic equations are not derived from fundamental considerations and the mathematical theory of fluids is not yet fully developed](#) [3]. Still nowadays, the most important contribution to the theory of turbulence is due to the Russian mathematician Andrei Kolmogorov. [In 1941, a conceptual framework for turbulence \(K41 theory\) was defined by Kolmogorov \[4–6\]. The K41 which was originally derived](#) for homogeneous and isotropic turbulence (i.e. statistically invariant under translations and rotations). After more than 70 years, it has been found out that the K41 theory may also explain turbulent flows over rough walls, by rationalizing the empirical scaling of Blasius and Strickler included in the Nikuradse's experiments [7]. From a technological point of view, this finding has tremendous implications for heat transfer enhancement techniques [8–10].

Fundamental experiments in turbulence are extremely difficult, because they are expensive and require long runs for collecting enough statistical data on the fluctuating quantities of interest. This is the reason why direct numerical simulations of turbulence are considered valuable alternatives. [Von Neumann predicted in 1949 a revolution in the study of turbulence thanks to the advent of digital computers, because of the possibility to simulate the fluid dynamic equations in 3D turbulent regimes](#)

[1]. However, the first three-dimensional simulations of turbulence were carried out only many years after, when the advent of supercomputers and the development of (pseudo)-spectral numerical techniques based on fast Fourier transform algorithms unlocked adequate simulation capabilities: Steven Orszag and G.S. Patterson could achieve such a goal just in 1972 [11]. Clearly, numerical simulations offer the advantage of accessing the entire velocity field and other quantities of interest (e.g. vorticity, local energy dissipation, etc.) [1]. The mesh size of these simulations (nowadays, up to tens of billions of grid-points) determines the spatial resolution, which depends on the maximum Reynolds number of the turbulent flow: the higher is the Reynolds number, the bigger is the mesh size. Due to recent progresses in high performance computing, the feasible Reynolds numbers are approaching those recovered in experimental facilities. However, many times history has shown that the main speedup in numerical computations comes from more efficient algorithms rather than better hardware [12,13]. More than 20 years ago, the lattice Boltzmann method [14–20] was proposed as a powerful numerical method, which is prone to take advantage of the modern resources of high performance computing, especially for multi-physics and multi-scale simulations. The range of applications of the lattice Boltzmann method is very broad, including thermal radiation [21], thermal conduction [22], combustion [23–26], porous media [27,28], multi-component flows [29,30] and turbulence [31–33], to mention a few. In particular, it was argued that turbulence can be more efficiently modeled by extended kinetic (Boltzmann) equation rather than continuum Navier-Stokes equations [31,32], by means of a proper discretization (lattice). Recently, a further improvement in computational performances was achieved by link-wise artificial compressibility method [34], which can be considered as a subsequent refinement of the lattice Boltzmann algorithm. Moreover, stability of kinetic schemes can be also improved using the pioneering idea of limiters [35].

In most of the engineering applications where turbulent flows are involved, the direct numerical simulation is still unfeasible. Large eddy simulations and Reynolds averaged Navier-Stokes simulations are commonly used, instead [36]. Large eddy simulations using the lattice Boltzmann method have been carried out [37–40], as well as those using Reynolds averaged Navier-Stokes (RANS) equations [41,42]. However, in the context of lattice Boltzmann method, engineering turbulence models are still lacking thus more research efforts are required [19]. Among the closure models for the Reynolds averaged equations, the $k - \epsilon$ model is one of the most popular [36]. The model takes its name from the turbulent kinetic energy k and the turbulent dissipation rate ϵ . The role of $k - \epsilon$ model in the theory of turbulence can be found in Ref. [43]. The first two-equation model for predicting turbulent flows was proposed by Kolmogorov in 1942 [44], using fluctuation energy and frequency as main variables. In 1968, Harlow and Nakayama proposed the $k - \epsilon$ model for turbulence [45], which was later refined [46]. However, the true development of the model is credited to Launder, Hanjalic and Jones [47,48], whereas the collaboration with Spalding brought out the superiority of this model to a broad scientific audience [49–51].

In spite of its success from the practical point of view, the theoretical foundations of the $k - \epsilon$ model are still unclear. In fact, the model is made by two phenomenological equations and, in particular, the equation for the dissipation rate of turbulent kinetic energy is guessed by analogy with the kinetic energy one [36]. The idea to apply statistical mechanics to the study of fully developed turbulent flows is quite old, and it dates back to the pioneering work by Reynolds in 1883 [3]. Indeed, the statistical approach is one of the main approaches to turbulence (along with the structural and deterministic ones). In particular, non-extensive statistical mechanics [52] and the recently proposed fluctuation theorems [53] appear promising in understanding turbulence. However, a fundamental problem still remains in investigating the relation between the definition of entropy in case of non-equilibrium flows and the most popular turbulent models (e.g. $k - \epsilon$ model), which is exactly what we investigate here.

Recent trends in thermodynamics may help in achieving this goal. Starting from the theoretical framework introduced by Lars Onsager, Ilya Prigogine paved the way to the Thermodynamics of Irreversible Processes (TIP) by extending the fundamental Gibbs relation to non-equilibrium

states [54,55]. Such extension assumes that local equilibrium is achieved throughout the system, namely all subparts of the system are close to equilibrium condition and can be safely described by thermodynamic relationships and variables. Extended Irreversible Thermodynamics (EIT) [56,57] is another active field of investigation, where the local equilibrium assumption can be eventually overcome. The basic idea underlying EIT is that thermodynamic quantities are related to dissipative fluxes, which are considered as independent variables. Hence, the generalized Gibbs relation for non-equilibrium states can be obtained from the differential form of the generalized entropy, and it satisfies the following requirements: 1) in the limit of quasi-static processes, it can be reduced to the equilibrium Gibbs relation; 2) it is Galilean invariant; 3) results are supported by experimental evidences [58]. This procedure is not even limited to bulk flows, as it can be successfully adopted for studying non-equilibrium interfaces [59–61].

Surprisingly enough, only recently Extended Irreversible Thermodynamics has paid attention to turbulent flows [62–65]. There are two main approaches in literature. In the first approach, Jansen [66] and Hauke [67] have extended entropy-based stability analysis to turbulent flows. The key idea consists in applying the Reynolds time averaging to the entropy transport equation obtained by the Thermodynamics of Irreversible Processes, i.e. by assuming that local equilibrium assumption holds. This approach has been somehow re-proposed recently and even applied to commercial codes [68–71]. However, the entropy transport equation is highly non-linear, and several ways to perform the Reynolds time averaging could be adopted. For example, multiplying this equation by the temperature before applying the time-averaging leads to simplified calculations, but a closure problem appears (for fluctuating temperature and entropy production correlations) and different models have been proposed [72]. In fact, the mean entropy production cannot be easily expressed by other mean flow variables alone [72]. We believe that these difficulties arise from understanding the local equilibrium assumption. Hence, we aim to clarify the derivation of entropy production in turbulent flows. The entropy production is helpful in the design and optimization of devices dealing with turbulent flows (e.g. by the entropy generation minimization approach [75,76]).

In this work, materials and methods representing the starting point of our analysis are briefly summarized in Section 2; then, the main results for turbulent flows are reported in Section 3, where the $k - \epsilon$ model is recast by a kinetic approach. Finally, Section 4 presents some considerations derived from the reported results; whereas conclusions are drawn in Section 5.

2. Materials and methods

In the asymptotic limit of low Mach number flows, the incompressible limit of the Navier-Stokes-Fourier system of equations for Newtonian fluids with constant transport coefficients [73,74] can be written as

$$\nabla \cdot \mathbf{u} = 0, \quad (1)$$

$$\frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} = \frac{D\mathbf{u}}{Dt} = -\frac{1}{\rho_0} \nabla p + \nu \nabla^2 \mathbf{u}, \quad (2)$$

$$\frac{\partial h}{\partial t} + \mathbf{u} \cdot \nabla h = \frac{Dh}{Dt} = \frac{\lambda}{\rho_0} \nabla^2 T + 2\nu (\nabla^S \mathbf{u})^2 + \frac{1}{\rho_0} \frac{Dp}{Dt}, \quad (3)$$

where ρ_0 is the average fluid density (assumed constant and different from the actual fluid density ρ), \mathbf{u} is the fluid velocity, p is the pressure, ν is the kinematic viscosity, h is the enthalpy, λ is the thermal conductivity, and $\nabla^S \mathbf{u} = 1/2 (\nabla \mathbf{u} + \nabla^T \mathbf{u})$ is the strain rate tensor. Alternative formulations of (1) may be expressed in terms of the internal energy or total energy, instead of enthalpy.

It is well known that, in regimes where momentum convection prevails on momentum diffusion ($\mathbf{u} \cdot \nabla \mathbf{u} \gg \nu \nabla^2 \mathbf{u}$) or, equivalently, Reynolds number is larger than a flow-dependent threshold, the flow field is characterized by rapid variations of pressure and velocity in space and time, i.e. by chaotic coherent structures called turbulent eddies. This discussion can be more rigorous by adopting characteristic quantities, which can be defined in different ways according to what they refer to (fields

or operator). On the one hand, the characteristic quantity u_c gives the magnitude of the velocity field, being $u_c = \max(\mathbf{u})$ in the considered domain. On the other hand, operators may involve more difficult definitions. For instance, the characteristic length l_c is defined by

$$l_c = \frac{O(\varphi)}{O(\nabla\varphi)} = \max_i \left(\frac{O(\varphi)}{O(\partial\varphi/\partial x_i)} \right), \quad (4)$$

where φ is a generic field property of the fluid flow. Hence, $\mathbf{u} \cdot \nabla \mathbf{u} = O(u_c^2/l_c)$ and $\nu \nabla^2 \mathbf{u} = O(\nu u_c/l_c^2)$. This clarifies the reason why the inequality $\mathbf{u} \cdot \nabla \mathbf{u} \gg \nu \nabla^2 \mathbf{u}$ implies large Reynolds numbers: $Re = u_c l_c / \nu \gg 1$.

As originally suggested by Reynolds in 1895, let us consider the time-averaged equations of motion for fluid flows, i.e. the so-called Reynolds-averaged Navier Stokes equations (RANS) [36]. First, let us introduce the filter operator $\langle \cdot \rangle$ for the generic quantity φ

$$\langle \varphi \rangle = \lim_{\tau \rightarrow \infty} \frac{1}{\tau} \int_{t-\tau}^t \varphi(t', \mathbf{x}) dt', \quad (5)$$

where $\langle \varphi \rangle$ is assumed independent on the initial condition t (in the context of chaotic dynamical system, this means that the system can only have one strange attractor).

From a practical point of view, the limit in (5) is truncated to some finite time, which is assumed much larger than the characteristic time of turbulent fluctuations. The previous definition allows one to introduce the average velocity field $\bar{\mathbf{u}} = \langle \mathbf{u} \rangle$ and the corresponding velocity fluctuation $\mathbf{u}' = \mathbf{u} - \bar{\mathbf{u}}$ or, equivalently, to decompose the actual velocity field, namely $\mathbf{u} = \bar{\mathbf{u}} + \mathbf{u}'$. Introducing the previous decomposition in the divergence-free condition given by Eq. (1) and taking the time average $\langle \cdot \rangle$ shown in Eq. (5) yield

$$\nabla \cdot \bar{\mathbf{u}} = 0 \quad (6)$$

and consequently $\nabla \cdot \mathbf{u}' = 0$, meaning that both the average and fluctuating fields are divergence-free. Proceeding in a similar way for Eq. (2) yields

$$\frac{\partial \bar{\mathbf{u}}}{\partial t} + \bar{\mathbf{u}} \cdot \nabla \bar{\mathbf{u}} + \langle \mathbf{u}' \cdot \nabla \mathbf{u}' \rangle = -\frac{1}{\rho_0} \nabla \bar{p} + \nu \nabla^2 \bar{\mathbf{u}}, \quad (7)$$

where $\bar{p} = \langle p \rangle$. The term $\langle \mathbf{u}' \cdot \nabla \mathbf{u}' \rangle$ represents the novel physical content of the RANS momentum equation. Of course, in order to derive a set of closed RANS equations, the latter term must be modeled by quantities depending on the averaged quantities (or their gradients) only. First of all, this term must be made symmetric. Taking into account that $\nabla \cdot \mathbf{u}' = 0$, the following condition holds

$$\langle \mathbf{u}' \cdot \nabla \mathbf{u}' \rangle = \nabla \cdot \langle \mathbf{u}' \otimes \mathbf{u}' \rangle. \quad (8)$$

Next, let us consider the Boussinesq's eddy viscosity assumption, namely

$$\langle \mathbf{u}' \otimes \mathbf{u}' \rangle = -\nu_t (\nabla \bar{\mathbf{u}} + \nabla \bar{\mathbf{u}}^T) = -2\nu_t \nabla^S \bar{\mathbf{u}}, \quad (9)$$

where ν_t is the eddy viscosity (additional kinetic viscosity due to turbulent eddies beyond molecular one) and $\nabla^S \bar{\mathbf{u}}$ is the strain rate tensor defined as $\nabla^S \bar{\mathbf{u}} = (\nabla \bar{\mathbf{u}} + \nabla \bar{\mathbf{u}}^T)/2$. It is easy to prove that $\nabla \bar{\mathbf{u}} = \nabla^S \bar{\mathbf{u}} + \nabla^W \bar{\mathbf{u}}$ and, more importantly, $\nabla^S \bar{\mathbf{u}} : \nabla^W \bar{\mathbf{u}} = 0$, where $\nabla^W \bar{\mathbf{u}} = (\nabla \bar{\mathbf{u}} - \nabla \bar{\mathbf{u}}^T)/2$ is the vorticity tensor. Substituting the Boussinesq's eddy viscosity assumption into Eq. (7), and taking into account that $2\nabla \cdot \nabla^S \bar{\mathbf{u}} = \nabla^2 \bar{\mathbf{u}}$ (because of Eq. (6)), yield

$$\frac{\partial \bar{\mathbf{u}}}{\partial t} + \bar{\mathbf{u}} \cdot \nabla \bar{\mathbf{u}} = -\frac{1}{\rho_0} \nabla \bar{p} + (\nu + \nu_t) \nabla^2 \bar{\mathbf{u}}. \quad (10)$$

It is clear that working with RANS is a successful approach, as far as an accurate model is defined to compute the corrective factor $(\nu + \nu_t)$ in Eq. (10). Clearly, the key idea is to investigate the part of kinetic energy due to turbulent fluctuations. Let us substitute $\nabla^2 \mathbf{u}$ with $2 \nabla \cdot \nabla^S \mathbf{u}$ in (2) and let us multiply the result by \mathbf{u} , namely

$$\frac{\partial e_k}{\partial t} + \mathbf{u} \cdot \nabla e_k = \frac{D e_k}{D t} = -\frac{1}{\rho_0} \nabla p \cdot \mathbf{u} + 2\nu (\nabla \cdot \nabla^S \mathbf{u}) \cdot \mathbf{u}, \quad (11)$$

where $e_k = \mathbf{u}^2/2$ is the total kinetic energy. After some simple algebra, the previous equation can be rewritten as

$$\frac{\partial e_k}{\partial t} + \nabla \cdot \left[(e_k + p_k) \mathbf{u} - 2\nu \mathbf{u} \cdot \nabla^S \mathbf{u} \right] = -\epsilon_k \leq 0, \quad (12)$$

131 where $p_k = p/\rho_0$ is the kinetic pressure and $\epsilon_k = 2\nu(\nabla^S \mathbf{u})^2$ is the (positively defined) dissipation
 132 function of the total kinetic energy (the square power $(\nabla^S \mathbf{u})^2$ simply means $\nabla^S \mathbf{u} : \nabla^S \mathbf{u}$). Similarly to
 133 what has been done for the velocity field, let us now decompose both the total kinetic energy e_k and
 134 its dissipation function ϵ_k , namely $e_k = \langle e_k \rangle + e'_k$ and $\epsilon_k = \langle \epsilon_k \rangle + \epsilon'_k$, respectively. In this case, the
 135 main difference is that the time average of the previous quantities, e.g. $\langle e_k \rangle$, does not coincide with
 136 the same definition applied to averaged quantities, e.g. \bar{e}_k . In particular, the following relations hold

$$\langle e_k \rangle = \frac{1}{2} \langle (\bar{\mathbf{u}} + \mathbf{u}') \cdot (\bar{\mathbf{u}} + \mathbf{u}') \rangle = \bar{e}_k + k, \quad (13)$$

$$\langle \epsilon_k \rangle = 2\nu \langle \nabla^S (\bar{\mathbf{u}} + \mathbf{u}') : \nabla^S (\bar{\mathbf{u}} + \mathbf{u}') \rangle = \bar{\epsilon}_k + \epsilon, \quad (14)$$

where $\bar{e}_k = \bar{\mathbf{u}}^2/2$, $k = \langle (\mathbf{u}')^2 \rangle/2$ is the turbulent kinetic energy, $\bar{\epsilon}_k = 2\nu(\nabla^S \bar{\mathbf{u}})^2$ and $\epsilon = 2\nu\langle (\nabla^S \mathbf{u}')^2 \rangle$ is the turbulent dissipation function. For example, the previous definitions imply that $e'_k = \bar{\mathbf{u}} \cdot \mathbf{u}' + \mathbf{u}' \cdot \mathbf{u}'/2 - k$ and consequently $\langle e'_k \rangle = 0$, even though $\langle e_k \rangle \neq \bar{e}_k$. The turbulent kinetic energy k is the excess of kinetic energy due to turbulent fluctuations beyond the one caused by the average flow. Similarly, the turbulent dissipation ϵ is the excess of dissipation due to turbulent fluctuations. These are the two main quantities defining this approach to turbulence modeling, and this is the reason why this method is called $k - \epsilon$ model [36]. The second key idea is that the eddy viscosity ν_t depends on k and ϵ only. The physical dimensions of ϵ are those of kinetic energy divided by time, thus it can be interpreted as the dissipation rate of turbulent kinetic energy. Based on dimensional analysis, the following phenomenological relation is assumed for the eddy viscosity

$$\nu_t = C_t \frac{k^2}{\epsilon}, \quad (15)$$

137 where C_t is a tunable constant of the model (see next).

The next step consists in deriving a closed set of equations for k and ϵ . Let us substitute the previous decompositions in Eq. (12) and then perform the time averaging. Some difficulties may arise from cubic (third-order) terms with respect to velocity, i.e. $\langle e_k \mathbf{u} \rangle$, but the following condition allows one to sort them out:

$$\langle e_k \mathbf{u} \rangle = \langle e_k \rangle \bar{\mathbf{u}} + \langle \mathbf{u}' \cdot \mathbf{u}' \mathbf{u}' \rangle / 2 + \bar{\mathbf{u}} \cdot \langle \mathbf{u}' \otimes \mathbf{u}' \rangle, \quad (16)$$

138 where the last term can be expressed by the Boussinesq's eddy viscosity assumption (9). Exploiting
 139 the condition (16), it follows:

$$\begin{aligned} & \frac{\partial \langle e_k \rangle}{\partial t} + \nabla \cdot \left[(\langle e_k \rangle + \bar{p}_k) \bar{\mathbf{u}} + \langle (\mathbf{u}' \cdot \mathbf{u}' / 2 + p'_k) \mathbf{u}' \rangle \dots \right. \\ & \left. \dots - 2(\nu + \nu_t) \bar{\mathbf{u}} \cdot \nabla^S \bar{\mathbf{u}} - 2\nu \langle \mathbf{u}' \cdot \nabla^S \mathbf{u}' \rangle \right] = -\bar{\epsilon}_k - \epsilon \leq 0. \end{aligned} \quad (17)$$

On the other hand, multiplying Eq. (7) by the average velocity $\bar{\mathbf{u}}$ yields

$$\frac{\partial \bar{e}_k}{\partial t} + \nabla \cdot \left[(\bar{e}_k + \bar{p}_k) \bar{\mathbf{u}} - 2(\nu + \nu_t) \bar{\mathbf{u}} \cdot \nabla^S \bar{\mathbf{u}} \right] = -\bar{e}_k - \frac{\nu_t}{\nu} \bar{e}_k \leq 0. \quad (18)$$

Subtracting Eq. (18) from Eq. (17) and taking into account that $k = \langle e_k \rangle - \bar{e}_k$ (because of Eq. (13)) yield

$$\frac{\partial k}{\partial t} + \nabla \cdot \left[k \bar{\mathbf{u}} + \langle (\mathbf{u}' \cdot \mathbf{u}' / 2 + p'_k) \mathbf{u}' \rangle - 2\nu \langle \mathbf{u}' \cdot \nabla^S \mathbf{u}' \rangle \right] = \frac{\nu_t}{\nu} \bar{e}_k - \epsilon. \quad (19)$$

Taking into account the following equivalence

$$-2\nu \langle \mathbf{u}' \cdot \nabla^S \mathbf{u}' \rangle = -\nu \nabla k + 2\nu \nu_t \nabla^S \bar{\mathbf{u}}, \quad (20)$$

Eq. (19) can be rewritten as

$$\frac{\partial k}{\partial t} + \nabla \cdot \left[k \bar{\mathbf{u}} - \nu \nabla k + \langle (\mathbf{u}' \cdot \mathbf{u}' / 2 + p'_k) \mathbf{u}' \rangle + 2\nu \nu_t \nabla^S \bar{\mathbf{u}} \right] = \frac{\nu_t}{\nu} \bar{e}_k - \epsilon, \quad (21)$$

140 which is the standard form for the turbulent kinetic energy equation (TKE).

Some simplifications are usually applied to the flux of turbulent kinetic energy. First of all, the last term of such a flux is usually negligible at high Reynolds number flows, because it is proportional to $\nu \nu_t$ (even though ν_t can be up to roughly ten times ν , still this term is proportional to ν^2). Secondly, the (leading) term $\langle (\mathbf{u}' \cdot \mathbf{u}' / 2) \mathbf{u}' \rangle$ clearly shows the turbulent transport of the quantity $\mathbf{u}' \cdot \mathbf{u}' / 2$, which is the argument of the turbulent kinetic energy k . Hence, the key idea is to generalize the gradient-diffusion approximation [36], namely

$$\langle (\mathbf{u}' \cdot \mathbf{u}' / 2 + p'_k) \mathbf{u}' \rangle + 2\nu \nu_t \nabla^S \bar{\mathbf{u}} \approx \langle (\mathbf{u}' \cdot \mathbf{u}' / 2 + p'_k) \mathbf{u}' \rangle \approx -\frac{\nu_t}{\sigma_k} \nabla k, \quad (22)$$

where σ_k is a tunable constant of the model (see next). Consequently, the equation of the turbulent kinetic energy in the $k - \epsilon$ model becomes

$$\frac{\partial k}{\partial t} + \nabla \cdot \left[k \bar{\mathbf{u}} - (\nu + \nu_t / \sigma_k) \nabla k \right] = \frac{\nu_t}{\nu} \bar{e}_k - \epsilon. \quad (23)$$

In the latter equation, the sign of the right hand side is no more uniquely prescribed. Here, the quantity $(\nu_t / \nu) \bar{e}_k$ acts as turbulent energy production, moving kinetic energy from the mean flow to the turbulent fluctuations; while ϵ acts as turbulent energy dissipation, moving energy in the opposite direction. The same theoretical framework is used to derive the equation for turbulent dissipation. However, the equation of turbulent dissipation in the $k - \epsilon$ model is completely heuristic, being substantially derived by analogy with the previous equation [36]. The source/sink of turbulent dissipation is derived by dividing the right hand side of Eq. (23) by a proper characteristic time ($\sim k / \epsilon$) and introducing *ad-hoc* some tunable constants, namely

$$\frac{\partial \epsilon}{\partial t} + \nabla \cdot \left[\epsilon \bar{\mathbf{u}} - (\nu + \nu_t / \sigma_\epsilon) \nabla \epsilon \right] = \frac{\epsilon}{k} \left(C_{\epsilon 1} \frac{\nu_t}{\nu} \bar{e}_k - C_{\epsilon 2} \epsilon \right), \quad (24)$$

141 where σ_ϵ , $C_{\epsilon 1}$ and $C_{\epsilon 2}$ are tunable constants of this model. The standard $k - \epsilon$ model is defined by Eqs.
 142 (6, 10) for the average fluid flow, by Eq. (15) for the eddy diffusivity, by Eqs. (23, 24) for the turbulent
 143 kinetic energy and turbulent dissipation and, finally, by the following set of constants, $C_t = 0.09$,
 144 $C_{\epsilon 1} = 1.44$, $C_{\epsilon 2} = 1.92$, $\sigma_k = 1.0$, $\sigma_\epsilon = 1.3$ [36].

145 3. Results

Let us start considering the entropy production of (incompressible) laminar flows. [Non-equilibrium thermodynamics of laminar flows can be obtained by an entropy production](#)

equation, which can be derived by following the typical guidelines of Thermodynamics of Irreversible Processes (TIP) [54,55]. Let us assume that all subparts of the system are close to equilibrium conditions, so that they can be described by classical thermodynamics. In equilibrium conditions, the fundamental Gibbs relation allows to relate entropy with other thermodynamic potentials, namely $Tds = dh - dp/\rho_0$, being T the temperature and s the entropy. Here, we assume that this relation holds also in non-equilibrium conditions, where the Gibbs relation becomes the entropy definition. However, this definition must be Galilean invariant and thus Lagrangian time derivatives must be considered, namely

$$T \frac{Ds}{Dt} = \frac{Dh}{Dt} - \frac{1}{\rho_0} \frac{Dp}{Dt}. \quad (25)$$

Substituting Eq. (3) into Eq. (25) yields

$$T \frac{Ds}{Dt} = \frac{\lambda}{\rho_0} \nabla^2 T + 2\nu (\nabla^S \mathbf{u})^2. \quad (26)$$

The previous equation can be rewritten as

$$\frac{Ds}{Dt} = \frac{c_p \alpha}{T} \nabla^2 T + \frac{2\nu}{T} (\nabla^S \mathbf{u})^2, \quad (27)$$

where $\alpha = \lambda/(\rho_0 c_p)$ is the thermal diffusivity. By further elaborating on the first term at the right hand side of the previous expression yields

$$\frac{Ds}{Dt} + \nabla \cdot \left(-\frac{c_p \alpha}{T} \nabla T \right) = \frac{c_p \alpha}{T^2} (\nabla T)^2 + \frac{2\nu}{T} (\nabla^S \mathbf{u})^2 \geq 0, \quad (28)$$

or equivalently

$$\frac{\partial s}{\partial t} + \nabla \cdot \left(s \mathbf{u} - \frac{c_p \alpha}{T} \nabla T \right) = \sigma'_\alpha + \sigma'_\nu \geq 0, \quad (29)$$

where

$$\sigma'_\alpha = \alpha \left(\frac{c_p}{T^2} \right) (\nabla T)^2 \geq 0, \quad (30)$$

$$\sigma'_\nu = \nu \left(\frac{2}{T} \right) (\nabla^S \mathbf{u})^2 \geq 0. \quad (31)$$

146 Note that the prime notation is used to indicate the entropy production per unit of mass, i.e. σ' ,
 147 instead of the more common production per unit of volume, i.e. $\sigma = \rho_0 \sigma'$. In the previous equations,
 148 each specific transport phenomenon is a source of entropy production, namely: σ'_α and σ'_ν represent
 149 the entropy produced by heat transfer (ruled by temperature gradient) and by fluid flow (ruled
 150 by strain rate), respectively. Clearly, each entropy source is in agreement with the second law of
 151 thermodynamics, namely $\sigma'_\alpha \geq 0$ and $\sigma'_\nu \geq 0$. Same considerations can be done for the global entropy
 152 production, namely $\sigma'_\alpha + \sigma'_\nu \geq 0$. This confirms that the hypothesis reported in Eq. (25) is valid for
 153 non-equilibrium states, at least as far as laminar flows are concerned.

In case of turbulent flows, the situation is more complex. First, the entropy production due to velocity gradients σ'_ν (Eq. (31)) bears a strong resemblance with the dissipation function ϵ_k appearing in the kinetic energy equation (12), namely

$$\sigma'_\nu = \frac{\epsilon_k}{T}. \quad (32)$$

The above observation paves the way to a meaningful formal analogy. In fact, kinetic models are often used to explain microscopically the entropy production; hence, the previous observation suggests that the same kinetic models may be useful to explain also the turbulent dissipation function ϵ_k and, consequently, the turbulent kinetic energy k . The simplest kinetic model is the celebrated Bhatnagar-Gross-Krook (BGK) model [77]. Here, we propose to interpret the $k - \epsilon$ turbulence model

as a set of coupled BGK-like equations. Let us reformulate Eq. (23), which is the only one rigorously derived in $k - \epsilon$ model, as follows:

$$\frac{Dk}{Dt} - \nabla \cdot [(v + \nu_t/\sigma_k)\nabla k] = \frac{1}{\tau_k} (k_{eq} - k), \quad (33)$$

where $\tau_k = k/\epsilon$ is the characteristic relaxation time and k_{eq} is the local equilibrium for the turbulent kinetic energy, namely

$$k_{eq} = k \frac{\bar{\epsilon}_k \nu_t}{\epsilon \nu}. \quad (34)$$

Similarly, Eq. (24) can be recast as

$$\frac{D\epsilon}{Dt} - \nabla \cdot [(v + \nu_t/\sigma_\epsilon)\nabla \epsilon] = \frac{1}{\tau_\epsilon} (\epsilon_{eq} - \epsilon) - \frac{1}{\tau_\epsilon} \left(1 - \frac{C_{\epsilon 1}}{C_{\epsilon 2}}\right) \epsilon_{eq}, \quad (35)$$

where $\tau_\epsilon = \tau_k/C_{\epsilon 2}$ is the second characteristic relaxation time and ϵ_{eq} is the local equilibrium for the turbulent dissipation function, namely

$$\epsilon_{eq} = \bar{\epsilon}_k \frac{\nu_t}{\nu}. \quad (36)$$

154 The last term in Eq. (35) is an empirical forcing. It is worth the effort to elaborate further on the
 155 analogy with the kinetic equations for rarefied gas. In the Boltzmann equation, the external forcing
 156 is described by the term $\mathbf{g} \cdot \nabla_{\mathbf{v}} f$, where \mathbf{g} is the acceleration vector due to the external force field, \mathbf{v}
 157 is the single-particle velocity vector and f is the single-particle distribution function [78]. Assuming
 158 $f \approx f_{eq}$, where f_{eq} is the Gaussian distribution function, yields $\mathbf{g} \cdot \nabla_{\mathbf{v}} f \approx -\mathbf{g} \cdot (\mathbf{v} - \mathbf{u})/e f_{eq}$, where
 159 e is the specific internal energy. In the last expression, $\mathbf{g} \cdot (\mathbf{v} - \mathbf{u})/e$ is the characteristic frequency of
 160 the external force field, which remarkably corresponds to $1/\tau_\epsilon (1 - C_{\epsilon 1}/C_{\epsilon 2})$ in the last term of Eq.
 161 (35). Hence, the celebrated $k - \epsilon$ model for turbulent flows is nothing more than a set of two coupled
 162 BGK-like equations (34, 36) with an empirical forcing. Realizing this formal analogy represents the
 163 most important result of the present paper, with important consequences discussed in the following.

Before proceeding further, it is worth to highlight an important simplification. In Eq. (28), some terms proportional to the product between $(1/T)$ (generalized intensive quantity) and ∇T (generalized force) appear. In the following, Reynolds decomposition will be considered only if the temperature is the argument of a spatial gradient (owing to the small size of the turbulent eddies). On the other hand, the average value of temperature will be considered for the intensive quantity $1/\bar{T}$, because turbulent fluctuations around the room temperature are negligible (this is not the case for \mathbf{u}' , because $\bar{\mathbf{u}}$ can be eventually zero). Introducing the usual Reynolds decompositions for T (in generalized force only), s , h and \mathbf{u} , and performing the time averaging $\langle \cdot \rangle$ yield

$$\frac{D\bar{s}}{Dt} + \langle \mathbf{u}' \cdot \nabla s' \rangle + \nabla \cdot \left(-\frac{c_p \alpha}{\bar{T}} \nabla \bar{T} \right) = \frac{c_p \alpha}{\bar{T}^2} (\nabla \bar{T})^2 + \left\langle \frac{c_p \alpha}{\bar{T}^2} (\nabla T')^2 \right\rangle + \frac{\bar{\epsilon}_k + \epsilon}{\bar{T}}. \quad (37)$$

Let us consider the advection term, namely $\langle \mathbf{u}' \cdot \nabla s' \rangle = \nabla \cdot \langle s' \mathbf{u}' \rangle$. The argument of the divergence operator can be expressed by the gradient-diffusion approximation [36], namely

$$\langle s' \mathbf{u}' \rangle = -\beta \nabla s = -\beta \nabla s(\bar{T}, \rho_0) = -\frac{c_p \gamma}{\bar{T}} \nabla \bar{T}, \quad (38)$$

where β and γ are tunable transport coefficients and, in particular,

$$\gamma = \beta \frac{\bar{T}}{c_p} \left. \frac{\partial s}{\partial \bar{T}} \right|_{\rho_0}. \quad (39)$$

Substituting Eq. (38) into Eq. (37) yields

$$\frac{\partial \bar{s}}{\partial t} + \nabla \cdot \left[\bar{s} \bar{\mathbf{u}} - \frac{c_p (\alpha + \gamma)}{\bar{T}} \nabla \bar{T} \right] = \frac{c_p \alpha}{\bar{T}^2} (\nabla \bar{T})^2 + \left\langle \frac{c_p \alpha}{\bar{T}^2} (\nabla T')^2 \right\rangle + \frac{\bar{\epsilon}_k + \epsilon}{\bar{T}}. \quad (40)$$

We now have to find out some approximated expressions for the main quantities, namely k and ϵ . Let us consider again the BGK-like equation (33), which is more rigorous than Eq. (35) and is also easier to be analyzed because there is no forcing term. The main fluid flow characteristic time is defined as $\tau_c = l_c / u_c$ (see above). Clearly, the characteristic relaxation time of turbulent kinetic energy τ_k is much shorter than the fluid flow characteristic time, namely $\tau_k / \tau_c \ll 1$, because the turbulent structures are much smaller. Hence, it is possible to find out an approximated solution of the set of BGK-like equations defining the $k - \epsilon$ model in the asymptotic limit $\tau_k / \tau_c \ll 1$. For our purposes, it is enough to consider the following formal expansion, without expanding the differential operators [78], namely

$$k = k^{(0)} + (\tau_k / \tau_c) k^{(1)} + (\tau_k / \tau_c)^2 k^{(2)} + (\tau_k / \tau_c)^3 k^{(3)} + \dots \quad (41)$$

Substituting the previous ansatz into Eq. (33) and collecting terms with the same order of magnitude with regards to τ_k / τ_c [78], we obtain $k^{(0)} = k_{eq}$ at the leading order. This means that $k = k_{eq} + O(\tau_k / \tau_c)$ and $k \approx k_{eq}$ in the asymptotic limit $\tau_k / \tau_c \ll 1$ or, equivalently, $\epsilon \approx \epsilon_{eq}$. Substituting $\epsilon \approx \epsilon_{eq}$ into (40) yields

$$\frac{\partial \bar{s}}{\partial t} + \nabla \cdot \left[\bar{s} \bar{\mathbf{u}} - \frac{c_p (\alpha + \gamma)}{\bar{T}} \nabla \bar{T} \right] = \frac{c_p \alpha}{\bar{T}^2} (\nabla \bar{T})^2 + \left\langle \frac{c_p \alpha}{\bar{T}^2} (\nabla T')^2 \right\rangle + \left(1 + \frac{\nu_t}{\nu} \right) \frac{\bar{\epsilon}_k}{\bar{T}}. \quad (42)$$

The derivation proposed here is based on the formal analogy of Eq. (33) with kinetic equations, in particular with BGK-like equations. However, this is consistent with the canonical derivation based on $\epsilon \approx (\nu_t / \nu) \bar{\epsilon}_k$, which means that there is substantially a balance between turbulent kinetic energy production and dissipation. The condition $\epsilon = (\nu_t / \nu) \bar{\epsilon}_k$ also implies

$$\nu (\nabla^S \mathbf{u}')^2 = \frac{\nu_t}{\nu} \nu (\nabla^S \bar{\mathbf{u}})^2, \quad (43)$$

which allows computing $(\nabla^S \mathbf{u}')^2$ by means of $(\nabla^S \bar{\mathbf{u}})^2$, where the latter term is usually the only one available in practical calculations. The same idea can be applied to simplify the entropy production due to temperature gradient as well. It is easy to verify that the balance between turbulence production and dissipation implies

$$\alpha (\nabla T')^2 = \frac{\alpha_t}{\alpha} \alpha (\nabla \bar{T})^2, \quad (44)$$

where $\alpha_t = \nu_t / Pr_t$ and Pr_t is the turbulent Prandtl number. Substituting Eq. (44) into Eq. (42) yields

$$\frac{\partial \bar{s}}{\partial t} + \nabla \cdot \left[\bar{s} \bar{\mathbf{u}} - \frac{c_p (\alpha + \gamma)}{\bar{T}} \nabla \bar{T} \right] = \frac{c_p (\alpha + \alpha_t)}{\bar{T}^2} (\nabla \bar{T})^2 + \frac{2(\nu + \nu_t)}{\bar{T}} (\nabla^S \bar{\mathbf{u}})^2 \geq 0, \quad (45)$$

which is valid for both laminar and turbulent flows, and it represents the generalization of the second law of thermodynamics for turbulent flows.

4. Discussion

Equation (45) confirms the applicability of the Thermodynamics of Irreversible Processes to (incompressible) laminar and turbulent flows. Some comments are reported in the following.

1. In this paper, we present an alternative derivation of Eq. (45) based on a kinetic approach. This approach provides a novel perspective on the $k - \epsilon$ turbulence model, which remains one of

the most successful models for many engineering applications, even though it is still affected by empirical assumptions for the turbulent dissipation function. In particular, our approach clarifies that this model is nothing more than a set of coupled BGK-like equations with a proper forcing, see the last term in Eq. (35). Note that the formal expansion proposed for k in Eq. (41) may not be suitable for ϵ , because the forcing term would change the local equilibrium, which must be unique in kinetic theory. Hence, some further investigations are required to find out the most suitable expansion for analyzing the high-order asymptotics. This is not surprising, because different asymptotic approaches (Chapman-Enskog, Hilbert, Grad, etc.) have been long debated in kinetic theory of rarefied gas [78].

2. Equation (45) proves that four terms are the main sources of entropy production rates in turbulent flows: 1) direct dissipation, 2) indirect (turbulent) dissipation, 3) heat conduction driven by average temperature gradients and 4) heat conduction driven by fluctuating temperature gradients [68–70]. These production rates (and their sum) are positively defined, consistently with the second law of thermodynamics.
3. In Eq. (45), the entropy production can be expressed as

$$\sigma' = \sum_k \eta'_k X_k^2, \quad (46)$$

being η'_k the phenomenological coefficients of irreversible phenomena ($\eta'_1 = (\alpha + \alpha_t) c_p / \bar{T}^2$ and $\eta'_2 = (\nu + \nu_t) 2 / \bar{T}$) and X_k the generalized thermodynamic forces ($X_1 = \nabla \bar{T}$ and $X_2 = \nabla^S \bar{\mathbf{u}}$). We selected k subscript as equal to the dimensionality of the corresponding thermodynamic force (vector $k = 1$, tensor $k = 2$). Consequently, $X_k^2 = X_k * X_k$, where the generalized product $*$ means scalar product \cdot for $k = 1$ and saturation product $:$ for $k = 2$.

5. Conclusions

In this paper, we present an alternative derivation of the entropy production in turbulent flows, based on a formal analogy with the kinetic theory of rarefied gas. This analogy allows proving that the celebrated $k - \epsilon$ model for turbulent flows is nothing more than a set of coupled BGK-like equations with a proper forcing. This opens a novel perspective on this model, which may help in sorting out the heuristic assumptions essential for its derivation: for example, the balance between turbulent kinetic energy production and dissipation. Moreover, this has also important implications for applications, because the second law of thermodynamics for turbulent flows given by Eq. (45) is very popular in the design and optimization of devices dealing with hypersonic flows (e.g. by the entropy generation minimization approach [75,76]). The new perspectives introduced by this work may find application in a broad variety of fields, spanning from aerospace (e.g. aeroelastic study of flexible flapping wings [79]) to materials (e.g. nature-inspired structures for fluid drag reduction [80]) research, from biomedical (e.g. turbulent blood flow [81]) to heat transfer (e.g. turbulent heat transfer in heat exchangers [82]) applications, from automotive (e.g. air conditioning components [83]) to atmosphere [84] modeling.

Acknowledgments: Authors would like to acknowledge the NANOBRIDGE project “Heat and mass transport in NANO-structures by molecular dynamics, systematic model reduction, and non-equilibrium thermodynamics” (PRIN 2012, MIUR) and the NANOSTEP project “NANOfluid-based direct Solar absorption for Thermal Energy and water Purification”.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. R. Benzi, U. Frisch, *Turbulence*, Scholarpedia 5:3, 3439 (2010).
2. O. Darrigol, *World of Flow: A History of Hydrodynamics from Bernoulli to Prandtl*, Oxford University Press, 2005.
3. G. Gallavotti, *Foundations of Fluid Dynamics*, Springer-Verlag, 2002.

4. A.N. Kolmogorov, The local structure of turbulence in incompressible viscous fluid for very large Reynolds number, *Dokl. Akad. Nauk. SSSR* 30, 9-13 (1941).
5. A.N. Kolmogorov, On degeneration (decay) of isotropic turbulence in an incompressible viscous liquid, *Dokl. Akad. Nauk. SSSR* 31, 538-540 (1941).
6. U. Frisch, *Turbulence, the Legacy of A.N. Kolmogorov*, Cambridge University Press, 1995.
7. G. Gioia, P. Chakraborty, Turbulent Friction in Rough Pipes and the Energy Spectrum of the Phenomenological Theory, *Phys. Rev. Lett.* 96, 044502 (2006).
8. L. Ventola, F. Robotti, M. Dialameh, F. Calignano, D. Manfredi, E. Chiavazzo, P. Asinari, Rough surfaces with enhanced heat transfer for electronics cooling by direct metal laser sintering, *International Journal of Heat and Mass Transfer* 75, 58-74 (2013).
9. L. Ventola, M. Dialameh, M. Fasano, E. Chiavazzo, P. Asinari, Convective heat transfer enhancement by diamond shaped micro-protruded patterns for heat sinks: Thermal fluid dynamic investigation and novel optimization methodology, *Applied Thermal Engineering* 93, 1254-1263 (2016).
10. M. Fasano, L. Ventola, F. Calignano, D. Manfredi, E.P. Ambrosio, E. Chiavazzo, P. Asinari, Passive heat transfer enhancement by 3D printed Pitot tube based heat sink, *International Communications in Heat and Mass Transfer*, In press (2016).
11. S.A. Orszag, G.S. Patterson, Numerical simulation of turbulence: statistical models and turbulence, *Lecture Notes in Physics* 12, 127-147, Springer (1972).
12. E. Chiavazzo, *Invariant Manifolds and Lattice Boltzmann Method for Combustion*, PhD Dissertation, ETH, 2009.
13. E. Chiavazzo, M. Fasano, P. Asinari, Inference of analytical thermodynamic models for biological networks, *Physica A* 392, 1122-1132 (2013).
14. G.R. McNamara, G. Zanetti, Use of the Boltzmann equation to simulate lattice-gas automata, *Phys. Rev. Lett.* 61, 2332 (1988).
15. Y. Qian, D'd'Humières, P. Lallemand, Lattice BGK models for Navier-Stokes equation, *Europhys. Lett.* 17, 479 (1992).
16. X. He, L.-S. Luo, A priori derivation of the lattice Boltzmann equation, *Phys. Rev. E* 55, R6333 (1997).
17. S. Chen, G.D. Doolen, Lattice Boltzmann method for fluid flows, *Annu. Rev. Fluid Mech.* 30, 329 (1998).
18. S. Succi, *The Lattice Boltzmann Equation for Fluid Dynamics and Beyond*, Oxford University Press, 2001.
19. D. Yu, R. Mei, L.-S. Luo, W. Shyy, Viscous flow computations with the method of lattice Boltzmann equation, *Progress in Aerospace Sciences* 39:5, 329-367 (2003).
20. C.K. Aidun, J.R. Clausen, Lattice-boltzmann method for complex flows, *Annual Review of Fluid Mechanics* 42, 439-472 (2010).
21. P. Asinari, S.C. Mishra, R. Borchellini, A lattice Boltzmann formulation to the analysis of radiative heat transfer problems in a participating medium, *Numerical Heat Transfer Part B-Fundamentals* 57, 1-21 (2010).
22. E. Chiavazzo E., P. Asinari P., Reconstruction and modeling of 3D percolation networks of carbon fillers in a polymer matrix, *International Journal of Thermal Sciences* 49, 2272-2281 (2010).
23. E. Chiavazzo, I.V. Karlin, A. N. Gorban, K. Boulouchos, Combustion simulation via lattice Boltzmann and reduced chemical kinetics, *Journal of Statistical Mechanics: Theory and Experiment* 6, P06013 (2009).
24. E. Chiavazzo, I.V. Karlin, A. N. Gorban, K. Boulouchos, Coupling of the model reduction technique with the lattice Boltzmann method for combustion simulations, *Combust. Flame* 157, 1833-1849 (2010).
25. E. Chiavazzo, I.V. Karlin, A. N. Gorban, K. Boulouchos, Efficient simulations of detailed combustion fields via the lattice Boltzmann method, *International Journal of Numerical Methods for Heat and Fluid Flow* 21, 494-517 (2011).
26. A.F. Di Rienzo, P. Asinari, E. Chiavazzo, N.I. Prasianakis, J. Mantzaras, Lattice Boltzmann model for reactive flow simulations, *Europhysics Letters* 98, 34001 (2012).
27. P. Asinari, M.R. von Spakovsky, M. Calí Quaglia, V. Kasula, Direct numerical calculation of the kinematic tortuosity of reactive mixture flow in the anode layer of solid oxide fuel cells by the lattice Boltzmann method, *Journal of Power Sources* 170:2, 359-375 (2007).
28. U.R. Salomov, E. Chiavazzo, P. Asinari, Pore-scale modeling of fluid flow through gas diffusion and catalyst layers for high temperature proton exchange membrane (HT-PEM) fuel cells, *Computers & Mathematics with Applications* 67:2, 393-411 (2014).

29. P. Asinari, Lattice Boltzmann scheme for mixture modeling: analysis of the continuum diffusion regimes recovering Maxwell-Stefan model and incompressible Navier-Stokes equations, *Physical Review E, Statistical, Nonlinear, and Soft Matter Physics* 80, 056701 (2009).
30. P. Asinari, Multiple-relaxation-time lattice Boltzmann scheme for homogeneous mixture flows with external force, *Physical Review E, Statistical, Nonlinear, and Soft Matter Physics* 77, 056706 (2008).
31. H. Chen, S. Kandasamy, S. Orszag, R. Shock, S. Succi, V. Yakhot, Extended Boltzmann kinetic equation for turbulent flows, *Science* 301, 633 (2003).
32. S. Ansumali, I.V. Karlin, S. Succi, Kinetic theory of turbulence modeling: smallness parameter, scaling and microscopic derivation of Smagorinsky model, *Physica A* 338, 379-394 (2004).
33. P. Asinari, L.-S. Luo, A Consistent Lattice Boltzmann Equation with Baroclinic Coupling for Mixtures, *Journal of Computational Physics* 227, 3878-3895 (2008).
34. P. Asinari, T. Ohwada, E. Chiavazzo, A.F. Di Rienzo, Link-wise artificial compressibility method, *Journal of Computational Physics* 231, 5109-5143 (2012).
35. R.A. Brownlee, A.N. Gorban, J. Levesley, Nonequilibrium entropy limiters in lattice Boltzmann methods, *Physica A* 387, 385-406 (2008).
36. S.B. Pope, *Turbulent Flows*, Cambridge University Press, 2000.
37. J.M.G. Eggels, Direct and large-eddy simulation of turbulent fluid flow using the lattice-Boltzmann scheme, *International Journal of Heat and Fluid Flow* 17, 307-323 (1996).
38. Z.Y. Lu, Y. Liao, D.Y. Qian, J.B. McLaughlin, J.J. Derksen, K. Kontomaris, Large eddy simulations of a stirred tank using the lattice Boltzmann method on a nonuniform grid, *Journal of Computational Physics* 181, 675-704 (2002).
39. M. Krafczyk, J. Tölke, L.-S. Luo, Large-eddy simulations with a multiple-relaxation-time LBE model, *International Journal of Modern Physics B* 17, 33-39 (2003).
40. S. Geller, S. Uphoff, M. Krafczyk, Turbulent jet computations based on MRT and Cascaded Lattice Boltzmann models, *Computers and Mathematics with Applications* 65:12, 1956-1966 (2013).
41. C.M. Tekeira, Incorporating turbulence models into the Lattice-boltzmann method, *International Journal of Modern Physics C* 9:8, 1159-1175 (1998).
42. G. Kumar, S.S. Girimaji, Progress in the application of lattice Boltzmann method for turbulent flows, in *Proceedings of the International Offshore and Polar Engineering Conference*, 1104-1111, 22nd International Offshore and Polar Engineering Conference, Rhodes, 2012.
43. C.D. Scott-Pomerantz, *The k-epsilon model in the theory of turbulence*, PhD Dissertation, University of Pittsburgh, 2004.
44. A.N. Kolmogorov, Equations of motion of an incompressible turbulent fluid, *Izv Akad Nauk SSSR Ser Phys* 6:1-2, 56-58 (1942).
45. F.H. Harlow, P.I. Nakayama, *Transport of turbulence-energy decay rate*, Los Alamos science laboratory report (University of California), LA-3854, 1968.
46. B.J. Daly, F.H. Harlow, Transport Equations in Turbulence, *Physics of Fluids* 13, 2634-2649 (1970).
47. K. Hanjalic, B.E. Launder, A Reynolds-stress model of turbulence and its application to asymmetric shear flows, *Journal of Fluid Mechanics* 52, 609-638 (1972).
48. W.P. Jones, B.E. Launder, The prediction of laminarization with a two-equation model of turbulence, *International Journal of Heat and Mass Transfer* 15:2, 301-314 (1972).
49. B.E. Launder, A. Morse, W. Rodi, D.B. Spalding, The prediction of free shear flows: a comparison of the performance of six turbulence models, in *Proceedings of the NASA Conference on Free Shear Flows*, Langley VA, 1972.
50. B.E. Launder, D.B. Spalding, *Mathematical Models of Turbulence*, Academic Press, London, 1972.
51. B.E. Launder, D.B. Spalding, The numerical computation of turbulent flows, *Comput. Methods Appl. Mech. Eng.* 3:2, 269-289 (1974).
52. C. Beck, Application of generalized thermostatics to fully developed turbulence, *Physica A: Statistical Mechanics and its Applications* 277:1, 115-123 (2000).
53. S. Ciliberto, N. Garnier, S. Hernandez, C. Lacpatia, J.-F. Pinton, G. Ruiz Chavarria, Experimental test of the Gallavotti-Cohen fluctuation theorem in turbulent flows, *Physica A: Statistical Mechanics and its Applications* 340:1-3, 240-250 (2004).
54. I. Prigogine, *Introduction to Thermodynamics of Irreversible Processes*, Interscience, 1961.

55. S.R. de Groot, P. Mazur, *Non-Equilibrium Thermodynamics*, North-Holland, 1962.
56. D. Jou, L. Restuccia, Mesoscopic transport equations and contemporary thermodynamics: An introduction, *Contemporary Physics* 52:5, 465-474 (2011).
57. D. Jou, J. Casas-Vázquez, G. Lebon, *Extended Irreversible Thermodynamics*, Springer Verlag, 2012.
58. K. Glavatskiy, *Multicomponent interfacial transport as described by the square gradient model: evaporation and condensation*, PhD Dissertation, Trondheim, 2009.
59. D. Bedeaux, E. Johannessen, A. Røsjorde, The nonequilibrium van der Waals square gradient model. (I). The model and its numerical solution, *Physica A: Statistical Mechanics and its Applications* 330:3-4, 329-353 (2003).
60. E. Johannessen, D. Bedeaux, The nonequilibrium van der Waals square gradient model. (II). Local equilibrium of the Gibbs surface, *Physica A: Statistical Mechanics and its Applications* 330:3-4, 354-372 (2003).
61. E. Johannessen, D. Bedeaux, The nonequilibrium van der Waals square gradient model. (III). Heat and mass transfer coefficients, *Physica A: Statistical Mechanics and its Applications* 336:3-4, 252-270 (2004).
62. M. Safari, M.R.H. Sheikhi, M. Janbozorgi, H. Metghalchi, Entropy transport equation in large eddy simulation for exergy analysis of turbulent combustion systems, *Entropy* 12:3, 434-444 (2010).
63. R. Farran, N. Chakraborty, A direct numerical simulation-based analysis of entropy generation in turbulent premixed flames, *Entropy* 15:5, 1540-1566 (2013).
64. M. Safari, F. Hadi, M.R.H. Sheikhi, Progress in the Prediction of Entropy Generation in Turbulent Reacting Flows Using Large Eddy Simulation, *Entropy* 16:10, 5159-5177 (2014).
65. H. Yarmand, G. Ahmadi, S. Gharekhani, S.N. Kazi, M.R. Safaei, M.S. Alehashem, A.B. Mahat, Entropy generation during turbulent flow of zirconia-water and other nanofluids in a square cross section tube with a constant heat flux, *Entropy* 16:11, 6116-6132 (2014).
66. K.E. Jansen, *The Role of Entropy in Turbulence and Stabilized Finite Element Methods*, Ph.D. Dissertation, Stanford University, 1993.
67. G. Hauke, *A Unified Approach to Compressible and Incompressible Flows and a New Entropy-Consistent Formulation of the K-Epsilon Model*, Ph.D. Dissertation, Stanford University, 1995.
68. F. Kock, H. Herwig, Local entropy production in turbulent shear flows: A high-Reynolds number model with wall functions, *International Journal of Heat and Mass Transfer* 47:10-11, 2205-2215 (2004).
69. F. Kock, H. Herwig, Entropy production calculation for turbulent shear flows and their implementation in cfd codes, *International Journal of Heat and Fluid Flow* 26:4, 672-680 (2005).
70. H. Herwig, F. Kock, Local entropy production in turbulent shear flows: A tool for evaluating heat transfer performance, *Journal of Thermal Science* 15:2, 159-167 (2006).
71. C. Habchi, T. Lemenand, D. Della Valle, L. Pacheco, O. Le Corre, H. Peerhossaini, Entropy production and field synergy principle in turbulent vortical flows, *International Journal of Thermal Sciences* 50:12, 2365-2376 (2011).
72. O.B. Adeyinka, G.F. Naterer, Modeling of entropy production in turbulent flows, *Journal of Fluids Engineering, Transactions of the ASME* 126:6, 893-899 (2004).
73. G.K. Batchelor, *An Introduction to Fluid Dynamics*, Cambridge University Press, 2000.
74. H.W. Liepmann, A. Roshko, *Elements of Gasdynamics*, John Wiley & Sons Inc, 2002.
75. A. Bejan, *Entropy Generation Minimization: The Method of Thermodynamic Optimization of Finite-size Systems and Finite-time Processes*, CRC Press, 1995
76. A. Bejan, M. J. Moran, *Thermal Design and Optimization*, John Wiley & Sons Inc, 1996.
77. P.L. Bhatnagar, E.P. Gross, M. Krook, A Model for Collision Processes in Gases. I. Small Amplitude Processes in Charged and Neutral One-Component Systems, *Physical Review* 94:3, 511-525 (1954).
78. C. Cercignani, *The Boltzmann Equation and Its Applications*, Springer New York, 2012.
79. A. De Rosis, G. Falcucci, S. Ubertini, F. Ubertini, Aeroelastic study of flexible flapping wings by a coupled lattice Boltzmann-finite element approach with immersed boundary method, *Journal of Fluids and Structures* 49, 516-533 (2014).
80. Y.C. Jung, B. Bhushan, Biomimetic structures for fluid drag reduction in laminar and turbulent flows, *Journal of Physics: Condensed Matter* 22, 035104 (2009).
81. N.J. Quinlan, P.N. Dooley, Models of Flow-Induced Loading on Blood Cells in Laminar and Turbulent Flow, with Application to Cardiovascular Device Flow, *Annals of Biomedical Engineering* 35, 1347-1356 (2007).

82. X. Li, J. Meng, Z. Guo, Turbulent flow and heat transfer in discrete double inclined ribs tube, *International Journal of Heat and Mass Transfer* 52, 962-970 (2009).
83. F. Cola, M. De Gennaro, D. Perocchio, E. Canuto, S. Daniele, P. Napoli, G. Toscano Rivalta, E. Chiavazzo, M. Fasano, P. Asinari, Integrated receivers with bottom subcooling for automotive air conditioning: Detailed experimental study of their filling capacity, *International Journal of Refrigeration* 62, 72-84 (2016).
84. P.J. Sellers, R.E. Dickinson, D.A. Randall, A.K. Betts, F.G. Hall, J.A. Berry, G.J. Collatz, A.S. Denning, H.A. Mooney, C.A. Nobre, N. Sato, C.B. Field, A. Henderson-Sellers, Modeling the Exchanges of Energy, Water, and Carbon Between Continents and the Atmosphere, *Science* 24, 502-509 (1997).

© 2016 by the authors. Submitted to *Entropy* for possible open access publication under the terms and conditions of the Creative Commons Attribution license (<http://creativecommons.org/licenses/by/4.0/>)