

## New position control tools for runaway experiments at JET

L. Calacci<sup>1</sup>, M. Ariola<sup>2</sup>, G. Artaserse<sup>4</sup>, M. Baruzzo<sup>5</sup>, D. Carnevale<sup>1</sup>, G. De Tommasi<sup>4</sup>,  
E. Joffrin<sup>6</sup>, M. Lennholm<sup>5</sup>, M. Passeri<sup>1</sup>, C. Possieri<sup>1</sup>, C. Reux<sup>6</sup>,  
F. Rimini<sup>5</sup>, Niko Sciatore<sup>1</sup>, D. Valcarcel<sup>5</sup> the JET Contributors<sup>7</sup>

<sup>1</sup> *Dip. di Ing. Civile ed Informatica, Università di Roma Tor Vergata, Italy*

<sup>2</sup> *CREATE-Università degli Studi di Napoli Parthenope, Centro Direzionale di Napoli, Isola  
C4, 80143 Napoli, Italy*

<sup>3</sup> *CREATE-Università degli Studi di Napoli Federico II, via Claudio 21, 80125, Napoli, Italy*

<sup>4</sup> *ENEA, Fusion and Nuclear Safety Department, Via E. Fermi 45, 00044 Frascati, Italy*

<sup>5</sup> *Euratom-CCFE, Culham Science Centre, OX14 3DB, Abingdon, UK*

<sup>6</sup> *CEA, IRFM, F-13108 Saint-Paul-lez-Durance, France*

<sup>7</sup> *See the author list of “X. Litaudon et al 2017 Nucl. Fusion 57 102001”*

Runaway beam confinement and dissipation remain one of the main concern for ITER operation and a clear solution has not been found yet. ITER will be provided with a Shattered Pellet Injection (SPI) system as the primary disruption mitigation technique given the promising results provided by DIII-D [3]. To further study such technique an SPI system has been recently installed at JET and to provide reliable results an improved runaway beam position control system [2, 1] is proposed. In this work we propose to use a dynamic observer to estimate in real-time the vertical speed of the runaway beam. This dynamic observer should replace the standard static estimator used at JET by the vertical stabilization system, once the runaway beam is detected. In particular, the instantaneous input/output matrix of the new observer, whose inputs are the magnetic measurements, is equal to the standard observer, meanwhile the dynamic and state-to-output matrices are optimized in order to fit the vertical position reconstructed using EFIT. The new observer has the same high frequency behavior of the standard one plus the capability of detecting the RE beam slow vertical drift. An innovative tool to improve the beam position control is also described. This method uses a graph data structure to store an adaptive probabilistic route-map that links different states of the plasma and that can be obtained either using experimental data or via a simulators. Such structure is then used to estimate an optimal control policy via reinforcement learning techniques.

### References

- [1] L. Boncagni et al., A first approach to runaway electron control in FTU, FED 88 (6-8), 1109-1112
- [2] D. Carnevale et al., Runaway electron beam control, PPCF 61 (1), 014036 (2018)
- [3] N. Commaux et al., First demonstration of rapid shutdown using neon shattered pellet injection for thermal quench mitigation on DIII-D, Nucl. Fusion 56 046007 (2016)
- [4] C. Reux et al, Runaway electron beam generation and mitigation during disruptions at JET-ILW, Nucl. Fusion 55 129501 (2015)
- [5] B. Esposito et al., Runaway electron generation and control, PPCF 59 (1), (2017)