

CASE STUDY ON EFFECTS OF THE MANDATORY VALIDATION ON BUS COMMERCIAL SPEED

Original

CASE STUDY ON EFFECTS OF THE MANDATORY VALIDATION ON BUS COMMERCIAL SPEED / Pronello, C.; Gaborieau, J. B.; Rappazzo, V.. - ELETTRONICO. - (2019). (Intervento presentato al convegno Transportation Research Board 98th Annual meeting tenutosi a Washington D.C. nel 13-17 January 2019).

Availability:

This version is available at: 11583/2726983 since: 2020-02-16T15:15:13Z

Publisher:

Transportation Research Board TRB

Published

DOI:

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

1 **CASE STUDY ON EFFECTS OF THE MANDATORY VALIDATION ON BUS**
2 **COMMERCIAL SPEED**

3
4
5
6 **Cristina Pronello, Corresponding Author**

7 Sorbonne Universités – Université de Technologie de Compiègne Département Génie des
8 systèmes urbains (GSU) & EA 7284 AVENUES, France

9 Rue du docteur Schweitzer CS 60319, 60203 COMPIEGNE Cedex France

10 Tel: +33 (0)3 44234406; Email: cristina.pronello@utc.fr

11 Politecnico di Torino, Dipartimento Interateneo di Scienze, Progetto e Politiche del Territorio, Italy
12 Viale Mattioli, 39. 10125, Torino, Italy

13 Tel: +39 011 0905613; Fax: +39 011 0906450; Email: cristina.pronello@polito.it

14
15 **Jean-Baptiste Gaborieau**

16 Dipartimento Interateneo di Scienze, Progetto e Politiche del Territorio. Politecnico di Torino, Italy
17 Viale Mattioli, 39. 10125, Torino, Italy

18 Tel: +39 011 0905640; Fax: +39 011 0906450; Email: jeanbaptiste.gaborieau@polito.it

19
20 **Valentina Rappazzo**

21 Dipartimento Interateneo di Scienze, Progetto e Politiche del Territorio. Politecnico di Torino, Italy
22 Viale Mattioli, 39. 10125, Torino, Italy

23 Tel: +39 011 0905605; Fax: +39 011 0906450; Email: valentina.rappazzo@polito.it

24
25
26 Word count: 5,275 words text + 3 tables x 250 words (each) = 6,025 words

27
28
29
30
31
32
33 Submission Date: 23 July 2018

1 ABSTRACT

2 The paper aims to define the new operational requirements and procedures to allow the GTT
3 (Torino public transport company) to implement mandatory validation without negative impacts
4 on both the company and the users. To this end, a four-step methodology has been put forward:
5 a) choice of the reference route and trip sampling; b) data acquisition; c) boarding time analysis
6 and d) future scenario definition.

7 Attained results show that the most unfavourable situation for the company is banning people
8 from boarding the bus/tram through any door (the case today) because it requires, in order to
9 maintain the same time interval at bus stops, an increase of trips in the morning peak hour. Thus,
10 the present system limits the outcomes negatively for the users in terms of waiting time.

11 However, a change could lead to such positive consequences as fuller passenger cooperation to
12 validate tickets/passes and a more ordered boarding, thus reducing fraud and improving the
13 image of the company.

14

15

16

17

18 *Keywords:* Public Transport, Boarding Time, Commercial Speed, Smart Card, Validation.

19

1 INTRODUCTION

2 The mandatory validation of transport tickets and passes when boarding public transport is useful
3 to ensure a correct collection of fares, to limit free-ridership and to consolidate company
4 revenues. Besides, it is a convenient practice for collecting huge amount of travel data, allowing
5 a better operation, management, processing of information and control of the public service (1-
6 4). However, it may demand extra time for the users as well as some operational adjustments for
7 the public transport (PT) operators.

8 Dwell time is defined by York (5) as the time when the wheels are stationary at a bus stop
9 while other researchers consider it as the time from the bus doors' opening to their complete
10 closing (6-8). This latter definition may include the time when the doors are already, or still,
11 "open" even though passengers are not getting on or off.

12 Dwell time depends on several factors according to the specific characteristics of the:

- 13 • vehicle (number and width of the doors, steps at the doors, deck height, number of decks,
14 length and typology of the vehicle) (6,9-11);
- 15 • infrastructure (location and length of the platforms, dedicated lanes) (9,12,13);
- 16 • payment system (on board or not) and ticket type (paper, magnetic, smart card) (9,14).

17 However, despite the above factors, the key elements influencing dwell time are the
18 transport demand and its characteristics (15): the number of passengers moving from one mode
19 to another at the stop and their age (9); particular conditions such as the presence of wheelchairs
20 and strollers; time of day and weather conditions (15).

21 The dwell time may be very significant as regards to the total travel time. By analysing
22 the data referring to several US cities from 1957 to 1980, Levinson (16) estimated that dwell
23 time in urban areas accounts for 9 to 26% of overall travel time, depending on incoming
24 passengers. More recently, Tirachini (14), analysing public transport in Sydney, Australia, found
25 lower values, from 3 to 13%, according to the transport demand. Such figures show how
26 intervening on the factors affecting dwell time is crucial to increasing commercial speed and,
27 consequently, to increasing the efficiency of operations of the Public Transport company. This
28 would also guarantee positive impacts for the users (9), since a more precise detection of
29 passenger flow would help to organise the service, and better tailor transport offers to user needs.
30 Furthermore, validation would help detect fraud.

31 Multiple regression models are the typical approach used to estimate the influence of the
32 different factors on dwell time (9); those models are based on data related to the number of
33 passengers getting on (boarding) and off (alighting) at each stop, as suggested by the Transit
34 Capacity and Quality of Service manual (15). Instead, Levinson (16) defined a linear relation: the
35 dwell time is 5 seconds plus 2.75 seconds per passenger getting on and off (s/pax), while
36 Fernández et al. (17) estimated a range of 2.05 to 6.04 s for each passenger.

37 The TCSQ Manual (15) suggests using a multivariate linear regression differentiating
38 incoming and outgoing flows and proved that boarding time for incoming passengers is greater
39 than alighting time for outgoing passengers. Moreover, the change of vehicle/mode (in both
40 directions) is faster during peak hours because of the different users' typology at different times
41 of day. Similar to Levinson (16), the TCSQ Manual (15) proposes adding a constant time for
42 each passenger boarding on or alighting from the bus.

43 Tirachini (9) suggests considering the difference between a simultaneous passengers'
44 flow (use of different doors for boarding and alighting) or a sequential one (the same door used
45 both for getting on and off).

46 Several studies analysed the influence of vehicle occupancy, particularly focusing on the
47 effects of crowding and friction between passengers while boarding and alighting (6-8). Zhang

1 and Teng (18) proved that considering the crowding on the bus allows for a better estimation of
2 the dwell time than using only the number of people boarding and alighting.

3 Sun et al. (13) showed that high occupancy slows down boarding (+0.340 s/pax) while
4 slightly speeding up alighting (-0.083 s/pax). When the occupancy is about 60% of vehicle
5 capacity, internal frictions produce delays in the boarding time since the incoming flow can get
6 on only when the vehicle occupancy falls below a minimum level (13). Tirachini (9) focused
7 mainly on the effects of frictions when boarding occurs in parallel queues. The relevance of this
8 effect is surprisingly high, since boarding time requires extra time equal to 1.25 s/pax; these
9 delays are more significant when the transport demand is higher.

10 To reduce bus travel time, Levinson (16) considered decreasing the number of stops and
11 the length of dwell times to be more effective, thanks to changes in fare collection policies and
12 door configuration, than providing bus priority lanes or reducing traffic-related congestion.

13 Notwithstanding several existing studies, an additional effort is needed to understand
14 which is the best configuration, taking into account the different contexts and typologies of
15 passengers.

16 This paper aims to test the effect on boarding time – on public transport lines in Torino –
17 of different hypotheses related to different doors' operation by evaluating three different
18 scenarios. The motivation of the research arises because the Gruppo Torinese Trasporti (GTT),
19 the PT company operating in Torino, was wondering whether changing or not the current way
20 passengers board buses and trams. Indeed, a recent Italian law of the Regione Piemonte (L.R. n.
21 1, 27.01.2015, art. 21, comma 29, came into force in May 2017) has required mandatory
22 validation by all PT passengers, including pass holders – the previous practice being that only
23 single ticket holders had to validate.

24 The purpose of the above regional initiative would allow for the collection of massive
25 travel data (1-4) and, thus, support the transport authority (Agenzia della Mobilità Piemontese)
26 to: evaluate if the current network well suit the current demand; monitor the quality of the
27 service; better plan and program the transport services and, eventually, trigger a social control
28 onboard thus making the system less susceptible to free-ridership.

29 Despite the fact that the new practice would generate multiple benefits, the GTT has had
30 to face several operational issues:

- 31 • the increase of boarding time and consequently of travel time, entailing a lower
32 commercial speed;
- 33 • the change in scheduling and, therefore, in the overall costs;
- 34 • the appropriate relocation of ticket machines and the introduction of new ones to speed
35 up boarding time.

36 The scenario analysed by Tirachini (14) in Sydney – simultaneous flows, each through
37 one door – is dissimilar to the Torino sequential flows through four doors. Indeed, the rule
38 provides an alternating flow, alighting first and then boarding, but the practice of simultaneous
39 flows through a double-stream door is common. The current study, unlike the Sydney study, does
40 not differentiate the relevance of the characteristics of the vehicle, since all data are referred to
41 the same bus typology (3-axle, 18 m long articulated urban buses).

42 The next section focuses on the methodology, describing the survey and the data analysis
43 design. Following this, results are discussed and conclusions and suggestions to transport
44 company are put forward.

45 **METHODOLOGY**

46 GTT decided to test the introduction of the mandatory validation before putting it into place,
47

1 asking for the help of the authors to design the pilot program on the GTT lines. The test has
2 followed a four-step methodology: 1) selection of a test line, choosing the reference route and
3 trip sampling; 2) data collection; 3) data analysis design and model specification; and 4) scenario
4 definition and analysis.

5 The urban and suburban network operated by GTT includes approximately 100 lines with
6 different functions (ordinary, special, school, etc.) and, therefore, different passenger typologies.
7 As the introduction of mandatory validation is supposed to increase boarding time, line 18 was
8 selected for the test, being one of the ten surface lines carrying 50% of total passengers, the third
9 most-used line of the entire surface network, and the first most-used bus line. Line 18 runs along
10 the North-South axis from Piazza Sofia (S Terminus) to Piazza Caio Mario (C Terminus) along
11 28.168 km (17.5 mi), round-trip, on non-dedicated lanes, serving 88 stops (44 per direction,
12 terminus excluded).

13 The buses used along line 18 are IRISBUS CITELIS produced by Iveco, 18 meters long
14 and supported by 3 axles. They are equipped with four two-way working doors: boarding and
15 alighting is authorised through all doors, with priority for passengers getting off. The vehicle
16 capacity is equal to 159 passengers, including one disabled person.

17 Sample trips to collect data on dwell time were selected according to the following
18 criteria:

- 19 • weekday peak-hour trips: morning (7:00 – 9:00) and evening (16:00 – 20:00); peak-hour
20 trips represent time of the day with the greatest ridership;
- 21 • weekday off-peak trips (9:00 – 16:00) in order to highlight, albeit partially, differences in
22 scopes, habits, and user typologies that could influence boarding times;
- 23 • weekend trips: periods of greatest ridership (16:00 – 21:00 on Saturdays, 10:00 – 12:00
24 and 17:00 – 20:00 on Sundays) to have a picture of weekend trips;
- 25 • weather: all selected trips were run during non-rainy days, to limit bias resulting from
26 differences in atmospheric conditions;
- 27 • holidays were excluded as they represent unusual periods for transport demand.

28 The sample does not consider all the above listed criteria due to operational and
29 economic reasons, as explained in section 2.1 ahead. All trips were sampled from a period
30 running from September to December 2016.

31 **Data collection**

32 A wide range of methods was considered for the data collection on passenger boarding and
33 alighting, from automatic passenger counting devices to manual on-board monitoring.
34 Eventually, data recording by closed-circuit television (CCTV, video surveillance cameras) was
35 used because this method allows for the collection of all necessary data about the passenger and
36 does not require additional hardware or staff costs. Moreover, the use of CCTV images is
37 allowed by Italian Article 100.1, D.L. 30 June 2003, n° 196, for educational and research
38 purposes.
39

40 The vehicles used along the selected trips were identified, and when they returned to
41 depot, the hard-drives were collected, the raw files were transferred to local machines and an
42 operator analysed the videos and logged the following variables into a data sheet:

- 43 • trip direction, bus number and trip number, in order to associate the video with a single
44 trip;
- 45 • opening time of the first door; usually all doors open at once, but in some cases some
46 doors remained closed;

- 1 • closing time of the last door; usually doors do not close all at once but depend on the
2 driver and passenger flow through each door;
- 3 • number of people boarding and alighting; flows through each door are bidirectional,
4 people can get on or off. For each door the number of outgoing and incoming travellers was
5 recorded;
- 6 • particular events. As some stops are located close to traffic lights, drivers often hold the
7 doors open until the end of the green cycle. To exclude the traffic light influence, the time of the
8 last passenger boarding was recorded and a 3-second interval added to simulate the closing time
9 of the doors as in free-flow traffic conditions. Moreover, any special event that could cause an
10 abnormal timeframe between the opening and the closing of the doors was recorded (e.g.
11 boarding of disabled people, families with strollers, or change of driver);
- 12 • stop duration at both termini (departure and arrival); the number of passengers on board
13 and closing time of the doors were recorded at the departure terminus as well as opening time of
14 doors and number of people alighting at the arrival terminus.

15 The above data were used to calculate the following variables for each stop:

- 16 • timeframe of opening/closing of doors: $T_{o/c}$ = timeframe between the opening of the first
17 door and the complete closing of the last one, including the mechanical time to close the door;
- 18 • number of people boarding: N_b = total number of people getting on at the given stop;
- 19 • number of people alighting: N_a = total number of people getting off at the given stop;
- 20 • load factor: $\%_{occ}$ = ratio of the number of people on board to vehicle capacity (equal to
21 159 passengers);
- 22 • total trip time; T_{tt} = timeframe between the closing of the last door at the departure
23 terminus and the opening of the first door at the arrival terminus;
- 24 • door usage percentage; D_{ib} , D_{ia} = ratio of total number of passengers at each stop
25 boarding (b) and alighting (a) at the door (i), to total number of passengers at each stop boarding
26 and alighting at all doors. Even though the data collection through the on-board video-
27 surveillance cameras allowed the manual acquisition of appropriate information, there are some
28 external and internal methodological limitations:
 - 29 – difficulties in obtaining desired specific CCTV registration disks due to a lack of full
30 availability: damaged or malfunctioning hard-drives;
 - 31 – poor visibility: the CCTV's camera position and framing were designed for security
32 purposes, making them suboptimal for visualising and counting passengers.

33 Finally, occupancy, flow speed, parallel boarding, light refraction and low video quality
34 made manual counting time-consuming, forcing the operator logging the information to watch
35 the videos again to observe all the details useful to collect the needed data.

37 **Data analysis design and model specification**

38 The model specification, based on the relevant literature (8, 13, 18) is described in equation (1).
39 Boarding and alighting have to be separately considered, since their associated times can be very
40 different (15) as the mandatory smart-card validation concerns boarding passengers only.

41 The relation between the dependent variable $T_{o/c}$ and the independent variables – number
42 of people alighting, the number of people boarding and ridership percentage – has been studied
43 thanks to a backward stepwise multiple regression analysis, where successive iterative estimates
44 were computed after deletion of insignificant ($p > 0.05$) regression coefficients, β_i . The model was
45 defined as follows:

$$46 \quad 47 \quad T_{o/c} = c + \beta_1 N_a + \beta_2 N_b + \beta_3 \%_{occ} + \beta_4 N_a^2 + \beta_5 N_b^2 + \beta_6 \%_{occ}^2 + \beta_7 N_a N_b + \beta_8 \times N_b \%_{occ} + \beta_9 N_a \%_{occ} + \varepsilon \quad (1)$$

1 where:
 2 c = intercept;
 3 N_a = number of people alighting through the most used door at the given stop;
 4 N_b = number of people boarding through the most used door at the given stop;
 5 $\%_{occ}$ = ridership percentage;
 6 β_i = regression coefficients associated with the independent variables, their quadratic
 7 measures and their respective pairwise interactions;
 8 ε = normally distributed error term.

9 The most used doors were identified by adding boarding and alighting passengers; thus,
 10 the maximum number of persons getting off and on through these doors is defined as N_{maxa} and
 11 N_{maxb} . Two different estimates of parameters were produced for weekdays and for weekends
 12 because the influence of the independent variables on $T_{o/c}$ is moderated by factors depending on
 13 the day of the week, notably trip scope, user habits and user typologies (15).
 14

15 Definition and analysis of future scenarios

16 For each of the selected bus trips, three scenarios were defined along with the Current Situation
 17 (two-way working doors and non-mandatory smart-card validation, values from previously
 18 manually recorded data) and are summarised in Table 1.
 19

20 **TABLE 1 Scenario definition**
 21

	Mandatory smart-card validation	Door 1	Door 2	Door 3	Door 4
S₀	NO	Boarding and alighting	Boarding and alighting	Boarding and alighting	Boarding and alighting
S₁	YES	Boarding and alighting	Boarding and alighting	Boarding and alighting	Boarding and alighting
S₂	YES	Boarding only	Alighting only	Alighting only	Alighting only
S₃	YES	Boarding only	Alighting only	Alighting only	Boarding only

22
 23 Concerning scenarios S_2 and S_3 , the number of boarding and alighting passengers through
 24 each door were assigned as follows:

- 25 • Scenario S_2 : all boarding passengers were associated with the front door (door 1) whereas
 26 those alighting from door 1 were equally redistributed through doors 2 to 4;
- 27 • Scenario S_3 : passengers currently boarding and alighting through doors 1 and 2 were
 28 associated, respectively, with doors 1 and 2; those currently boarding and alighting through
 29 doors 3 and 4 were associated, respectively, with doors 4 and 3.

30 The data referred to the current situation (scenario S_0) allowed for the calculation of:

- 31 • total dwell time, by adding dwell time over all stops;
- 32 • total running time, by adding the timeframes when doors are closed;
- 33 • total trip time, by adding total boarding time and total running time.

34 The total dwell time will vary according to the scenarios, whereas the total running time
 35 is assumed to be constant throughout the different scenarios. Scenario S_0 is used to validate the
 36 regression model by matching computed total dwell time with the current situation. For scenarios
 37 S_1 , S_2 and S_3 mandatory smart-card validation has been simulated by adding a 1- to 3-second
 38 delay per person boarding; consequently, for each scenario, three sub-scenarios were compared

1 (+1s, +2s, +3s); the reasons are:

- 2 • exact or estimated validation times taken from the literature were found to be irrelevant
 3 as they refer to specific and very diverse urban environments and transport systems, not suitable
 4 to Torino PT;
 5 • validation time may present high variability as it depends on the type of travel documents
 6 (e.g. smart-card or single ticket) and on traveller speed (8,9).

7 Afterwards, the necessary timeframes between the opening and the closing of each door
 8 were calculated and the simulated dwell time was assumed as time related to the door with the
 9 largest timeframe for each stop.

10 For each trip and scenario, the single dwell times and the total dwell times were
 11 simulated. By adding up the total dwell and running time, the commercial speed – for each trip
 12 and scenario – was calculated.

13 Trips were divided into subgroups corresponding to different headways, both during the
 14 week and the weekend, in order to identify the number of vehicles needed to maintain the current
 15 level of service:

- 16 • weekdays:
 17 – from 7:00 to 9:00 6 minutes headway
 18 – from 9:00 to 16:00 7 minutes headway
 19 – from 16:00 to 20:00 8 minutes headway
 20 • weekends:
 21 – Saturdays 10 minutes headway
 22 – Sundays 16 minutes headway.

23 Finally, according to GTT practice, dwell time is considered to be 5 minutes at the arrival
 24 terminus.

25 RESULTS

26 Regression analyses were carried out on data referring to both weekdays and weekends. Table 2
 27 reports the model parameters as well as the corresponding standard errors (Se).
 28

29 **TABLE 2 Regression model parameters (weekdays and weekends)**

30

	Weekdays		Weekends	
Adjusted R ²	0.497		0.378	
Y	β_i	Se	β_i	Se
c	7,060***	0.408	8,584***	0.550
Nmax _a	1,347***	0.157	1,030***	0.135
Nmax _b	1,627***	0.188	1,044***	0.290
% _{occ}	-0.138***	0.032	–	–
N _a ²	-0.031**	0.011	–	–
N _b ²	-0.066**	0.021	0.081*	0.034
% _{occ} ²	0.003***	0.001	–	–
N _a *N _b	-0.080*	0.036	–	–
N _b *% _{occ}	0.017**	0.006	–	–
N _a *% _{occ}	–	–	–	–

31 * significant at p <0.05; **significant at p <0.01; ***significant at p <0.001

32 The intercept estimate (c) is the timeframe during which the doors are open without
 33

1 passenger flow: such timeframe covers the mechanical time necessary for opening and closing
2 the doors and the time taken by the operator between the last passenger boarding and the
3 activation of the door lock device. The mechanical opening/closing time is nearly 6 seconds (3
4 for opening, 3 for closing) and the driver operation (door lock) can vary according to his/her
5 alertness.

6 During the week, according to the model, alighting time per person is slightly lower ($\beta_1=$
7 1.347 s) than boarding time ($\beta_2 = 1.627$ s), which is consistent with the current literature. The
8 negative coefficients of the squared values of the number of people boarding ($\beta_5= -0.066$) and
9 alighting ($\beta_4= -0.031$) signify a decrease of marginal (boarding or alighting) time with the
10 increase of passengers going through doors, or, mathematically, that the second derivative of
11 time is negative. Thus, dwell time at crowded stops will be less affected by the presence of
12 additional travellers than dwell time at less crowded stops. Then, the load factor has a non-linear
13 effect on dwell time ($\beta_3=-0.138$, $\beta_6=0.003$) that drops digressively when loadings increase.

14 The interaction between the number of alighting and boarding passengers leads to a
15 reduction of the dwell time ($\beta_7= -0.080$); this effect can be explained by assuming there are
16 parallel flows of people getting in and out, allowed by the width of the doors. On the contrary,
17 the interaction between the number of boarding passengers and the load factor increases the
18 boarding time ($\beta_8 =0.017$); this is consistent with the notion of friction between boarding and on-
19 board passengers.

20 During the weekends, fewer variables influence the boarding time; the average time per
21 passenger is lower than for weekdays and very similar for boarding ($\beta_2= 1.04$ s) and alighting
22 ($\beta_1=1.03$ s). Another difference between the weekend and weekdays is the presence, on
23 weekends, of an increased marginal time per boarding passenger, significant (p-value <0.05)
24 even though quite small ($\beta_5=0.08$).

25 Finally, on weekends, loadings do not have a significant impact on dwell time. The first
26 hypothesis was that vehicle loadings are lower during weekends than during weekdays,
27 explaining why the regression model was insensitive to passenger flow variation. However, after
28 comparing average loadings over single trips for both periods, no significant difference was
29 observed, thus conflicting with the first hypothesis.

30 Table 3 shows the main results for the different scenarios, focusing on the change of
31 commercial speed (V_{comm}) and, consequently, on the number of vehicles required to avoid both
32 an increase of the waiting time at the bus stop and an increase of the overall travel time.

33 The simulation of scenario 0 (two-way working doors and non-mandatory smart-card
34 validation) represents the current situation very well, revealing the good fit of the model. The
35 computed Total Dwell Time (TDT) slightly differs from the current scenario: the maximum
36 difference (-2.69%) is recorded for the weekdays from 09:00 to 16:00. The predicted commercial
37 speed fits the current one well, showing a maximum difference of +0.34%, recorded for the same
38 time slot (weekdays, 9:00-16:00). Observed and simulated TDT range from 11% (morning
39 period) to 15% (Sunday) of the total trip time, confirming the lower impact of TDT during peak
40 time, as consistent with state-of-the-art literature (15).

41 The good fit of the model justifies its use to estimate the effects of mandatory validation
42 on the different scenarios.

43 Scenario 1 (two-way working doors and mandatory smart-card validation) is slightly critical,
44 notably in the two peak-periods (07:00 - 09:00 and 16:00 - 20:00), when all sub-scenarios would
45 require a supplementary vehicle in order to avoid an increase of the waiting time. The worst sub-
46 scenario (+3 s/pax to validate) causes a non-negligible decrease of the commercial speed (> -
47 4.5%) for all the considered periods. Nevertheless, such a scenario would not affect the

1 **TABLE 3 Results of simulations of the different scenarios**

2

		Current	S ₀	S ₁ +1s	S ₁ +2s	S ₁ +3s	S ₂ +1s	S ₂ +2s	S ₂ +3s	S ₃ +1s	S ₃ +2s	S ₃ +3s
Weekdays 7-9	TDT [s]	460.60	466.03	538.33	592.41	659.16	597.66	737.62	880.42	564.52	654.03	752.23
	Δ TDT/current mean		1.18%	16.88%	28.62%	43.11%	29.76%	60.14%	91.15%	22.56%	41.99%	63.31%
	Total trip time [s]	4124.40	4129.83	4202.13	4256.21	4322.96	4261.46	4401.42	4544.22	4228.32	4317.83	4416.03
	Vcomm [km/h] / [mi/h]	12.3 / 7.6	12.3 / 7.6	12.1 / 7.5	11.9 / 7.4	11.7 / 7.3	11.9 / 7.4	11.5 / 7.2	11.2 / 6.9	12 / 7.4	11.7 / 7.3	11.5 / 7.1
	Δ Vcomm/current mean		-0.13%	-1.85%	-3.10%	-4.59%	-3.22%	-6.29%	-9.24%	-2.46%	-4.48%	-6.60%
	N. veh. (suppl/current)	24.58 (0)	24.61 (0)	25.01 (1)	25.31 (1)	25.68 (1)	25.34 (1)	26.12 (2)	26.91 (2)	25.16 (1)	25.65 (1)	26.20 (2)
Weekdays 9-16	TDT [s]	488.20	475.04	551.43	628.73	701.32	647.07	806.97	966.87	605.94	671.43	779.81
	Δ TDT/current mean		-2.69%	12.95%	28.79%	43.66%	32.54%	65.29%	98.05%	24.12%	37.53%	59.73%
	Total trip time [s]	3929.60	3916.44	3992.83	4070.13	4142.72	4088.47	4248.37	4408.27	4047.34	4112.83	4221.21
	Vcomm [km/h] / [mi/h]	12.9 / 8	12.9 / 8	12.7 / 7.9	12.5 / 7.7	12.2 / 7.6	12.4 / 7.7	11.9 / 7.4	11.5 / 7.1	12.5 / 7.8	12.3 / 7.7	12 / 7.5
	Δ Vcomm/current mean		0.34%	-1.58%	-3.45%	-5.14%	-3.89%	-7.50%	-10.86%	-2.91%	-4.46%	-6.91%
	N. veh. (suppl/current)	20.14 (0)	20.08 (0)	20.44 (0)	20.81 (0)	21.16 (1)	20.90 (0)	21.66 (1)	22.42 (2)	20.70 (0)	21.01 (1)	21.53 (1)
Weekdays 16-20	TDT [s]	497.67	485.86	574.86	663.86	752.86	695.52	844.97	1012.31	622.87	741.75	862.71
	Δ TDT/current mean		-2.37%	15.51%	33.39%	51.28%	39.76%	69.79%	103.41%	25.16%	49.05%	73.35%
	Total trip time [s]	4194.67	4182.86	4271.86	4360.86	4449.86	4392.52	4541.97	4709.31	4319.87	4438.75	4559.71
	Vcomm [km/h] / [mi/h]	12.1 / 7.5	12.1 / 7.5	11.9 / 7.4	11.6 / 7.2	11.4 / 7.1	11.5 / 7.2	11.2 / 6.9	10.8 / 6.7	11.7 / 7.3	11.4 / 7.1	11.1 / 6.9
	Δ Vcomm/current mean		0.28%	-1.81%	-3.81%	-5.73%	-4.50%	-7.65%	-10.93%	-2.90%	-5.50%	-8.01%
	N. veh. (suppl/current)	18.73 (0)	18.68 (0)	19.05 (1)	19.42 (1)	19.79 (1)	19.55 (1)	20.17 (2)	20.87 (2)	19.25 (1)	19.74 (1)	20.25 (2)
Saturdays	TDT [s]	545.00	538.06	611.81	661.56	737.53	775.05	893.77	1040.52	698.92	816.06	935.79
	Δ TDT/current mean		-1.27%	12.26%	21.39%	35.33%	42.21%	63.99%	90.92%	28.24%	49.74%	71.70%
	Total trip time [s]	3780.75	3773.81	3847.56	3897.31	3973.28	4010.80	4129.52	4276.27	3934.67	4051.81	4171.54
	Vcomm [km/h] / [mi/h]	13.4 / 8.3	13.4 / 8.3	13.2 / 8.2	13 / 8.1	12.8 / 7.9	12.6 / 7.9	12.3 / 7.6	11.9 / 7.4	12.9 / 8	12.5 / 7.8	12.2 / 7.5
	Δ Vcomm/current mean		0.18%	-1.74%	-2.99%	-4.85%	-5.74%	-8.45%	-11.59%	-3.91%	-6.69%	-9.37%
	N. veh. (suppl/current)	13.60 (0)	13.58 (0)	13.83 (0)	13.99 (0)	14.24 (1)	14.37 (1)	14.77 (1)	15.25 (2)	14.12 (1)	14.51 (1)	14.91 (1)
Sundays	TDT [s]	541.00	541.04	625.54	647.56	742.03	848.87	997.84	1168.34	760.72	901.02	1042.57
	Δ TDT/current mean		0.01%	15.63%	19.70%	37.16%	56.91%	84.44%	115.96%	40.61%	66.55%	92.71%
	Total trip time [s]	3700.00	3700.04	3784.54	3806.56	3901.03	4007.87	4156.84	4327.34	3919.72	4060.02	4201.57
	Vcomm [km/h] / [mi/h]	13.7 / 8.5	13.7 / 8.5	13.4 / 8.3	13.3 / 8.3	13 / 8.1	12.7 / 7.9	12.2 / 7.6	11.7 / 7.3	12.9 / 8	12.5 / 7.8	12.1 / 7.5
	Δ Vcomm/current mean		0.00%	-2.23%	-2.80%	-5.15%	-7.68%	-10.99%	-14.50%	-5.61%	-8.87%	-11.94%
	N. veh. (suppl/current)	8.33 (0)	8.33 (0)	8.51 (0)	8.56 (0)	8.75 (0)	8.97 (0)	9.29 (1)	9.64 (1)	8.79 (0)	9.08 (1)	9.38 (1)

3

operational requirements to satisfy the demand on Sunday. In fact, although the +3s sub-scenario causes a considerable decrease of the commercial speed (-5.15%, the second highest value in S_3), the number of vehicles currently used in this time period allows such a drawback to be overcome, avoiding adding another one, as required for the other periods. For the S_{1+3s} scenario, the share of TDT on total trip time increases from 15% (morning period) to 17% (afternoon and evening period) and to 19% for the weekend. Scenario 2 (boarding from the front door only, mandatory smart-card validation and alighting through all other doors) is the most critical one, requiring at least one supplementary vehicle for all time periods and sub-scenarios, except for the "+1s" scenario in the off-peak period during the week and on Sunday.

In this latter case the decrease of commercial speed is important (-7.68%), but the number of vehicles currently used in S_0 would allow the current quality of service to be maintained. The most serious deficiencies would clearly occur in the "+3s" sub-scenario: a) two supplementary vehicles needed for all time-periods except Sunday, despite the great decrease of commercial speed (-14.5%); and b) the highest impact of the simulated TDT on the total trip time (27%) for the two peak-periods on the weekdays, when two supplementary vehicles would also be required in the "+2s" sub-scenario. The " S_{3+1s} " sub-scenario (boarding from the front and the rear doors, mandatory smart-card validation and alighting through middle doors) would not require any supplementary vehicle as regards the two similar cases of " S_{2+1s} ": the off-peak period on weekdays and on Sunday. The same cannot be said of the "+3s" sub-scenario, which would require two supplementary vehicles to avoid any increase in the waiting time at the bus stop during the morning and evening peak-periods on weekdays.

In this case, the share of TDT on total trip time varies from 17% in the morning period to 25% on Sunday. For all other sub-scenarios, only one supplementary vehicle would be needed. The observed values of the average commercial speed differ according to the different time periods, due to the change of both running time (mainly affected by traffic conditions) and dwell time. The lowest commercial speed is observed in the evening peak-period, followed by the morning period, the weekday off-peak period and, finally, Saturday and Sunday. For the different scenarios, the commercial speed varies only in function of the dwell time which, in turn, depends on the different use of the doors and on the different delays considered for mandatory validation.

DISCUSSION AND CONCLUSIONS

The regression model offers a good estimate of dwell times, notably for weekday trips, and the estimates of boarding and alighting times per passenger are consistent with the existing literature:

- results for weekdays show a dwell time equal to 7 seconds idling time plus 1.627s per boarding passenger; Levinson (16) proposed considering 5 seconds idling time plus 2.75s per boarding passenger;
- Sun et al. (13) found that high occupancy slows down boarding; the estimate of interaction between boarding and load factor confirms this phenomenon;
- estimates of boarding time (1.627s) and alighting time per passenger (1.347s) are remarkably close to values suggested by the TCQS Manual (15): 1.5s per boarding passenger and from 1.2 to 1.8 s per alighting passenger. These values are proposed for a situation with two available doors, comparable to our situation where, although 4 doors are available, only two of them are wide enough to allow simultaneous boarding/alighting passenger flows.

Observed data highlight that in the current situation, with two-way working doors, the passengers prefer both to board and alight through doors 2 and 3 (which together account for 65% of the total flows, mainly for alighting), while doors 1 and 4 are less used and then mainly

1 for boarding. This may be due to the bus layout, which has less space in the front, due to the
2 driver cabin. The length of the bus (18 m) may explain lower use of door 4, which is sometimes
3 less accessible from the platform.

4 The results from the scenario simulations will allow GTT to carry out an economical
5 evaluation and take the best decision in order to satisfy both operational and user needs. From
6 the Company's point of view, the most critical scenarios would be the ones entailing the
7 abolition of two-way working doors (S_2 and S_3), particularly if the boarding would then be
8 allowed only through only one door (S_2). The company should indeed increase the number of
9 circulating buses in order to guarantee the same level of service. However, such a change may
10 lead to positive consequences, such as a tidier boarding process and a greater propensity to
11 validate, since in S_2 the boarding would occur through the door next to the driver. The company
12 could benefit from a lower fraud rate and its public image would benefit from that. Furthermore,
13 the introduction of canalised flows would encourage the passengers to occupy areas currently
14 underused, such as corridors and the inner parts of the buses. As a consequence, crowding would
15 decrease in the door areas, creating less friction among the passengers during boarding and
16 alighting.

17 The variation of the number of buses needed depends on validation time: the same
18 number of buses is required both for Scenario 2 (boarding through the front door – door 1) with 2
19 s of validation time and for Scenario 3 (boarding through doors 1 and 4) with 3 s of validation
20 time.

21 The suppression of two-way working doors could be quite unfavourable, particularly if
22 implemented together with the introduction of mandatory validation. Passengers who are still not
23 used to the new practice, may take a rather long time to validate. Considering the lack of precise
24 data related to the effective validation time, the choice to keep the two-way working doors would
25 need more thought, perhaps requiring an initial test period to evaluate the magnitude of the
26 impact produced by the validation.

27 In fact, a test period would allow the real changes produced by mandatory validation to
28 be assessed and also, notably, precise data about the average validation time to be collected.
29 Afterwards, the introduction of channelled flows may be considered and possibly tested. Of
30 course, the different proofs-of-payment which may be used for validation entail different
31 validation times and, thus, different Total Dwell Times. Tirachini (9) proved that, compared to
32 the absence of validation, the increase of the boarding time varies from 1% to 17% with the use
33 of a smart card, from 26% to 77% with the use of a magnetic card, and from 241% to 619% with
34 on-board payment. Compared to the magnetic card, the use of a smart card allows saving from
35 22% to 51% of boarding time.

36 The study has highlighted the great importance of having precise data concerning
37 passenger counts. This information, used to analyse the dwell time, allows transport companies
38 to partially understand their user habits and the effective use of the PT service; these are, of
39 course, key elements for proper and efficient management of the transport system. To this extent,
40 it would be crucial to take advantage of more efficient and automatic data collection methods,
41 given the problems faced during the manual data collection.

42 For the time being, GTT has introduced mandatory validation and it is trying to
43 encourage users to validate by means of an intensive advertising campaign. Estimates from the
44 company show that less than 20% of passengers validate. Such a figure reflects the difficulty
45 users experience when the buses are crowded, discouraging virtuous behaviour. From the city's
46 perspective, the introduction of mandatory validation is expected to trigger more revenue from
47 tickets sales and less free ridership thanks to social control over the validation. Indeed, the city

1 being the owner of GTT, both a lower financial contribution and a lower dependency on
2 transport authority subsidies would alleviate the current expenditures, which are continuously
3 challenged due to the decrease of regional funds. Nevertheless, the decrease of commercial speed
4 will require a greater number of vehicles in order to maintain a constant waiting time at stops,
5 implying that the service must be optimised to tackle the current budget restrictions. However,
6 the mix of mandatory validation with other policies such as traffic priority schemes for PT
7 services, can induce an increase in the quality of service in the coming years.

9 ACKNOWLEDGEMENTS

10 This paper is a result of a collaboration between Politecnico di Torino and GTT company that
11 made their data available for analysis.

14 REFERENCES

- 15 1. Bagchi, M., White, P.R. 'The potential of public transport smart card data' *Transport*
16 *Policy* 2005, Vol. 12, no. 5, pp. 464-474.
- 17 2. Pelletier, M., Trépanier, M., Morency, C. 'Smart card data use in public transit: A
18 literature review', *Transportation Research Part C* 2011, Vol. 19, pp. 557–568.
- 19 3. Park, J.Y., Kim, D.J. 'The Potential of Using the Smart Card Data to Define the Use of
20 Public Transit in Seoul' *Transportation Research Record: Journal of the Transportation*
21 *Research Board* 2008, Vol. 2063, pp. 3–9.
- 22 4. Briand, A., Côme, E., Trépanier, M., Oukhellou, L. 'Analyzing year-to-year changes in
23 public transport passenger behaviour using smart card data', *Transportation Research*
24 *Part C* 2017, Vol. 79, pp. 274–289.
- 25 5. York, I.O. 'Factors affecting bus-stop times', *Transport Research Laboratory*, 1993,
26 Project Report 2, Crowthorne.
- 27 6. Dueker, K., Kimpel, T., Strathman, J., Callas, S. 'Determinants of Bus Dwell Time',
28 *Journal of Public Transportation* 2004, Vol. 7, no. 1, pp. 21–40.
29 <https://doi.org/10.5038/2375-0901.7.1.2>.
- 30 7. Lin, T., Wilson, N. H. M. 'Dwell Time Relationships for Light Rail Systems',
31 *Transportation Research Record* 1992, Vol. 1361, pp. 287–295.
- 32 8. Tirachini, A., Hensher, D. A. 'Bus congestion, optimal infrastructure investment and the
33 choice of a fare collection system in dedicated bus corridors', *Transportation Research*
34 *Part B: Methodological* 2011, Vol. 45, no. 5, pp. 828–844.
- 35 9. Tirachini, A. 'Bus dwell time: the effect of different fare collection systems, bus floor
36 level and age of passengers' *Transportmetrica A: Transport Science* 2013, Vol. 9, no. 1,
37 pp. 28-49.
- 38 10. Levine J., Torng, G. 'Dwell-Time Effects of Low-Floor Bus Design', *Journal of*
39 *Transportation Engineering* 1994, Vol. 120, no. 6, pp. 914-929
- 40 11. Fernández, R; Zegers, P; Weber, G; Tyler, N. 'Influence of platform height, door width
41 and fare collection on bus dwell time. Laboratory evidence for Santiago de Chile',
42 *Transportation Research Record: Journal of the Transportation Research Board* 2010,
43 Vol. 2143, pp. 59-66.

- 1 12. Moreno Gonzalez, E.G., Romana, M.G., Alvaro, O.M. ‘Bus dwell-time model of main
2 urban route stops: case study in Madrid, Spain’, *Transportation Research Record* 2012,
3 Vol. 2274, pp. 126-134.
- 4 13. Sun, L., Tirachini, A., Axhausen, K. W., Erath A., Lee, D. H. ‘Models of bus boarding
5 and alighting dynamics’, *Transportation Research Part A: Policy and Practice* 2014,
6 Vol. 69, pp. 447–460.
- 7 14. Tirachini, A. ‘Estimation of travel time and the benefits of upgrading the fare payment
8 technology in urban bus services’, *Transportation Research Part C: Emerging
9 Technologies* 2013, Vol. 30, pp. 239–256.
- 10 15. Hunter-Zaworski, K. Transit Capacity and Quality of Service – Manual, 2nd Edition,
11 Transit Cooperative Research Program Report 100, 2003, Transportation Research Board
12 of the National Academy, Washington DC.
- 13 16. Levinson, H.S. ‘Analyzing transit travel time performance’, *Transportation Research
14 Record* 1983, Vol. 915, pp. 1-6.
- 15 17. Fernández, R., del Campo, M., Swett, C. ‘Data collection and calibration of passenger
16 service time models for the Transantiago system’, In *European Transport Conference*,
17 Oct. 2008, The Netherlands.
- 18 18. Zhang, C., Teng, J. ‘Bus Dwell Time Estimation and Prediction: A Study Case in
19 Shanghai-China’, *Procedia – Social and Behavioral Sciences* 2013, Vol. 96, pp. 1329–
20 1340.