

3D printing of sol-gel and melt-derived glass-ceramics for bone regeneration

*Original*

3D printing of sol-gel and melt-derived glass-ceramics for bone regeneration / Fiume, E.; Baino, F.; Massera, J.; Massai, D.; Bignardi, C.; Verne', E.. - ELETTRONICO. - 1:(2020), pp. 156-156. (Intervento presentato al convegno 44th International Conference & Exposition on Advanced Ceramics & Composites (ICACC 2020) tenutosi a Daytona Beach (FL, USA) nel 26-31 Gennaio, 2020).

*Availability:*

This version is available at: 11583/2793650 since: 2020-02-17T10:10:17Z

*Publisher:*

American Ceramic Society

*Published*

DOI:

*Terms of use:*

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

*Publisher copyright*

(Article begins on next page)

**The American Ceramic Society**  
**44th International Conference & Exposition  
on Advanced Ceramics and Composites**

**ABSTRACT BOOK**

**January 26–31, 2020  
Daytona Beach, Florida**

# Introduction

---

This volume contains abstracts for over 950 presentations during the 44th International Conference & Exposition on Advanced Ceramics & Composites in Daytona Beach, Florida. The abstracts are reproduced as submitted by authors, a format that provides for longer, more detailed descriptions of papers. The American Ceramic Society accepts no responsibility for the content or quality of the abstract content. Abstracts are arranged by day, then by symposium and session title. An Author Index appears at the back of this book. The Meeting Guide contains locations of sessions with times, titles and authors of papers, but not presentation abstracts.

## How to Use the Abstract Book

---

Refer to the Table of Contents to determine page numbers on which specific session abstracts begin. At the beginning of each session are headings that list session title, location and session chair. Starting times for presentations and paper numbers precede each paper title. The Author Index lists each author and the page number on which their abstract can be found.

Copyright © 2020 The American Ceramic Society ([www.ceramics.org](http://www.ceramics.org)). All rights reserved.

### MEETING REGULATIONS

The American Ceramic Society is a nonprofit scientific organization that facilitates the exchange of knowledge meetings and publication of papers for future reference. The Society owns and retains full right to control its publications and its meetings. The Society has an obligation to protect its members and meetings from intrusion by others who may wish to use the meetings for their own private promotion purpose. Literature found not to be in agreement with the Society's goals, in competition with Society services or of an offensive nature will not be displayed anywhere in the vicinity of the meeting. Promotional literature of any kind may not be displayed without the Society's permission and unless the Society provides tables for this purpose. Literature not conforming to this policy or displayed in other than designated areas will be disposed. The Society will not permit unauthorized scheduling of activities during its meeting by any person or group when those activities are conducted at its meeting place in interference with its programs and scheduled activities. The Society does not object to appropriate activities by others during its meetings if it is consulted with regard to time, place, and suitability. Any person or group wishing to conduct any activity at the time and location of the Society meeting must obtain permission from the Executive Director or Director of Meetings, giving full details regarding desired time, place and nature of activity.

**Diversity Statement:** The American Ceramic Society values diverse and inclusive participation within the field of ceramic science and engineering. ACerS strives to promote involvement and access to leadership opportunity regardless of race, ethnicity, gender, religion, age, sexual orientation, nationality, disability, appearance, geographic location, career path or academic level.

Visit the registration desk if you need access to a nursing mother's room or need further assistance. For childcare services, please check with the concierge at individual hotels for a listing of licensed and bonded child care options.

The American Ceramic Society plans to take photographs and video at the conference and reproduce them in educational, news or promotional materials,

whether in print, electronic or other media, including The American Ceramic Society's website. By participating in the conference, you grant The American Ceramic Society the right to use your name and photograph for such purposes. All postings become the property of The American Ceramic Society.

---

During oral sessions conducted during Society meetings, **unauthorized photography, videotaping and audio recording is prohibited**. Failure to comply may result in the removal of the offender from the session or from the remainder of the meeting.

---

**Registration Requirements:** Attendance at any meeting of the Society shall be limited to duly registered persons.

**Disclaimer:** Statements of fact and opinion are the responsibility of the authors alone and do not imply an opinion on the part of the officers, staff or members of The American Ceramic Society. The American Ceramic Society assumes no responsibility for the statements and opinions advanced by the contributors to its publications or by the speakers at its programs; nor does The American Ceramic Society assume any liability for losses or injuries suffered by attendees at its meetings. Registered names and trademarks, etc. used in its publications, even without specific indications thereof, are not to be considered unprotected by the law. Mention of trade names of commercial products does not constitute endorsement or recommendations for use by the publishers, editors or authors.

Final determination of the suitability of any information, procedure or products for use contemplated by any user, and the manner of that use, is the sole responsibility of the user. Expert advice should be obtained at all times when implementation is being considered, particularly where hazardous materials or processes are encountered.

Copyright © 2020. The American Ceramic Society ([www.ceramics.org](http://www.ceramics.org)). All rights reserved.

11:20 AM

## (ICACC-S15-035-2020) 3D printing of sol-gel and melt-derived glass-ceramics for bone regeneration

E. Fiume<sup>\*1</sup>; F. Bairo<sup>1</sup>; J. Massera<sup>3</sup>; D. Massari<sup>2</sup>; C. Bignardi<sup>2</sup>; E. Verné<sup>1</sup>

1. Politecnico di Torino, Department of Applied Science and Technology, Italy
2. Politecnico di Torino, Department of Mechanical and Aerospace Engineering, Italy
3. Tampere University of Technology, Biomedtech Institute and Faculty of Biomedical Sciences and Engineering, Finland

Scaffolds for bone grafting procedures have to satisfy a series of minimum requirements to provide mechanical support while allowing cell migration and fluid exchange. However, traditional manufacturing techniques suffer from poor repeatability and low control on porosity, which may preclude a safe therapeutic use of the device. In this sense, additive manufacturing technologies represent a powerful platform to easily tailor all these parameters by simply acting on the design and process parameters. In this work, a glass-ceramic based on the system  $\text{SiO}_2\text{-CaO-P}_2\text{O}_5\text{-Na}_2\text{O-MgO-K}_2\text{O}$  was successfully synthesized for the first time by sol-gel route and compared to the correspondent melt-derived material. Thermal properties, crystallization and surface area were object of study for comparison. In a second part of the study, both the systems were used as basic materials for the production of highly controlled grid-like 3D scaffolds by robocasting technology. Bioactivity and ion release were assessed by soaking the scaffolds in Simulated Body Fluid (SBF), in both static and dynamic conditions. In the latter case, a customized perfusion system designed for continuous SBF recirculation through the scaffolds was used to mimic physiological conditions. Up to now, results are promising and future studies deserve to be carried out to investigate cellular response and mechanical properties of the developed scaffolds.

## Direct Writing and Ink Jet Printing III

Room: Coquina Salon B

Session Chair: Michael Halbig, NASA Glenn Research Center

1:30 PM

## (ICACC-S15-036-2020) Sol-Gel Derived Inks for 3d Printed Glass Optics (Invited)

R. J. Dylla-Spears<sup>\*1</sup>; K. Sasan<sup>1</sup>; T. Fears<sup>1</sup>; N. Dudukovic<sup>1</sup>; M. Johnson<sup>1</sup>; D. Nguyen<sup>1</sup>; T. Yee<sup>1</sup>; O. Herrera<sup>1</sup>; C. Mah<sup>1</sup>; A. Lange<sup>1</sup>

1. Lawrence Livermore National Laboratory, Optics and Materials Science & Technology, USA

Techniques for three-dimensional (3d) printing of glass have opened the door to novel glass optics with both unconventional structures and tailored compositions. In the direct ink writing (DIW) approach, rheologically tuned silica-containing pastes are first extruded through a nozzle at room temperature and deposited in the geometry of interest, forming low density green bodies. The green bodies are then converted to full density, optically homogeneous glass by a series of heat treatments. The 3d-printed glass components have material and optical properties that rival conventionally prepared optical grade fused silica. However, to fully realize the potential of this technique for preparing novel optics requires the development of a library of ink formulations that lead to glasses with different properties. Several sol-gel approaches to ink preparation leading to refractive index control in 3d printed silicate glasses will be presented. In addition, efforts to blend and thermally process these inks into gradient composition optics will be described. This work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344 within the LDRD program 16-SI-003 and 19-ERD-020. LLNL-ABS-765937

2:00 PM

## (ICACC-S15-037-2020) Quantifying the Link between Rheology and Printability for Ceramic On-Demand Extrusion

A. J. Martin<sup>\*1</sup>; J. Watts<sup>1</sup>; G. Hilmal<sup>1</sup>; M. C. Leu<sup>2</sup>; T. Huang<sup>3</sup>

1. Missouri University of Science & Technology, Materials Science and Engineering, USA
2. Missouri University of Science & Technology, Mechanical & Aerospace Engineering, USA
3. Kansas City National Security Campus, USA

This study will continue research to link feedstock rheology to the 'printability' of ceramic components fabricated by Ceramic On-Demand Extrusion (CODE), a direct-write extrusion process which utilizes a rising oil bath to prevent excessive and non-uniform drying. Relevant background work assessing extrudability and printability will be discussed. Next, a comprehensive approach to couple rheology to object printing parameters will be described, and a wide range of zirconia pastes will be explored to establish process-property relationships. Paste microstructure will also be explored. From these investigations the constraints on ideal paste design will be discussed.

2:20 PM

## (ICACC-S15-039-2020) Robocasting of reaction bonded silicon carbide structures

L. Wahl<sup>\*1</sup>; N. Travitzky<sup>1</sup>

1. Friedrich-Alexander-University Erlangen-Nürnberg, Material Science and Engineering, Germany

Additive manufacturing of ceramics shows great potential to overcome the shape limitations of traditional fabrication methods due to the layerwise deposition of material. In this work, a novel shaping method for the manufacturing of reaction bonded silicon carbide (RBSC) structures was investigated. RBSC is attractive for high temperatures and extreme condition applications, such as turbines and bearings, due to its outstanding thermal and mechanical properties. To produce RBSC, a highly filled paste consisting of silicon carbide and carbon powder was developed and printed by robocasting technology using nozzles with diameter of 0.5 and 1.5 mm. To enable printing, the paste has to show suitable rheology, which means the presence of a yield point and a shear-thinning behavior. After heat treatment, the samples were further processed using the liquid silicon infiltration technique to obtain dense near-net shape RBSC. Different structures such as lattices, hollow cylinders, bending bars and gyroids were printed to show the variability of robocasting. The mechanical and physical properties of the robocasted samples were measured and are comparable with those of traditionally fabricated RBSC. These results open the field for a wide variety of materials, which can be processed in similar manner.

## Fused Deposition Modeling

Room: Coquina Salon B

Session Chair: Rebecca Dylla-Spears, Lawrence Livermore National Laboratory

3:20 PM

## (ICACC-S15-040-2020) Ceramic matrix composites fabricated by Fused Filament Fabrication (FFF)

H. Klemm<sup>\*1</sup>; J. Abel<sup>1</sup>; A. Michaelis<sup>2</sup>; M. Singh<sup>3</sup>

1. FhG IKTS Dresden, Germany
2. Fraunhofer IKTS, Germany
3. Ohio Aerospace Institute, USA

Ceramic matrix composites with SiC short fibers have been fabricated by Additive Manufacturing (AM) using a thermoplastic approach. By means of Fused Filament Fabrication (FFF) or Fused Deposition Modelling (FDM) a ceramic part is shaped layer by layer using a thermoplastic filament which is extruded through a heated nozzle.