POLITECNICO DI TORINO Repository ISTITUZIONALE

Recent developments in the Italian technical rules for dams and barrages

Original

Recent developments in the Italian technical rules for dams and barrages / Barpi, F.; Pascucci, V.; Ricciardi, C.; Salandin, P.; Scarpelli, G. - In: DAMS AND RESERVOIRS. - ISSN 1368-1494. - (2022), pp. 1-5. [10.1680/jdare.22.00096]

Availability: This version is available at: 11583/2963817 since: 2022-05-18T15:01:28Z

Publisher: ICE Publishing

Published DOI:10.1680/jdare.22.00096

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

1	Article	type:	paper
			1

2 Manuscript revised on 12/01/2022

3 4 5 6	RECENT	DEVELOPMENTS IN THE ITALIAN TECHNICAL RULES FOR DAMS AND			
7	7 BARRAGES				
8	Fabrizio Bai	rpi			
9	• Asso	ociate professor, Department of Structural, Geotechnical and Building Engineering, Politecnico di Torino,			
10	Italy				
11	• Ema	ail: fabrizio.barpi@polito.it			
12	• OR(CID: 0000-0001-8371-5690			
13					
14	1 Valter Pascucci				
15	• Sen	ior member of Consiglio Superiore dei Lavori Pubblici, Italy			
16	• Ema	ail: <u>valterpascucci@virgilio.it</u>			
17					
18	18 Carlo Ricciardi				
19	• Forr	ner member of Consiglio Superiore dei Lavori Pubblici, Italy			
20	• Ema	ail: <u>carloricciardi.cr@libero.it</u>			
21					
22	22 Paolo Salandin				
23	• Full	professor, Department of Civil, Environmental and Architectural Engineering, Università di Padova, Italy			
24	• Ema	ail: paolo.salandin@unipd.it			
25	• OR(CID: 0000-0002-4461-7104			
26					
27	Giuseppe S	Scarpelli			
28	•Full Prof	essor, Department of Materials, Environmental Sciences and Urban Planning, Università Politecnica delle			
29	Marche, Italy				
30	• Ema	ail: g.scarpelli@univpm.it			
31	• OR(CID: 0000-0002-0839-6834			
32					
33					

Full contact details of corresponding author. Fabrizio Barpi, Department of Structural, Geotechnical and
 Building Engineering, Politecnico di Torino, Italy. Email: fabrizio.barpi@polito.it

36

37 Abstract

The paper describes the Italian technical regulations for dams and barrages issued in 2014 by the Minister of Infrastructure and Transport, where substantial changes in the existing rules are introduced by suggesting a design approach based on the semi-probabilistic method at limit states. The paper highlights the most innovative aspects as well as the critical issues, suggests some improvements and underlines the need for further updating of the legislation.

43

44 Keywords

45 Barrages, dams, seismic design, structural safety, technical regulation.

46

47

- 48
- 49

50 1. INTRODUCTION

51 The paper examines the regulatory situation of dams and barrages following the approval of the Decree of the Minister of Infrastructure and Transport "Technical standards for the design and construction of dam 52 53 and barrages" of June 26, 2014 (hereinafter DM2014) [1]. This decree replaces the previous legislation, 54 dating back to 1982 (DM1982), which had to be updated in relation to the changes in the technical 55 standards for the construction sector, such as the Technical Standards for Construction of January 14, 2008 56 (NTC2008) recently updated on January 17, 2018 (NTC2018) [2]. This succession of technical standards 57 resulted in the misalignment of the DM1982 with respect to the construction regulations and determined the 58 need for its profound renewal with the current legislation of June 26, 2014. The regulatory framework 59 proposed in the DM2014 substantially embraced the inspiring criteria of the Eurocodes (already accepted in 60 the NTC2008 and NTC2018), superseding the previous legislation, which remained substantially based on 61 the allowable stress design method. However, this update has led to some uncertainties and criticalities 62 which will be described below.

63

64 **2. DECREE OF JUNE 26, 2014**

65 2.1 General description

66 The decree introduced, for the first time in Italy, the semi-probabilistic limit state method for dams and 67 established the Monitoring Board (of which the authors were members) for the examination of its first 68 application at the Higher Council of Public Works (Consiglio Superiore dei Lavori Pubblici, the technical 69 advisory body of the Ministry of Public Works for projects and issues of urban interest). The DM2014 is 70 particularly advanced since, to the knowledge of the authors, it is one of only three regulations on dams 71 based on the semi-probabilistic method at limit states, although it may be noticed that the other two are the 72 French Recommandations and Chinese standards, which do not have the mandatory character of the Italian 73 technical standards. DM2014 is divided in eight main sections described below.

74 Section 'A. General prescriptions' states that this legislation applies to all dams and barrages in the 75 Italian territory. For dams whose height does not exceed 10 m or which determine a reservoir volume not 76 exceeding 100,000 m³, the Administration responsible for security supervision will decide on a case-by-case 77 basis and, in relation to the characteristics of the dam, which rules are to be applied. It also requires that the 78 design and construction of the works and interventions covered by the standard must comply with the (at the 79 time) current Technical Standards for Construction (NTC2008), now updated. An important issue is that the 80 design procedure must be based on investigations and analysis of varying complexity in relation to the level 81 of detail required.

Section '*B. Classification and definition*' lists some definitions and presents a classification scheme used later in the document. Four main dams typology are listed, i.e., concrete dams, embankment dams, barrages and dams built with more than one materials.

85 The 'C. Common rules' section defines the external forces (dead load, hydrostatic pressure, temperature 86 effects, uplift pressure, ice thrust, silt effect) and, in particular, seismic forces. The safety of the dam should 87 be analyzed considering the following conditions: 1) normal operation, 2) repairable damage, without 88 uncontrolled release of water, 3) unrepairable damage, without uncontrolled release of water, 4) damage 89 resulting in the uncontrolled release of water, or risk of loss of human life, 5) collapse of the structure. The 90 Limit State of Immediate Operability is defined by the exit from condition 1), the Limit State of Damage is 91 defined by the transition from condition 2) to condition 3). The Limit State of Safeguard of Life is defined by 92 the achievement of condition 4) while the Limit State of Failure is defined by the achievement of the 93 condition 5). The first two are considered as Serviceability Limit States while the last two are Ultimate Limit

94 States

95 Three types are defined: '*Strategic*', the dams whose functionality during and following seismic events is 96 of fundamental importance for the purposes of civil protection; '*Relevant dams*' for the consequences of a 97 possible collapse (all large dams; dams classified in this way according to regional regulations); and '*Dams* 98 *of normal importance*', all dams not belonging to the previous types (i.e., small dams). According to this 99 classification, the reference return period for the seismic action is obtained, and, following the Italian seismic 100 hazard mapping, the corresponding actions (i.e., design spectra) to be used for design are defined.

101 This section also defines the combinations of the different forces, the partial safety factors and 102 combination coefficients that should be taken from the NTC2008 (or NTC2018). Some details are given 103 about the monitoring systems to be installed in the dam body and in the foundation (the projects must 104 include a general plan of the control devices).

105 Section 'D. Concrete dams' discusses dams made of concrete and rolled-compacted concrete, and 106 specifies in detail the different limit states and seismic models (pseudo-static and dynamic using spectrum-107 compatible accelerograms) to be carried out for safety analyses for gravity and vaulted dams. Several stress 108 limits for tension and compression for some Serviceability Limit States are listed. A short part is devoted to 109 vaulted dams. Section 'E. Embankment dams' states that the non-linear behavior and the interaction 110 phenomena between the different soil phases, as well as the sequence of construction and reservoir 111 operations, must be taken into account in the models and calculations. Particular attention must be paid to 112 the prediction of the settlements evolution, including both hydrodynamic phenomena and the phenomena 113 due to the structural viscosity of the solid skeleton of the soils, and to the evaluation of differential 114 settlements, to evaluate their admissibility during time. Section 'F. Barrages' proposes a classification and 115 some hints about the water flood to be used in the design procedure, while section 'G., Mixed dams', 116 describes dams built using mixed materials (as concrete and earth).

117 The last part, section '*H. Existing dams*', is devoted to dams with the structure already completed at the 118 time of the safety assessment or at the the time of interventions. An aspect of particular importance 119 concerns the existing dams that will have to be subjected to safety assessment of the entire structure or 120 parts of it, when the general conditions established by the NTC2008 (now replaced by the NTC2018) are 121 fulfilled. The criteria to define safety are defined together with the different possible interventions to obtain a 122 given level of safety. The following categories of intervention are identified: 1. *restructuring* interventions

(aimed at achieving the levels of safety and functionality envisaged by these regulations for new dams); *improvements* aimed at increasing the pre-existing safety, even without necessarily reaching the levels required for new constructions; *repairs* or local interventions affecting isolated elements and which, in any case, lead to an improvement of the pre-existing safety conditions; *downgrading*, with a reduction in the height of the dam and/or the reservoir volume); 2. *decommissioning* interventions to deprive the dam of the hydraulic function, but ensuring the safety of the site and of the downstream territories.

129 It is mandatory to proceed at least with seismic improvement interventions when the analyses carried out 130 to evaluate the seismic safety show the achievement of an Ultimate Limit State.

For concrete and masonry dams, the mechanical properties of the component materials and their variability within the dam body must be assessed by on-site and laboratory tests on samples taken from the dam body, reconstructing the actual situation; possible filtration phenomena in the foundation must also be identified. Any significant cracks present will be identified; the state of any reinforcements, joints and any sealing devices will also be investigated. It is recommended to experimentally evaluate the local stress level. For embankment dams, the same assessment of the actual condition must be evaluated and the filtration phenomena through the dam body and in the foundation must also be identified.

138 The seismic actions are defined in the same way for new dams but with the reference return period 139 reduced; for Strategic dams a dynamic analysis is required. An estimate of the maximum seismic action the 140 dam can withstand is also required.

141

142 2.2 Critical issues

143 This section examines the the major criticalities of DM2014. Some of them emerged during the activity of 144 the Monitoring Board that wrote a report on the results of the monitoring activity and a proposed update.

145 The NTC2008 in §4.1 write: "with the exception of those works for which there is a specific regulation of a 146 particular nature" and in §6.8 "the embankment dams materials are subject to specific legislation", 147 suggesting that the dams are excluded from these rules. This is perhaps the starting point of the critical 148 issues of the DM2014, which constantly refers to the technical standards of buildings from which, however, 149 the dams seem to be excluded. Eurocode 8 [3] itself writes "Special structures, such as nuclear power 150 plants, offshore structures and large dams, are excluded from the scope and scope of EN 1998.". This 151 provision disappears in the revision of the Eurocodes in progress, as it has now been clarified that the 152 Eurocodes can be used for the verification of any engineering work although it will be necessary to use

153 specially prepared supplementary standards for dams, as for other special works.

154 From the point of view of the application of the DM2014, in particular for existing dams, the main issues 155 concern the use of criteria and coefficients defined for ordinary civil works with partial safety coefficients and 156 combinations parameters with the values defined by the NTC2008 and not instead, as it should be (see the 157 aforementioned French guidelines) tailored ad hoc. These coefficients lead to inconsistencies in the design 158 and verification phase. The experience acquired with the application of the NTC2008 gave rise to the need 159 for its substantial revision, which led to the update of 2018. This update makes the application of the 160 DM2014 even more difficult, due to the explicit reference in the part A of a regulation (NTC2008) no longer 161 in force.

The adoption of the verification methodologies provided for civil works is therefore a cause of inconsistencies and uncertainties on the results. An example is the case of existing gravity dams, for which a prominent Italian dam manager produced in 2014 several comparisons between the dimensions of the dam obtained by applying the DM2014 and the previous DM1982. The study shows that not all load combinations and design approaches of DM2014 lead to acceptable results, as the current sizing may be less restrictive and therefore less safe than those obtained with the previous legislation in some conditions.

All this is more evident by the specific examination of DM2104: the substantial differences between the loads in dams and other constructions are neglected (for example the weight of the structures, which for dams assumes a stabilizing character) and great importance is given to the seismic aspect, which is considered more relevant than the hydrological/hydraulic aspect (while the greater vulnerability of dams with respect to hydraulic aspects is known, such as flood events). In fact, it should be noted that the NTCs follow an approach mainly oriented towards buildings, with particular attention to their behavior in seismic conditions.

175 Furthermore, some of the limit states are not easily distinguishable, for example, the Limit State of 176 Safeguard of Life and the Limit State of Failure, the classification of dams based on the intended use 177 (instead of, for example, the potential consequences of dam failure) is under discussion, the safety margin 178 on the resistance of the soil is expressed through identical partial coefficients for cohesion and the tangent 179 of the friction angle, an aspect that is not found in other regulations, while it would be appropriate to express 180 this margin on the overall resistance, without necessarily binding the standard to the use of a specific 181 criterion of collapse. The seismic combination at the Ultimate Limit State, for small seismic events, is less 182 critical than the fundamental combination at the maximum regulation level. An important novelty is the zero

183 tensile strength for some combinations at the Serviceability Limit State, acceptable for cracking control 184 purposes in reinforced concrete structures with relatively small geometric dimensions, but which leads to 185 excessive structural dimensions in the case of dams.

186 The standard also lacks indications on the structure (or *behaviour*) factor, an index of the ductility of the 187 structure, which is thus left to the arbitrariness of those who perform the analyses, although in the past, 188 other regulations suggested possible values to be adopted.

189 The main problematic aspects of DM2014 for gravity dams are, as already mentioned above, related to 190 the use of partial safety coefficients and combinations with the values set by the NTC2008 and the null 191 tensile strength of the material. This limitation leads to an oversizing of the structures with respect to 192 DM1982. Furthermore, the thermal load generally leads to incompatible tensile stresses with the condition of 193 null tensile stresses. It should be noted that the verification for thermal loads was not required by the 194 previous legislation, which increases the difficulty of these verifications for existing dams. Moreover, the 195 verification of the tangential stresses leads to unrealistic results due to the limits imposed on the reference 196 stress and the lack of stress limits in the presence of seismic loads should be corrected. The problem 197 concerning the absence of tensile stresses also concerns vaulted dams, where the stresses due to thermal 198 loads are of particular importance.

Few indications are given for embankment dams, however rather generic, just as generic information is given for rolled concrete and rockfill dams with concrete mantle, two types particularly used in recent years.

Finally, it is therefore clear that the procedure of analysis for dams cannot simply be taken up by the NTCs and Eurocodes and that it is necessary to address the issue of safety from a more systemic perspective in which, in addition to the limit states already envisaged for the dam, a series of other possible critical issues concerning the entire plant are considered, with the hydraulic works, the control and monitoring systems of the work and the upstream and downstream area of the basin, the mechanical devices whose functioning is the critical element for the general safety of the plant. The safety of the reservoir and the dam has to be understood as the safety of a unitary system.

208 3. POSSIBLE SOLUTIONS

The critical issues highlighted in the previous sections suggest difficulties in the application of the standard, especially in the case of static and seismic analysis of existing dams. However, it should be emphasized that the Italian dams have an average age of about 60 years so even the use of the DM1982 could lead to problematic situations for many plants.

213 To overcome these difficulties, while awaiting an update of the rules from the Monitoring Board, 214 reference can be made to a series of documents prepared by the various subjects operating in the field of 215 dam research. The Directorate General for dams of the Ministry of Infrastructures and Transport, 216 responsible for the approval of the safety analysis carried out by the dam owners/managers, has prepared 217 the 'Instructions for the application of the Technical Regulations' [4] which should allow designers to 218 overcome the most difficult aspects in the application of the DM2014. The instructions represent a 219 contribution to the definition of an evaluation procedure designed to avoid possible qualitative and/or 220 subjective evaluation (common for dams, where often an engineering judgment is required).

A similar publication concerns the ancillary works, which in order to consider the dam and ancillary works as a system, must be subjected to verification as well as the dam [5]. On the subject of ancillary works, the ITCOLD report [6] should also be mentioned. The National Institute of Geophysics and Volcanology published in 2017 a guide for the preparation of the seismotectonic study, prescribed to evaluate certain seismic loads [7].

Finally, it should be noted that documentation of particular interest for dams and ancillary works can be consulted on the websites of the International Commission On Large Dams (Bulletin and others) [8], of the Federal Guidelines for Dam Safety [9], of the US Army Corps of Engineers [10] and the US Bureau of Reclamation [11]. Many other countries (European and non-European) have their own legislation on dams that can certainly be useful to consult, together with those just mentioned, to fill the gaps in the Italian one on specific aspects.

232

233 4. CONCLUSIONS

The paper described the Italian current regulatory framework for dam, wit some hints on the engineering background that inspired the principles contained therein. The innovative issues and the critical aspects for the verifications were briefly presented in order to allow a conscious application of the standards. Some possible solutions of the most critical aspects suggested in this paper are from the activity of the Monitoring Board in the proposal of update of the DM2014. Among other aspects, an autonomous formulation with respect to the technical standards for constructions, although inspired by the same principles, is required.

240

241 **REFERENCES**

242 [1] Decreto del Ministero delle Infrastrutture e dei Trasporti. Norme tecniche per la progettazione e

- 243 la costruzione degli sbarramenti di ritenuta (dighe e traverse). 26/06/2014.
- 244 [2] Decreto del Ministero dei Lavori Pubblici. Norme tecniche per le costruzioni. 17/01/2018.
- [3] EN 1998, Design of structures for earthquake resistance, Brussels: Bsi., 2004.
- [4] Lanzi A., Paoliani P., Istruzioni per l'applicazione della Normativa Tecnica di cui al D.M. 26.06.2014
- 247 (*NTD14*) *e al D.M. 17.01.2018 (NTC18*), Divisione VI Strutture e Geotecnica, Ministero delle
 248 Infrastrutture e dei Trasporti, 2019.
- Ufficio strutture e geotecnica dell'Ufficio tecnico dighe di Napoli. Verifiche di sicurezza sismica
 degli scarichi e delle opere accessorie e complementari Riferimenti per l'istruttoria
 (04/04/2016).
- Zinetti F. (coordinator), *Opere idrauliche associate alle dighe*. Comitato Nazionale Italiano delle
 Grandi Dighe, 2012.
- 254 [7] Basili R., D'Amico V., Meletti C., Valensise G., *Linee-guida per la redazione e le istruttorie degli*255 *studi sismotettonici relativi alle grandi dighe*. Istituto Nazionale di Geofisica e Vulcanologia,
 256 27/09/2017.
- 257 [8] International Commission On Large Dams. Link: <u>https://www.icold-cigb.org/</u>
- 258 [9] Federal Guidelines for Dam Safety (FEMA). Link: <u>https://www.fema.gov/</u>
- 259 [10] U.S. Army Corps of Engineers (USACE). Link: https://www.usace.army.mil/
- 260 [11] U.S. Bureau of Reclamation (USBR). Link: https://www.usbr.gov
- 261

Addendum. The Italian regulations are published on the "*Gazzetta Ufficiale della Repubblica Italiana*" (https://www.gazzettaufficiale.it), the official source of the regulations in Italy. It is a necessary condition for an ordinary law to be published in the Gazzetta Ufficiale to come into force. For instance, the DM2014 is published on the Gazzetta Ufficiale n. 156 of 08/07/2014.