

## CONTENTS

<b>Introduction</b>		<b>7</b>
 <b>PART I – Outside engine design environment: market, vehicle, hybridization and components overview</b>		
<b>I-I</b>	From worldwide market to the engine	13
<b>I-II</b>	Propulsion system features to support hybridization	25
<b>I-III</b>	Main engine components	64
<b>I-IV</b>	From vehicle to propulsion system performance	92
<b>I-V</b>	Reference	103
 <b>PART II – Integrate engine design methodology</b>		
<b>II-I</b>	Target definition	114
<b>II-II</b>	Engine breath capacity and ports design	123
<b>II-III</b>	Engine performance baseline	131
<b>II-IV</b>	Effects of exhaust engine breath capacity on engine performance	160
<b>II-V</b>	Turbochargers screening and its effect on engine performance	163
<b>II-VI</b>	Crankshaft design & Peak Firing Pressure	176
<b>II-VII</b>	Cam profile & Engine performance	192
<b>II-VIII</b>	Reference	194

**PART III – Multi-body dynamics of valvetrain system and friction assessment for cam-roller follower valvetrain system subjected to non-Newtonian regime of lubrication**

<b>III-I</b>	Introduction to elasto-hydrodynamic lubrication	196
<b>III-II</b>	Valvetrain characterization	210
<b>III-III</b>	Valvetrain modeling	212
<b>III-IV</b>	Quasi-static model	212
<b>III-V</b>	Quasi-static model – Results and discussion	219
<b>III-VI</b>	Dynamic model	237
<b>III-VII</b>	Dynamic model – Results and discussion	241
<b>III-VIII</b>	Quasi-static and dynamic model – Results discussion and comparison	296
<b>III-IX</b>	Reference	302
<b>Conclusion</b>		<b>314</b>