POLITECNICO DI TORINO Repository ISTITUZIONALE

Orbital angular momentum modes from vertical-cavity surface-emitting lasers

Original

Orbital angular momentum modes from vertical-cavity surface-emitting lasers / Debernardi, Pierluigi; Tibaldi, Alberto; Orta, Renato; Boffi, Pierpaolo; Coviello, Domenico; Martelli, Paolo; Martinelli, Mario; Gerlach, Philipp. - In: SPIE NEWSROOM. - ISSN 1818-2259. - ELETTRONICO. - (2016). [10.1117/2.1201606.006513]

Availability: This version is available at: 11583/2645178 since: 2016-07-14T14:47:22Z

Publisher: SPIE

Published DOI:10.1117/2.1201606.006513

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Orbital angular momentum modes from vertical-cavity surface-emitting lasers

Pierluigi Debernardi, Alberto Tibaldi, Renato Orta, Pierpaolo Boffi, Domenico Coviello, Paolo Martelli, Mario Martinelli, and Philipp Gerlach

A computationally efficient theoretical approach is used to assess the performance of novel devices with directly emitting optical vortex modes.

With the increasing amount of information that travels in telecommunication systems, single-mode fiber-based infrastructures are no longer sufficient, and there is a continuous need to improve the transmission channel capacity. Among the approaches currently being explored, mode-division multiplexing is one of the most appealing. In this technique-because modes with different topological charge (ℓ) are orthogonal—an additional degree of freedom (i.e., the spatial dimension) can be added to the well-established time, wavelength, polarization, and coding parameters.^{1–4} Although this new dimension has already been successfully implemented in architectures that are based on digital signal processors (DSPs),^{1,2} the huge amount of data still leads to an extremely high power consumption. A passive, full-optical solution would therefore minimize DSP usage and the related power requirements, and would fit well within a 'green technology' paradigm.

Mastering the orbital angular momentum (OAM) of light is currently one of the most popular topics in the field of optics. Since the OAM of light was first described with simplified mathematical models of laser beams (Laguerre–Gaussian beams),⁶ several researchers have exploited the concept in a large variety of applications. These applications include optical manipulation,⁷ imaging,^{8,9} single-photon detection,¹⁰ and mode multiplexing/demultiplexing.^{11,12} Indeed, one of the most critical aspects of realizing a passive, full-optical approach for the enhancement of the telecommunication channel capacity is the generation of orbital angular momentum (OAM) light modes in optical fibers. Such modes are usually obtained from stan-



Figure 1. Schematic diagram of a vertical-cavity surface-emitting laser (VCSEL), loaded with spiral-phase plate (SPP), which can be used to generate an orbital angular momentum (OAM) beam. The sub-wavelength (SW) grating and axes are not shown to scale.⁵

dard laser beams with the use of a mode converter. Several conversion techniques—based on bulky optical components—have been extensively described in the literature, e.g., hologram-based techniques that exploit computer-programmed spatial light modulators,^{13, 14} as well as modal filters that are based on the use of spiral-phase plates (SPPs) and that impress the az-imuthal angular momentum onto the beam.¹⁵ Although these methods are well-established for bulk optics systems, light sources that directly emit OAM modes have yet to be realized and they would represent a major leap towards the implementation of fully integrated high-capacity networks.

Continued on next page



Newsroom

10.1117/2.1201606.006513 Page 2/4



Figure 2. Modal profiles of four VCSEL devices. (a) A bare device and three devices loaded with SPPs that have topological charge (ℓ) of (b) 1, (c) 2, and (d) 3. The maps in the top part of the figure show a 30 × 30 μ m² area, at a distance of 100 μ m from the outcoupling section. The images in the middle row are cross-sectional cuts—in the x (transverse coordinate) and z (longitudinal coordinate) directions—through the field intensity. The transverse geometries of the devices (with the SPPs in red) are shown at the bottom. Ox. aper.: Oxide aperture. E: Electric field. Ex: Component of the electric field in the x-direction. Re(Ex): Real part of Ex.⁵



Figure 3. (Left) Far-field (E_x) intensity and (right) phase maps of (top) an ideal Laguerre-Gaussian mode and (bottom) the mode emitted by the $\ell = 1$ SPP-VCSEL. revs: Revolutions.⁵

In our work we have conducted a parametric investigation of the modal performance of single-mode single-polarization vertical-cavity surface-emitting lasers (VCSELs) that are loaded with a micro-SPP. Our theoretical work, for which we used our in-house VCSEL electromagnetic (VELM) simulator,¹⁶ was designed to complement previous experimental work (by another group) in which the commercial VCSEL loaded with a micro-SPP was proposed (see Figure 1).¹⁷ VCSELs are axisymmetric semiconductor lasers that radiate orthogonally to its constituent layers. These layers serve as high-reflectivity mirrors and define the 1λ cavity (where λ is the wavelength) of the VCSEL resonator.¹⁸ In addition, the circular radiation feature of VCSELs makes them optimal for fiber coupling. In aluminum gallium arsenide VC-SELs, an oxide aperture acts as a guide for the optical field and the electric current. This feature, combined with the high reflectivity of the mirrors, means that low threshold currents (at the milliamp level) and high efficiencies can be achieved. Furthermore, the radiation from these devices is emitted at a wavelength of about 850nm, i.e., where the electrically pumped gallium arsenide quantum wells that compose the active region exhibit the maximum material gain.

Newsroom

10.1117/2.1201606.006513 Page 3/4



Figure 4. The effect of misalignment (the distance between the SPP and VCSEL axes) on $\ell = 1$ SPP-VCSEL mode. Far-field intensity maps are shown on the left, where the misalignment (Mis) and mode purity (Pur) are given in nm. (Right) The relationship between mode purity and misalignment.⁵

The experimentally produced SPP-VCSEL was obtained by growing a pillar of silicon nitride on the emitting aperture, and a focused ion beam manufacturing process was used to obtain the SPP.¹⁷ In the experimental study, it was also shown that the device could directly emit OAM modes. This SPP-VCSEL device is thus an extremely interesting prospect, in terms of its compactness, low power consumption, and low cost.

Our theoretical work is based on expanding the unknown VCSEL field, in terms of cylindrical wave functions. In our approach, the expansion coefficients are propagated by means of a generalized transmission matrix formalism, which is based on coupled-mode theory. The condition of a mode repeating itself after a full-cavity roundtrip is rephrased in terms of an eigenproblem. Its solutions provide the modal wavelengths, the corresponding threshold gains, and field topographies. Our technique is computationally efficient and finds the modes of complex 3D structures (not axisymmetric) within a few minutes on a modern PC.^{19,20} As an example, the simulated field profiles for an unprocessed VCSEL and for three micro-SPP geometries (used to obtain OAM beams with different topological charges) are shown in Figure 2.

We present the results of a preliminary, qualitative comparison between the modes of the the SPP-VCSEL device (ℓ of 1) and their ideal (i.e., Laguerre-Gaussian) counterparts in Figure 3. From our VELM results it is also possible to compute a more quantitative estimate of the OAM mode's purity and to thus evaluate the modal performance of the device.⁵ The simulated mode purities agree with the measured values previously reported.¹⁷ For instance, we obtain results of 85%, 86%, and 78% for the fields in Figure 2(b), (c), and (d). These results compare well with the experimental data for the corresponding fields, i.e., 89%, 84%, and 78%, respectively. In an extended simulation campaign, we proved the robustness of the SPP-VCSEL design for most variations. We found only one exception, which was the SPP misalignment with respect to the VCSEL axis. From our results shown in Figure 4, a degradation of the far-field patterns can be observed. In addition, the decreasing efficiency trend, with increasing misalignment, is illustrated.

In summary, we have developed a theoretical approach to assess the modal performance of VCSELs. In particular, we have used our computationally efficient technique to verify a previously experimentally proposed device that is loaded with a spiral-phase plate. The effectiveness, speed, and reliability of our VELM simulator also opens up the possibility of exploring other implementations of SPP-VCSELs. In our future work, supported by technological affordability studies, we hope to further develop these devices, improve the purity of the emitted OAM modes, and reduce the manufacturing costs associated with the VCSELs.

Author Information

Pierluigi Debernardi and Alberto Tibaldi

Institute of Electronics, Computer and Telecommunication Engineering (IEIIT), CNR Turin, Italy

Renato Orta

Department of Electronics and Telecommunications Polytechnic University of Turin Turin, Italy

Pierpaolo Boffi, Domenico Coviello, Paolo Martelli, and **Mario Martinelli**

Department of Electronics, Information and Bioengineering Polytechnic University of Milan Milan, Italy

Philipp Gerlach

Philips Photonics Philips GmbH Ulm, Germany



References

1. P. J. Winzer, Spatial multiplexing in fiber optics: the 10× scaling of metro/core capabilities, Bell Labs Tech. J. 19, pp. 22–30, 2014.

2. R. Ryf, S. Randel, A. H. Gnauck, C. Bolle, A. Sierra, S. Mumtaz, M. Esmaeelpour, et al., Mode-division multiplexing over 96km of few-mode fiber using coherent 6 × 6 MIMO processing, J. Lightwave Technol. 30, pp. 521–531, 2012.

3. N. Bozinovic, Y. Yue, Y. Ren, M. Tur, P. Kristensen, H. Huang, A. E. Willner, and S. Ramachandran, *Terabit-scale orbital angular momentum mode division multiplexing in fibers*, Science 340, pp. 1545–1548, 2013.

4. D. Richardson, J. M. Fini, and L. E. Nelson, *Space-division multiplexing in optical fibres*, **Nat. Photon. 7**, pp. 354–362, 2013.

5. P. Debernardi, A. Tibaldi, P. Gerlach, P. Martelli, P. Boffi, M. Martinelli, D. Coviello, and R. Orta, *Modal performance of spiral phase plate VCSELs*, **IEEE J. Quant. Electron. 52**, p. 2400108, 2016. doi:10.1109/JQE.2016.2548428

6. L. Allen, M. W. Beijersbergen, R. J. C. Spreeuw, and J. P. Woerdman, *Orbital angular momentum of light and the transformation of Laguerre-Gaussian laser modes*, Phys. Rev. A 45, pp. 8185–8190, 1992.

7. H. He, M. E. J. Friese, N. R. Heckenberg, and H. Rubinsztein-Dunlop, *Direct* observation of transfer of angular momentum to absorptive particles from a laser beam with a phase singularity, **Phys. Rev. Lett. 75**, pp. 826–831, 1995.

8. G. A. Swartzlander, E. L. Ford, R. S. Abdul-Malik, L. M. Close, M. A. Peters, D. M. Palacios, and D. W. Wilson, *Astronomical demonstration of an optical vortex coronagraph*, **Opt. Express 16**, pp. 10200–10207, 2008.

9. S. Fürhapter, A. Jesacher, S. Bernet, and M. Ritsch-Marte, *Spiral interferometry*, **Opt. Lett. 30**, pp. 1953–1955, 2005.

10. J. Leach, M. J. Padgett, S. M. Barnett, S. Franke-Arnold, and J. Courtial, *Measuring the orbital angular momentum of a single photon*, **Phys. Rev. Lett. 88**, p. 257901, 2002. doi:10.1103/PhysRevLett.88.257901

11. P. Boffi, P. Martelli, A. Gatto, and M. Martinelli, *Mode-division multiplexing in fibre-optic communications based on orbital angular momentum*, J. Optics 15, p. 075403, 2013. doi:10.1088/2040-8978/15/7/075403

12. P. Martelli, P. Boffi, A. Fasiello, and M. Martinelli, *Interferometric orbital angular momentum mode multiplexer/demultiplexer based on pairs of cylindrical lenses*, **Electron.** Lett. 51, pp. 278–280, 2015.

13. V. Y. Bazhenov, M. S. Soskin, and M. V. Vasnetsov, Screw dislocations in light wavefronts, J. Modern Opt. 39, pp. 985–990, 1992.

14. J. E. Curtis, B. A. Koss, and D. G. Grier, *Dynamic holgraphic optical tweezers*, **Opt.** Commun. 207, pp. 169–175, 2002.

15. T. Watanabe, M. Fujii, Y. Watanabe, N. Toyama, and Y. Iketaki, *Generation of a doughnut-shaped beam using a spiral phase plate*, **Rev. Sci. Instrum. 75**, pp. 5131–5135, 2004.

16. P. Debernardi and G. P. Bava, *Coupled mode theory: a powerful tool for analyzing complex VCSELs and designing advanced device features*, **IEEE J. Sel. Topics Quant. Electron. 9**, pp. 905–917, 2003.

17. H. Li, D. B. Phillips, X. Wang, Y.-L. D. Ho, L. Chen, X. Zhou, J. Zhu, S. Yu, and X. Cai, *Orbital angular momentum vertical-cavity surface-emitting lasers*, **Optica 2**, pp. 547–552, 2015.

18. R. Michalzik ed., VCSELs: Fundamentals, Technology and Applications of Vertical-Cavity Surface-Emitting Lasers, p. 560, Springer, 2013.

 P. Debernardi, B. Kogel, K. Zogal, P. Meissner, M. Maute, M. Ortsiefer, G. Bohm, and M.-C. Amann, Modal properties of long-wavelength tunable MEMS-VCSELs with curved mirrors: comparison of experiment and modeling, IEEE J. Quant. Electron. 44, pp. 391–399, 2008.

 P. Debernardi, R. Orta, T. Gr, and M. C. Amann, 3-D vectorial optical model for high-contrast grating vertical-cavity surface-emitting lasers, IEEE J. Quant. Electron. 49, pp. 137–145, 2013.