National energy security assessment in a geopolitical perspective

Original

National energy security assessment in a geopolitical perspective / Bompard, ETTORE FRANCESCO; Carpignano, Andrea; Erriquez, M.; Grosso, Daniele; Pession, M.; Profumo, Francesco. - In: ENERGY. - ISSN 0360-5442. - 130:(2017), pp. 144-154. [10.1016/j.energy.2017.04.108]

Availability:

This version is available at: 11583/2670307 since: 2017-05-04T18:24:10Z

Publisher:

Elsevier

Published

DOI:10.1016/j.energy.2017.04.108

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

NATIONAL ENERGY SECURITY ASSESSMENT IN A GEOPOLITICAL PERSPECTIVE

E. Bompard^(), A. Carpignano^(*), M. Erriquez^(**), D. Grosso^(*), M. Pession^(*), F. Profumo^(*)*

Abstract

The possibility of ensuring the energy needed by a country is a fundamental requirement for the economic growth and social welfare of that country. The fulfillment of this need is particularly challenging for those countries that are characterized by a low level of energy self-sufficiency. The evaluation of energy security needs to consider different dimensions and is of the utmost importance as a benchmark to conceive and implement different policies. The assessment of the level of security should rely on science-based models that are able to track the rapidly evolving geopolitical scenarios, and to provide detailed information and quantitative indexes to policy decision makers. In this paper, an overarching methodology is outlined to evaluate energy security, in which its external and internal dimensions are considered and integrated: the security of the energy supply from abroad (external) and the security of national energy infrastructures (internal). Attention is then focused on the external dimension, and two indexes are defined, by means of a probabilistic approach, in terms of the expected value of supply and economic impacts. The methodology is then applied to the Italian case, considering different geopolitical scenarios, and conclusions are provided about the energy security of the country.

^(*) POLITECNICO DI TORINO, Dipartimento Energia, ettore.bompard@polito.it

^(**): Consultant and former officer of the Arma dei Carabinieri, m.m.erriquez@gmail.com

1. INTRODUCTION

Energy security is a crucial issue for each and every country. It may be defined as the capability of ensuring the availability of different typologies of energy for the final uses, in the needed quantity, where requested, over short, mid and long time horizons. It is necessary to ensure access to the commodity sources, their transportation (using suitable corridors) to the country, the possible transformation into secondary commodities and its distribution inside the country itself, by means of appropriate infrastructures.

It should be underlined that – in general terms – the energy security of a country depends not only on the possibility of obtaining the needed amount of energy commodities by means of local production or by importing from abroad (supply side), but also on the flexibility in the end-use demand (demand side).

In countries characterised by a low self-sufficiency, such as Italy (24.1% in 2014), the security issues related to the acquisition of energy commodities, depending on geopolitical scenarios, is particularly critical. At the EU28 level, the energy self-sufficiency is about 46.5%. At the same time, the security of the internal transport/distribution of energy, related to the National infrastructures, is also relevant.

Thus, the evaluation of the level of energy risk, at a given point in time, and its evolution over a short time horizon, by means of science-based approaches, are crucial to define and improve defence and mitigation countermeasures. Instead, in the mid-long term, the analysis of the risk related to possible alternative scenarios allows strategic planning to be made in terms of new sources and new intra-national and infra-national infrastructures.

For these reasons, a methodological approach is proposed in this paper to assess, in a comprehensive way, the security of a country, through a quantification of the energy security, which is able to capture supply risks and provide the basis of a cost-benefit analysis.

The methodological contribution of this work is represented by the adaptation of the classical risk analysis approach, used in studies of industrial technologies and plants, to the analysis of the security of energy supply in a geopolitical perspective, and by the coupling of this new approach with a detailed characterisation of the energy corridors, which, in this way, makes it possible to take into account their spatial dimension and to embed it in the mathematical relationships defined to evaluate the risk parameter.

The risk indexes related to the single corridors and the overall national supply risk (both physical – in terms of energy losses – and economic) can thus be used to help support decision makers in assessing and ranking the criticalities of the energy system and in performing comparative scenario analyses of different strategic options that involve energy imports and infrastructures.

The relevance of the proposed approach, which links technical, geopolitical and economic considerations, lies in the fact that the energy supply of a country is affected by several aspects (economy, geopolitical relationships and security) that interact with each other and which need to be investigated in an integrated perspective. In particular, on one hand, the geopolitical situation can have a significant influence on the energy commodity costs, thus having an impact on the economy, and on the other can determine the country's level of energy supply security and have effects on the supply availability, which – in turn – again affects the economy.

The developed methodology is here illustrated with reference to the Italian situation.

The paper is structured as follows. The state of the art, related to the geopolitical risk indicators, is summarised in sec.2; the adopted methodological approach is described in sec.3; the results of an application to a case study, related to the energy supply to Italy, is presented in sec 4.

2. LITERATURE REVIEW OF ENERGY SECURITY INDICATORS

Over the last decade, the evaluation of the security and affordability of the energy supply has played an increasing role, and has been one of the main issues for policy makers, especially in high energy import dependent countries, like many of the European Union Member States, including Italy.

Several approaches have been proposed to quantify the level of security of supply to a country, most of which are based on the definition of numerical risk parameters that are able to take into account geopolitical aspects and/or country-dependent energy indicators. Krut et al. [1] performed a classification of some of the main energy indexes by distinguishing between ten simple indicators (including import dependency, reserve-to-production ratio and energy prices) and five aggregated indexes (i.e. the Oil Vulnerability Index (OVI), the Willingness to Pay Index, the IEA Energy Security Index (ESI), the Supply-Demand Index and the Shannon Index).

Referring to these five indexes, Gupta [2] evaluated an overall oil vulnerability index (OVI) that depends on the combination of seven indicators, related to oil supply and consumption and to the economic level of the receiving country (GDP per capita, oil import dependency, oil consumption per GDP unit). Bollen [3] based his study on a cost-benefit analysis, and this led to the definition of a “Willingness to Pay” function that measures the percentage of GDP that the analysed country is willing to pay in order to decrease its risk. IEA ESI [4] evaluated the effects of the supply market concentration on energy commodity prices, taking into account the geopolitical risk rating of the supply countries. Scheepers et al. [5,6] analysed the Supply-Demand Index, defined on the basis of experts' judgement by means of scoring rules, and focused on the whole energy chain (including conversion, transport, supply and demand of energy in the mid-long term). The Shannon-Wiennier Index (SWI) [7], which quantifies diversification by taking into account the share of each commodity in the fuel mix composition, is also used to evaluate energy security. Martchamadol et al. [8] performed an analysis of the state of the art, in which several indicators were taken into

81 account. Among these indicators, the following can be mentioned: the WEC Assessment Index (AI) [9], which
 82 evaluates energy security by means of five indicators (including net energy imports and diversification of the energy
 83 supply); the WEC Energy Sustainability Country Index (ESCI) [10], which is based on 22 indicators, including oil
 84 reserves, stock and energy security; the APERC study [11], which considers five indicators (such as the net import
 85 dependency, the net oil import dependency and the oil import dependency from Middle Eastern countries); the
 86 UNDESA Energy Indicators for Sustainable Development [12]; the Global Network on Energy for Sustainable
 87 Development (GNESD) indicator [13]. They also developed a new composite index, the Aggregated Energy Security
 88 Performance Indicator (AESPI) [8], which ranges between 0 (low security) and 10 (high security), and which is built
 89 using 25 indicators. These indicators are evaluated on the basis of the historical data series of the population, the GDP,
 90 the energy production, the net import and consumption, the power generation capacity, the transformation and
 91 transmission losses, and the coal, crude oil and natural gas emission factor values.
 92 Most of the energy risk indicators are assumed steady over time. Apart from the above mentioned AESPI index, only a
 93 few other indexes, such as the Supply-Demand Index defined by Scheepers et al. and the Composite Indicator
 94 developed by Badea et al. [14], have taken into consideration a forecasted time evolution. These indicators were both
 95 based on energy projections from the PRIMES model, and are used by the European Commission to evaluate the EU
 96 Trends up to 2030 [15]. The study by Checchi et al. [16] also focused on the long-term evaluation of the security of
 97 energy supply, referring to the results of the PRIMES model, but it did not set any index to quantify this evaluation.
 98 Among the indicators based on time series analyses, the International Index of Energy Security Risk (IIESR), set up by
 99 the U.S. Chamber of Commerce Institute for 21st Century Energy [17], allows the security level of 25 large consuming
 100 countries throughout the world to be compared on a yearly basis. This approach refers to the identification of eight
 101 index categories (including reserves and the production of oil, natural gas and coal, and energy imports). A set of 29
 102 metrics was defined for each of these categories. The 1980-2012 time horizon was taken into account for all of the
 103 metrics; moreover, each of these metrics was normalised with reference to the 1980 OECD value. The normalised
 104 metrics were then weighted, using the International Weightings Index, which gives the percentage contribution of each
 105 category to the total, in order to calculate the overall IIESR value. Sovacool [18] defined an indicator for the evaluation
 106 of the energy security of a country, referring to the European Union, the United States, China, India, Japan, South
 107 Korea, Australia, New Zealand and ten countries belonging to the Association of Southeast Asian Nations (ASEAN).
 108 For this purpose, five fundamental dimensions of energy security were identified (availability, reliability, technological
 109 development, sustainability and regulations). In turn, these dimensions were subdivided into 20 components, each of
 110 which was related to a metric. Frondel et al. [19,20,21] proposed and implemented a methodology aimed at classifying
 111 countries (in particular those belonging to the G7) on the basis of the risk level related to the primary energy commodity
 112 supply in the mid-long term; the authors defined, for each commodity, a risk indicator expressed as a function of the
 113 probability of commodity flow disruption for the various exporting countries, and of the square value of the percentage
 114 contribution given by each exporting country and by the local production to the energy demand fulfilment in the
 115 analysed country. In turn, the supply unavailability for a certain country was evaluated on the basis of considerations
 116 associated with the geopolitical situation and economic stability, while the share values for the exporting countries were
 117 correlated to the Herfindahl index [22], which measures the import concentration for a specific commodity.
 118 Guivarch et al. [23] analysed the possible evolution of energy security in Europe from a decarbonisation perspective, by
 119 taking into account the time evolution of a set of indicators (based on the concepts of resilience, robustness and
 120 sovereignty) in the case of different scenarios. A study focusing on the impacts of alternative climate mitigation policy
 121 scenarios on South Korea, Japan and China was instead performed by Matsumoto et al. [24] by means of a computable
 122 general equilibrium model.
 123 Valdés Lucas et al. [25] explored, over a long-term time horizon, the correlation between the deployment of renewables
 124 and energy security, considering several indicators related to three energy policy dimensions: competitiveness, security
 125 of supply and environment.
 126 Biresselioglu et al. [26] considered natural gas supply security and the evolution of different indicators (including the
 127 number of supply countries, the total volume of gas imported and the fragility of supply countries over the 2001-2013
 128 period in order to build a Supply Security Index (SSI) through an application of the Principal Component Analysis
 129 (PCA) technique. Another study – carried out by Flouri et al. [27] – focused on natural gas, and was devoted to
 130 exploring, using a Monte Carlo simulation approach, how a disruption in the natural gas supply from Algeria, for
 131 geopolitical reasons, could affect the natural gas supply security of the EU: this analysis in particular highlighted the
 132 relevant role played by the diversification of suppliers in increasing energy security.
 133 Kisel et al. [28] described the different methods and indicators that are adopted to assess energy security and to
 134 delineate energy policies, and they proposed an Energy Security Matrix that is able to organise the most significant
 135 indicators in a structured way from the point of view of operational and technical resilience, technical vulnerability,
 136 economic dependence and political affectability in different sectors.
 137 Among the other studies that have focused on the relevance of the geopolitical element in the evaluation of the risk
 138 related to the energy supply, those carried out by Correlje and van der Linde [29], Costantini et al. [30], Hedenus [31]
 139 and Umbach [32] can be mentioned. The FP-7 European project “Risk of Energy Availability: Common Corridors for
 140 Europe Supply Security” (REACCESS) [33] developed tools that can be used to conduct a quantitative assessment of
 141 the geopolitical risk for scenario analyses. In this project – characterized by the link between three forecasting TIMES-
 142 based [34] optimisation energy models – a risk index (steady over time and ranging between 0 and 100) was defined for

all the commodity source countries and for all the countries crossed by the above mentioned corridors. This index is a function of the socio-political, energetic, political-institutional and economic security level of the country, and it was calculated by means of factor analysis techniques (Marín-Quemada et al. [35,36,37]). During the follow-up phase of the project, these indexes were combined, through an application of the reliability theory, in order to define a single risk index for each corridor; for this purpose, the risk index related to each crossed country was assumed as the probability that a corridor crossing that country would fail (Gerboni et al. [38]). Furthermore, starting from the same risk indexes per country, Doukas et al. [39] developed a web-based tool for the analysis of the natural gas and oil corridors, and they tested it by means of a case study focused on the Greek energy supply. Using the same approach (based on the factor analysis), Muñoz et al. [40] defined the country composite indicator GESRI (Geopolitical Energy Supply Risk Index), which – unlike the one proposed by Marín-Quemada et al. – combines the social and political dimensions in a single risk vector and introduces a new vector that describes the relations between the exporting and transit countries with the EU-27. Finally, in the framework of the REACCESS project, Carpignano et al. [41] proposed a methodological approach to evaluate the technological risk and the loss of production caused by corridor failures, and included these parameters among those used to analyse optimal scenarios for the EU energy supply.

3. INDICATORS FOR NATIONAL ENERGY SECURITY ASSESSMENT

The overall energy security of a country depends on two different “fronts”. The first is “internal” and is related to: a) the quantification of the highest or lowest availability of national resources for each considered primary energy commodity (natural gas, oil, coal); b) resilience to possible internal attacks against the infrastructures (distribution networks) or transformation plants (refineries, regasification terminals, etc.).

The second is “external” and includes: a) the geopolitical security of the commodity source country; b) the security of the infrastructures up to the national entry point, taking into consideration the route of the energy corridors (open sea or captive) and the risk indexes associated with each crossed country; c) the possible effects on imports due to the unavailability (at different temporal scales) of the above mentioned infrastructures.

A security index can be conceived for each of these “fronts”, and the combination of the two provides the overall assessment of the national security of the Country.

The nomenclature of the main indexes and parameters is given in Table 2. Generally speaking, the internal risk can be expressed as a function of the resilience of the transmission/distribution infrastructure:

$$R_{int} = f(\vartheta_{c,d})$$

Assuming $\vartheta_{c,d}$ as the Resilience index, which is used to quantify the resilience of the internal distribution/transmission network d_d for commodity c_c . This index has been disregarded in this paper and attention has been focused on the external one.

The proposed index for the external risk is a weighted function of the contribution given by the risk indexes associated with the source and crossed countries, and of the energy content of the commodity imported through each corridor.

An index $\varphi_k \in [0,100]$, which is mainly related to the geopolitical situation, has been associated to each country to quantify the criticality of that country; this index is estimated as described in sec. 2 and can continuously be tracked and updated over time.

A corridor i is defined as:

$$\forall i_i \in \mathcal{J} : i_i = \{c_c, l_i, \mathcal{K}_i\} \mid c \neq i,$$

corridor $i_i \in \mathcal{J}$ is defined by a length $l_i \in \mathcal{L}$, a commodity $c_i \in \mathcal{C}_i$, a set of crossed countries $\mathcal{K}^i$ with $k_i \in \mathcal{K}^i$, the country of origin, $\dim(\mathcal{K}^i) = K_i$ the number of countries crossed.

A risk index ξ'_i is defined for each corridor i_i and its probability of failure is identified [38]:

$$\xi'_i = 100 \cdot \left[1 - \prod_{k_i \in \mathcal{K}_i} \left(1 - \frac{\varphi_k}{100} \right) \right] \quad (1)$$

In (1):

$\left(1 - \frac{\varphi_k}{100} \right)$ is the probability of success of crossing country k ,

$\prod_{k_i \in \mathcal{K}_i} \left(1 - \frac{\varphi_k}{100} \right)$ is the probability (of independent events) of success of crossing all the countries involved along the corridor route,

$1 - \prod_{k_i \in \mathcal{K}_i} \left(1 - \frac{\varphi_k}{100} \right)$ is the probability of failure for the entire corridor, and it is expressed as the complement of the probability of success.

Corridors are composed of different branches in different countries; each segment has a different length; a “spatial dimension” in the exposure to risk is assumed, in the sense that, given a φ_k index for a country, its contribution to the overall risk of the corridor would be proportional to the length of the segment of the corridor in that country. The total length l_i of corridor i is given by the sum of the length of the branches of the corridor in the crossed countries:

$$l_i = \|B^i\|_1$$

An empirical weighting function γ_k is introduced into (1) in order to incorporate this aspect:

$$\xi_i = 100 \cdot \left[1 - \prod_{k_i \in \mathcal{K}_i} \left(1 - \frac{\gamma_k \cdot \varphi_k}{100} \right) \right] \quad (2)$$

The assumed values of γ_k are reported in Tab. 1 as a function of the ratio between the real length of the corridor branch, b_b , and the average length of the corridor branches $\bar{b}_i$ (3).

$$\bar{b}_i = \frac{l_i}{K_i} \quad (3)$$

Open sea routes and submarine pipelines, territorial waters and international waters are all involved in the risk assessment of the corridor. In order to avoid an underestimation of the risk related to maritime routes, in comparison to the one related to terrestrial corridors, a zone of influence is defined for each country, and a portion of the international waters is also covered, to which the same index φ_k as the country is provided.

The risk, R_i , associated to corridor i , is defined as the product between the probability of failure ξ_i and the damage, in terms of loss of energy $E_{c,i}$, associated to a commodity c_c :

$$R_i = \sum_{c_i \in \mathcal{C}_i} \frac{\xi_i}{100} \cdot E_{c,i} \quad (4)$$

The overall external risk, for all the corridors supplying the given country, is:

$$R_{ext} = \sum_{i_i \in \mathcal{I}} R_i \quad (5)$$

As far as time granularity is concerned, the analyses can be carried out considering different time scales (year, quarter, months,...). A higher time discretization, such as a monthly analysis, would allow specific criticalities, such as those related to the natural gas supply during winter months, to be highlighted.

The risk in (5) can be converted into equivalent monetary units through the national *energy intensity of the economy* Q (TJ/G€), which is defined as the ratio between the gross internal energy consumption (TJ) and the Gross Domestic Product (GDP, G€):

$$R_{int,m} = \frac{R_{int}}{Q} \quad (6)$$

$$R_{ext,m} = \frac{R_{ext}}{Q} \quad (7)$$

This conversion is useful to evaluate the economic impact of the geopolitical energy risk, because a possible loss of energy, due to the unavailability of an energy supply, causes a loss of GDP [42].

The sum of the two indicators, weighted using two coefficients, w_1 and w_2 , allows the *National Energy Security Index* R_n to be defined (Fig.1):

$$R_n = w_1 \cdot R_{int} + w_2 \cdot R_{ext} \quad (8)$$

where w_1 and w_2 are defined on the basis of the percentage import dependency χ :

$$w_1 = 1 - \chi \quad (9)$$

$$w_2 = \chi \quad (10)$$

The above described methodology is able to highlight any possible criticalities related to the fulfilment of the national requirement in the case of geopolitical issues that affect the supply and/or the transport/distribution of energy to end-users.

Focusing on the external dimension of security, it is possible to define the “expected supply”. The probability of success (availability) of each corridor is:

$$\omega_i = 100 \cdot \left[\prod_{k_i \in \mathcal{K}_i} \left(1 - \frac{\gamma_k \cdot \varphi_k}{100} \right) \right] \quad (11)$$

The expected supply value S_i for corridor i_i is the product of ω_i and the energy flow $E_{c,i}$ of the commodity c_c carried by the corridor:

$$S_i = \sum_{c_i \in \mathcal{C}_i} \frac{\omega_i}{100} \cdot E_{c,i} \quad (12)$$

The total expected supply S_{ext} (TJ) can be evaluated as:

$$S_{ext} = \sum_{i_i \in \mathcal{I}} S_i \quad (13)$$

The expected supply corresponds to the difference between the total supply, in energy terms E , and the overall external risk R_{ext} :

$$S_{ext} = E - R_{ext} \quad (14)$$

The adopted approach assumes that the events are independent, and offers a conservative overestimation of the risk.

Finally, it should be highlighted that the error analysis in the proposed modelling approach on the main parameters (such as energy flows, or corridor branch lengths) is not particularly relevant in comparison with the need to understand whether a certain event could happen or not. The aim of the adopted procedure is to associate a certain probability value to the single countries, which is able to describe the likelihood that a certain supply corridor crossing them fails due to geopolitical reasons, and is not to perform forecasting analyses on unpredictable events. Naturally, disruptive geopolitical events can suddenly occur, and these could significantly modify the probability value of the countries. For this reason, sensitivity analyses on the country risk index parameter are useful to evaluate the effects of such events on the global energy risk. Furthermore, when defining sensitivity scenarios, it could be appropriate to consider that a geopolitical event in a certain country can also affect other countries in the same geographical area, and as a result in some cases the geopolitical risk level should be considered jointly, and in the same way modified for the whole set of countries belonging to the same area. This could be particularly relevant for zones like the Middle-East and North-Africa (some examples are those of the so-called “Arab Spring” and the penetration of terroristic groups in these areas).

4. CASE STUDY: THE EXTERNAL SUPPLY TO ITALY

4.1 Definition of the scenarios

The proposed methodology has been applied to the security analysis of the Italian national energy supply. The contribution to the risk given by the internal component R_{int} has been neglected, and the analysis has only focused on the evaluation of the R_{ext} parameter.

A total of 263 corridors (pipelines, ships, railways, roads, power lines), carrying 6 commodities (coal, crude oil, refined petroleum products, natural gas, LNG, electricity) and accounting for 97.5% of the Italian energy inflows in 2014 have been considered [43,44]. Country risk indexes have been assumed on the basis of the FP-7 REACCESS ([35], [36], [37], [38]) project (Fig. 2, Tab. 3).

Italian energy security has been assessed against five possible adverse scenarios. The scenarios are characterized by two different types of situation; in the first, the criticality of the country is increased due to a deterioration of the geopolitical situation in the area (modelled by an increase in the geopolitical country index), while in the second the situation, the country causes actions that provide the actual failure of a corridor.

Five scenarios (S1-S5) have been taken into account (Tab. 4):

- S1) Increased activity of terroristic groups in North Africa (Algeria, Egypt, Libya and Tunisia);
- S2) Deterioration of the Italian/Qatari diplomatic relations, with cuts in gas/oil exports to Italy;
- S3) Antagonistic actions in Libya with disruption of the Greenstream gas pipeline;

291 S4) Increase in the contrast between Russia and the Ukraine, with a country risk increase and disruption of the NG and
292 oil corridors from Russia across the Ukraine;
293 S5) The simultaneous occurrence of S1 and S4.

294 295 **4.2 Energy security analysis for different scenarios**

296 The impact of the considered scenarios has been assessed, considering the energy risk R_{ee} and economic risk R_{em} values
297 (Tab. 5) and they have been compared with the values related to the year 2014 (Reference situation, *REF*:
298 corresponding to the actual configuration of flows, corridors and suppliers) with the Country indexes reported in Tab. 3.
299 In Tab. 6, the indexes have been computed considering only the natural gas supply, which accounts for 33% of the
300 Italian energy inflows in 2014.

301
302 S1 shows an increase, of about 3%, in both R_{ee} and R_{em} , mostly due to the large number of corridors (79, 30% of the
303 total) that are affected by the increase in geopolitical risk in the four countries; their average risk index for corridor ξ
304 increases by 17.6%, in comparison with the Reference, while the overall value of ξ increases by 5.4%.

305 In Tab. 7, the analysis is undertaken on a monthly time basis; both risk indexes, in this case, have a peak increase in
306 September, due to an increase in the flow exported by the countries involved in S1, in comparison with the one exported
307 by countries that do not undergo changes. An increase in the risk can be observed for S1 but, due to the absence of
308 actual disruptions, the inflows are still there.

309
310 S2 shows a criticality related to the LNG supply (the LNG supply from Qatar in 2014 was equal to 172.8 PJ/y). By
311 setting the corridor risk to 100% (i.e. full unavailability and expected supply = 0) for all the Qatari corridors, the overall
312 risk increases by 2.46%; this variation is due to the natural gas corridors (whose contribution to the total risk increases
313 by 5.79%, in comparison with the reference case).

314
315 S3 shows an increase of 3.52% in the overall risk caused by the disruption of the Greenstream NG corridor ($\xi = 100\%$).
316 This unavailability has a relevant effect on the NG risk, which increases by 8.27%. Furthermore, the amount of energy
317 lost in the case of a disruption of the Greenstream pipeline cannot be replaced by the same amount imported as LNG
318 from the same supplier, because the only Libyan LNG terminal (i.e. the one located in Marsa al-Brega) is presently out
319 of service and has been since 2011, as it was damaged during the civil war.

320
321 S4 involves the whole Italian natural gas import from Russia (corresponding to 48.82% of the total natural gas import)
322 and 3% of the crude oil import (one corridor). This situation has a particular impact on the overall risk, as it causes an
323 increase of 8.68% (which reaches 16.33% for the risk contribution only related to the natural gas supply). This effect is
324 prevalently due to the high level of import dependency on Russia: as a consequence, this can be a significant example of
325 the importance of supply diversification (in terms of energy sources, supply countries and corridors), in order to avoid
326 such criticalities and enhance the security level of a Country.

327
328 S5 combines the effects of S1 and S4. This situation is extremely risky because it affects 46.1% of the total Italian
329 energy supply, and it leads to a critical situation, especially for natural gas supply, as more than 70% of the imported
330 flux is involved; the percentage of oil, RPP and coal imports involved is lower, but is significant, as it ranges between
331 20% and 50%. The overall energy risk increases by 11.7%, above all due to the specific risk contribution of natural gas
332 (+20.4%). This relevant growth is justified by the fact that seven suppliers (Russia, the Ukraine, Algeria, Libya, Egypt,
333 Tunisia and Nigeria) and 98 corridors undergo changes. In particular, the average ξ increases by 17.5%, in comparison
334 with the Reference case.

335 336 **4.3 Mitigation actions**

337 If a scenario leads to a loss of energy flow (S2-S5), specific countermeasures have to be planned and implemented to
338 ensure the needed supply. Some of the possible mitigation options have been tested using the here presented model,
339 their feasibility has been analysed and their effects have been compared in terms of risk reduction, in comparison with
340 the related scenario. For S2, the following options were considered:

341
342 *MA1-S2) Replacement of the Qatari LNG flow with a flow from Algeria (50%, Transmed pipeline;) and Russia (50%,
343 TAG pipeline).*

344 This configuration – which is coherent with the maximum capacities at the national entry points – allows the needed
345 annual quantity of natural gas to be ensured with a risk reduction of 1.21%, in comparison with S2.

346 *MA2-S2) Replacement of the Qatari LNG flow with a flow from Norway (25%, Transitgas pipeline), the Netherlands
347 (25%, Transitgas pipeline) and Russia (50%, TAG pipeline).*

348 In this case, the reduction in the overall risk is lower than the one obtained from MA1-S2 (and equal to 2.10%), due to
349 the low risk level of the two European countries.

350 *MA3-S2) Replacement of the Qatari LNG flow with a flow from the UAE (100%, LNG to regasification terminals*
351 *located near Panigaglia and Porto Levante).*
352 The resulting overall risk reduction is close to the one obtained for MA2-S2 (-2.39% vs. - 2.10%). The obtained
353 configuration is similar to the reference one, due to the fact that the country indexes for Qatar (38.5) and the UAE
354 (39.4), and the ship route to deliver LNG to Italy, are comparable.
355 The effects of the mitigation actions are reported in Tab. 8.
356
357 For S3, two mitigation actions were identified:
358
359 *MA1-S3) Replacement of the Libyan NG flow with a flow from Algeria (50%, Transmed pipeline) and Nigeria (50%:*
360 *25% Transmed pipeline; 25% LNG).*
361 The risk reduces by 1.56%, in comparison with the S3 scenario. It should be noticed that the ξ associated to these
362 corridors is higher than the Greenstream one: this is not due to the source country indexes (as they are similar to the
363 Libyan one for both Algeria and Nigeria), but – and particularly for Nigeria – to the high number of countries that are
364 crossed.
365 *MA2-S3) Replacement of the Libyan NG flow with a flow from the UAE (50%, LNG) and Qatar (50%, LNG).*
366 The resulting risk reduces by 3.49%. This option allows only maritime routes, which are more flexible and therefore
367 more effective from the security point of view, to be used.
368 The missing flow cannot be replaced entirely by European Countries (Norway and the Netherlands) as the required
369 capacity is higher than the maximum one for the Transigas corridor, which should be involved in this case.
370 The effects of the mitigation actions are reported in Tab. 9.
371
372 For S4, two mitigation options are defined:
373
374 *MA1-S4) Replacement of the Russian crude oil flow with a flow from Kazakhstan (50%) and Azerbaijan (50%;*
375 *replacement of the Russian NG flow with a flow from Algeria (30%), Nigeria (30%), the Netherlands (10%), Norway*
376 *(10%), Libya (7%), Qatar (7%) and the UAE (6%), i.e. from all the other countries that supply Italy, according to the*
377 *maximum capacity of the pipelines.*
378 In this way, the overall risk decreases by 9.88%: this is mostly due to the decrease in the risk related to natural gas (-
379 21%).
380 *MA2-S4) Replacement of the Russian crude oil flow with a flow from the Russian corridors that do not cross the*
381 *Ukraine; replacement of the Russian NG flows as in MA1-S4.*
382 The results show a reduction in the overall risk index of -10.08%, which is comparable with the one obtained in MA2-
383 S3. As in MA2-S3, this reduction is mostly related to the diversification of the NG supply.
384 The possible evolution of the corridors can provide additional possibilities, in terms of mitigation effects. The supply
385 from Russia through different corridors (whose routes do not cross the Ukraine), mainly depends on future strategies
386 related to the possible new pipelines that could be built. One of these alternatives could be represented by the South
387 Stream project, even though this solution does not currently seem feasible. In fact, the South Stream project (a pipeline
388 of a total length of about 2380 km, of which 931 will be offshore through the Black Sea, from Russia to Bulgaria, with a
389 capacity of 63 bcm/y) was declared, at the end of 2013, not to be compliant with the EU Third Energy Package
390 regulations [45], which introduced incompatibility between producers and TSOs (thus affecting the role played by the
391 Russian natural gas production and distribution company Gazprom); furthermore, this decision has to be contextualized
392 in a more general framework of geopolitical tensions between the EU and Russia, caused by the economic sanctions
393 imposed after the Crimea crisis. After the declared abandon of the South Stream project by Russia, the alternative
394 Turkish Stream (or TurkStream) project was proposed. This pipeline – originally expected to have the same capacity as
395 the South Stream one – should run from Russia to Turkey and cross the Black Sea (with a subsea branch of about 900
396 km) and to deliver 31.5 bcm/y; the construction is planned to start in 2017 and to be completed by 2019. According to
397 the most recent information available, Russia could build an additional line to connect Turkey to Greece, thus allowing
398 Europe to be supplied (15.75 bcm/y to Turkey, 15.75 bcm/y to Europe). Among all the possible options, an
399 interconnection between the Turkish Stream and the Trans Adriatic Pipeline (TAP) can be mentioned. The TAP
400 pipeline infrastructure is presently under construction (with a length of 878 km, an initial capacity equal to 10 bcm/y
401 and a planned maximum capacity of 20 bcm/y). It runs from Greece to Italy and will be connected to the Trans
402 Anatolian Pipeline (TANAP) – as part of the Southern Gas Corridor (SGC) – in order to carry natural gas from the
403 Azeri field of Shah Deniz to Europe. The construction of the TAP pipeline, and in particular the possibility of linking it
404 to the Turkish Stream, could be relevant for Italy, as this situation could allow it to become a European hub for natural
405 gas imported from Azerbaijan and Russia. As far as the security point of view is concerned, in 2014 (the reference year
406 of the case study), Italy's overall natural gas import was equal to 55.78 bcm, of which 26.15 bcm came from Russia
407 (46.9%). In the long term, hypothesising that the TAP pipeline could reach its maximum capacity, if the gas import
408 remains constant, this corridor could impact on the supply for about 36%. By considering the latest data made available
409 by the Italian Ministry of Economic Development and referring to 2015 [46], an increase in the overall imports can be

observed of up to 61.20 bcm; furthermore, if the historical trends are analysed, it can be noticed that the 2014 gas import value is significantly lower than the average import related to the last 12 years (69.27 bcm, with a peak of 77.40 bcm in 2006). These observations, coupled with the constantly decreasing trend of local gas production (which accounted for 11.5% of the Gross Inland Consumption in 2014), have lead us to suppose that the import of natural gas in 2020 (the planned year for starting the TAP pipeline) could be higher than the present one. However, it can reasonably be expected that it will be lower than 80 bcm/y: in this case, the contribution of the TAP will range from 12.5% (starting capacity = 10 bcm/y) to 25% (expansion up to the maximum capacity = 20 bcm/y). Focusing on the risk indexes (Tab. 3), it is possible to notice that the country risk index related to Azerbaijan is higher than that of Russia (43.9 vs. 34.0), and that the corridor route of the TAP pipeline (which crosses Azerbaijan, Armenia, Turkey, Greece and Albania) cannot be considered “safer” than the TAG pipeline one (which crosses Russia, the Ukraine, Slovak and Austria). For these reasons, it is possible to conclude that the TAP corridor would probably not reduce the absolute value of the supply risk, but it could be useful to increase diversification of the supply, and it could also offer a relevant alternative that could help in the case of geopolitical tensions between Russia and the Ukraine.

Other options, such as the use of the Yamal pipeline, cannot be considered, because of the constraint on the maximum capacity at the entry point, which is located in Passo Gries.

The effects of the mitigation actions are reported in Tab. 10.

For S5, flows from Russia and crossing the Ukraine (3 gas corridors and 1 oil corridor) have to be supplied in another way (as in S4), while this is not compulsory for those from North Africa (but could be recommended because of the high risk in comparison with the Reference scenario, due to hypothesised increase in the activity of terroristic groups). If the Russian flows are replaced in such a way as to avoid the North African corridors, it can be seen that several alternative options are available for oil import: ship transportation could be used (with the oil still coming from Russia) or the supplier could be changed (Caucasian countries, North and South America). As far as natural gas is concerned, if the supply from North African countries is avoided, only 60% of the flow that has to be replaced can be provided without overcoming the maximum capacity of the national entry points. As a consequence, with the current configuration of infrastructures, suppliers and corridors, the problem cannot be solved. In order to overcome this issue, some important changes have to be considered, including improvements of the infrastructures (new regasification plants or new pipelines) and the increase in the diversification of suppliers.

The approach described in sec. 3 and the case study analysed in sec. 4 are proposed from a single country perspective. However, the methodology could be applied at different scales (country, region, macro-areas). In fact, it could be useful to explore the energy security issues, especially for developing countries like China or India (for example, mention can be made to the studies performed by Jiang-Bo et al. [47] – which focus on the historical evolution of Chinese energy supply security, considering four dimensions and seven indexes – and the one carried out by Bambawale et al. [48], which was based on the analysis of Indian energy security from different perspectives), which are characterised by a relevant energy consumption growth rate, and for countries that show a relevant import dependency.

As far as the latter ones are concerned, Asian countries, like Japan and South Korea, can be mentioned. The overall Japanese energy import dependency in 2014 was equal to 93.5%, with relevant values for natural gas (97.6%) and crude oil (99.7%), while for South Korea, the import dependency in 2014 was equal to 82.8% (99.3% for natural gas and 99.5% for crude oil) [49]. Some European Countries are also affected to a great extent by this issue [50]: among the most populated ones, the dependency level of Italy is significantly high, but the situation of smaller countries, such as the Baltic ones, should also be highlighted, due to the fact that, since their independence and up to recent years, they have depended completely on a single supplier (Russia) [51].

5. CONCLUSIONS

The proposed methodology (and the implemented tool) can provide a quantitative assessment of the energy security of a country in a geopolitical perspective. The methodology, implemented and tested with reference to the Italian case, has proved to be effective in supporting policy decision making in the short, mid and long term.

This methodology allows a comprehensive representation of the inflow of a country, the assessment of its geopolitical risk and a cost benefit analysis, which is useful to compare different strategic options, to be obtained; a) in the short-mid-term, to allocate efforts with the aim of protecting a given corridor b) in the mid/long term, to plan and activate new supply options and corridors.

In addition, this methodology provides an effective way of designing mitigation countermeasures in the presence of an increase in the geopolitical risk or of adverse events, which could causing a certain percentage of the needed supply to become unavailable; it allows their effectiveness to be compared, and the related economic impacts to be assessed in terms of reduction in GDP loss.

With reference to the case of the Italian external supply, the analysis of the considered scenarios has highlighted the relevant role played by diversification in reducing the overall external risk. In a low self-sufficient country, the spatial dimension of energy corridors (the routes, lengths and the geopolitical security of the crossed countries) significantly affects the risk value. Moreover, in a strategic perspective, as natural gas is the most “risky” commodity, investments in

new LNG connections and terminals, or to increase the capacity of existing ones, could be beneficial from the security point of view. Investments in preventive actions against terroristic attacks against sensitive targets, such as pipelines, for example, the Greenstream corridor, could also lead to significant benefits from an economic point of view, as they could prevent the loss of a relevant amount of the GDP as the consequence of the sudden unavailability of an energy supply. The examined scenarios are related to the current energy system. From a more general perspective, the need to take into account climate changes, and to introduce adequate policies and countermeasures could have an effect on energy security [52] and lead to a new paradigm, based on a strong decarbonisation of the energy system and on the relevant role that renewables could play. According to this approach, among the future energy scenarios, the one that considers electrical UHV super-grids at a global scale, which would be able to transport electricity generated from renewable sources, such as wind and solar, from large production areas (the North Pole and African desert zones, respectively) to large consumption areas (such as the U.S.A., Asia and Europe), thus shifting the end-use energy consumptions from fossil fuels to cleanly produced electricity, can be mentioned [53]. Such a configuration could lead to an evolution in energy security, and could radically change the overall situation. The methodological approach described in this paper to evaluate supply security could also be adopted in future works to analyse these possible future scenarios and to compare them with other more traditional ones.

ACKNOWLEDGEMENTS

The authors would like to thank the consortium partners of the FP7 REACCESS project, especially Prof. Evasio Lavagno, Dr. Raffaella Gerboni and Arch. Laura Schranz.

REFERENCES

- [1] Kruyt, B., van Vuuren, D.P., de Vries, H.J.M. and Groenenberg, H. (2009): "Indicators for energy security", Energy Policy, Vol. 37, Iss. 6, pp. 2166-2181.
- [2] Gupta, E. (2008): "Oil vulnerability index of oil-importing countries", Energy Policy, Vol. 36, Iss. 3, pp. 1195-1211.
- [3] Bollen, J. (2008): "Energy security, air pollution, and climate change: an integrated cost-benefit approach", Milieu- en Natuurplanbureau (MNP), Bilthoven.
- [4] International Energy Agency (2007): "Energy Security and Climate Policy Assessing, Interactions".
- [5] Scheepers, M. J. J., Seebregts, A. J., De Jong, J. J., & Maters, J. M. (2006): "EU Standards for energy security of supply", Petten, Amsterdam, The Hague: Energy Research Center of the Netherlands and Clingendael International Energy Program. ECN-C-06-036
- [6] Scheepers, M. J. J., Seebregts, A. J., De Jong, J. J., & Maters, J. M. (2007): "EU standards for energy security of supply – Updates on the crises capability index and the Supply–Demand Index", Petten, Amsterdam, The Hague: Energy Research Center of the Netherlands and Clingendael International Energy Program. ECN-C-07-004
- [7] Shannon, C. E. (1948): "A mathematical theory of communication", The Bell System Technical Journal, 27, pp. 379-423.
- [8] Martchamadol, J., Kumar, S. (2013): "An aggregated energy security performance indicator", Applied Energy, Vol. 103, pp. 653-670.
- [9] WEC (2009): "World Energy and Climate Policy: 2009 Assessment", World Energy Council Publication.
- [10] WEC (2010): "Pursuing sustainability: 2010 Assessment of country energy and climate policy", World Energy Council Publication.
- [11] Asia Pacific Energy Research Centre, A quest for Energy Security in The 21st Century Resources and, Constraints; 2007.
- [12] IAEA, UNDESA, IEA, EUROSTAT, EEA, Energy Indicators for Sustainable Development: Guidelines and Methodologies, International Atomic Energy Agency; 2005.
- [13] Fundación Bariloche (2008): "Energy security and energy efficiency. Global Network on Energy and Sustainable Development (GNESD)"
- [14] Badea, A. C., Rocco S., C. M., Tarantola, S., Bolado, R. (2011): "Composite indicators for security of energy supply using ordered weighted averaging", Reliability Engineering and System Safety, Vol. 96, pp. 651-662.
- [15] Capros, P., Mantzos, L., Tasios, N., De Vita, A., Kouvaritakis, N. (2010): "EU energy trends to 2030 », European Commission, Directorate-General for Energy
- [16] Checchi, A., Behrens, A. and Egenhofer, C. (2009): "Long-term energy security risks for Europe: a sector-specific approach", Centre for European Policy Studies (CEPS), Working document, No. 309, pp. 8-12.
- [17] Institute for 21st Century Energy, U.S. Chamber of Commerce (2013): "International Index of Energy Security Risk. Assessing Risk in a Global Energy Market", www.energyxxi.org
- [18] Sovacool, B.K., Mukherjee, I., Drupady, I.M. and D'Agostino, A.L. (2011a): "Evaluating energy security performance from 1990 to 2010 for eighteen Countries", Energy, Vol. 36, Iss. 10, pp. 5846-5853.
- [19] Frondel, M., Ritter, N., Schmidt, C. M. (2009): "Measuring Energy Supply Risks: A G7 Ranking", Ruhr Economic Paper No. 104, Rheinisch-Westfälisches Institut für Wirtschaftsforschung (RWI), Ruhr-University Bochum, TU Dortmund University, University of Duisburg-Essen.
- [20] Frondel, M., Ritter, N. and Schmidt, C.M. (2012): "Measuring long-term energy supply risks: A G7 ranking", Discussion Paper, SFB 823, No. 28, Technische Universität, Dortmund.
- [21] Frondel, M., Schmidt, C. M. (2014): "A measure of a nation's physical energy supply risk", The Quarterly Review of Economics and Finance, Vol. 54, pp. 208-215.
- [22] Herfindahl, O. C. (1950): "Concentration in the steel industry", Columbia University (unpublished doctoral dissertation).
- [23] Guivarch, C., Monjon, S. (2016): "Identifying the main uncertainty drivers of energy security in a low-carbon world: The case of Europe", Energy Economics, <http://dx.doi.org/10.1016/j.eneco.2016.04.007>

- [24] Matsumoto, K., Andriosopoulos, K. (2016): "Energy security in East Asia under climate mitigation scenarios in the 21st century", *Omega*, Vol. 59, Part A, pp. 60-71
- [25] Valdés Lucas, J.N., Escribano Francés, G., San Martín González, E. (2016): "Energy security and renewable energy deployment in the EU: *Liaisons Dangereuses* or Virtuous Circle?", *Renewable and Sustainable Energy Reviews*, Vol. 62, pp. 1032-1046.
- [26] Biresselioglu, M.E., Yelkenci, T., Oz, I.O. (2015): "Investigating the natural gas supply security: A new perspective", *Energy*, Vol. 80, pp. 168-176.
- [27] Flouri, M., Karakosta, C., Kladouchou, C., Psarras, J. (2015): "How does a natural gas supply interruption affect the EU gas security? A Monte Carlo simulation", *Renewable and Sustainable Energy Reviews*, Vol. 44, pp. 785-796.
- [28] Kisel, E., Hamburg, A., Härm, M., Leppiman, A., Ots, M. (2016): "Concept for Energy Security Matrix", *Energy Policy*, Vol. 95, pp. 1-9
- [29] Correlje, A. and van der Linde, C. (2006): "Energy supply security and geopolitics: A European perspective", *Energy Policy*, Vol. 34, Iss. 5, pp. 532-543.
- [30] Costantini, V., Gracceva, F., Markandya, A. and Vicini, G. (2007): "Security of energy supply: Comparing scenarios from a European perspective", *Energy Policy*, Vol. 35, Iss. 1, pp. 210-226.
- [31] Hedenus, F., Azar, C. and Johansson, D.J.A. (2010): "Energy security policies in EU-25 – The expected cost of oil supply disruptions", *Energy Policy*, Vol. 38, Iss. 3, pp. 1241-1250.
- [32] Umbach, F. (2010): "Global energy security and the implications for the EU", *Energy Policy*, Vol. 38, Iss. 3, pp. 1229-1240.
- [33] Biberacher M., De Miglio R., Gargiulo M., Gerboni R., Lavagno E., Schranz L., Tosato GC. (2011): "Risk of Energy Availability Common Corridors for Europe Supply Security - Summary Report", REACCESS Final Workshop, Brussels, Belgium.
- [34] Loulou R., Labriet M. (2008) ETSAP-TIAM: the TIMES integrated assessment model part I: model structure. *Computational Management Science* 5: 7–40
- [35] Marín-Quemada, J.M., Velasco, C. and Muñoz, B. (2009a): "Addressing competition in energy supply: weakening the impacts and improving energy security through complementarities", Deliverable 4.2 REACCESS Project, Risk of Energy Availability: Common Corridors for European Security of Supply, EC-FP7 Project Grant Agreement No. 212011.
- [36] Marín-Quemada, J.M., Velasco, C. and Muñoz, B. (2009b): "Competitive and complementary relations of the EU with the main energy consuming and producing countries", Technical Note 4.2-1 REACCESS Project, Risk of Energy Availability: Common Corridors for European Security of Supply, EC-FP7 Project Grant Agreement No. 212011.
- [37] Marín-Quemada, J.M., Velasco, C., García-Verdugo, J., Francés, G., Mahía, R., De Arce, R., San Martín González, E., Rodríguez, L. and Muñoz, B. (2009c): "Quantification of socioeconomic risk & proposal for an index of security of energy supply", Technical Note 4.5-1 and 4.5-2 REACCESS Project, Risk of Energy Availability: Common Corridors for European Security of Supply, EC-FP7 Project Grant Agreement No.: 212011.
- [38] Gerboni, R., Grosso, D., Lavagno, E., Kanudia, A., Tosato, GC. (2015): "Coupling World and European models: energy trade and energy security in Europe", in: "Informing Energy and Climate Policies Using Energy Systems Models" / Giannakidis G., Labriet M., Ó Gallachóir B., Tosato, GC., Springer International Publishing Switzerland, pp. 411-426, ISBN 9783319165394.
- [39] Doukas, H., Flamos, A., Karakosta, C., Flouri, M. and Psarras, J. (2010): "Web tool for the quantification of oil and gas corridors' socio-economic risks. The case of Greece", *International Journal of Energy Sector Management*, Vol. 4, No. 2, pp. 213-235.
- [40] Muñoz, B., García-Verdugo, J. and San-Martín, E. (2015): "Quantifying the geopolitical dimension of energy risks: A tool for energy modelling and planning", *Energy*, Vol. 82, pp. 479-500.
- [41] Carpignano, A., Nironi, C., Ganci, F. (2011): "Technological risk: a criterion for the optimisation of future EU energy supply scenarios", *International Journal of Energy Sector Management*, Vol. 5, Iss. 1, pp. 81-100.
- [42] Jun, E., Kim, W., Chang, S.H. (2009): "The analysis of security cost for different energy sources", *Applied Energy*, Vol. 86, pp. 1894-1901.
- [43] Ministero dello Sviluppo Economico - DGSAIE - Statistiche ed analisi energetiche e minerarie, <http://dgsaie.mise.gov.it/dgerm/>
- [44] Eurostat Energy Statistical Database, <http://ec.europa.eu/eurostat/web/energy/data/database>
- [45] Directive 2009/73/EC of the European Parliament and of the Council of 13 July 2009 concerning common rules for the internal market in natural gas and repealing Directive 2003/55/EC
- [46] Ministry of Economic Development, natural gas balance, <http://dgsaie.mise.gov.it/dgerm/bilanciogas.asp>
- [47] Geng, J.B., Ji, Q. (2014): "Multi-perspective analysis of China's energy supply security", *Energy*, Vol. 64, pp. 541-550.
- [48] Bambawale, M.J., Sovacool, B.K. (2011): "India's energy security: A sample of business, government, civil society, and university perspectives", *Energy Policy*, Vol. 39, pp. 1254-1264.
- [49] International Energy Agency Statistical Database, <http://www.iea.org/statistics/>
- [50] Prael, A., Weingartner, K. (2016): "Chapter 3 - A Study of Russia as Key Natural Gas Supplier to Europe in Terms of Security of Supply and Market Power", in *Low-carbon Energy Security from a European Perspective* (Lombardi, P., Gruenig, M. Eds.), Academic Press, Oxford, pp. 43-79.
- [51] Purvins, A., Fulli, G., Covrig, C.F., Chaouachi, A., Bompard, E.F., Carpaneto, E., Huang, T., Pi, R.J., Mutule, A., Oleinikova, I., Obushevs, A. (2016): "The Baltic power system between East and West interconnections", JRC Science for Policy report, doi:10.2790/41165
- [52] Cassen, C., Gracceva, F. (2016): "Chapter 7 - Energy Security in Low-Carbon Pathways", in *Low-carbon Energy Security from a European Perspective* (Lombardi, P., Gruenig, M. Eds.), Academic Press, Oxford, pp. 181-205.
- [53] Liu, Z. (2015): "Global Energy Interconnection", Academic Press, pp. 396.

604 TABLES

605
606

Table 1: Weighting function γ_k

$b/\bar{b}_i$	γ_k
0-0.2	0.90
0.2-0.5	0.93
0.5-0.9	0.96
0.9-1.1	1.00
1.1-1.5	1.04
1.5-2.0	1.07
>2.0	1.10

607
608

Table 2: Nomenclature

Set / Parameter	Description
$\mathcal{C} = \{\dots, c_c, \dots\}, \dim(\mathcal{C}) = C$	Set of energy commodities
$\mathcal{J} = \{\dots, i_i, \dots\}, \dim(\mathcal{J}) = I$	Set of energy corridors
$\mathcal{C}_i \subseteq \mathcal{C} \mid c_i \in \mathcal{C}_i$	Commodity delivered by corridor i_i
$\mathcal{K} = \{\dots, k_k, \dots\}, \dim(\mathcal{K}) = K$	Set of countries (both source and corridor)
$\mathcal{K}^i \subseteq \mathcal{K} \mid k_h \in \mathcal{K}^i$	Country crossed by corridor i_i
$\mathcal{L} = \{\dots, l_{l_i}, \dots\}, \dim(\mathcal{L}) = L=I$	Set of corridor lengths (km)
$\mathcal{B}^i = \{\dots, b_{b_i}, \dots\}, \dim(\mathcal{B}) = B^i$	Set of the lengths of branches of corridor i_i
$\mathcal{D} = \{\dots, d_d, \dots\}, \dim(\mathcal{D}) = D$	Set of distribution / transmission infrastructures
γ_k	Geopolitical country index weight for Country k , depending on the length of each corridor branch
$\vartheta_{c,d}$	Resilience index for the internal distribution network d carrying commodity c
ξ_i	Risk index of corridor i
ϕ_k	Geopolitical country index for country k
χ	Import dependency (%)
ω_i	Probability of success of corridor i
Q	Energy Intensity of the Economy
w_1	Weight coefficient for the internal risk
w_2	Weight coefficient for the external risk
R_i	Risk of corridor i
$R_{int (ext)}$	Overall internal (external) risk value
$R_{int (ext),m}$	Overall internal (external) risk, monetary units
S_i	Expected supply of corridor i
$S_{int (ext)}$	Overall internal (external) expected supply
E	Total energy supply
$E_{c,i}$	Energy flow of commodity c carried by corridor i
R_n	National Energy Security Index

609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624

625

Table 3: Geopolitical country index φ_k

Source Country	φ	Source Country	φ
Algeria	44.7	Mexico	31.7
Angola	61.7	the Netherlands	10.5
Australia	12.5	Nigeria	48.0
Austria	22.0	Norway	0.4
Azerbaijan	43.9	Qatar	44.2
Belgium	25.8	Russia	34.0
Canada	9.9	Saudi Arabia	47.9
China	44.1	Slovenia	28.7
Colombia	39.9	South Africa	36.1
Congo	55.0	Spain	24.1
Egypt	47.0	Switzerland	22.8
France	23.0	Syria	52.5
Gabon	44.5	Thailand	40.1
Germany	12.3	Tunisia	44.7
Ghana	52.7	Turkey	41.8
Greece	30.2	Turkmenistan	52.3
India	38.3	the Ukraine	35.9
Indonesia	46.0	the UAE	43.1
Iran	50.4	the USA	5.9
Iraq	67.9	Venezuela	39.9
Kazakhstan	38.3		
Kuwait	38.5		
Libya	47.5		

626
627
628

Table 4: Scenarios for the energy security analysis

S	Description	Country risk φ_k	Corridor disruption
S1	Increased activity of terroristic groups in NA	+15% Algeria, Egypt, Libya, Tunisia	-
S2	Deterioration of the Italian/Qatari relations	-	Unavailability of all the Qatari LNG corridors (4)
S3	Antagonistic actions in Libya	-	Disruption of the NG Greenstream corridor (1)
S4	Increase in contrast between Russia and the Ukraine	+10% Russia, Ukraine	Closure of the NG/Oil pipelines in the Ukraine (3 +1)
S5	Simultaneous Scenarios 1 + 4	+15% Algeria, Egypt, Libya, Tunisia; +10% Russia, Ukraine	Closure of NG/Oil pipelines in the Ukraine (3 +1)

629
630

Table 5: Impact analysis for various scenarios, all commodities (reference 2014)

	Total Supply		
	Energy risk [TJ/y]	Economic risk [G€/y]	Percentage variation
REF	3320988,0	848,9	-
S1	3421496,4	874,6	+ 3,03%
S2	3402748,3	869,8	+ 2,46%
S3	3437896,7	878,7	+ 3,52%
S4	3609261,2	922,6	+ 8,68%
S5	3709769,6	948,2	+ 11,70%

631
632
633

634

Table 6: Impact analysis for various scenarios - only NG (reference 2014)

	Natural Gas Supply		
	Energy risk [TJ/y]	Economic risk [G€/y]	Percentage variation
REF	1412834,3	361,1	-
S1	1470743,8	375,9	+ 4,10%
S2	1494594,5	382,0	+ 5,79%
S3	1529742,9	391,0	+ 8,27%
S4	1643575,4	420,1	+ 16,33%
S5	1701484,9	434,9	+ 20,40%

635

636

Table 7: Monthly energy and economic risk variation for S1

	Energy risk [TJ/month]		Economic risk [G€/month]		% variation
	REF	S1	REF	S1	
January	326301,9	335475,6	83,4	85,7	+ 2,8%
February	266461,9	275681,2	68,1	70,5	+ 3,5%
March	285720,8	292396,6	73,0	74,7	+ 2,3%
April	271453,4	280431,3	69,4	71,7	+ 3,3%
May	303996,6	313961,8	77,7	80,3	+ 3,3%
June	260970,7	267085,1	66,7	68,3	+ 2,3%
July	290410,6	297436,9	74,2	76,0	+ 2,4%
August	259432,6	268039,6	66,3	68,5	+ 3,3%
September	246424,2	255304,8	63,0	65,3	+ 3,6%
October	264644,3	271567,0	67,6	69,4	+ 2,6%
November	266992,5	276374,6	68,2	70,6	+ 3,5%
December	278178,6	287741,8	71,1	73,5	+ 3,4%

637

638

Table 8: Energy and economic risk variation for mitigation actions to S2

	Energy risk [TJ/y]	Economic risk [G€/y]	Percentage variation
S2	3353434,3	857,2	-
MA1-S2	3360660,8	859,0	-1,21%
MA2-S2	3329944,1	851,2	-2,10%
MA3-S2	3319985,2	848,6	-2,39%

639

640

Table 9: Energy and economic risk variation for mitigation actions to S3

	Energy risk [TJ/y]	Economic risk [G€/y]	Percentage variation
S3	3387423,0	865,8	-
MA1-S3	3334651,4	852,4	-1,56%
MA2-S3	3269333,4	835,7	-3,49%

641

642

Table 10: Energy and economic risk variation for the S4 mitigation actions

	Energy risk [TJ/y]	Economic risk [G€/y]	Percentage variation
S4	3555031,6	908,7	-
MA1-S4	3203725,9	818,9	-9,88%
MA2-S4	3196688,0	817,1	-10,08%

643

644

645

646

647

648

649

650

651
652
653

654
655
656
657

Fig. 1 – “Fronts” and risk indexes in a national energy security assessment

658
659
660
661
662

Fig. 2 – Polar representation of the geopolitical country index ϕ_k