

Enhancement of waste activated sludge (WAS) anaerobic digestion by means of pre- and intermediate treatments. Technical and economic analysis at a full-scale WWTP

Original

Enhancement of waste activated sludge (WAS) anaerobic digestion by means of pre- and intermediate treatments. Technical and economic analysis at a full-scale WWTP / Campo, Giuseppe; Cerutti, Alberto; Zanetti, Mariachiara; Scibilia, Gerardo; Lorenzi, Eugenio; Ruffino, Barbara. - In: JOURNAL OF ENVIRONMENTAL MANAGEMENT. - ISSN 0301-4797. - STAMPA. - 216:(2018), pp. 372-382. [10.1016/j.jenvman.2017.05.025]

Availability:

This version is available at: 11583/2673008 since: 2018-05-21T13:07:38Z

Publisher:

Elsevier

Published

DOI:10.1016/j.jenvman.2017.05.025

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

Elsevier preprint/submitted version

Preprint (submitted version) of an article published in JOURNAL OF ENVIRONMENTAL MANAGEMENT © 2018, <http://doi.org/10.1016/j.jenvman.2017.05.025>

(Article begins on next page)

1 **Enhancement of Waste Activated Sludge (WAS) anaerobic digestion by means of pre- and intermediate**
2 **treatments. Technical and economic analysis at a full-scale WWTP**

3
4
5
6
7 4 Giuseppe Campo¹§, Alberto Cerutti¹§, Mariachiara Zanetti¹, Gerardo Scibilia², Eugenio Lorenzi², Barbara
8
9 5 Ruffino^{1*}

10
11 6 ¹Department of Environment, Land and Infrastructure Engineering, Politecnico di Torino, corso Duca degli
12
13
14 7 Abruzzi 24 – 10129 Torino, Italy

15
16 8 ²Società Metropolitana Acque Torino S.p.A., via Po 2 – 10090 Castiglione Torinese (TO), Italy

17
18
19 9
20
21 10 **Revision April 2017**

22
23
24 11
25
26 12
27
28 13
29
30 14 *Corresponding author

31
32 15 Barbara RUFFINO

33
34 16 DIATI, Department of Environment, Land and Infrastructure Engineering

35
36 17 Politecnico di Torino

37
38 18 Corso Duca degli Abruzzi, 24

39
40 19 10129 Torino, ITALY

41
42 20 Ph. +39.011.0907663

43
44 21 Fax +39.011.0907699

45
46 22 e-mail: barbara.ruffino@polito.it

47
48 23
49 24 § Authors contributed equally to the study

25 **Abstract**

1
26 Anaerobic digestion (AD) is the most commonly applied end-treatment for the excess of waste activated
3
4
27 sludge (WAS) generated in biological wastewater treatment processes. The efficacy of different typologies
5
6
28 of pre-treatments in liberating intra-cellular organic substances and make them more usable for AD was
7
8
9
29 demonstrated in several studies. However, the production of new extracellular polymeric substances (EPSs)
10
11
30 that occur during an AD process, due to microbial metabolism, self-protective reactions and cell lysis,
12
13
31 partially neutralizes the benefit of pre-treatments. The efficacy of post- and inter-stage treatments is
14
15
32 currently under consideration to overcome the problems due to this unavoidable byproduct.

16
17
18
33 This work compares three scenarios in which low-temperature (<100°C) thermal and hybrid (thermal+alkali)
19
20
21
34 lysis treatments were applied to one sample of WAS and two samples of digestate with hydraulic retention
22
23
35 times (HRTs) of 7 and 15 days. Batch mesophilic digestibility tests demonstrated that intermediate
24
25
26
36 treatments were effective in making the residual organic substance of a 7-day digestate usable for a
27
28
37 second-stage AD process. In fact, under this scenario, the methane generated in a two-stage AD process,
29
30
31
38 with an in-between intermediate treatment, was 23% and 16% higher than that generated in the scenario
32
33
39 that considers traditional pre-treatments carried out with 4% NaOH at 70 and 90°C respectively.
34
35
40
41 Conversely, in no cases (70 or 90°C) the combination of a 15-day AD process, followed by an intermediate
36
37
38
39 treatment and a second-stage AD process, made possible to obtain specific methane productions (SMPs)
40
41
42 higher than those obtained with pre-treatments.

43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

51 Introduction

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Conventional biological treatments carried out in wastewater treatment plants (WWTPs) are intended to reduce the load of organic substances and nutrients from wastewaters before discharge in receiving water bodies. Biological treatments concentrate more than 60% of the initially diluted organic matter in waste activate sludge (WAS) that contains total (TS) and volatile solids (VS) (Garrido et al., 2013). Then, 60% of the initial energy content of the wastewater (3.2 MJ/kg TS) is transferred into WAS (with a heating value of 17.5 MJ/kg TS, according to Cano et al., 2015) and can be recovered as biogas from an anaerobic digestion (AD) process.

It is however well known that most of the organic substances in WAS are found in insoluble microbial cells, which show low bioavailability for the subsequent AD process (Traversi et al., 2015; Xiao et al., 2015). Traditional pre-treatments (mechanical, thermal, chemical or a combination of them) are intended to make the biological substrates more usable for enzymatic attack through the disruption of cell walls (Collivignarelli et al., 2015; Carrère et al., 2010; Teo, 2016). However, several authors demonstrated that also Extracellular Polymeric Substances (EPSs) in sewage sludge is a factor for poor anaerobic digestion (Shana et al., 2015; Williams et al., 2015). EPS is a part of sludge biochemical composition (carbohydrates and proteins) and two types of EPSs are involved in WAS digestion. One type is part of the biochemical composition of the activated sludge fed to the digester, the other type is released from the sludge that undergoes digestion because of microbial metabolism, self-protective reaction and cell lysis (Shana et al., 2015). The use of sludge pre-treatment technologies may only help to reduce the amount of EPS in the sludge feedstock but cannot prevent its production during an AD process due to bacteria growth, substrate consumption, self-protection of microorganisms from adverse environmental conditions or cell decay. Thus, EPS is an unavoidable by-product of the WAS digestion process. Therefore, a possible solution to deal with EPS production during sludge digestion is to make use of intermediate hydrolysis processes (IHPs, Li et al., 2013; Williams et al., 2015).

IHPs consist of conventional mesophilic AD followed by a hydrolysis process. These treatments only concentrate on the slowly degradable parts of the sludge, in contrast to pre-treatment methods. Despite

77 the possible advantages of post/inter-stage treatments, these configurations have until now received little
1
278 attention in comparison to pre-treatments. To the best of our knowledge, only very few cases study
3
4
79 compared the performances of pre- and inter-stage (or post) treatments on sludge destined to AD. Nielsen
5
6
80 and coauthors (2011) compared moderate thermal (80 °C), high thermal (loop autoclave at 130–170 °C)
8
9
81 and thermo-chemical (170 °C/pH 10, KOH) pre-treatments with inter-stage treatments carried out under
10
11
82 the same operating conditions. They concluded that thermal or thermo-chemical treatments of WAS were
12
13
83 more effective when applied as an inter-stage treatment rather than a pre-treatment. This behavior was
14
15
84 particularly evident for the strongest treatment condition (170 °C/pH 10, KOH), for which the increase in
16
17
85 the methane yield was of 28%, when applied as an inter-stage, and only of 2% when applied as a pre-
18
19
86 treatment.

22
23
87 A very recent study (Ortega-Martinez et al., 2016) demonstrated that thermal inter-treatment could
24
25
88 improve the methane production by 45% and 20% compared to conventional anaerobic digestion and pre-
26
27
89 treatments followed by anaerobic digestion, respectively. Ortega-Martinez and coauthors carried out pre-
28
29
90 and inter-treatments in a laboratory-scale thermal steam explosion system at temperature values that
30
31
91 ranged from 110 to 200°C and for contact times of 10, 30 and 50 minutes. Also, Shana and coauthors
32
33
92 (Shana et al., 2011; 2013) stated the advantage of IHPs compared to pre-treatments using very hard
34
35
93 operating conditions (165°C, 7 bar, 30 min). They demonstrated that IHPs produced 20% more biogas than
36
37
94 pre-treatments.

41
42
95 Conversely, some other authors concentrated their attention only on post- or inter-stage treatments,
43
44
96 without a comparison with pre-treatments carried out under the same operating conditions. Takashima
45
46
97 and Tanaka (2014) demonstrated that post- and inter-stage treatment configurations showed good
47
48
98 performances in organic matter destruction and methane production by testing acid thermal post-
49
50
99 treatments (ATPT) at a lab scale at the temperature values of 25; 100 and 180 °C and pH of 2; 4 and 6
51
52
100 obtained with HCl.

55
56
101 Li and coauthors (2013) tested alkaline post-treatment at a lab scale. They extracted 5% of sludge from a
57
58
102 semi-continuous digester between the 8th and the 12th hour of a 24-h digestion cycle. The sludge was
59
60

103 disintegrated with 0.1 mol/L NaOH and returned to the digester after neutralization. The results showed
1
104 that alkaline post-treatment increased the level of soluble organic substances in the extracted sludge,
3
105 particularly of volatile fatty acids and polysaccharides. This process resulted in a 33% enhancement of
4
6
106 biogas production in comparison with the control. A very recent experience (Zhang et al., 2016)
8
107 demonstrated the effectiveness of free nitrous acid (FNA i.e. HNO_2 , in the range of 0.77 – 3.85 mg N/L for
10
11
108 24 h) used to hydrolyze samples of already anaerobically digested sludge. The FNA treatment at the lowest
12
13
109 concentration resulted in the highest increase in methane production (40%) compared to the control.
15
16
110 In this work, only-thermal and hybrid (thermo-chemical) processes that use alkali species (NaOH and
17
18
111 $\text{Ca}(\text{OH})_2$) were employed for pre-treatments and intermediate treatments. Pre-treatments and
19
20
112 intermediate treatments were carried out at the temperature values of 20, 70, 90 °C for contact times of
22
23
113 1.5 hours. Pre-treatments involved samples of WAS provided by the local wastewater treatment plant
24
25
114 (WWTP, 2,000,000 population equivalent, p.e.), thickened to a final total solid (TS) content in the order of
27
28
115 4.5%. Intermediate treatments were carried out on two samples of digestate, one generated in the WWTP
29
30
116 and characterized by a hydraulic retention time (HRT) of 7 days, the other produced in a pilot scale reactor
31
32
117 and characterized by a HRT of 15 days. Performances of pre- and intermediate treatments were compared
34
35
118 at three levels of analysis:

- 119 1. by assessing the disintegration rate (DR) parameter, as a quick response of the efficacy of the
37
38
120 treatment;
40
41
- 121 2. by evaluating the increase in biogas and methane production using lab-scale digesters;
42
43
44
- 122 3. by assessing the benefit produced by pre- and intermediate treatments, in terms of increase in the
45
46
123 economic revenues, for a full-scale plant (2,000,000 p.e.).
47
48

124 125 **2. Materials and Methods**

126 **2.1. WAS and digestate samples**

127 Three kinds of substrates were employed for this study. The first two substrates, a WAS and a digestate,
58
128 were collected from the SMAT WWTP located in Castiglione Torinese (NW Italy, 2,000,000 p.e.). The SMAT
60
61
62
63
64
65

129 plant is a conventional WWTP, the details of the units and processes that make up the water line and the
1
130 sludge line are described in Panepinto et al., 2016. The third substrate was the digestate produced in a pilot
3
131 scale (300-L) apparatus.
5

6
132 The sample of WAS was collected from one of the secondary clarifiers placed after the biological
8
133 compartment of the water line. Under the WWTP normal operating conditions, WAS has a TS content of
10
134 approximately 0.8% and a VS/TS ratio of 0.7. For experimental purposes the WAS sample was thickened on
12
135 a cloth filter to reach a final TS content of approximately 5%.
15

16
136 The sample of digestate from the WWTP was collected at the exit of one of the six anaerobic digesters
17
137 employed for the treatment of sludge produced in the WWTP. Digesters are fed with sludge of different
18
138 quality: primary, secondary or a mixture of two. Under normal operating conditions, the digesters work in a
20
139 one-stage modality with a HRT of 17 days. However, in the period in which the digestate was sampled
22
140 (March 2016), all the secondary sludge was digested in one system that combined two digesters working in
23
141 a two-stage modality. Digestate was taken at the exit of the first-stage digester that had a HRT of only 7
24
142 days. Also, the sample of digestate was thickened on a cloth filter to reach a final TS content of 4.5%.
25
26

27
143 The sample of digestate collected from the 300-L digester was produced in a test that involved the WAS
28
144 generated in the Castiglione Torinese WWTP. The pilot scale digester was described in detail in Fiore et al.,
29
145 2016. Shortly, it had an operating volume of 240 L and worked in mesophilic conditions under an organic
30
146 loading rate of approximately $2 \text{ kgTS/m}^3 \cdot \text{d}$. The HRT was of 15 days. When the sample of digestate was
31
147 collected for the study, the digester had been working for 75 days. The WAS used as a feeding substrate has
32
148 had an average TS content of $3.18 \pm 0.22\%$ and an average VS/TS ratio of 0.693 ± 0.013 . Also, the digestate
33
149 collected from the 300-L digester was thickened before use. The original sample had a TS content of
34
150 $2.58 \pm 0.06\%$ with a VS/TS ratio of 0.626 ± 0.005 . After thickening, the TS content increased up to 4.30%.
35
36
37
38
39

40
151 The characteristics of the three substrates used for the tests are summarized in Table 1. Each value was
41
152 obtained as an average of three replicates.
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

153 **2.2. Lysis tests**

1
154 Tests of low-temperature thermal lysis and hybrid thermo-chemical lysis were performed only on the
3
4
155 samples of WAS and digestate collected from the WWTP. The methods employed were described in detail
5
6
156 in Ruffino et al. (2016). Tests were carried out at the three values of temperature of 20; 70 and 90°C, using
8
157 two alkali agents, NaOH and Ca(OH)₂. Contact time was equal to 90 minutes and the mixture was stirred
10
11
158 energetically for 1 minute every 15 minutes. The doses of alkali employed were of 4 and 8% of the TS
12
13
159 content and came from the results of a previous work (Ruffino et al., 2016). That work was aimed at
15
160 identifying the optimal alkali dosage for the treatment of WAS and demonstrated that, in the range 2-20 g
17
18
161 alkali/100 g TS, 4-8 was the most suitable dose for a hydrolysis process.

20
162 For what concerns the sample of digestate from the 300-L digester (15-day digestate), the effect of thermo-
22
23
163 chemical lysis was verified only for the two specific working conditions that demonstrated to be the most
24
25
164 promising, that is (70°C; 4% NaOH) and (90°C; 4% NaOH). Samples that underwent this treatment were
27
28
165 subsequently used for digestibility tests (see Section 2.3).
29
30
31

32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
2.3. Digestibility tests

168 Anaerobic digestion tests were carried out using the procedures described in previous works (Ruffino et al.,
36
37
169 2015; 2016). The tests were performed in batch mode and mesophilic conditions (35-38°C) in the apparatus
39
40
170 shown in Figure 1. Due to the limited availability of reactors, only six tests could be carried out
41
42
171 simultaneously. A total of five series of tests were carried out in this study. Three series of tests involved
43
44
172 samples of WAS, one series the 7-day digestate (from the full scale WWTP) and one series the 15-day
46
47
173 digestate (from the 300-L digester). Specifically, digestibility tests involved samples of WAS treated with
48
49
174 thermal (70°C and 90°C) and hybrid (20-70-90°C with 4% NaOH) processes and samples of 7-d and 15-d
50
51
175 digestate treated with hybrid (70-90°C with 4% NaOH) processes.

54
55
56
176 In each series, two samples (in two replicates) treated with lysis processes were digested with a control
57
58
177 (untreated) sample (also in two replicates). The inoculum used for the tests was the digestate collected
59
60
61
62
63
64
65

178 from the 300-L reactor (TS content of $2.58 \pm 0.06\%$ with a VS/TS ratio of 0.626 ± 0.005). The ratio between
1
179 food and microorganisms (F/M), as TS, was in the order of 1.5 in all tests.

180 As in previous experiences (Ruffino et al., 2015; 2016), the biogas produced from the reactors was collected
181 in two 5-L Tedlar® bags connected in parallel. The characterization and measure of the volume of the
182 produced biogas was carried out daily, throughout the whole duration of the test. The characterization,
183 that is the volumetric composition of the biogas in terms of CH_4 , CO_2 , O_2 and “balance” (the fraction made
184 up of gases that are different from the first three) was obtained by flushing 500 mL of biogas through a
185 biogas analyzer (Biogas Check, Geotechnical Instruments Ltd). The residual volume of the biogas after
186 characterization was measured by replacing volumes of water with the residual gas and referring the
187 obtained value to the normal conditions (273.15 K and 101.325 kPa).

188 189 **2.4. Analytical methods**

190 All the analytical parameters monitored in the lysis tests (TS, VS, pH, electric conductivity (EC), soluble COD
191 (sCOD) and ammonium NH_4^+) were determined using Standard Methods (APHA, AWWA, WEF, 2012).

192 Soluble COD is the fraction of COD separated after a centrifugation at 4000 rpm for 15 minutes and a
193 subsequent filtration on a 0.45 μm nylon membrane, as recommended by Roeleveld and van Loosdrecht
194 (2002).

195 Specific COD value (as $\text{g O}_2/\text{g VS}$) was evaluated using the elemental composition of the sludge as in Van
196 Lier et al. (2008). The elemental composition of WAS and digestate samples was determined using a Flash
197 2000 ThermoFisher Scientific CHNS analyzer.

198 199 **3. Results and Discussion**

200 **3.1. Characterization of WAS and digestate samples**

201 The complete physical and chemical characterization of the three substrates is shown in Table 1. As
202 anticipated in Section 2, the thickening process, carried out with a cloth filter, produced a final TS content

203 in the order of 4.00-5.00% in all samples. Some parameters (pH value, sCOD and ammonia concentration)
1
204 were of the same order of magnitude in the three samples.
3

205 The both samples of digestate had a VS content lower than that of the WAS sample. This was because the
4
206 AD process consumes biodegradable substance. Between the two samples of digestate, the substrate
5
207 coming from the 300-L digester had the lowest VS/TS content, in agreement with the higher HRT (15 days
6
208 vs. 7 days).
7
8
9
10
11
12

1209 Moreover, both digestates had an EC value that was approximately three times the EC of the WAS sample
13
14
15
16
210 (3.5 and 2.9 mS/cm vs. 1.1 mS/cm), this was probably a consequence of the release of intracellular ions due
17
18
211 to rupture of the cell membranes during an AD process. Specific COD values for the WAS and 7-day
19
20
212 digestate samples were quite similar. The elemental composition of the 15-day digestate was assumed
21
22
23
213 equal to that of the 7-day digestate.
24
25
26
27

215 **3.2 Results of lysis tests**

28
29

216 The efficacy of the treatments of lysis was assessed by using the disintegration rate (DR) parameter.
30
31

$$217 DR = \frac{sCOD_I - sCOD_0}{tCOD_0 - sCOD_0} \cdot 100\% \quad (1)$$

32
33
34
35
36

218 This parameter has been largely employed to evaluate the efficacy of lysis processes (Dohányos et al.,
37
38
219 1997). It relates the soluble COD released by the lysis treatment to the particulate fraction (tCOD-sCOD) of
39
40
41
220 the sludge COD, that is the fraction that can be potentially hydrolyzed during the treatment. In Equation 1
42
43
44
221 sCOD_I is the soluble COD after the lysis process, sCOD₀ is the soluble COD of the untreated sludge and
45
46
222 tCOD₀ is the total COD of the sludge.
47
48

223 Figure 2 shows the DR values for all the lysis treatments carried out on both the WAS and 7-day digestate
49
50
51
224 samples. The results were grouped by type of treatment: only thermal, with Ca(OH)₂ at the doses of 4 and 8
52
53
225 g alkali/ 100 g TS and with NaOH at the same doses. Each group of bars reported the comparison between
54
55
226 the WAS sample (light bars) and the 7-day digestate (dark bars) at the three operating temperature values
56
57
227 (20, 70 and 90°C). As shown in Figure 2, the DR parameter varied from a few percent to up to 40%.
58
59
60
61
62
63
64
65

228 The only-thermal treatment, at the temperature of 70 °C, showed a better efficiency on digestate than on
1
229 WAS. An opposite behavior was observed for the working temperature of 90°C. In fact, the increase of
3
4
230 temperature from 70 °C to 90 °C doubled the efficiency in hydrolyzing particulate COD for the WAS sample,
5
6
231 the DR of which increased from approximately 12% to 22%. Conversely, for the same increase in
8
232 temperature, the increase of hydrolyzed COD in the digestate was only in the order of 45%, because the DR
10
11
233 rose from 15% to 21%. The chemical treatment carried out at 20 °C was, on average, more efficient on WAS
12
13
234 than on digestate. The trend, in most cases, reversed if the combined effect of the alkali agent and
15
16
235 temperature was considered. The thermo-chemical treatment carried out at 70 °C was, on average, more
17
18
236 efficient on digestate than on WAS.

237 DR values obtained from the hybrid lysis processes carried out on the 15-d digestate were of 9.1% and 15%,
22
23
238 for the temperature of 70°C and 90°C respectively. These DRs were sensibly lower than the values
24
25
239 registered for the WAS and 7-d digestate samples treated with the same operating conditions.

240 In the scientific literature, there are several studies that report the efficacy of thermal low-temperature or
29
30
241 hybrid thermo-chemical pre-treatments on WAS (Carrère et al., 2016; Zhen et al., 2017) or other substrates
31
32
242 (Passos et al., 2017), but very few examples of treatments carried out on intermediate sludge (i.e. sludge
34
35
243 after a partial digestion process) or digestate. Among these, Li and coauthors (2013) found a value of sCOD
36
37
244 in the order of 2,000 mg/L, after the treatment with a 0.1 M NaOH solution of a substrate produced by the
38
39
245 digestion of 80% primary sludge and 20% of biofilm sludge. The concentration of TS in the digested sludge
41
42
246 was in the order of 20 g/l, so the employed alkali dose should have been of 20 g NaOH/100 g TS. The value
43
44
247 of sCOD found by Li and coauthors (2013) must be referred to an estimated tCOD equal to 20-22,000 mg/l,
46
47
248 consistent with a TS content of 2%, to obtain a final DR of 10%. This result was in line with the outcome of
48
49
249 the tests carried out at ambient temperature in the present study.

50
51
250 The increase in pH value in samples that underwent a lysis treatment was an inevitable result of the alkali
53
54
251 addition. As shown in Figure 3, the final pH value depended on the type and dose of chemical used for the
55
56
252 test and, for a lesser extent, on the type of substrate (WAS or digestate). The highest pH values, in the
57
58
253 order of 10-11 pH units, were found for samples treated with NaOH at the dose of 8 g NaOH/100 g TS at 20
60
61
62
63
64
65

254 °C. Such a dose, in the order of 0.1 M, should produce a final pH value of approximately 13 pH units. In fact,
1
255 for each liter of treated sludge, there was approximately 45-48 g of TS and a dose of NaOH of 3.6 – 3.8 g
3
4
256 was employed for tests (i.e. approximately 0.1 moles, NaOH MW = 39.997 g/mol). However, the liberation
5
6
257 of sCOD, rich in organic acids, aided in buffering the increase of pH. The final pH value resulted from a
8
258 balance between the addition of alkali agent and the buffering capacity of the substrate. The buffer
10
11
259 phenomenon occurred in all series of treatments and was slightly more evident for the samples of WAS. In
12
13
260 fact, for those samples, the release of soluble COD was on average higher than for the digestate.
15
16
261 Treatment with alkali (or the combination alkali-low temperature), in addition to causing an evident
17
18
262 basification, also determined an increase in the electrical conductivity (EC) for most part of the samples.
20
263 Figure 4 shows the ratio between the EC after the lysis treatment and the EC of the untreated samples, of
22
264 1.09 mS/cm for the WAS and 3.53 mS/cm for the digestate, respectively, as shown in Table 1. Lysis pre-
24
25
265 treatments carried out on WAS determined an increase in the EC for all treatment conditions. Values of EC
27
266 increased up to 3-5 times when the samples of WAS were treated with doses of NaOH.
29
30
267 The hybrid treatment with NaOH on digestate produced increases in the EC values of quite limited extent
31
32
268 (1.2-1.7 times the reference value). Conversely, intermediate treatments on digestate produced a
34
35
269 reduction in the EC value when the treatment was carried out with only heat or by combining heat and
36
37
270 $\text{Ca}(\text{OH})_2$. In fact, EC reduced from 3.53 mS/cm (for the untreated sample) to 2.85 mS/cm (-20%, for the
38
39
271 sample treated at 20°C with 4% of $\text{Ca}(\text{OH})_2$) to 1.74 mS/cm (-50%, for the sample treated at 20°C with 8% of
41
42
272 $\text{Ca}(\text{OH})_2$). The EC decrease was much more pronounced for the lowest temperature values. Decrease in EC
43
44
273 may be due to the generation of calcium salts, with very low solubility, and subsequent precipitation.
46
47
274
48
49
275

3.3 Anaerobic digestion tests

276 AD tests carried out in this and in a previous work (Ruffino et al., 2016) showed a substantial variability in
53
277 the specific production of biogas and methane of the raw WAS sample (i.e. not subjected to any treatment)
55
278 from one series of tests to another. The specific biogas production amounted to values in the order of
58
279 $0.257 \pm 0.020 \text{ Nm}^3/\text{kg VS}_{\text{added}}$ (average on five different raw WAS samples), while the specific production of
60
61
62
63
64
65

280 methane was $0.166 \pm 0.015 \text{ Nm}^3/\text{kg VS}_{\text{added}}$, with methane volumetric percentages that ranged between 61
1
281 and 67%. In order to compare the results obtained in the different series of tests, all the specific methane
3
4
282 production (SMP) curves have been scaled on a reference untreated WAS sample characterized by a
5
6
283 specific production of methane equal to the average value ($0.166 \text{ Nm}^3/\text{kg VS}_{\text{added}}$) found over all series.
8
284 Curves of Figure 5 show the evolution of SMP for WAS samples treated under different conditions (only-
10
11
285 thermal or a combination of thermal and alkali treatments). Digestibility tests lasted 21 days. After that
12
13
286 time the tests were considered completed since the daily marginal production of biogas or methane was
15
16
287 less than 1% of the overall production (VDI Standard 2006). The only-thermal treatment carried out on the
17
18
288 WAS sample determined an increase in SMP of 14% for the temperature of 70°C and of approximately 20%
20
289 for the temperature of 90°C. These observations were in line with the results of a previous study (Ruffino et
22
23
290 al., 2015) carried out on WAS samples collected from the same WWTP and subjected to thermal pre-
24
25
291 treatments. In that case, SMP increases of 21% and 31% were recorded after thermal pre-treatments
27
292 processes carried out for 3 hours at 70 and 90 °C respectively. The tests described in that study differed
29
30
293 from those reported in the present study not only for the duration of the pre-treatment (180 minutes vs. 90
31
32
294 minutes) but also for the ratio between substrate and inoculum. In the old tests this ratio was in fact in the
34
35
295 order of 2.5.
36
37
296 A comparison between only-thermal and hybrid pre-treatments carried out at the same temperature value
38
39
297 demonstrated that hybrid pre-treatments were more effective in biogas/methane production. Hybrid pre-
41
42
298 treatments produced an SMP increase of 40% and 66% for the sample treated at 70 °C and 90°C
43
44
299 respectively. The SMP increase was calculated with reference to the untreated sample.
46
47
300 Figure 6 compares the curves of SMP obtained for WAS and the two samples of digestate treated under the
48
49
301 same operating conditions (thermo-alkali with 4% NaOH at temperature values of 70°C and 90°C).
50
51
302 Untreated digestate with a HRT of 7 days produced approximately 16% less methane than the sample of
53
54
303 untreated WAS ($0.143 \pm 0.003 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$ vs. $0.166 \pm 0.015 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$). When the 7-day
55
56
304 digestate was subjected to a hybrid process, its SPM increased by 31% and 54% at 70°C and 90°C
58
59
305 respectively. The 7-day digestate treated at 70°C with 4% NaOH generated $0.185 \pm 0.003 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$.

306 Conversely, SMP rose to $0.223 \pm 0.002 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$ when the hybrid treatment was carried out at
1
307 90°C . These percentage increases were of the same order of magnitude of those found by Boni and
3
4
308 coauthors (2016). They tested ultrasonication in order to make the organic matter contained in
5
6
309 lignocellulosic AD residues usable for new AD processes and they obtained a maximum gain in biogas
8
9
310 production in the order of 30%. It has to be pointed out that the digestate employed for the tests in Boni et
10
11
311 al. (2016) had a residual SMP in the order of $0.150 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$, similar to the 7-day digestate used in
12
13
312 this work. Conversely, Sambusiti and coauthors (2015) did not observe a beneficial effect of thermal and
15
16
313 alkaline post-treatments in enhancing methane potentials of digestates from agricultural residues.
17
18
314 SMP of the 15-day digestate was approximately 250% less than that of the untreated WAS (0.047 ± 0.001
19
20
315 $\text{Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$ vs. $0.166 \pm 0.015 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$). Hybrid treatments at 70 and 90°C could increase
22
23
316 SMP by respectively 131 and 184% compared to the untreated digestate sample. However, that increase
24
25
317 was not sufficient to equal the specific production of the untreated WAS. SMPs of the 15-day digestate
27
28
318 were in fact of $0.109 \pm 0.005 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$ and $0.134 \pm 0.004 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$, when intermediate
29
30
319 treatments were carried out at 70 and 90°C , respectively.
32
320 These results demonstrated that a significant amount of organic matter could not be converted to methane
34
35
321 and carbon dioxide in a 15-day mesophilic AD process. TS and VS content of the sample used for the tests
36
37
322 was respectively in the order of 2.58% and 1.62% ($\text{VS}/\text{TS} = 0.626$). TSs and VSs of the substrate fed to the
38
39
323 digester 15 days before (i.e. untreated WAS) were 3.33% and 2.27% respectively ($\text{VS}/\text{TS} = 0.681$). That
41
42
324 means that the VS reduction observed in the 300-L digester was in the order of only 30%. This was in line
43
44
325 with the results reported in some studies that demonstrated that a 15-day AD process carried out in
46
47
326 mesophilic conditions could degrade no more than 30-40% of the overall organic substrate (Nielsen et al.,
48
49
327 2011; Takashima and Tanaka, 2014).
50
51
328 Figure 7 shows the possible result of the combination of an AD process carried out on an untreated WAS
53
54
329 sample and the subsequent application of intermediate treatments to 7-day and 15-day digestates. A 7-day
55
56
330 AD process carried out on an untreated WAS sample could extract approximately 65% of the ultimate
58
59
60
61
62
63
64
65

331 methane content. If the AD process lasted 15 days, the amount of methane extracted rose to 95% (see
1
332 Figures 5 and 6).

333 Curves 1 (in diagrams a and b of Figure 7) represent the time evolution of SMP of the WAS samples that
2
334 underwent a hybrid process carried out at 70 or 90°C. Curves 2 combine the SMP due to a 7-day AD process
3
335 carried out on an untreated WAS sample with the SMP due to an intermediate treatment carried out on a
4
336 7-day digestate. Finally, curves 3 combine the result of a 15-day AD process carried out on an untreated
5
337 WAS sample with the results of an intermediate treatment of a 15-day digestate.

338 Figure 7a demonstrates that the combination of AD plus hybrid intermediate treatment at 70°C made
6
339 possible to produce the same amount of methane (i.e. $0.233 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$), obtained with the hybrid
7
340 pre-treatment carried out on WAS, in a shorter time. In fact, the final SMP recorded after a 20-day one-
8
341 stage AD process was obtained already after 12 days from the beginning of the tests. When pre- or
9
342 intermediate treatments were carried out at 90°C (see Figure 7b), a (7+8)-day process that includes a first-
10
343 stage AD, an intermediate treatment and a second-stage AD was necessary to equal the production
11
344 obtained from a WAS sample subjected to pre-treatment and subsequently digested for 20 days.

345 The outcomes of the experimentation demonstrated that, for both temperature values (70 and 90°C), a
12
346 process that combines an intermediate treatment of a 7-day digestate with a two-stage digestion with an
13
347 overall length of 20 days (7+13), could produce more methane than the sequence of pre-treatment and AD
14
348 with the same duration. Specifically, the intermediate treatment carried out at 70°C produced 0.286 Nm^3
15
349 $\text{CH}_4/\text{kg VS}_{\text{added}}$ vs. $0.232 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$ generated using the pre-treatment (+23%). Conversely, the
16
350 intermediate treatment carried out at 90°C produced $0.317 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$ vs. $0.274 \text{ Nm}^3 \text{ CH}_4/\text{kg VS}_{\text{added}}$
17
351 (+16%).

352 As shown in Figure 7, in no cases (70 or 90°C) the combination of AD of untreated WAS, intermediate
18
353 treatment of a 15-day digestate and subsequent second-stage digestion made possible to obtain a SMP
19
354 higher than those obtained with pre-treatments. In fact, the SMP of the combined system could equal that
20
355 of the pretreated sludge only if the combined process had a whole length of 30 days or more.

356 **4. Technical assessment**

1
357 The technical and economic assessment carried out in this Section was referred to the full scale SMAT
3
4
358 WWTP located in Castiglione Torinese. The treatment scheme for pre- and intermediate treatments is
5
6
359 shown in Figure 8.
8

360 It is well known that a mesophilic AD process is self-sustainable if the heat generated by the process is
10
11
361 sufficient to heat the sludge from the ambient (approx. 15°C) to the process (38°C) temperature and keep
12
13
362 the temperature constant into the digester. In fact, one part of the heat provided must offset the heat
15
16
363 losses, through the digester walls, due to the exchange with the exterior environment. The heat losses can
17
18
364 be evaluated by considering the geometry of the digester, the materials employed for its construction and
20
21
365 the temperature of soil (15°C) and exterior environment (as monthly averages, as reported in UNI 10349
22
23
366 rule, Ruffino et al., 2014). This assessment considered the heat losses with the outside in the worst case
24
25
367 (i.e. winter condition). For one digester, they amounted at 158.5 MJ/h.

26
368 The sludge flow rate was of 58.8 m³/h, for both primary and secondary sludge, under normal operating
29
30
369 conditions of the WWTP. It was also assumed that the average VS/TS ratio was 0.7 for both kinds of sludge.
31

32
370 All the thermal balances performed to assess the technical sustainability of pre- and intermediate
34
35
371 treatments considered:

- 372 • a thermal efficiency of the combined heat and power (CHP) unit of 0.42;
- 373 • an electrical efficiency of the CHP unit of 0.42;
- 374 • an efficiency in the thermal exchange processes of 1;

375
376 In the case of pre-treatments, heat must obviously be provided also for thermal (or hybrid) hydrolysis. If
48
49
377 the sludge is thermal treated, its extra heat can be conveniently used to heat primary sludge (see Figure 8).
50

51
378 In the case of pre-treatments, secondary sludge heated at 70 or 90°C, after hybrid treatment, was mixed
53
54
379 with primary sludge (at ambient temperature). Both types of sludge were then digested with a HRT of 20
55
56
380 days.

57
381 A complete thermal balance for the pre-treatment scenario must include:
60
61
62
63
64
65

382 $Q_{HYD_P} + Q_{LOSS} + Q_{PRIM} = Q_{AD} + Q_{HYD_SLUD}$

- 383 • Q_{HYD_P} , is the thermal power necessary to heat the secondary sludge from the ambient to the pre-
384 treatment temperature (70 or 90°C) and maintain the process for the fixed contact time (1.5
385 hours);
- 386 • Q_{LOSS} , are the heat losses (integrated over time) with the exterior environment during the AD
387 process;
- 388 • Q_{PRIM} , is the thermal power necessary to heat the primary sludge from the ambient to the digester
389 (mesophilic) temperature;
- 390 • Q_{AD} , is the thermal power generated in the AD process;
- 391 • Q_{HYD_SLUD} , is the thermal power available, after secondary sludge hydrolysis, to heat the primary
392 sludge before digestion.

393 If the TS content of the primary sludge was fixed to 3.5%, positive terms of the thermal balance equaled the
394 negative terms when the TS content of the secondary sludge was of 3.7%, at 70°C, and 4.9%, at 90°C,
395 respectively.

396 In the case of intermediate treatments, as shown in Figure 8, the secondary sludge fed the first-stage
397 digester (HRT = 7 days) after a pre-thickening process. This process increased the sludge TS content up to
398 2.75%. Consequently, the mass flow rate of dry solid was 1617.5 kg/h. The secondary sludge was then
399 digested for 7 days and subsequently treated at 70 or 90°C with alkali (NaOH 4%). Heated sludge was mixed
400 with the cold primary sludge and them both were finally digested with a HRT of 13 days.

401 A complete thermal balance for the intermediate treatment scenario must include:

402 $Q_{WARM} + Q_{LOSS1} + Q_{HYD_I} + Q_{PRIM} + Q_{LOSS2} = Q_{AD1} + Q_{AD2} + Q_{HYD_SLUD}$

- 403 • Q_{WARM} , is the thermal power necessary to heat the secondary sludge from the ambient to the
404 digester (mesophilic) temperature in the first-stage AD;
- 405 • Q_{LOSS1} , are the heat losses (integrated over time) with the exterior environment in the first- and
406 second-stage digesters;

- Q_{HYD_I} , is the thermal power necessary to warm the digestate, from secondary sludge, from mesophilic to the intermediate treatment temperature (70 or 90°C) and maintain the process for the fixed contact time (1.5 hours);
- Q_{PRIM} , is the thermal power necessary to warm the primary sludge from the ambient to the digester (mesophilic) temperature;
- Q_{ADI} , is the thermal power generated in the first- and second-stage AD process;
- Q_{HYD_SLUD} , is the thermal power available, after the intermediate hydrolysis of the digestate from the secondary sludge, to warm the primary sludge before digestion.

Figure 9a shows the thermal power (kW) required and available, as a function of the TS content of the secondary sludge, for the scenario that considers intermediate treatments at 70 and 90°C. The positive terms of the thermal balance equaled the negative terms when the TS content of secondary sludge was respectively of 3.25%, at 70°C, and 4.25%, at 90°C. As in the previous case, it was assumed that the TS content of the primary sludge before digestion was in the order of 3.5%. It was also assumed that the TS of the secondary sludge was not altered by the first-stage AD process.

If a focus is made only on the stage of mixing between primary and secondary (after first-stage digestion and IHP) sludge, it can be demonstrated that not in all cases the heat carried by the secondary sludge after IHP was sufficient to warm the primary sludge to the temperature value required for the second-stage AD process. In detail, when the digestate from the first-stage AD was treated at 90°C (see Figure 9b), the heat supplied by this flux was sufficient to warm the primary sludge for any digestate TS content (up to 6.5%). Conversely, when the first-stage digestate was treated at 70°C, only TS values of less than 4.25% may guarantee the thermal self-sustainability of the mixing stage.

5. Economic analysis

Tests carried out in this and in a previous work (Ruffino et al., 2016) demonstrated that, for low temperature values (<100°C) and low dosage of alkali (4%), a combination of thermal and alkali pre-

433 treatments was more effective than a single treatment. However, alkali used for the treatment has a cost of
1
434 0.3 €/kg (Solvay, 2016). The increase in methane, and the consequent increase in the produced heat and
3
435 electricity, must balance the reagent cost. As shown in Section 3.1, the treatment with alkali increased the
4
5
6
436 pH to values in the order of 8.5 – 8.8, depending on the process temperature. In a previous experience, it
8
437 was demonstrated that pH values not too far from neutrality (i.e. in the order of 8.5) did not adversely
10
11
438 affect the performance of the AD process (Ruffino et al., 2016). In fact, the inoculum could buffer the
12
13
439 increase in pH due to the alkali effect. Then, acidic agents were considered not to be necessary in the
15
16
440 implementation of hybrid pre-treatments.

17
18
441 For the economic analysis, it was assumed that all the heat produced by the digesters was used to sustain
20
21
442 the whole system (combination of hydrolysis and digestion), according to the working conditions fixed in
22
23
443 Section 2.1. In this way, the employment of an auxiliary fuel can be completely avoided. The plant's
24
25
444 managers can sell the net produced electricity at the price of 0.217 €/kWh, that includes the public subsidy
27
28
445 (0.077 €/kWh). Therefore, the economic value of the methane used to produce electricity was equal to
29
30
446 0.885 €/Nm³ CH₄.

31
32
447 The economic revenues of the plant in the absence of pre- or intermediate processes for the treatment of
34
35
448 secondary sludge was in the order of 530 €/h (Ruffino et al., 2014). The introduction of thermal or hybrid
36
37
449 pre-treatments in the full scale WWTP could increase the revenues from electricity sale between 13% and
38
39
450 25%. Conversely, intermediate treatments on a 7-day digestate could provide a gain of 26% or 32%,
41
42
451 depending on the process temperature (70 or 90°C, see Table 2). Only the scenario that considered the use
43
44
452 of alkali at ambient temperature (20°C) determined a worsening in the economic performance of the plant.
46
47
453 In this case, the value of the electricity produced from AD was not sufficient to compensate for the costs of
48
49
454 alkali and acid reagents. In fact, under this scenario, the pH resulting after the hybrid hydrolysis was too
50
51
455 high (9.9) and it had to be corrected with the addition of an acid before digestion.

456 **Conclusions**

1
457 This paper wanted to demonstrate the superiority of intermediate lysis treatments compared to traditional
3
458 pre-treatments carried out under the same operating conditions. Intermediate treatments could make the
5
6
459 residual organic substance of a partially digested sludge usable for a second-stage AD process. To the best
8
460 of our knowledge, until now only very few studies have focused on the comparison of the performances of
10
11
461 these two operating schemes. This work can get some clues for a more effective treatment of sewage
12
13
462 sludge in a full scale WWTP.

15
16
463 The analysis was carried out at three levels. Values of DR, specific productions of biogas and methane, and
17
18
464 final revenues from the electricity sale were determined by performing tests on WAS and digestates, with
19
20
465 HRTs of 7 and 15 days respectively, and by using the tests' outcomes for a full-scale cost-benefit
22
23
466 assessment.

24
25
467 It was demonstrated that:

27
468 (1) when results were reported in terms of DR values, thermal and hybrid lysis treatments were on
29
30
469 average more effective on a digestate than on a WAS. This outcome was particularly evident when
31
32
470 mild treatments (i.e. carried out at 70°C or in the presence of Ca(OH)₂) were applied;

34
35
471 (2) intermediate treatments were effective in making the residual organic substance of a 7-day digestate
36
37
472 usable for a second-stage AD process. In fact, under this scenario, the methane generated in a two-
38
39
473 stage AD process, with an in-between intermediate treatment, was 23% and 16% higher than in the
41
42
474 scenario that considers traditional pre-treatments, with 4% NaOH, at 70 and 90°C respectively.
43
44
475 Conversely, in no cases (70 or 90°C) the combination of a 15-day AD process of untreated WAS
46
476 followed by an intermediate treatment and a second-stage AD, made possible to obtain SMPs higher
48
49
477 than those obtained with pre-treatments.

50
51
478 (3) the introduction of thermal or hybrid pre-treatments in a full scale WWTP (2,000,000 p.e.) could
53
54
479 increase the revenues from the electricity sale between 13% and 25%, in comparison with the present
55
56
480 scenario. Conversely, intermediate treatments on a 7-day digestate could provide a gain of 26% or
57
58
481 32%, depending on the process temperature (70 or 90°C).

482
1
483
3
4
484
5
6
485
8
9
486
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Acknowledgments

This paper is dedicated to the memory of prof. Giuseppe Genon.

SMAT, Societa` Metropolitana Acque Torino, is gratefully acknowledged for funding this research.

The authors wish also to thank Giovanna Zanetti for performing CHNS characterization of the samples.

References

1. APHA, AWWA, WEF. Standard Methods for examination of water and wastewater. 22nd ed. Washington: American Public Health Association; 2012, 1360 pp. ISBN 978-087553-013-0
2. Boni M.R., D'Amato E., Poletti A., Pomi R., Rossi A., 2016. Effect of ultrasonication on anaerobic degradability of solid waste digestate. *Waste Manage.* 48, 209-217.
3. Cano R., Pérez-Elvira S.I., Fdz-Polanco F., 2015. Energy feasibility study of sludge pretreatments: A review. *Appl Energ* 149, 176–185
4. Carrère, H., Dumas, C., Battimelli, A., Batstone, D.J., Delgenès, J.P., Steyer, J.P., Ferrer, I., 2010. Pretreatment methods to improve sludge anaerobic degradability: a review. *J. Hazard. Mater.* 183, 1–15.
5. Carrère H., Antonopoulou G., Affes R., Passos F., Battimelli A., Lyberatos G., Ferrer I., 2016. Review of feedstock pretreatment strategies for improved anaerobic digestion: From lab-scale research to full-scale application. *Bioresource Technol.* 199, 386-397.
6. Collivignarelli M.C., Castagnola F., Sordi M., Bertanza G., 2015. Treatment of sewage sludge in a thermophilic membrane reactor (TMR) with alternate aeration cycles. *J Environ Manage* 162, 132-138.
7. Dohányos M., Záborská J., Jeníček P., 1997. Enhancement of sludge anaerobic digestion by use of a special thickening centrifuge. *Water Sci. Technol.* 36, 145-153.
8. Fiore S., Ruffino B., Campo G., Roati C., Zanetti M.C., 2016. Scale-up evaluation of the anaerobic digestion of food-processing industrial wastes. *Renew Energ*, 96, 949-959.
9. Garrido J.M., Fdz-Polanco M., Fdz-Polanco F., 2013. Working with energy and mass balances: a conceptual framework to understand the limits of municipal wastewater treatment. *Water Sci Technol* 67(10), 2294–2301.
10. Li H., Zou S., Li C., Jin Y., 2013. Alkaline post-treatment for improved anaerobic digestion. *Bioresource Technol.* 140, 187-191.
11. Nielsen H.B., Thygesen A., Thomsen A.B. and Schmidt J.E., 2011. Anaerobic digestion of waste activated sludge – comparison of thermal pretreatments with thermal inter-stage treatments. *J Chem Technol Biotechnol* 86, 238–245.
12. Ortega-Martinez E., Sapkaite I., Fdz-Polanco F., Donoso-Bravo A., 2016. From pre-treatment toward inter-treatment. Getting some clues from sewage sludge biomethanation. *Bioresource Technol.* 212, 227–235.
13. Panepinto D., Fiore S., Zappone M., Genon G., Meucci L., 2016. Evaluation of the energy efficiency of a large wastewater treatment plant in Italy. *Appl Energ* 161, 404–411.
14. Passos F., Ortega V., Donoso-Bravo A., 2017. Thermochemical pretreatment and anaerobic digestion of dairy cow manure: Experimental and economic evaluation. *Bioresource Technol.* 227, 239-246.
15. Roeleveld P.J., van Loosdrecht M.C.M., 2002. Experience with guidelines for wastewater characterisation in The Netherlands. *Water Sci Technol* 45(6), 77–87.
16. Ruffino, B., Campo, G., Zanetti, M.C., Genon, G., 2014. Improvement of activated sludge anaerobic digestion: thermal and economical perspectives. *WIT Trans. Ecol. Environ.* 190, 979–991. DOI 10.2495/EQ140922
17. Ruffino B., Campo G., Genon G., Lorenzi E., Novarino D., Scibilia G., Zanetti M.C., 2015. Improvement of anaerobic digestion of sewage sludge in a wastewater treatment plant by means of mechanical and thermal pre-treatments: Performance, energy and economical assessment. *Bioresource Technol.* 175, 298-308.

18. Ruffino B., Campo G., Cerutti A., Zanetti M.C., Lorenzi E., Scibilia G., Genon G., 2016. Preliminary Technical and Economic Analysis of Alkali and Low Temperature Thermo-alkali Pretreatments for the Anaerobic Digestion of Waste Activated Sludge. *Waste Biomass Valor.* 7, 667-675. DOI 10.1007/s12649-016-9537-x
19. Sambusiti, C., Monlau, F., Ficara, E., Musatti, A., Rollini, M., Barakat, A., Malpei, F., 2015. Comparison of various post-treatments for recovering methane from agricultural digestate. *Fuel Process. Technol.* 137, 359–365.
20. Shana A., Ouki S.K., Asaadi M., Pearce P., 2011. Application of an innovative process for improving mesophilic anaerobic digestion of sewage sludge. In: 16th European Biosolids and Organic Resources Conference.
21. Shana A., Ouki S., Asaadi M., Pearce P., Mancini G., 2013. The impact of intermediate thermal hydrolysis on the degradation kinetics of carbohydrates in sewage sludge. *Bioresource Technol.* 137, 239–244.
22. Shana A.D., Ouki S., Asaadi M., Pearce P., 2015. The impact of intermediate thermal hydrolysis process and conventional thermal hydrolysis process on biochemical composition during anaerobic digestion of sewage sludge. *Proceedings of 20th European Biosolids & Organic Resources Conference & Exhibition, Manchester, 9-11/11/2015*, pp. 1-15.
23. Solvay. <http://www.solvaychemicals.com/EN/Home.aspx> (2016)
24. Takashima M., Tanaka Y., 2014. Acidic thermal post-treatment for enhancing anaerobic digestion of sewage sludge. *Journal of Environmental Chemical Engineering* 2, 773–779.
25. Teo C.W., 2016. Unified Theory and Model for Anaerobic Hydrolysis in Municipal Wastewater Treatment: Review of Enzymological Aspects and Hydrolysis Assessments. *J. Environ. Eng.*, 04016041.
26. Traversi D., Romanazzi V., Degan R., Lorenzi E., Carraro E., Gilli G., 2015. Microbial-chemical indicator for anaerobic digester performance assessment in full-scale wastewater treatment plants for biogas production. *Bioresource Technol.* 186, 179-191.
27. van Lier, J.B., Mahmoud, N., Zeeman, G., 2008. Anaerobic wastewater treatment In: *Biological Wastewater Treatment. Principles modeling and Design*. Chapter 16. Henze, M., van Loosdrecht, M.C.M., Ekama, G.A., Brdjanovic, D. eds. ISBN: 9781843391883. IWA Published London UK.
28. VDI Standard 2006. VDI 4630 Fermentation of organic materials. Characterization of the substrate, sampling, collection of material data, fermentation tests, pp. 92, available on line at <http://www.vdi.eu/guidelines>, last accessed 10/01/2017.
29. Williams T.O., Burrowes P., Fries K., Newbery C., Whitlock D., 2015. Treatment of WAS with thermal hydrolysis and mesophilic anaerobic digestion. *Proceedings of 20th European Biosolids & Organic Resources Conference & Exhibition, Manchester, 9-11/11/2015*, pp. 1-8.
30. Xiao B., Liu C., Liu J., Guo X., 2015. Evaluation of the microbial cell structure damages in alkaline pretreatment of waste activated sludge. *Bioresource Technol.* 196, 109-115.
31. Zhang T., Wang Q., Ye L., Yuan Z., 2016. Enhancing post anaerobic digestion of full-scale anaerobically digested sludge using free nitrous acid treatment. *J Ind Microbiol Biotechnol.* 43, 713–717, DOI 10.1007/s10295-016-1742-x.
32. Zhen G., Lu X., Kato H., Zhao Y., Li Y.-Y., 2017. Overview of pretreatment strategies for enhancing sewage sludge disintegration and subsequent anaerobic digestion: Current advances, full-scale application and future perspectives. *Renew. Sust. Energ. Rev.*, 69, 559-577.

List of Figure legends

Figure 1. Apparatus for anaerobic digestion tests

Figure 2. DR values after lysis processes

Figure 3. pH values after lysis processes

Figure 4. EC/EC₀ values after lysis processes

Figure 5. Time evolution of SMP for WAS samples pre-treated under different operating conditions

Figure 6. Time evolution of SMP obtained for WAS and the two samples of digestate (7-day and 15-day) treated under the same operating conditions

Figure 7. Curves 1. Time evolution of SMP of WAS after a hybrid process carried out at 70°C (a) or 90°C (b). Curves 2. Combination of the cumulative SMP due to a 7-day AD process on untreated WAS with the SMP due to an intermediate treatment on a 7-day digestate (a, 70°C; b, 90°C). Curves 3. Combination of the SMP due to a 15-day AD process on untreated WAS with the SMP due to an intermediate treatment on a 15-day digestate (a, 70°C; b, 90°C).

Figure 8. Treatment scheme for pre- and intermediate treatments

Figure 9. Thermal power (kW) required and available for IHPs (a) and thermal balance for the mixing of primary and secondary sludge (b) as a function of the TS content of the secondary sludge

List of Table legends

Table 1. Characteristics of the three substrates used for the experimentation

Table 2. Summary of the results obtained from digestibility tests and economic analysis



Figure 1. Apparatus for anaerobic digestion tests




Figure 2. DR values after lysis processes




Figure 3. pH values after lysis processes




Figure 4. EC/EC₀ values after lysis processes




Figure 5. Time evolution of SMP for WAS samples pre-treated under different operating conditions




Figure 6. Time evolution of SMP obtained for WAS and the two samples of digestate (7-day and 15-day) treated under the same operating conditions






Figure 7. Curves 1. Time evolution of specific methane production of WAS after a hybrid process carried out at 70°C (a) or 90°C (b). Curves 2. Combination of the cumulative SMP due to a 7-day AD process on untreated WAS with the SMP due to an intermediate treatment on a 7-day digestate (a, 70°C; b, 90°C).

Curves 3. Combination of the SMP due to a 15-day AD process on untreated WAS with the SMP due to an intermediate treatment on a 15-day digestate (a, 70°C; b, 90°C).

**CONVENTIONAL
PRE-TREATMENTS**



**IHP, INTERMEDIATE
HYDROLYSIS PROCESS**




Figure 8. Treatment scheme for pre- and intermediate treatments





Figure 9. Thermal power (kW) required and available for IHPs (a) and thermal balance for the mixing of primary and secondary sludge (b) as a function of the TS content of the secondary sludge

	TS (%)	VS/TS (%)	pH	EC (mS/cm)	C (%)	H (%)	N (%)	S (%)	O (%)	gO ₂ /gVS	tCOD (mg/l)	sCOD (mg/l)	NH ₄ ⁺ (mg/l)
WAS	4.88	0.70	6.78	1.09	49.2	6.65	7.77	0.82	35.6	1.347	46,000	210	128
7-day Digestate	4.58	0.67	7.36	3.53	49.6	6.77	7.64	0.77	35.3	1.372	42,100	125	299
15-day Digestate	4.30	0.63	7.56	2.88	NA	NA	NA	NA	NA	NA	37,200	525	35

NA: not available

Table 1. Characteristics of the three substrates used for the experimentation

Treatment	Final pH value	CH ₄ specific production (Nm ³ /kg VS _{added})	Increase in CH ₄ specific production (%)	Increase in the revenue (%)
Untreated WAS	6.78	0.166	-	-
20°C, NaOH 4% (*)	9.93	0.212	+ 28.0	-5.3
70°C	6.42	0.189	+ 14.2	+13.2
70°C, NaOH 4%	8.81	0.233	+ 40.5	+17.2
90°C	6.49	0.199	+ 20.1	+16.0
90°C, NaOH 4%	8.51	0.276	+ 66.6	+24.5
7-day digestate, 70°C, NaOH 4%	8.79	0.287	+ 72.7	+26.4
7-day digestate, 90°C, NaOH 4%	8.70	0.317	+ 91.3	+32.3

(*) addition of HCl at a dose of 1.5 g HCl/ 100 g TS required to decrease the pH value up to 8.5

Table 2. Summary of the results obtained from digestibility tests and economic analysis