

# Assessment of inspection strategies in assembly manufacturing processes

Elisa Verna<sup>1</sup>, Gianfranco Genta<sup>2</sup>, Fiorenzo Franceschini<sup>3</sup> and Maurizio Galetto<sup>4</sup>

**Key words:** quality control, inspection effectiveness, inspection cost

## Extended abstract

In general, assembly manufacturing processes may be decomposed into a number ( $m$ ) of workstations, i.e., process steps, each one potentially critical in generating defects [2,4]. In each workstation, different quality controls may be performed. Each  $i$ -th workstation can be described through three parameters [4]: (i)  $p_i$ : probability of occurrence of a defective-workstation-output; (ii)  $\alpha_i$ : probability of erroneously signalling a defective-workstation-output after the control (i.e., type-I inspection error); (iii)  $\beta_i$ : probability of erroneously not signalling a defective-workstation-output after the control (i.e., type-II inspection error), where  $i=1,\dots,m$ . The first parameter ( $p_i$ ) is a physiological characteristic of the process in normal working conditions, and can be *a priori* estimated using defect-generation models or empirical/simulation methods [3,5]. The estimates of  $\alpha_i$  and  $\beta_i$  depend on the characteristics of the inspection procedure and the technical skills and/or experience of the inspector [1]. According to this model, two indicators which depict the overall effectiveness and economic convenience of an inspection strategy may be obtained

---

<sup>1</sup> Elisa Verna  
DIGEP, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy,  
e-mail: elisa.verna@polito.it

<sup>2</sup> Gianfranco Genta  
DIGEP, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy,  
e-mail: gianfranco.genta@polito.it

<sup>3</sup> Fiorenzo Franceschini  
DIGEP, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy,  
e-mail: fiorenzo.franceschini@polito.it

<sup>4</sup> Maurizio Galetto  
DIGEP, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy,  
e-mail: maurizio.galetto@polito.it

[2]. The first one,  $D$ , is the mean total number of defective-workstation-outputs which are erroneously not signaled in all the inspections, defined as [4]:

$$D = \sum_{i=1}^m p_i \cdot \beta_i \quad (1)$$

The second one is the total inspection cost,  $C_{tot}$ , which can be expressed as [2,3]:

$$C_{tot} = \sum_{i=1}^m [c_i + NRC_i \cdot p_i \cdot (1 - \beta_i) + URC_i \cdot (1 - p_i) \cdot \alpha_i + NDC_i \cdot p_i \cdot \beta_i] \quad (2)$$

where  $c_i$  represents the cost of the inspection activity;  $NRC_i$  and  $URC_i$  are respectively the necessary- and unnecessary-repair cost; and  $NDC_i$  is the cost of undetected defects.

The proposed model and the two inspection indicators, reported in Eqs. (1) and (2), are supposed to have both an analytical and predictive connotation. According to a cost-benefit logic, the combined use of the inspection indicators allows the comparison of alternative inspection strategies in terms of effectiveness and cost, and the selection of the most appropriate according to the manufacturer requirements. This may represent a powerful and practical approach to assist inspection designers in early design phases of new assembly manufacturing processes. For instance, it may be adopted to choose between a complete inspection, i.e., when quality controls are performed after each workstation, and a partial inspection in selected workstations. Once the optimal strategy has been identified through the proposed method, it will be used each time an inspection activity is carried out. Since the proposed indicators enable the identification of the most critical workstations, more effective control procedures may be designed. Furthermore, as the assessment of inspection strategies is closely related to inspection errors  $\alpha_i$  and  $\beta_i$ , a study on the impact that inspection errors have on inspection strategies selection is proposed.

The proposed approach may be exploited for a wide range of industrial processes, and is particularly useful in the case of short-run productions, for which most of the statistical process control techniques are unsuitable. In this work, a case study concerning the comparison of three alternative inspection procedures for a production of hardness testing machines is presented.

## References

1. Duffuaa, S.O., Khan, M.: Impact of Inspection Errors on the Performance Measures of a General Repeat Inspection Plan. *Int. J. Prod. Res.*, 43(23), 4945-4967 (2005)
2. Franceschini F., Galetto M., Genta G., Maisano D.A.: Selection of quality-inspection procedures for short-run productions. *Int. J. Adv. Manuf. Technol.*, 99(9-12), 2537-2547 (2018)
3. Galetto M., Verna E., Genta G., Franceschini F.: Robustness analysis of inspection design parameters for assembly of short-run manufacturing processes. In: *Proceedings book of the 3rd International Conference on Quality Engineering and Management*, pp. 255-274 (2018)
4. Genta G., Galetto M., Franceschini F.: Product complexity and design of inspection strategies for assembly manufacturing processes. *Int. J. Prod. Res.*, 1-11 (2018)
5. Krugh, M., Antani, K., Mears, L., Schulte, J.: Prediction of Defect Propensity for the Manual Assembly of Automotive Electrical Connectors. *Procedia Manuf.*, 5, 144-157 (2016)