POLITECNICO DI TORINO Repository ISTITUZIONALE

Steady-state analysis of pollutant transport to assess landfill liner performance

Original

Steady-state analysis of pollutant transport to assess landfill liner performance / Dominijanni, A.; Manassero, M. - In: ENVIRONMENTAL GEOTECHNICS. - ISSN 2051-803X. - STAMPA. - 8:7(2021), pp. 480-494. [10.1680/jenge.19.00051]

Availability: This version is available at: 11583/2770580 since: 2022-02-01T17:15:35Z

Publisher: ICE Publishing

Published DOI:10.1680/jenge.19.00051

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Steady-State Analysis of Pollutant Transport To Assess Landfill Liner Performance

by

Andrea Dominijanni^{1*} and Mario Manassero²

¹ Assistant Professor, Department of Structural, Geotechnical and Building Engineering, Politecnico

di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (Italy); Ph: +39 011 090 7705; Fax +39 011

090 4899; E-mail: andrea.dominijanni@polito.it

ORCID number: https://orcid.org/0000-0002-0254-6002

² Professor, Department of Structural, Geotechnical and Building Engineering, Politecnico di Torino,

Corso Duca degli Abruzzi 24, 10129 Torino (Italy); Ph: +39 011 090 4820; Fax +39 011 090 4899;

E-mail: <u>mario.manassero@polito.it</u>

ORCID number: https://orcid.org/0000-0001-7621-5022

* Corresponding Author

Word count: 5203

Number of Tables: 3

Number of Figures: 12

ABSTRACT

New analytical solutions are presented for the assessment of the impact of contaminant transport through landfill liners on groundwater quality under steady-state conditions. These solutions can be applied to evaluate the equivalency and the effectiveness of landfill liners, even those that include a geomembrane, taking into account the presence of a natural attenuation layer interposed between the engineered barrier and the underlying aquifer. The impact of a contaminant on groundwater quality is quantified through the determination of the contaminant concentration along the horizontal direction of the groundwater flow for the case of thin aquifers that are only a few meters thick. For the case of thick aquifers, both a closed-form analytical solution and a step-by-step numerical solution are provided for the calculation of the variations in the contaminant concentration in horizontal and vertical directions within the aquifer.

Keywords chosen from ICE Publishing list: Groundwater, Numerical methods, Waste containment & disposal system

List of notation

α_{T}	is the transverse dispersivity within the aquifer
γ , Γ , η , η_D , η' , η'_D , χ	are dimensionless parameters of the analytical solutions
Δh	is the hydraulic head difference across the landfill bottom barrier
ΔX	is the interval of the horizontal distance for the numerical solution
$\Delta Y'$	is the interval of the vertical distance for the numerical solution
θ	is the volumetric water content
Θ	is the transmissivity of the interface between the geomembrane and the
	underlying soil
Dg	is the diffusion coefficient of the geomembrane
D _h	is the hydrodynamic dispersion/diffusion coefficient of the landfill bottom
	barrier
D _{h,x}	is the hydrodynamic dispersion/diffusion coefficient in the horizontal direction
	within the aquifer
D _{h,y}	is the hydrodynamic dispersion/diffusion coefficient in the vertical direction
	within the aquifer
D _{hi}	is the hydrodynamic dispersion/diffusion coefficient of the i-th layer of the
	landfill bottom barrier
J _s	is the pollutant vertical mass flux coming from the landfill
Kg	is the partition coefficient between the geomembrane and the solute
L	is the thickness of the landfill bottom barrier
Lg	is the geomembrane thickness
Li	is the thickness of the i-th layer of the barrier
Lw	is the length of the geomembrane wrinkle
Nı	is the number of mineral layers in the landfill bottom barrier
N _X	is the number of nodes in the horizontal direction for the numerical solution
$N_{Y'}$	is the number of nodes in the vertical direction for the numerical solution
P _L	is the Peclet number of the landfill bottom barrier
Q	is the leakage rate through a single hole of the geomembrane
RC	is the dimensionless relative concentration of the pollutant
Х	is the dimensionless horizontal distance below the landfill

Y, Y'	are dimensionless vertical distances from the top of the aquifer
Yaq	is the dimensionless depth of the aquifer
a, d, G	are the dimensionless parameters of the numerical solution
b	is the half-width of the geomembrane wrinkle
c	is the pollutant concentration in a thick aquifer
c ₀	is the pollutant concentration in the landfill leachate
c _b	is the pollutant concentration at the bottom of the landfill barrier
c _x	is the pollutant concentration in a thin aquifer
c _{x0}	is the pollutant concentration in the aquifer upstream from the landfill
h	is the thickness of the aquifer
h _b	is the height of the water level at the bottom of the landfill barrier
h _p	is the height of the ponded leachate above the landfill bottom barrier
keq	is the equivalent hydraulic conductivity of the landfill bottom barrier
ki	is the hydraulic conductivity of the i-th layer of the landfill bottom barrier
l	is the horizontal length of the landfill in the direction of the groundwater flow
n _{aq}	is the porosity of the aquifer
n _h	is the number of the geomembrane defects per unit area
ni	is the porosity of the i-th layer of the landfill bottom barrier
q	is the vertical infiltration flux coming from the landfill
q_x	is the groundwater horizontal flux
q _{x0}	is the groundwater horizontal flux upstream the landfill
q_y	is the groundwater vertical flux
r	is the number of the series terms of the analytical solution for aquifers with a
	finite thickness
t	is the time
V _{x0}	is the horizontal seepage velocity of groundwater upstream from the landfill
х	is the horizontal distance below the landfill
у	is the vertical distance from the top of the aquifer

1 1. INTRODUCTION

2 The design of landfill liners is aimed at minimizing both leachate flow and contaminant transport due to advection and molecular diffusion from the waste to the groundwater system (Rowe et al., 2004; 3 Shackelford, 2014). Modern liners comprise compacted clay layers (CCLs) and/or geosynthetic 4 components, such as geomembrane layers (GMLs) and geosynthetic clay layers (GCLs). GMLs can 5 be coupled with CCLs and GCLs to form composite liners that provide optimal groundwater 6 protection. Moreover, the aquifer located beneath the landfill is typically separated from the waste 7 8 not only by these engineered barriers, but also by a natural foundation or attenuation layer (AL), 9 which plays an important role in limiting contaminant migration (Rowe and Brachman, 2004).

10 The preliminary design of a lining system generally requires the assessment of both its *equivalency* 11 with the lining system that is prescribed by the environmental regulations in force and its effectiveness with respect to specified performance criteria (Katsumi et al., 2001; Foose, 2010). One common 12 performance criterion is that the design should ensure an acceptable risk for human health and the 13 environment, which is typically quantified through a prescribed maximum value of the contaminant 14 concentration in the groundwater. For this reason, the assessment of liner performance generally 15 requires one to ascertain that the concentration of pollutants that are released by the waste remains 16 below a prescribed threshold level at a specified compliance point, which is commonly represented 17 18 by a monitoring well located in the underlying aquifer and downstream from the landfill (Figure 1). Numerical solutions implemented in software products are currently available to evaluate the 19 groundwater contaminant concentration below the landfill (Rowe and Booker, 1985a, 1985b; El-Zein 20 21 and Rowe, 2008; El-Zein et al., 2012; Xie et al. 2016). However, such numerical solutions do not exclude the interest in implementing analytical solutions, which may be considered useful analysis 22 tools, due to their simplicity and repeatability. In this paper, analytical solutions are developed under 23 the restrictive assumptions of steady-state conditions and constant source concentration in the waste 24 leachate. These conditions, which were also assumed by Guyonnet et al. (2001) and Foose (2010), 25 26 exclude the possibility of modeling time-varying properties and time-dependent phenomena, and

typically result in conservative predictions of the groundwater contaminant concentration
(Shackelford, 1990; Rabideau and Khandelwal, 1998; Rowe et al., 2004). As a result, such solutions
should not be considered as long-term, realistic simulations of contaminant migration, but rather as
conservative estimates of the risk related to a given contaminant concentration in the waste leachate,
in a similar way to a Tier-2 analysis of the ASTM risk-based corrective action (RBCA) standard
(ASTM, 2015) for a polluted site.

The scenarios considered in this paper include vertical pollutant transport through an engineered 33 barrier, which can overlie a foundation or attenuation layer, and horizontal transport in the underlying 34 aquifer (Figure 1). With respect to the already available steady-state analysis approaches (Guyonnet 35 36 et al., 2001; Foose, 2010), the solutions that are derived in this paper allow the contaminant concentration distribution to be evaluated within the aquifer beneath the landfill. A first analytical 37 solution is derived for the case of aquifers that are sufficiently *thin* in order to neglect the vertical 38 distribution of the contaminant concentration in the groundwater. When the aquifers are *thick* and the 39 vertical dispersion of the contaminants cannot be neglected, a two-dimensional mass balance in the 40 aquifer has to be considered, and a set of analytical and step-by-step numerical solutions is developed. 41 An example of the application of the proposed analytical solutions is presented to assess the migration 42 of an organic pollutant (toluene, C₆H₅-CH₃) for the case of composite liners, in which the mineral 43 44 layers (CCL or GCL) are coupled with a GML.

45 2. POLLUTANT CONCENTRATION IN THIN AQUIFERS

If the thickness of the aquifer, h, is no more than a few meters, the vertical component of the
groundwater volumetric flux can be neglected with respect to the horizontal one. The water balance
inside an aquifer volume of infinitesimal length, dx, can be expressed as follows:

49

$$50 \qquad h \cdot \frac{dq_x}{dx} = q \tag{1}$$

51

where q_x is the horizontal groundwater flux, q is the vertical (infiltration) flux coming from the landfill and x is the horizontal distance below the landfill taken in the direction of the groundwater flow (Figure 2). After integration of Eq. 1, the groundwater flux q_x varies linearly beneath the landfill as follows:

56

57
$$q_x = q_{x0} + \frac{q}{h} \cdot x$$
(2)

58

59 where q_{x0} is the groundwater flux just upstream from the landfill, i.e. at location x = 0.

For thin aquifers, the pollutant concentration can be assumed to be invariant with the vertical position, and transport by advection is dominant relative to transport by longitudinal hydrodynamic dispersion/diffusion in the horizontal direction (Rowe and Booker, 1985a). Under steady-state conditions, the pollutant mass balance inside the aquifer can be obtained by combining the horizontal advective mass flux with the vertical mass flux derived from the landfill, J_s , as follows:

65

$$66 \qquad h \cdot \frac{d}{dx} (q_x \cdot c_x) = J_s \tag{3}$$

67

68 where c_x is the pollutant concentration in the aquifer beneath the landfill (Figure 2).

The vertical flux of a miscible pollutant though a multi-layer barrier is given by (Manassero et al.,
2000; Guyonnet et al., 2001):

71

72
$$J_s = q \frac{c_0 \cdot \exp(P_L) - c_b}{\exp(P_L) - 1}$$
 (4)

73

where c_0 is the pollutant concentration in the leachate on the top of the barrier, c_b is the pollutant concentration at the bottom of the barrier, which is supposed to coincide with the top of the aquifer located beneath the landfill, and P_L is the dimensionless Peclet number of the barrier.

The Peclet number, which represents the ratio of advective transport rate to diffusive-dispersivetransport, can be expressed as follows:

79

$$80 P_{\rm L} = \frac{q}{\Lambda} (5)$$

81

where Λ is the equivalent diffusivity of the multi-layer barrier. For a volatile organic compound
(VOC), which can diffuse through GMLs, Λ is given by (Manassero et al., 2000; Guyonnet et al.,
2001; Katsumi et al., 2001; Foose, 2010; Shackelford, 2014):

85

86
$$\Lambda = \frac{1}{\frac{L_g}{K_g \cdot D_g} + \int_0^L \frac{dz}{\theta \cdot D_h}}$$
(6)

87

88 where L_g is the thickness of the geomembrane that is placed at the top of the barrier, K_g is the partition 89 coefficient between the geomembrane and solute, D_g is the diffusion coefficient of the geomembrane, 90 θ is the volumetric water content, D_h is the hydrodynamic dispersion/diffusion coefficient in the 91 vertical direction and L is the total thickness of the barrier system. If pollutant transport occurs under saturated conditions, the volumetric water content is equal to the porosity of the layers whichconstitute the barrier system, and the equivalent diffusivity can be expressed as follows:

94

95
$$\Lambda = \frac{1}{\frac{L_g}{K_g \cdot D_g} + \sum_{i=1}^{N_1} \frac{L_i}{n_i \cdot D_{hi}}}$$
(7)

96

where L_i is the thickness of the i-th layer, n_i is the porosity of the i-th layer, D_{hi} is the hydrodynamic dispersion/diffusion coefficient of the i-th layer and N_l is the number of mineral layers in the barrier system (Figure 3).

100 In the absence of the GML or in the case of degradation of the GML, Λ can be calculated by omitting 101 the first term related to the GML at the denominator of Eq. 6 or 7. For inorganic solutes, whose 102 diffusion through GMLs is extremely slow and can be neglected with respect to the transport through GML holes, the mass flux through composite barriers, $J_{s(Composite)}$, can be calculated by multiplying 103 the mass flux without the GML, J_{s(Mineral)}, by the ratio between the leakage area and the total area of 104 the barrier, expressed as the ratio between the leakage rate through the composite barrier, $q_{(Composite)}$, 105 and the water volumetric flux through the mineral barrier without the GML, $q_{(Mineral)}$, i.e. $J_{s(Composite)} =$ 106 $J_{s(Mineral)} \cdot q_{(Composite)}/q_{(Mineral)}$, as proposed by Katsumi et al. (2001) and Foose (2010). 107

In a thin aquifer, the pollutant concentration at the top of the aquifer, c_b , can be assumed to coincide with the concentration in the aquifer, c_x , as the change in pollutant concentration along the vertical direction is negligible.

As a result, when Eq. 4 is inserted into Eq. 3, and the variation of q_x along the x-direction, which is given by Eq. 2, is taken into account, the pollutant mass balance yields the following first-order differential equation:

115
$$\frac{\mathrm{d}\mathbf{c}_{x}}{\mathrm{d}x} + \chi \cdot \left(\frac{\mathbf{q}}{\mathbf{q}_{x0} \cdot \mathbf{h} + \mathbf{q} \cdot \mathbf{x}}\right) \cdot \mathbf{c}_{x} = \chi \cdot \left(\frac{\mathbf{q}}{\mathbf{q}_{x0} \cdot \mathbf{h} + \mathbf{q} \cdot \mathbf{x}}\right) \cdot \mathbf{c}_{0}$$
(8)

117 where

119
$$\chi = \frac{\exp(P_L)}{\exp(P_L) - 1} = \frac{1}{1 - \exp(-P_L)}.$$
 (9)

121 The analytical solution of Eq. (8), associated to the boundary condition

123
$$c_x(x=0) = c_{x0}$$
 (10)

where c_{x0} is the initial groundwater contaminant concentration that comes from upstream of the landfill, is given by:

128
$$c_x = c_{x0} + (c_0 - c_{x0}) - (c_0 - c_{x0}) \cdot \left(\frac{q_{x0} \cdot h}{q_{x0} \cdot h + q \cdot x}\right)^{\chi}$$
 (11)

130 Defining the relative concentration, RC, as follows:

132
$$\operatorname{RC} = \frac{c_{x} - c_{x0}}{c_{0} - c_{x0}},$$
 (12)

the analytical solution can also be expressed in the following dimensionless form:

136
$$RC = 1 - \left(\frac{\eta}{\eta + X}\right)^{\chi}$$
(13)

138 where $X = x/\ell$ is the dimensionless distance beneath the landfill, with reference to the landfill length 139 in the direction of the groundwater flow, ℓ , and

140

141
$$\eta = \frac{q_{x0} \cdot h}{q \cdot \ell} .$$
 (14)

142

The parameter η represents the ratio of the horizontal-to-vertical volumetric flow rates. The relative concentration at a given point in the aquifer beneath the landfill is a decreasing function of η ; i.e., when $\eta \rightarrow \infty$, the relative concentration tends to zero, which corresponds to "perfect flushing", as shown in Figure 4. The influence of the Peclet number of the barrier on the relative concentration is limited to values of P_L lower than 4.

148 When $P_L > 4$, the vertical solute mass flux is dominated by advection, and can be expressed as follows: 149

$$150 \qquad \mathbf{J}_{s} = \mathbf{q} \cdot \mathbf{c}_{0}. \tag{15}$$

151

Under such conditions, the relative concentration no longer depends on P_L, and can be expressed asfollows:

154

155
$$RC = \frac{X}{\eta + X}.$$
 (16)

156

157 When the vertical volumetric flux is nil (i.e. q = 0), the Peclet number is also nil and the vertical solute 158 mass flux is given by:

160
$$\mathbf{J}_{s} = \Lambda \cdot \left(\mathbf{c}_{0} - \mathbf{c}_{b} \right). \tag{17}$$

162 Under such conditions, the relative concentration that is obtained from the solute mass balance within163 the aquifer can be expressed as follows:

165
$$\operatorname{RC} = 1 - \exp\left(-\frac{X}{\eta_{\mathrm{D}}}\right)$$
 (18)

167 where

169
$$\eta_{\rm D} = \frac{q_{\rm x0} \cdot \mathbf{h}}{\Lambda \cdot \ell}.$$
 (19)

171 **3. POLLUTANT CONCENTRATION IN THICK AQUIFERS**

When the thickness of the aquifer is not limited to a few meters, the variation in pollutant concentration in the vertical direction becomes significant, and a two-dimensional geometry needs to be taken into account. Therefore, the pollutant mass balance, within a non-deformable aquifer, can be expressed as follows:

176

177
$$\mathbf{n}_{aq} \frac{\partial \mathbf{c}}{\partial t} = \mathbf{n}_{aq} \frac{\partial}{\partial \mathbf{x}} \left(\mathbf{D}_{h,x} \frac{\partial \mathbf{c}}{\partial \mathbf{x}} \right) + \mathbf{n}_{aq} \frac{\partial}{\partial \mathbf{y}} \left(\mathbf{D}_{h,y} \frac{\partial \mathbf{c}}{\partial \mathbf{y}} \right) - \frac{\partial}{\partial \mathbf{x}} \left(\mathbf{q}_{x} \cdot \mathbf{c} \right) - \frac{\partial}{\partial \mathbf{y}} \left(\mathbf{q}_{y} \cdot \mathbf{c} \right)$$
(20)

178

where n_{aq} is the aquifer porosity, c = c(x,y) is the pollutant concentration within the aquifer, x is the horizontal distance beneath the landfill, y is the vertical distance from the top of the aquifer, $D_{h,x}$ and $D_{h,y}$ are the horizontal and vertical hydrodynamic dispersion/diffusion coefficients in the aquifer, respectively, and q_x and q_y are the horizontal and vertical components of the groundwater volumetric flux in the aquifer, respectively. Under steady-state conditions, and assuming pure advection as the dominant transport mechanism in the horizontal direction, the mass balance is represented by a parabolic partial differential equation (Rubin and Buddemeier, 1996; Charbeneau, 2000):

186

187
$$\frac{\partial}{\partial x} (q_x \cdot c) = n_{aq} \frac{\partial}{\partial y} \left(D_{h,y} \frac{\partial c}{\partial y} \right) - \frac{\partial}{\partial y} (q_y \cdot c).$$
(21)

188

In an aquifer of thickness h with an impermeable layer at the bottom, the vertical volumetric flux q_y can be assumed to vary linearly with the depth from the vertical infiltration value (i.e. q) at y = 0 to a null value at y = h (Charbeneau et al., 1995):

193
$$q_y = q \cdot \left(1 - \frac{y}{h}\right). \tag{22}$$

195 In order to preserve the volumetric balance within the aquifer

196

197
$$\frac{\partial q_x}{\partial x} + \frac{\partial q_y}{\partial y} = 0, \qquad (23)$$

198

the horizontal volumetric flux must also vary linearly along the horizontal direction, as in Eq. 2:

201
$$q_x = q_{x0} + \frac{q}{h} \cdot x .$$
 (24)

202

If the horizontal volumetric flux in the aquifer is appreciably greater than the vertical volumetric flux, then the transverse mechanical dispersion can be assumed to be dominant relative to molecular diffusion and the longitudinal mechanical dispersion in the vertical direction (Rubin and Buddemeier, 1996). As a result, the coefficient $D_{h,y}$ can be calculated as follows:

207

$$D_{h,y} = \alpha_T \cdot V_{x0}$$
(25)

209

where α_T is the transverse dispersivity within the aquifer and $v_{x0} = q_{x0}/n_{aq}$ is the horizontal seepage velocity of groundwater upstream from the landfill.

The pollutant mass balance can be expressed, using Eqs. 22, 24 and 25, as follows:

213

214
$$q_x \frac{\partial c}{\partial x} = \alpha_T \cdot q_{x0} \cdot \frac{\partial^2 c}{\partial y^2} - q_y \frac{\partial c}{\partial y}.$$
 (26)

215

The boundary condition associated with Eq. 26 at the top of the aquifer (i.e. at y = 0) is obtained by imposing continuity between the vertical solute flux coming from the landfill and the vertical solute flux entering the aquifer:

219

220
$$q_y \cdot c - \alpha_T \cdot q_{x0} \cdot \frac{\partial c}{\partial y} = q \cdot \frac{c_0 \cdot \exp(P_L) - c}{\exp(P_L) - 1}$$
 at $y = 0$. (27)

221

If the bottom of the aquifer is constituted by an impermeable layer, the boundary condition at y = his given by

224

225
$$\frac{\partial c}{\partial y} = 0$$
 at $y = h$. (28)

226

The following initial condition is then sufficient to formulate the mathematical problem pertaining tothe mass balance (i.e. Eq. 26):

229

230
$$c = c_{x0}$$
 at $x = 0$. (29)

231

A numerical solution to this problem can be obtained by adopting a step-by-step calculation procedure, in which a discretization based on centered finite differences in direction y and the forward Euler method are used to integrate with respect to variable x (see Appendix 1).

However, an analytical solution can be found for cases in which the aquifer thickness is very large, by assuming a semi-infinite aquifer and neglecting vertical advection in comparison to vertical transverse mechanical dispersion in the mass balance (but not in the boundary condition at y = 0). Since $h \rightarrow \infty$ for a semi-infinite aquifer, the horizontal volumetric flux given by Eq. 24 can be assumed constant (i.e. $q_x = q_{x0}$) and the mass balance can be expressed as follows:

241
$$\frac{\partial c}{\partial x} = \alpha_{\rm T} \cdot \frac{\partial^2 c}{\partial y^2}.$$
 (30)

An analytical solution to Eq. 30, associated with the boundary condition given by Eq. 27 and the initial condition given by Eq. 29, can be derived from the set of solutions provided by Carslaw and Jaeger (1959) and Crank (1975) for heat and diffusion problems as follows:

246

$$c(x, y) = c_{x0} + (c_0 - c_{x0}) \cdot \left[\operatorname{erfc} \left(\frac{y}{2 \cdot \sqrt{\alpha_T \cdot x}} \right) - \exp\left(\gamma \cdot y + \gamma^2 \cdot \alpha_T \cdot x\right) \cdot \operatorname{erfc} \left(\frac{y}{2 \cdot \sqrt{\alpha_T \cdot x}} + \gamma \cdot \sqrt{\alpha_T \cdot x} \right) \right]$$
(31)

248

249 where

250

251
$$\gamma = \frac{q}{\alpha_{\rm T}} \cdot q_{\rm x0} \cdot \left[\frac{\exp(P_{\rm L})}{\exp(P_{\rm L}) - 1} \right].$$
(32)

252

253 The same analytical solution can also be expressed in the following dimensionless form:

254

255
$$RC = \operatorname{erfc}\left(\frac{Y}{2 \cdot \sqrt{X}}\right) - \exp\left(\Gamma \cdot Y + \Gamma^{2} \cdot X\right) \cdot \operatorname{erfc}\left(\frac{Y}{2 \cdot \sqrt{X}} + \Gamma \cdot \sqrt{X}\right)$$
(33)

256

257 where

259
$$RC = \frac{c - c_{x0}}{c_0 - c_{x0}}$$
 (34a)

$$260 X = \frac{x}{\ell} (34b)$$

261
$$Y = \frac{y}{\sqrt{\alpha_{\rm T} \cdot \ell}}$$
(34c)

262
$$\Gamma = \gamma \cdot \sqrt{\alpha_{\rm T} \cdot \ell} = \frac{\chi}{\eta'}$$
 (34d)

263
$$\eta' = \frac{q_{x0} \cdot \sqrt{\alpha_T \cdot \ell}}{q \cdot \ell}.$$
 (34e)

265 When the Peclet number is higher than 4 (i.e. $P_L > 4$), the vertical transport is dominated by advection, 266 χ tends to unity and the parameter Γ reduces to:

267

268
$$\Gamma = \frac{\mathbf{q} \cdot \ell}{\mathbf{q}_{x0} \cdot \sqrt{\mathbf{\alpha}_{\mathrm{T}} \cdot \ell}} = \frac{1}{\eta'}.$$
(35)

269

270 If the vertical volumetric flux is nil (i.e. q = 0), the vertical transport is purely diffusive, and the 271 parameter Γ is given by:

272

273
$$\Gamma = \frac{1}{\eta'_{\rm D}}.$$
 (36a)

274

where

276

277
$$\eta'_{\rm D} = \frac{q_{\rm x0} \cdot \sqrt{\alpha_{\rm T} \cdot \ell}}{\Lambda \cdot \ell} \,. \tag{36b}$$

If a threshold value of the relative concentration, RC_{lim}, is assumed in the analysis of the pollutant 279 migration from the landfill, the thickness of a pollutant plume in the groundwater can be derived 280 through Eq. 33 by finding the depth at which $RC = RC_{lim}$. As an example, the thickness of the pollutant 281 plume is plotted in Figure 5 for RC_{lim} = 0.001, 0.005, 0.01 and Γ = 0.05. The use of the analytical 282 solution given by Eq. 33 allows to avoid the introduction of a semi-empirical formula for the thickness 283 of the pollutant plume, as described in Charbeneau et al. (1995), as well as the calculation of a 284 boundary layer thickness through approximate solutions, as described in Rubin and Buddemeier 285 (1996). 286

The relevance of neglecting the vertical advective transport in Eq. 30 can be appreciated by comparing 287 the relative concentrations, calculated with Eq. 33, to the numerical solution described in Appendix 288 1. The relative concentrations determined at X = 1 with both the analytical and numerical solutions 289 are shown in Figure 6 as a function of the dimensionless depth, $Y' = y / h = Y \cdot (\sqrt{\alpha_T \cdot \ell}) / h$, while 290 varying the upstream horizontal groundwater flow, q_{x0} , from $1 \cdot 10^{-8}$ to $1 \cdot 10^{-6}$ m/s for the following 291 set of parameters: $q = 1 \cdot 10^{-10}$ m/s, $\Lambda = 1 \cdot 10^{-10}$ m/s, $P_L = 1$, $\ell = 1000$ m, $\alpha_T = 1$ m, h = 100 m. The 292 293 analytical solution appears to be in good agreement with the numerical results, at least as long as the ratio between the vertical volumetric flux, q, and the horizontal volumetric flux, q_{x0} , is less than 1%, 294 i.e. $q/q_{x0} < 0.01$. 295

The approximation arising from the assumption of infinite thickness for the aquifer can be appreciated 296 297 in Figure 7 by comparing the relative concentration that has been calculated at X = 1 with Eq. 33 to the results provided by the numerical solution, varying the aquifer thickness from h = 20 m to h = 100298 m for the following set of parameters: $q = 1 \cdot 10^{-10}$ m/s, $\Lambda = 1 \cdot 10^{-10}$ m/s, $P_L = 1$, $\ell = 1000$ m, $\alpha_T = 1$ 299 m, $q_{x0} = 1 \cdot 10^{-6}$ m/s. The analytical solution results are sufficiently accurate for h = 100 m when the 300 ratio of the aquifer thickness, h, to the landfill length, ℓ , is greater than 10% (h/ ℓ > 0.1). If this 301 condition is not fulfilled, an improvement to the analytical solution given by Eq. 33 can be obtained 302 by reflecting the concentration curve at the bottom impermeable boundary (i.e. at y = h) and 303

superimposing the reflected curve onto the original one. Repeating this procedure a number j = r of times, the resulting solution can be expressed as follows:

306

307

$$RC = \sum_{j=1}^{r} \operatorname{erfc}\left(\frac{2 \cdot Y_{aq} \cdot (j-1) + Y}{2 \cdot \sqrt{X}}\right) - \exp\left[\Gamma \cdot (2 \cdot Y_{aq} \cdot (j-1) + Y) + \Gamma^{2} \cdot X\right] \cdot \operatorname{erfc}\left(\frac{2 \cdot Y_{aq} \cdot (j-1) + Y}{2 \cdot \sqrt{X}} + \Gamma \cdot \sqrt{X}\right) + \operatorname{erfc}\left(\frac{2 \cdot Y_{aq} \cdot j - Y}{2 \cdot \sqrt{X}}\right) - \exp\left[\Gamma \cdot (2 \cdot Y_{aq} \cdot j - Y) + \Gamma^{2} \cdot X\right] \cdot \operatorname{erfc}\left(\frac{2 \cdot Y_{aq} \cdot j - Y}{2 \cdot \sqrt{X}} + \Gamma \cdot \sqrt{X}\right)$$

$$(37)$$

308

where $Y_{aq} = h/\sqrt{\alpha_T \times \ell}$ is the relative depth of the aquifer. When Eq. 37 is used, the analytical solution is also in good agreement with the numerical results obtained for h = 20 m, as shown in Figure 8.

312 4. APPLICATION EXAMPLES

The following examples are provided to illustrate how the previously derived steady-state solutions can be employed in order to assess the *equivalency* and *effectiveness* of different landfill barriers. Because any realistic analysis should be based on specific data that have been measured by means of field and/or laboratory tests, the results of the following examples are only representative of the proposed analysis approach and should therefore not be generalized to analogous barriers that are characterized by different parameter values and/or are exposed to different boundary conditions.

Two barriers scenarios are considered herein. The first barrier scenario is a composite barrier comprising a 1.5-mm-thick *geomembrane liner* (GML) and a 1-m-thick *compacted clay liner* (CCL), which overlies a 3-m-thick attenuation layer (AL). The second barrier scenario is a composite barrier comprising a 1.5-mm-thick *geomembrane liner* (GML) and a 10-mm-thick *geosynthetic clay liner* (GCL), which overlies a 4-m-thick attenuation layer (AL) (Figure 9). The two barriers are therefore characterized by approximately the same total thickness (i.e. $L \cong 4$ m).

325 The height of the ponded leachate in the leachate collection and removal system (LCRS), h_{p} , is assumed to be equal to 0.5 m, which is the minimum thickness of the LCRS that is required by 326 European Directive 1999/31/EC, and the hydraulic head at the bottom of the barrier, h_b, is assumed 327 to be equal to 1.5 m (Figure 9). As a result, the difference in the hydraulic head between the top of 328 the mineral layers and the bottom of the attenuation layer, Δh , is equal to 3 m for the barrier with the 329 CCL and 3.01 m for the barrier with the GCL. The physical, hydraulic and transport parameters that 330 331 have been assigned to the geomembrane and the mineral layers are reported in Figure 9 and in Table 1. 332

The CCL is hypothesized to be characterized by an average value of the hydraulic conductivity that corresponds to the maximum value that is permitted by the European and USA regulations, i.e. $k = 1 \cdot 10^{-9}$ m/s. The porosity, n, and tortuosity factor, τ_a , values have been estimated from the data on the kaolinite specimens that were tested by Shackelford and Daniel (1991a,b).

The GCL hydraulic conductivity and porosity values are derived from the results of the laboratory 337 test conducted by Puma et al. (2015) with an aggressive permeant solution of 0.25 M of CaCl₂ under 338 an effective confining stress of 70 kPa. These selected values take into account the increase in 339 hydraulic conductivity and the reduction in void ratio that are induced by a long-term permeation 340 with an aqueous solution having a high salt concentration. The GCL tortuosity factor is derived from 341 the data on the sodium bentonite specimen tested by Dominijanni et al. (2013), neglecting the solute 342 restriction effect that is related to chemico-osmotic phenomena, which represents a conservative 343 assumption. Typical parameter values of a silty soil have been selected for the AL (Manassero et al., 344 2000; Rowe and Brachman, 2004; Rowe et al., 2004). The analysis is developed for toluene (C₆H₅-345 CH₃), which is a common component of municipal solid waste landfill leachates. 346

The leakage through composite barriers that include the GML has been calculated as the product of the number of holes per unit area in the GM, n_h , and the leakage rate through a single hole that coincides with a wrinkle, which, assuming no interaction between adjacent wrinkles, can be written as follows (Rowe, 1998):

351

352
$$Q = 2 \cdot L_{w} \left[k_{eq} \cdot b + (k \cdot L \cdot \Theta)^{0.5} \right] \frac{\Delta h}{L}$$
(38)

353

where L_w is the length of the wrinkle, k_{eq} is the hydraulic conductivity the underlying mineral barrier, 2b is the width of the wrinkle, L is the thickness of the underlying mineral layer (or the total thickness of the underlying mineral barrier), Θ is the transmissivity of the interface between the GML and the underlying soil, and Δh is the hydraulic head loss across the barrier system.

358 The equivalent hydraulic conductivity, k_{eq} , in Eq. 38 is calculated as the harmonic mean of the 359 hydraulic conductivities of individual layers:

361
$$k_{eq} = \frac{L}{\sum_{i=1}^{N_{i}} \frac{L_{i}}{k_{i}}}$$
 (39)

where k_i is the hydraulic conductivity of the i-th layer. The calculation of k_{eq} also includes the contribution of the attenuation layer that is placed between the engineered barrier system and the underlying aquifer.

The following parameters have been assumed for the calculation of the leakage rate per unit area, q: 366 $n_h = 1$ hole in a wrinkle per hectare, $L_w = 3$ m, 2b = 0.2 m, $\Theta = 4 \cdot 10^{-8}$ m²/s for the contact between 367 GML and CCL and $\Theta = 3.5 \cdot 10^{-11}$ m²/s for the contact between GML and GCL. The value of 368 transmissivity, Θ , that has been assigned to the GML - CCL contact represents the average value of 369 the range estimated by Rowe (1998), which varies from $1.6 \cdot 10^{-8}$ m²/s to $1 \cdot 10^{-7}$ m²/s for this type of 370 composite barrier. Analogously, the value of transmissivity, Θ , that has been assigned to the GML -371 GCL contact represents the average value of the range provided by Harpur et al. (1993), which varies 372 between $6 \cdot 10^{-12}$ m²/s and $2 \cdot 10^{-10}$ m²/s (Rowe and Brachman, 2004). 373

The obtained results (Table 2) show that the leakage rate through the composite barrier with GCL (q = 3.4 lphd) is appreciably lower than the leakage rate through the composite barrier with CCL (q = 9.8 lphd), because of the better contact conditions between the GML and GCL.

The free-solution diffusion coefficient, D₀, is equal to $9.7 \cdot 10^{-10}$ m²/s for toluene (Yaws, 1995). The average values of the geomembrane partition coefficient and the diffusion coefficient have been assumed equal to K_g = 96 and D_g = $0.47 \cdot 10^{-12}$ m²/s, respectively (Rowe, 1998), on the basis of the data by Park and Nibras (1993) pertaining to the migration of toluene in aqueous solutions.

The effective diffusion coefficient for the mineral layers has been calculated as the product of the apparent tortuosity factor, τ_a , and the free-solution diffusion coefficient (Shackelford and Daniel, 1991a). The longitudinal dispersivity of the mineral layers has been assumed equal to a tenth of the thickness of the barrier layers to calculate the mechanical dispersion coefficients, which are defined

as the product of the longitudinal dispersivity and the seepage velocity (Shackelford and Rowe, 1998; 385 Guyonnet et al., 2001). The hydrodynamic dispersion/diffusion coefficients in the vertical direction, 386 D_{hi}, have been calculated as the sum of the effective diffusion coefficients and the mechanical 387 dispersion coefficients (Shackelford, 1993). The calculated values of the equivalent diffusivity, Λ , 388 and the Peclet number, P_L, are reported in Table 2. In the presence of the GML, the Peclet number is 389 390 lower than 1, thus indicating the dominance of diffusion over advection in the migration process of this organic contaminant, which is able to diffuse through the geomembrane. Similar conclusions 391 were reached by Katsumi et al. (2001), Foose (2010) and Pu et al. (2015, 2016a, 2016b, 2016c, 2019). 392 393 When the performance of a composite barrier is assessed, the finite service life of the geomembrane needs to be taken into account (Sangam and Rowe, 2002; Rowe, 2005). For example, Rowe (2006) 394 pointed out that the service life of geomembranes is of the order of 15-50 years at temperatures of 395 50-60 °C. As a result, the volumetric flux through the mineral layers, q, has been calculated 396 conservatively for both of the barriers without taking into account the presence of a geomembrane, 397 398 in order to assess the barrier performance after geomembrane degradation. Under the assumption of 399 saturated conditions in the liners and the attenuation layer, q has been determined as follows:

400

401
$$q = k_{eq} \frac{h_p + L - h_b}{L}$$
 (40)

402

The CCL barrier is characterized by a value of $q = 2.91 \cdot 10^{-9}$ m/s, which is significantly lower than the value $q = 4.39 \cdot 10^{-8}$ m/s that has been found for the GCL barrier. This high value of the volumetric flux of the GCL barrier is related to the degradation of the hydraulic containment ability of GCL, due to the permeation of aggressive aqueous solutions, which has been considered in the selection of the value to assign to the GCL hydraulic conductivity. The Peclet number of the considered example mineral barriers are larger than 10, thus showing that, in the absence of the geomembrane, advection controls the contaminant migration processes. 411 *Thin aquifer*

If the aquifer beneath the landfill with a length ℓ of 1,000 m is sufficiently thin (h = 3 m), the analytical solution (Eq. 13) can be used to assess the variation of the contaminant concentration in the aquifer along the direction of the groundwater flow.

The values of η and the relative concentration at $x = \ell$, which have been calculated assuming that the horizontal groundwater volumetric flux just upstream from the landfill, q_{x0} , is equal to $1 \cdot 10^{-6}$ m/s (= 31.6 m/yr), are reported in Table 3 for all the considered example barriers. The calculated relative concentrations of toluene in the aquifer are shown as a function of the horizontal distance below the landfill in Figure 10, for all the considered cases.

The composite barrier with the GCL is more effective than the composite barrier with the CCL in reducing the toluene concentrations in the aquifer, even though a conservative value of the GCL hydraulic conductivity, which can be reached after a long-term permeation with an aggressive aqueous solution, has been assumed. The concentration of toluene increases along the direction of the groundwater flow beneath the landfill. Therefore, the maximum value of contaminant concentration is reached at $x = \ell$, i.e. just downstream from the landfill.

After the degradation of the geomembrane, the effectiveness of the barriers is reduced significantly and, as a result, the relative concentration below the landfill increases by more than one order of magnitude. Under such conditions, the CCL is more efficient than the GCL, due to the better ability of the CCL to reduce the contaminant diffusive flux.

430

431 *Thick aquifer*

If the aquifer thickness is not limited to a few meters, the vertical distribution of the contaminant needs to be taken into account by means of the analytical solutions presented by Eqs. 33 or 37, or by means of the numerical solution presented in the appendix. In this case, the contaminant concentration in the aquifer is dependent not only on the horizontal flushing resulting from the groundwater flow,

but also on the vertical dispersion. In this example, the aquifer thickness, h, has been assumed equal to 100 m and the transverse dispersivity within the aquifer, α_T , has been assumed equal to 1 m, based on the indications of Rowe et al. (2004) in case of availability of high-quality experimental data.

The landfill length, ℓ , and the upstream horizontal groundwater volumetric flux, q_{x0} , have been assumed equal to 1,000 m and $1 \cdot 10^{-6}$ m/s (= 31.6 m/yr), respectively, in the same way as for the thin aquifer example.

The calculated relative concentrations of toluene are shown in Figures 11 as a function of the aquifer

depth, y, at the distances x = 100 m, 500 m and 1,000 m (i.e. at X = 0.1, 0.5 and 1) beneath the landfill.

444 The contaminant concentration decreases with depth and increases over the horizontal distance.

The analytical solution for the barrier constituted by a GCL overlying an attenuation layer is not accurate, as the ratio $q/q_{x0} = 4.4\%$ is greater than 1% (Figure 11d).

If a limiting value of the relative concentration is selected, a contaminant plume can be defined within the aquifer by means of the available analytical solution. For example, the toluene plumes corresponding to the limiting value of the relative concentration RC_{lim} of 0.01% are shown in Figure 12 for the two barrier examples with the intact geomembrane.

452 **5. CONCLUSIONS**

453 The illustrative examples have shown the application of steady-state analytical solutions for the assessment of the contaminant concentration within an aquifer that is located below a landfill. On the 454 basis of such an analysis, the *equivalence* between landfill barriers which consist of different liners 455 456 can be established. Moreover, the effectiveness of the barrier in limiting contaminant migration and the related risk to groundwater quality can also be evaluated. With respect to the previous steady-457 state analysis approaches (Manassero et al., 2000; Guyonnet et. al., 2001; Foose, 2010), the proposed 458 analytical solutions allow the contaminant concentration distribution to be evaluated in the horizonal 459 direction of the groundwater flow, and eventually in the vertical direction for the case of thick 460 aquifers. However, when the ratio between the vertical and horizontal water fluxes, i.e. q/q_{x0} , is higher 461 than 1%, the proposed analytical solution for thick aquifers is not accurate and should be replaced by 462 the numerical solution that is presented in Appendix 1. 463

The principal benefit of using such solutions is the possibility of conducting an analysis that involves a limited number of parameters and allows the influence of the liner properties (e.g. hydraulic conductivity, thickness, defects) and the field conditions (e.g. aquifer thickness, groundwater velocity) on the final result to be evaluated. Since the assumed boundary conditions are conservative with respect to the evaluation of the contaminant concentration within the aquifer, the proposed analysis can be compared to a Tier-2 risk assessment of the ASTM risk-based corrective action (RBCA) standard (ASTM, 2015) for a polluted site.

A possible interesting development of the proposed steady-state analysis method is the application within a probabilistic approach in which the boundary conditions and the model parameters (such as the leachate contaminant concentration, the hydraulic conductivity of the mineral layers and the number, size and location of the geomembrane defects) take on a random nature. In fact, the obtained analytical solutions may be implemented in a Monte Carlo algorithm to relate the pollutant concentration in the aquifer not only to the most representative values of the involved model parameters, but also to their variance.

478 APPENDIX 1

The pollutant mass balance given by Eq. 26 can be expressed in the following dimensionless form:

480

481
$$\frac{\partial RC}{\partial X} = d \cdot \frac{\partial^2 RC}{\partial Y'^2} - a \frac{\partial RC}{\partial Y'}$$
(A1)

482

483 where

484

485
$$Y' = y/h$$
 (A2)

486
$$d = \frac{\alpha_{\rm T} \cdot \mathbf{q}_{\rm x0} \cdot \ell}{\left(\mathbf{q}_{\rm x0} + \frac{\mathbf{q} \cdot \ell}{\mathbf{h}} \cdot \mathbf{X}\right) \cdot \mathbf{h}^2},\tag{A3}$$

487
$$\mathbf{a} = \frac{\mathbf{q} \cdot (\mathbf{1} - \mathbf{Y}') \cdot \ell}{\left(\mathbf{q}_{x0} + \frac{\mathbf{q} \cdot \ell}{\mathbf{h}} \cdot \mathbf{X}\right) \cdot \mathbf{h}}.$$
 (A4)

488

The Y' variable can be discretized into $N_{Y'} + 1$ nodes, which are numbered from 0 to $N_{Y'}$ and are separated by equal intervals of $\Delta Y' = 1/N_{Y'}$. Similarly, the X variable can be discretized into $N_X + 1$ nodes, which are numbered from 0 to N_X and are separated by equal intervals $\Delta X = 1/N_X$.

Using a centered finite difference to approximate the derivatives in variable Y' and the Euler forward
method to integrate with respect to the variable X, the following step-by-step calculation procedure
is found:

495

496
$$RC_{i}^{j+1} = RC_{i}^{j} + \left(d^{j} \cdot \frac{RC_{i+1}^{j} - 2 \cdot RC_{i}^{j} + RC_{i-1}^{j}}{\Delta Y'^{2}} - a_{i}^{j} \cdot \frac{RC_{i+1}^{j} - RC_{i-1}^{j}}{2 \cdot \Delta Y'}\right) \cdot \Delta Y'$$
 (A5)

497

498 where

$$RC_{i}^{j+1} = RC(X_{j+1}, Y'_{i})$$

$$RC_{i}^{j} = RC(X_{j}, Y'_{i})$$

$$RC_{i+1}^{j} = RC(X_{j}, Y'_{i+1})$$

$$RC_{i-1}^{j} = RC(X_{j}, Y'_{i-1})$$

$$d^{j} = d(X_{j})$$

$$a_{i}^{j} = a(X_{j}, Y'_{i}).$$

In order to apply Eq. A5 to all the nodes of the Y' variable, two fictitious nodes, which are numbered as -1 and $N_{Y'} + 1$ and are located outside the grid extremes, have to be introduced. The relative concentrations at these fictitious nodes are determined from the boundary conditions. The boundary condition that is obtained at the top of the aquifer by imposing flux continuity is given by Eq. 27, which can be discretized as follows:

507

508
$$\mathbf{G} \cdot \mathbf{RC}_{0}^{j} - \frac{\mathbf{RC}_{1}^{j} - \mathbf{RC}_{-1}^{j}}{2 \cdot \Delta \mathbf{Y}'} = \mathbf{G}$$
 (A6)

509

510 where

511

512
$$G = \frac{q}{q_{x0}} \cdot \frac{\exp(P_L)}{\exp(P_L) - 1} \cdot \frac{h}{\alpha_T}.$$
 (A7)

513

514 Similarly, at the bottom of the aquifer, Eq. 28 can be discretized as follows:

515

516
$$\frac{RC_{N_{Y}+1}^{j} - RC_{N_{Y}-1}^{j}}{2 \cdot \Delta Y'} = 0.$$
(A8)

517

518 The resulting step-by-step calculation procedure is:

Initial condition

For i varying from 0 to $N_{Y'}$

$$RC_{i}^{0} = 0$$

end

520

Integration in X For j varying from 0 to $N_x - 1$ $RC_{-1}^{j} = RC_{1}^{j} - G \cdot 2 \cdot \Delta Y' \cdot RC_{0}^{j} + G \cdot 2 \cdot \Delta Y'$ $RC^j_{N_{\mathbf{Y}'}+1} = RC^j_{N_{\mathbf{Y}'}-1}$ For i variying from 0 to $N_{Y'}$ $RC_{i}^{j+1} = RC_{i}^{j} + \left(d_{i}^{j} \cdot \frac{RC_{i+1}^{j} - 2 \cdot RC_{i}^{j} + RC_{i-1}^{j}}{\Delta Y'^{2}} - a_{i}^{j} \cdot \frac{RC_{i+1}^{j} - RC_{i-1}^{j}}{2 \cdot \Delta Y'}\right) \cdot \Delta X$ end

end

522

521

In order to obtain a stable solution, the following condition has to be respected in the choice of the 523 interval of integration ΔX (Sewell, 2005): 524

526
$$\Delta X \leq \frac{\Delta Y'^2}{2 \cdot d_{\text{max}}} = \frac{\Delta Y'^2 \cdot h^2}{2 \cdot \alpha_{\text{T}} \cdot \ell}.$$
 (A9)

527 **REFERENCES**

- ASTM (2015) *Standard Guide for Risk-Based Corrective Action*. American Society for Testing and
 Materials, Standard E2081-00 West Conshohocken, PA.
- 530 Carslaw HS and Jaeger JC (1959) *Conduction of heat in solids*. Clarendon Press, Oxford, UK.
- 531 Charbeneau RJ (2000) Groundwater hydraulics and pollutant transport. Prentice Hall, Upper Saddle

532 River, New Jersey (USA).

533 Charbeneau RJ, Weaver JW and Lien BK (1995) The hydrocarbon spill screening model (HSSM).

534 Volume 2: theoretical background and source codes. USEPA Report Cr 813080, EPA/600/R-

535 94/039b, Ada, Oklahoma, USA.

- 536 Crank J (1975) *The mathematics of diffusion*. Second Edition, Clarendon Press, Oxford, UK.
- 537 Dominijanni A, Manassero M and Puma S (2013) Coupled chemical-hydraulic-mechanical behaviour
 538 of bentonites. Géotechnique 63(3): 191-205.
- El-Zein A and Rowe RK (2008) Impact on groundwater of concurrent leakage and diffusion of
 dichloromethane through geomembranes in landfill liner. Geosynthetics International 15(1): 5571.
- 542 El-Zein A, McCarroll I and Touze-Foltz N (2012) Three-dimensional finite-element analyses of
- seepage and contaminant transport through composite geosynthetics clay liners with multipledefects. Geotextiles and Geomembranes 33: 34-42.
- Foose GJ (2010) A steady-state approach for evaluating the impact of solute transport through
 composite liners on groundwater quality. Waste Management 30: 1577-1586.
- Guyonnet D, Perrochet P, Côme B, Seguin J-J and Parriaux A (2001) On the hydro-dispersive
 equivalence between multi-layered mineral barriers. Journal of Contaminant Hydrology 51: 215231.
- 550 Harpur WA, Wilson-Fahmy RF and Koerner RM (1993) Evaluation of the contact between 551 geosynthetic clay liners and geomembranes in terms of transmissivity. In: *Proceedings of GRI*

- 552 *Seminar on Geosynthetic Liner Systems* (Koerner RM and Wilson-Fahmy RF (eds)). Industrial
- 553 Fabrics Association International, Philadelphia, PA, pp. 143–154.
- Katsumi T, Benson CH, Foose GJ and Kamon M (2001) Performance-based design of landfill liners.
 Engineering Geology 60: 139-148.
- Manassero M, Benson CH and Bouazza A (2000) Solid waste containment systems. In: *Proceedings of GeoEng2000*. Technomic, Lancaster, PA, vol. 1, pp. 520-642.
- Park JK and Nibras M (1993) Mass flux of organic chemicals through polyethylene geomembranes.
 Water Environment Research 65(3): 227-237.
- 560 Pu H, Fox PJ and Shackelford CD (2015) Contaminant transport through GML/CCL bottom liner
- with consideration of consolidation effects. In: *Proceedings of Geosynthetics 2015*. Industrial
 Fabrics Association International.
- 563 Pu H, Fox PJ and Shackelford CD (2016a) Contaminant transport through a compacted clay liner
- with the consideration of consolidation effects. In: *Proceedings of 5th Geo-Chicago Conference:*
- *Sustainable Waste Management and Remediation, Geo-Chicago 2016.* Geotechnical Special
 Publication 273, ASCE, pp. 118-127.
- Pu H, Fox PJ and Shackelford CD (2016b) Assessment of consolidation-induced contaminant
 transport for compacted clay liner systems. Journal of Geotechnical and Geoenvironmental
 Engineering 142(3): Article number 04015091.
- 570 Pu H, Fox PJ and Shackelford CD (2016c) Assessment of consolidation-induced VOC transport for
- a GML/GCL composite liner system. Journal of Geotechnical and Geoenvironmental Engineering
 142(11): Article number 04016053.
- Pu H, Fox PJ and Shackelford CD (2019) Effect of consolidation on VOC transport through a
 GM/GCL composite liner system. In: *Proceedings of the 8th International Congress on Environmental Geotechnics* (Zhan I, Chen Y and Bouazza A (eds.)), Springer, Singapore, pp. 601-
- 576 607.

- Puma S, Dominijanni A, Manassero M and Zaninetta L (2015) The role of physical pretreatments on
 the hydraulic conductivity of natural sodium bentonites. Geotextiles and Geomembranes 43: 263271.
- Rabideau A and Khandelwal A (1998) Boundary conditions for modeling transport in vertical
 barriers. Journal of Environmental Engineering 124(11): 1135-1139.
- Rowe RK (1998) Geosynthetics and the minimization of contaminant migration through barrier
 systems beneath solid waste. In: *Proceedings of 6th International Conference on Geosynthetics*.
 Industrial Fabrics Association International, St Paul, USA, pp. 27-103.
- Rowe RK (2005) Long-term performance of contaminant barrier systems. 45th Rankine Lecture.
 Géotechnique 55(9): 631-678.
- Rowe RK (2006) Some factors affecting geosynthetics used for geoenvironmental applications. In:
 Proceedings of the 5th International Congress on Environmental Geotechnics. Thomas Telford,
- 589 London, UK, vol.1, pp. 43-69
- Rowe RK and Booker JR (1985a) 1-D pollutant migration in soils of finite depth. Journal of
 Geotechnical Engineering 111(4): 479-499.
- Rowe RK and Booker JR (1985b) Two-dimensional pollutant migration in soils of finite depth.
 Canadian Geotechnical Journal 22(4): 429-436.
- Rowe RK and Brachman RWI (2004) Assessment of equivalency of composite liners. Geosynthetics
 International 11(4): 273-286.
- Rowe RK, Quigley RM, Brachman RWI and Booker JR (2004) *Barrier systems for waste disposal*,
 2nd Edition. Spon Press, London.
- Rubin H and Buddemeier RW (1996) A top specified boundary layer (TSBL) approximation
 approach for the simulation of groundwater contamination processes. Journal of Contaminant
 Hydrology 22: 123-144.

- Sangam HP and Rowe RK (2002) Effects of exposure conditions on the depletion of antioxidants
 from high-density polyethylene (HDPE) geomembranes. Canadian Geotechnical Journal 39(6):
 1221-1230.
- Sewell G (2005) *The numerical solution of ordinary and partial differential equations*, 2nd Edition.
 Wiley, Hoboken, New Jersey.
- 606 Shackelford CD (1990) Transit-time design of earthen barriers. Engineering Geology 29: 79-94.
- Shackelford CD (1993) Contaminant transport. Chapter 3. In: *Geotechnical practice for waste disposal* (Daniel DE (ed.)). Chapman and Hall, London, pp. 33-65.
- 609 Shackelford CD (2014) The ISSMGE Kerry Rowe lecture: The role of diffusion in environmental
- 610 geotechnics. Canadian Geotechnical Journal 51(11): 1219-1242.
- 611 Shackelford CD and Daniel DE (1991a) Diffusion in saturated soil: I. Background. Journal of
 612 Geotechnical Engineering 117(3): 467-484.
- Shackelford CD and Daniel DE (1991b) Diffusion in saturated soil: II. Results for compacted clay.
 Journal of Geotechnical Engineering 117(3): 485-506.
- 615 Shackelford CD and Rowe RK (1998) Contaminant transport modeling. In: Proceedings of 3rd
- 616 *International Congress on Environmental Geotechnics* (Sêco e Pinto PS (ed.)). Balkema,
 617 Rotterdam, pp. 939-956.
- Kie H, Chen Y, Thomas HR, Sedighi M, Masum SA and Ran Q (2016). Contaminant transport in the
- sub-surface soil of an uncontrolled landfill site in China: site investigation and two-dimensional
- numerical analysis. Environmental Science and Pollution Research 23(3): 2566-2575.
- 621 Yaws CL (1995) *Handbook of transport property data*. Gulf, Houston.

623 LIST OF TABLES

Table No.	Table Caption
1	Physical, hydraulic and transport parameters of the geomembrane and the
	mineral layers of the example landfill barriers.
2	Calculated values of transport parameters for the example landfill barriers.
3	Values of the dimensionless parameter $\boldsymbol{\eta}$ and the relative concentration of the
	contaminant at $x = \ell$, for a thin aquifer (h = 3 m, $q_{x0} = 1 \cdot 10^{-6}$ m/s, $\ell = 1000$
	m).

LIST OF FIGURES

Figure No.	Figure Caption
1	Reference scheme of the considered scenario, in which the pollutant released
	by the waste migrates vertically through the engineered barrier system and the
	natural attenuation layer to the underlying aquifer, where pollutant transport
	then becomes horizontal.
2	Reference scheme for the water volumetric balance and the contaminant mass
	balance within a thin aquifer beneath the landfill.
3	Vertical profile of a barrier constituted by engineered and/or natural layers.
Λ	Relative concentration in a thin aquifer at $X = x/\ell = 1$, as a function of the
4	Peclet number of the barrier and the dimensionless parameter η .
5	Thickness of contaminant plume, i.e. the depth at which $RC = RC_{lim}$, for RC_{lim}
5	= 0.001, 0.005, 0.01 and Γ = 0.05.
	Relative concentration of the contaminant as a function of the depth in the
6	aquifer, at the distance $X = x/\ell = 1$ beneath the landfill, for different values of
	the horizontal groundwater velocity, q_{x0} .
7	Comparison of the analytical solution for a semi-infinite aquifer and the
	corresponding numerical solution, in terms of relative concentration of the
	contaminant as a function of the depth in the aquifer, at the distance $X = x/\ell =$
	1 beneath the landfill, for different values of the aquifer thickness, h.
8	Comparison of the analytical solution for a finite aquifer and the
	corresponding numerical solution, in terms of relative concentration of the
	contaminant as a function of the depth in the aquifer, at the distance X = x/ ℓ =
	1 beneath the landfill, for different values of the aquifer thickness, h.

	Scheme of the two herries considered in the example analysis: (a) composite
9	barrier constituted by a geomembrane liner (GML) and a compacted clay liner (CCL); (b) composite barrier constituted by a geomembrane Liner (GML) and a geosynthetic clay liner (GCL).
	Relative concentration of toluene in a thin aquifer (h = 3 m, $q_{x0} = 1 \cdot 10^{-6}$ m/s)
10	
	beneath the landfill ($\ell = 1000 \text{ m}$).
11	Relative concentration of toluene as a function of the relative depth, $Y' = y/h$,
	at $X = 0.1, 0.5$ and 1 for the following barriers: (a) GML + CCL + AL; (b)
	GML + GCL + AL; (c) CCL + AL (degraded geomembrane); (d) GCL + AL
	(degraded geomembrane).
	(
12	Toluene plume beneath the landfill for $RC_{lim} = 0.0001 (0.01\%)$.