



POLITECNICO DI TORINO  
Repository ISTITUZIONALE

Innovative, mini, biodegradable radiosondes to track small-scale fluctuations in warm cloud and clear air environments

*Original*

Innovative, mini, biodegradable radiosondes to track small-scale fluctuations in warm cloud and clear air environments / Abdunabiev, Shahbozbek; Basso Tessa, C.; Tordella, Daniela; Paredes, Miryam; Pasero, Eros; Canavero, Flavio. - In: BULLETIN OF THE AMERICAN PHYSICAL SOCIETY. - ISSN 0003-0503. - ELETTRONICO. - Volume 64, Number 13(2019). ((Intervento presentato al convegno 72nd Annual Meeting of the APS Division of Fluid Dynamics.

*Availability:*

This version is available at: 11583/2784512 since: 2020-01-23T16:09:58Z

*Publisher:*

APS

*Published*

DOI:

*Terms of use:*

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

*Publisher copyright*

(Article begins on next page)

Abstract Submitted  
for the DFD19 Meeting of  
The American Physical Society

**Innovative, mini, biodegradable radiosondes to track small-scale fluctuations in warm cloud and clear air environments** SHAHBOZBEK ABDUNABIEV, TESSA C. BASSO, DANIELA TORDELLA, Politecnico di Torino, MIRYAM PAREDES, Envisens Technologies s.r.l., Politecnico di Torino, EROS PASERO, FLAVIO CANAVERO, Politecnico di Torino — Modelling clouds depends on a variety of chemical and physical processes. These processes range from the nanometer scale, where nucleation, coalescence and rain formation take place, to airflow dynamics which can range up to kilometres. Turbulence plays an important role in the behaviour of these processes and can be noted on different scales. The innovative, ultralight green radiosondes presented here are designed to passively track fluctuations of temperature, humidity, pressure and velocity for several hours on isopycnic surfaces in cloud and clear air environments at altitudes between 1-3 km. To equalize the buoyancy force to the weight of the system, the balloon is filled with a mixture of helium gas and air. The sonde incorporates various set of sensors and a long range/low power radio module, which makes it possible to track fluctuations. A Lagrangian set of data can then be obtained by fusion of GPS (Global Positioning System) and IMU (Inertial Measurement Unit) sensor output. GPS and IMU data can be integrated using the Kalman filter, where GPS provides the periodic updates for removing drifts in the IMU output. This data set can be of help in developing stochastic models to account for turbulence effects on cloud formation.

Ruth Teferi  
APS

Date submitted: 09 Aug 2019

Electronic form version 1.4