

A positivity preserving property result for the biharmonic operator under partially hinged boundary conditions

Original

A positivity preserving property result for the biharmonic operator under partially hinged boundary conditions / Berchio, E.; Falocchi, A.. - In: ANNALI DI MATEMATICA PURA ED APPLICATA. - ISSN 0373-3114. - STAMPA. - 200:4(2021), pp. 1651-1681. [10.1007/s10231-020-01054-6]

Availability:

This version is available at: 11583/2859018 since: 2021-08-03T09:23:47Z

Publisher:

Springer Science and Business Media Deutschland GmbH

Published

DOI:10.1007/s10231-020-01054-6

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)



Energy and Buildings

Available online 29 January 2020, 109824

In Press, Journal Pre-proof

Optimizing the transition between design and operation of ZEBs:lessons learnt from the Solar Decathlon China 2018 SCUTxPoliTo Prototype

Maria Ferrara ^a, [Ciro Lisciandrello](#) ^a, [Alessio Messina](#) ^a, [Mauro Berta](#) ^b, [Yufeng Zhang](#) ^c, [Enrico Fabrizio](#) ^a ^a DENERG- TEBE Research Group, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy^b DAD - China Room, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy^c South China University of Technology, Wushan Road, Tianhe District, Guangzhou, P.R.C

Received 17 July 2019, Revised 24 January 2020, Accepted 28 January 2020, Available online 29 January 2020.

Show less

<https://doi.org/10.1016/j.enbuild.2020.109824>[Get rights and content](#)

Abstract

In the context of the worldwide efforts to reduce energy consumptions and carbon dioxide (CO₂) emissions related to the building sector, reaching the high performance of a zero energy building (ZEB) has been demonstrated to be feasible, especially when the design phase is supported by integrated simulation-based optimization methods. It is necessary to pay special attention to the transition from building design to building operation and it is hard to find examples of real ZEB buildings where the that are optimized considering design and operation at the same time. In this context, the Solar Decathlon competition is a unique experimental field to advance in research about design, simulation, and optimization of ZEBs.

This study aims at presenting the energy-related scientific aspects behind and beyond the

winner building prototype of the Solar Decathlon China 2018 competition. An optimization-based calibration supported by sensitivity analysis is carried out to calibrate the simulation model of the ZEB prototype, based on data collected throughout the design and construction phase. Then, an original simulation-based optimization method is tailored to the purpose of maximizing the contest score, considering parameters related to both design and operation of the building.

A high level of model calibration was reached, and the contest score was improved by 15 points, helping the ZEB prototype to win the competition. Results demonstrated that the applied methodological framework was able to drive towards optimized and integrated design and operation strategies.

Keywords

Solar Decathlon; Integrated design; Simulation; Calibration; Optimization; TRNSYS; GenOpt, Matlab; Sensitivity analysis; simulation-based optimization

[Recommended articles](#)

[Citing articles \(0\)](#)

[View full text](#)

© 2020 Elsevier B.V. All rights reserved.

ELSEVIER

[About ScienceDirect](#) [Remote access](#) [Shopping cart](#) [Advertise](#) [Contact and support](#) [Terms and conditions](#)
[Privacy policy](#)

We use cookies to help provide and enhance our service and tailor content and ads. By continuing you agree to the [use of cookies](#).

Copyright © 2020 Elsevier B.V. or its licensors or contributors. ScienceDirect® is a registered trademark of Elsevier B.V.

ScienceDirect® is a registered trademark of Elsevier B.V.

 **RELX™**