

Bioethanol: role and production technologies

Original

Bioethanol: role and production technologies / Chiaramonti, D. - In: Improvement of Crop Plants for Industrial End Uses[s.l.] : springer, 2007. - pp. 209-251

Availability:

This version is available at: 11583/2790432 since: 2020-02-10T10:24:16Z

Publisher:

springer

Published

DOI:

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Bioethanol: role and production technologies

David Chiaramonti

Research Center for Renewable Energies, Department of Energetics “Sergio Stecco”, Faculty of Mechanical Engineering, University of Florence, Via di S. Marta 3, 50139 Florence, Italy (e-mail: david.chiaramonti@unifi.it)

1. Introduction

Bioethanol ($\text{CH}_3\text{CH}_2\text{OH}$) is a liquid biofuel which can be produced from several different biomass feedstocks and conversion technologies. Its main physical and chemical characteristics, compared to diesel and gasoline fuels, are given in the Table 8.1.

Table 8.1. Main physical and chemical properties of bioethanol (Source: DG XII 1994; Blondy 2005; Mc Cormick et al. 2001).

	Diesel	Ethanol	Gasoline
Low Heating Value - LHV (MJ/kg)	42.7	26.9	43.7
Low Heating Value - LHV (MJ/l)	36.4	21.0	32.0
Viscosity (cSt)	2.5	-	-
Density (kg/m^3) @ 15°C	830 - 880	790	700 - 780
Cetane number	> 45	below 8	-
Octane number (MON)	-	96 - 106	79 - 98
Stoichiometric ratio	14.5	9	15.1
Vapour pressure @ 38°C (psi)	0.04	2.5	7-9
Flash point (°C)	55-65	13	-40
Boiling temperature (°C)	170-340	78	33-213
Vaporization heat (kJ/kg)	-	842	300
Auto-ignition temperature (°C)	230-315	366	300-371
Flammability limits (°C)	64-150	13-42	(-40)-(-18)
Flammability limits (% vol)	0.6-5.6	3.3-19.0	1.4-7.6

Bioethanol can be used as chemical in industrial applications, as fuel for energy generation, or as food. It can be produced by synthesis or by fermentation processes, and be or not denatured. Ethanol can be used neat or blended with gasoline or diesel fuels. It is also used for the production of ETBE (Ethyl Tertiary Butyl Ether), an oxygenated fuel obtained by mixing ethanol and isobutylene and reacting them with heat over a catalyst. ETBE promotes clean gasoline combustion, thus improving air quality.

2. Bioethanol market

Biomass currently supply 4 % of EU energy needs from biomass (Biomass Action Plan, 2005). The increased use of biomass is expected to generate a wide range of benefits and advantages, such as a greater diversification of energy supply and reduction of energy imports, reduction of greenhouse gas emissions, and creation of new permanent jobs, especially in the rural areas.

Bioethanol is playing a very important role in the liquid fuel market: bioethanol worldwide production was greater than 18 Mt/y in 2003, sig-




Fig. 8.1. EU-25 and World bioethanol production (from Biofuel Barometer, June 2004).