POLITECNICO DI TORINO Repository ISTITUZIONALE

Life Cycle Inventory of technologies for stone quarrying, cutting and finishing: Contribution to fill data gaps

Original

Life Cycle Inventory of technologies for stone quarrying, cutting and finishing: Contribution to fill data gaps / Bianco, I.; Blengini, G. A., - In: JOURNAL OF CLEANER PRODUCTION. - ISSN 0959-6526. - ELETTRONICO. - 231:(2019), pp. 419-427. [10.1016/j.jclepro.2019.05.170]

Availability: This version is available at: 11583/2812974 since: 2020-04-17T11:14:29Z

Publisher: Elsevier Ltd

Published DOI:10.1016/j.jclepro.2019.05.170

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Accepted Manuscript

Life Cycle Inventory of technologies for stone quarrying, cutting and finishing: Contribution to fill data gaps

Isabella Bianco, Gian Andrea Blengini

PII: S0959-6526(19)31696-8

DOI: https://doi.org/10.1016/j.jclepro.2019.05.170

Reference: JCLP 16935

To appear in: Journal of Cleaner Production

Received Date: 4 August 2018

Revised Date: 2 May 2019

Accepted Date: 15 May 2019

Please cite this article as: Bianco I, Blengini GA, Life Cycle Inventory of technologies for stone quarrying, cutting and finishing: Contribution to fill data gaps, *Journal of Cleaner Production* (2019), doi: https://doi.org/10.1016/j.jclepro.2019.05.170.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



2

5

6

1

Life Cycle Inventory of technologies for stone quarrying, cutting and finishing: Contribution to fill data gaps.

Isabella Bianco^a*, Gian Andrea Blengini^a

^aPolitecnico di Torino, DIATI, corso Duca degli Abruzzi 24, 10129 Turin (Italy)

8 *Corresponding author. Politecnico di Torino, DIATI, corso Duca degli Abruzzi 24, 10129 Turin (Italy).

9 Tel.: +39 011 090 7652. E-mail address: <u>isabella.bianco@polito.it</u>

10

12

11 HIGHLIGHTS

- Life Cycle Inventory datasets on dimension stone technologies and tools
- 13 LCI on explosives, abrasive technologies and intermediate products
- Inventory of technologies widely employed in stone and other sectors
- Parameters to adapt LCI datasets to specific technologies/tools
- 16

17 ABSTRACT

18 Italy is among the major producers of dimension stones and a world leader in terms of technologies for stone quarrying, cutting and finishing. In the current context of European Environmental and Raw Material 19 policies, the stone sector is expected to enhance its overall sustainability and circularity. Previous studies 20 21 have used Life Cycle Assessment (LCA) to evaluate the environmental performance of stone production, 22 along the supply chain. Nevertheless, despite the fairly high level of maturity in terms of methodology, previous LCA studies have highlighted the scarce availability of Life Cycle Inventory (LCI) datasets related 23 to stone sector technologies, which inevitably required the introduction of heavy simplifications. The present 24 25 paper contributes to fill these gaps by providing detailed LCI datasets of the most common technologies and tools for stone quarrying, cutting and finishing. Datasets have been developed on the basis of primary data 26 27 provided by three major Italian producers of cutting tools, complemented with secondary data from 28 literature, where necessary. Moreover, modelling parameters have been set to enable the datasets update or 29 their adaptation to specific production chains of the stone or other sectors. "Supplementary Material" 30 provides details on the analysed technologies and on the related datasets (data sources, functional unit, 31 system boundaries, Life Cycle models, parameters and uncertainty). Finally, LCI datasets are provided in file 32 format as well.



34

35 KEYWORDS: dimension stone; Life Cycle Inventory; LCA; explosives; abrasive technologies; stone
 36 production chain

37 1. INTRODUCTION

The Italian territory features a significant lithological variety, which has been an important source of 38 39 dimension stones all over the centuries. Italy is among the main stone producers and a world leader in terms of technologies for quarrying, cutting and finishing. The present paper specifically focuses on such 40 technologies and provides datasets intended to facilitate the environmental profile measurement and to 41 42 support a better sustainability of the stone sector. In fact, as declared in the Circular Economy Action Plan 43 (European Commission, 2015), primary raw materials (which includes also dimension stones) play an 44 important role in production processes and attention must be paid to the environmental and social impacts of 45 their production. In this context, the European Union bases the Environmental and Raw Materials Policies 46 on the consolidated Life Cycle Thinking (LCT) approach (European Commission, 2010), which consists in 47 considering the entire life of products, services or projects to identify and reduce environmental, economic and social impacts all along the value production chain. To apply the concept of LCT to the stone sector, 48 49 both techniques and technologies employed in the production chain should be investigated. In particular, 50 techniques concern the operational way of carrying out quarrying, cutting and finishing processes, while technologies are basic tools and materials used to execute the techniques. For example, the main technique 51 for marble quarrying consists in drilling intersecting holes along the edges of the bench, in order to create a 52 53 close circuit where a wire is made rotating at high speed. This quarrying technique requires the use of 54 different technologies, such as rods, bits and diamond wires.

In this context, to better understand and possibly improve the overall sustainability of the stone production chain, a fairly comprehensive and reliable inventory of energy, materials, emissions and waste involved during the technique execution and during the tools and machineries life cycle should be made available.

To turn the LCT approach into a quantitative assessment, different tools have been developed, the most known of which is Life Cycle Assessment (LCA). The Integrated Product Policy (European Commission, 2003) has identified LCA as the best framework to assess potential impacts of products and services and since that moment LCA has been more and more employed to boost the smart and sustainable growth of the European Union. LCA has been significantly implemented in some construction materials' sectors, such as

in the ceramic, concrete and bricks sectors (Ibáñez-Forés and Bovea, 2016; Strazza et al., 2010; Torricelli et 63 al., 2009), while in the dimension stone sector it has been relatively less employed. The limited number of 64 LCA studies in this field could partially be ascribed to the high variability of the natural stone production 65 chain (mainly related to the choice of techniques/technologies and to site-specific conditions) and, most 66 67 probably, to the scarce availability of Life Cycle Inventory (LCI) datasets specific to the most common stone quarrying, cutting and finishing techniques and technologies. This lack of data is directly reflected in the 68 69 LCA studies available for the stone sector, which have been necessarily simplified. Nicoletti et al. (2002) performed a LCA to compare ceramic and marble tiles, mainly based on energy and water consumption. 70 Analogously, LCA studies have been developed by Traverso et al. (2010) who assessed the production of 71 Perlato marble from Sicily, and by Torricelli and Palumbo (2016) who focused on the supply chain of 72 Firenzuola stone from Tuscany. Nevertheless, also in these cases the assessments were mainly based on the 73 74 input flows of energy and water resources, while impacts connected to the specific cutting technologies were 75 not considered because of the unavailability of the related Life Cycle datasets. Similar studies have been 76 developed in other stone production countries, such as Greece (Gazi et al., 2012), United Kingdom and 77 Ireland (Crishna et al., 2011). Catarino et al. (2016) identified the main input/output flows of each unitary 78 operation of the Portuguese marble production chain, but did not clearly disclosed the inventory. In 2012, a 79 detailed LCI on the main techniques of the Brazilian stone production chain has been developed by the research centre CETEM of Rio de Janeiro (Castoldi Borlini Gadioli et al., 2012) and this same research 80 81 group is currently updating the datasets. Nevertheless, since these datasets refer to the Brazilian average 82 stone slab production, they are not necessarily representative of the Italian production. Mendoza et al. (2014) 83 and Bai et al. (2016) disclosed LCIs and calculated the related potential environmental impact of the 84 techniques employed respectively in the Spanish and Chinese granite production chains. However, in both 85 cases, the LCA was developed including simplified datasets of the employed technologies, probably because of unavailability of more detailed data (e.g. the diamond wire was accounted as steel, while the diamond 86 87 beads production was not considered).

The main novelty of this study is the development of detailed LCI datasets on the main quarrying, cutting 88 89 and finishing technologies, which are produced and widely employed in Italy, as well as exported worldwide. This paper aims therefore at contributing to fill the gaps of representative LCI datasets in the 90 91 stone sector by providing a set of data which are easily employable for the development of LCA studies 92 tailored on specific production chains. A strength of this work is the introduction, in the provided LCI 93 datasets, of editable parameters, which enable users to eventually update the datasets or to modify them according to specific production chains. Moreover, since analogous cutting technologies are employed also 94 95 in other contexts (such as, for example, for building demolitions), these datasets could easily be adapted to 96 other sectors. The inventory of each analysed technology is clearly quantified in this paper and is, as well, provided in file format in the Mendeley Data Repository, in order to allow its direct use in LCA software. 97 Therefore, the availability of flexible and replicable datasets is expected to provide a practical support for the 98 research on sustainability and circular economy and to increase the pool of publicly available data for 99 specific applications in the stone and other sectors. Whereas technologies datasets are here presented, a 100 companion paper (Bianco and Blengini, 2019) provides LCI data on the most common techniques used in 101 the stone sector. 102

103 104

2. METHODOLOGY

The development of LCI datasets of technologies for stone quarrying, cutting and finishing has beencarried out through the steps summarised in Fig. 1.



Figure 1: Scheme summarising the methodology followed for the development and share of the LCI datasets presented in this paper. The last step (in grey colour) will be accomplished in the next future.

Firstly, a preliminary investigation has been carried out in Italian quarries and transformation plants to 111 identify the most widespread technologies employed in the ornamental stone sector. Since techniques and 112 underlying technologies change mainly according to the hardness of the stone, the tools employed in both 113 soft stones (such as marbles) and hard stones (such as granites) were investigated. In particular, on-site 114 115 investigations took place in Piedmont and Tuscany regions and a literature review has been carried out to 116 check if also in other Italian Regions the same technologies are used. The main literature sources have been 117 Cardu (2013, 2012); Crivello (2012); Dadalto Sahao (2013); Giuffrida (2010); Gussoni (2016) Masciullo (2016); Primavori (2011, 1999). 118

Subsequently, it has been verified whether LCI datasets on the identified technologies or their components were already available in the main LCA databases. In particular, process datasets were searched in Gabi, Ecoinvent and ELCD databases. The production chain related to the unavailable LCI datasets has been further investigated through data collection with the aim of setting up good quality LCIs of the stone sector technologies.

To this aim, some enterprises producing stone quarrying, cutting and finishing technologies provided primary data. The enterprises that majorly collaborated to the project are Mega Diamant (Carrara, producing sintered diamond wire), Mimitalia (Vado Ligure, producing sintered tools) and Stein Varz (Crevoladossola, producing diamond cutting tools). Secondary data from scientific literature, patents and technical sheets were also employed for the datasets development.

Datasets were then developed according to ISO 14040-44 standards (The International Standards 129 Organisation, 2006a, 2006b) and the requirements of format and quality defined in the International 130 Reference Life Cycle Data System (ILCD) Handbook (European Commission, 2012). Therefore, the 131 European Commission underlined the need and the importance of relying on uniform, consistent and good 132 133 quality Life Cycle datasets (Recchioni et al., 2015) and, from 2014, developed the Life Cycle Data Network¹ 134 (LCDN) to host compliant Life Cycle datasets. The developed datasets include input flows of materials, 135 resources and energy and output flows of product, waste and emissions. As showed in Fig. 2, the processes of the waste treatment are included in the system boundaries only when, in the current practices, the waste is 136 137 reintegrated in the same production chain. This is the case, for example, of diamond beads of cutting diamond wires: beads often have a lifetime longer than other components of the wire and are generally 138 reused several times for the production of new diamond wires. On the contrary, waste that leave the stone 139

¹ http://eplca.jrc.ec.europa.eu/LCDN/

- 140 production value chain is quantified, but no credits or debits are associated to it in the developed datasets.
- 141 This choice is justified by the high variability of waste treatment, recycle, reuse or discard practices that
- 142 would compromise the representativeness of the dataset.



143 144

Figure 2: System boundaries of the developed LCI datasets.

The values of input/output flows are the average of the collected data. Primary data from Italian tools 145 146 producers have been preferred when available; secondary data from literature, technical sheets and patents have also been used to both complete and cross check primary data. The specific source(s) of data are 147 detailed in the Supplementary Material. In addition, for each input/output flow, data quality information is 148 149 provided to easily identify the level of datasets reliability. To this aim, the well-established Ecoinvent pedigree matrix (Weidema et al., 2013) has been used for the assessment of data sources quality. As showed 150 in Fig. 3, the pedigree matrix allows to evaluate the data sources according to five independent 151 characteristics (reliability, completeness, temporal correlation, geographic correlation and further 152 technological correlation) and each of them is rated with a score from 1 to 5 (where 1 corresponds to the 153 highest quality and 5 to the worst one, as described in Fig. 3). 154

CERT

Reliability	Verified data based on measurements	Verified data partly based on assumptions or non-verified data based on measurements	Non-verified data partly based on qualified estimates	Qualified estimate (e.g. by industrial expert)	Non-qualified estimates
Completeness	Representative data from all sites relevant for the market considered, over and adequate period to even out normal fluctuations	Representative data from > 50% of the sites relevant for the market considered, over an adequate period to even out normal fluctuations	Representative data from only some sites (<< 50%) relevant for the market considered or > 50% of sites but from shorter periods	Representative data from only one site relevant for the market considered or some sites but from shorter periods	Representativeness unknown or data from a small number of sites and from shorter periods
Temporal correlation	Less than 3 years of difference to the time period of the data set	Less than 6 years of difference to the time period of the data set	Less than 10 years of difference to the time period of the data set	Less than 15 years of difference to the time period of the data set	Age of data unknown or more than 15 years of difference to the time period of the data set
Geographical correlation	Data from area under study	Average data from larger area in which the area under study is included	Data from area with similar production conditions	Data from area with slightly similar production conditions	Data from unknown or distinctly different area (North America instead of Middle East, OECD-Europe instead of Russia)
Further technological correlation	Data from enterprises, processes and materials under study	Data from processes and materials under study (i.e. identical technology) but from different enterprises	Data from processes and materials under study but from different technology	Data on related processes or materials	Data on related processes on laboratory scale or from different technology

155

Figure 3. Econvent pedigree matrix. In the example showed in the Figure, the data quality can besummarized as (4,3,2,5,1).

With the support of Gabi software both Unit and System processes² have been developed. Specifically, 158 Unit processes enable the user to transparently identify and quantify input/output flows involved in each 159 technology. Moreover, Unit processes contain parameters that facilitate the eventual update of the dataset or 160 its adaptation to specific production chains. For example, the dataset of diamond disks can be easily 161 customized in function of the disk diameter, the thickness of the steel core, the number and dimensions of 162 163 diamond segments, etc. Parameters could therefore enable the datasets to be used also in reference to analogous cutting technologies used in other sectors (such as the Construction and Demolition sector). On 164 the other hand, system processes are provided for users that prefer to directly employ the datasets without 165 modifications, avoid the connection with background datasets or limit the size of the file model. 166

167 The inventory of these datasets is quantified in detail in the next paragraph, while the file format of Unit 168 and System datasets is available in the Mendeley Data Repository connected to this paper. Additional 169 information on the tools production chain and on the datasets modelling are provided in the "Supplementary 170 Material".

171 172

3. RESULTS: LCI DATASETS

Datasets presented in this paper are summarized in Fig. 4. The most common technologies for stonequarrying, cutting and finishing have been considered. Since some technologies are often employed in more

 $^{^{2}}$ A "unit process" is a gate-to-gate process, where input and output data are quantified with product flows and eventual elementary flows; a "system process" is an element with an aggregated inventory, where input and output data are all expressed as elementary flows.

175 than one phase of the stone production chain, technologies are here subdivided into: (i) explosives: tools used to create a controlled explosion and generally employed during the quarrying phase; (ii) abrasive 176 technologies: tools providing mechanical abrasion, employed during all the three phases of stone production 177 chain; (iii) intermediate products: semi-finished products necessary for the production of the before 178 mentioned technologies. Fig. 4 indicates, as well, the stone production phase(s) during which the different 179 180 explosive and abrasion technologies are used. Moreover, as it can be noticed, some intermediate products 181 concur to the production of different tools, such is the case, for example, of the diamond powder. For each developed dataset, additional information is provided in the "Supplementary Material". Specifically, datasets 182 sheets are organised as shown in Fig. 5 and contain details on the technologies production chains, data 183 sources, functional unit, system boundaries, life cycle model, parameters and uncertainty. 184



Figure 4: Scheme summarizing the LCI datasets described in this paper. Technologies are divided into 186 explosives, intermediate products and abrasive technologies. In brackets is indicated the phase of the stone 187 supply chain during which the finished tools are usually employed (Q= quarrying; C = cutting; F = 188 finishing). 189

Number assigned to the dataset, corresponding to the number showed in Fig. 3 and listed in tables 1-4 Name of the dataset							
LCI dataset 11: Sintered di	LCI dataset 11: Sintered diamond wire; for stone quarrying; at plant						
				Eventual graphical representations or photos<			
Technology description: To semi-automatic system. Subse	produce the diamond quently, the steel rope	l wire, beads are i e has to be covere	nserted in a steel rope with a d with a protecting layer []	Description of the technology and its production chain			
LCI data sources: Data were specialized in the production of	collected in the Italian of sintered diamond w	n enterprise Mega ires []	Diamant, located in Carrara and	Sources of data employed for the inventory development			
Functional unit: 1 m of sinte	red diamond wire wit	h plastic coating.		Reference unit of the dataset			
System boundaries and mo 1 m of sintered diamond wire composed by 6 strands (each o	odel description: Th with plastic coating. The one composed by 7 wi	e dataset includes he steel rope has res) wrapped arou	s processes for the production of a diameter of 4,85 mm and it is und a 19 wires core []	information on the processes included in the dataset and description of the related model			
Parameters: parameters allo	w the user to modify t	the number of bea	ads, the weight of the steel wire	[] Description of parameters			
Parameter Value Comment Implemented in the dataset. Bead 0,043 kg - mass of beads for 1 m of wire (see plan parameters) A table summarises the name, the value and the Electricity 3,240 MJ per m of wire manue, the value and the							
Data quality:							
	Unit of measure]	VALUE	DATA QUALITY	Data quality for each			
X Sintered diamond bead [kg] 0.0427 (1;3;1;1) X Electricity, IT grid mix [MJ] 3.24 (2;3;1;1) X [] (] (]							

190 191

Figure 5. Information provided in the Supplementary Material for each developed LCI dataset.

192 3.1 LCI of explosives in the dimension stone sector

Explosive tools are commonly employed in hard stone quarries to open benches and divide them into smaller commercial blocks. The most widespread technologies to perform a controlled splitting are black powder, detonating cords of penthrite, slow-burning fuses and detonators. These same tools are commonly employed also in other mining processes and in civil demolitions. Since Life Cycle databases do not currently include datasets on these tools, specific inventories have been developed, whose detailed input/output flows are gathered in Table 1 (LCI datasets 1-4). Reference processes from Gabi, Ecoinvent and ELCD databases are proposed.

201

TUPUT	TUATUO	FLOW NAME [Unit of measure]	VALUE	LCI DATASETS OF REFERENCE
		LCI dataset 1: Bla	ack powde	r
Х		Potassium nitrate [kg]	0.75	Ecoinvent: potassium nitrate, as N, at regional storehouse
Х		Charcoal [kg]	0.14	Ecoinvent: charcoal, at plant
Х		Sulphur [kg]	0.11	Gabi: Sulphur (elemental) at refinery
Х		Electricity, IT grid mix [MJ]	0.152	Gabi: IT Electricity grid mix

I	Х		Transport, lorry [kg*km]	1000	Gabi: Lorry transport
		Х	Black powder [kg]	1	-
		Х	Carbon dioxide [kg]	0.219	Elem. flow: Carbon dioxide, fossil
					[emission to air]
		Х	Nitrogen [kg]	0.058	Elem. flow: Nitrogen, atmospheric
					[emission to air]
		Х	Heat, waste [MJ]	3	Elem. flow: Heat, waste [emission to
					air]
		Х	Potassium sulphate [kg]	0.434	Elem. flow: Sulfuric acid [emission
					to air]
			LCI dataset 2: Slow	-burning f	use
	Х		Black powder [kg]	0.011	Ecoinvent: potassium nitrate, as N, at
					regional storehouse
	Х		Cotton [kg]	0.001	Ecoinvent: charcoal, at plant
	Х		PVC [kg]	0.016	Gabi: Sulphur (elemental) at refinery
	Х		Transport [kg*km]	28	Gabi: Small lorry (7.5t) incl. fuel
	Х		Oil [kg]	0.002	Ecoinvent: lubricating oil, at plant
		Х	Slow burning fuse [m]	1	
			LCI dataset 3: I	Detonator	
	Х		Aluminium [kg]	0.001	Gabi: Aluminium extrusion profile
					mix
	Х		Transport [kg*km]	2	Gabi: Small lorry (7.5t) incl. fuel
		Х	Detonator [pcs]	1	-
			LCI dataset 4: Det	onation co	rd
	Х		Pentaerythritol [kg]	0.0017	Ecoinvent: penta-erythritol, at plant
	Х		Nitric acid [kg]	0.0067	Gabi: Nitric acid (98%)
	Х		Toluene [kg]	0.0016	Gabi: Toluene
	Х		Polypropilene [kg]	0.018	Gabi: Polypropylene / Ethylene
					Propylene Diene Elastomer Granulate
					(PP/EPDM, TPE-O) Mix
	Х		Transport [kg*km]	14	Gabi: Small lorry (7.5t) incl. fuel
		X	Detonation cord: at quarry [m]	1	-

Table 1: Life Cycle Inventory of the main tools employed in hard stone quarries to perform the dynamic splitting
 technique. The data sources employed for the development of each dataset are the following. LCI datasets 1-2:
 Bacci, 2005; Davis, 1943; Evonik Industries, 2014; Reza et al., 2014; Selva and Nardin, 2013; von Maltitz, 2003.
 LCI dataset 3-4: Pravisani technical sheets; Palma Rojas et al., 2013.

206

207 3.2 LCI of intermediate products

208 The production of tools employed in the ornamental stone sector requires the use of different materials 209 and intermediate products, some of them highly widespread also in other sectors. Since for some relevant components little or even no data are currently available in Life Cycle databases, the related production 210 chains have been investigated as well and the resulting inventories are quantified in Table 2. In particular, 211 LCI datasets have been developed on synthetic diamond powder (LCI dataset 5), a material largely employed 212 for the production of abrasive tools, tungsten carbide (LCI dataset 6), employed in many different sectors for 213 its hardness; two different composition of metal matrices (LCI datasets 7-8), widely used to produce cutting 214 elements such as diamond segments (LCI dataset 10). Finally, the diamond powder is employed for the 215 production of the diamond beads (LCI dataset 9), which are the cutting elements of diamond wires employed 216 217 in stone quarries and transformation plants, but also for civil demolitions. 218

TUPUI	OUTPUT	FLOW NAME [Unit of measure]		VALUE	LCI DATASETS OF REFERENCE
		LCI data	aset 5: Diar	nond powd	ler
Х		Electricity, IT grid mix [MJ]		3024	Ecoinvent: electricity, production mix CN
X X	r 	Graphite [kg] Transport, transoceanic ship [kg*km]		1 170000	Ecoinvent: graphite, at plant Ecoinvent: transport, transoceanic freight ship
Х		Transport, lorry [kg*km]		0.063	Ecoinvent: transport, lorry 16-32t, EURO4
	X	Diamond powder [kg]		1	-
		LCI dataset	6: Tungsto	en carbide	(WC)
Х	[NaOH [kg]		0.91	Ecoinvent: Sodium hydroxide, 50% in
X		Al ₂ (SO ₄) ₃ -18H ₂ O [kg]		0.071	H2O, production mix, at plant/RER Ecoinvent: Aluminium sulphate, powder, at plant/RER
X		Sodium sulfide [kg]		0.044	Ecoinvent: Sodium sulphide
Х		$Mg(SO_4)-7H_2O[kg]$		0.027	Écoinvent: Magnesium sulphate, at plant/RER
Х	r	Ammonium hydroxide [kg]		0.106	Ecoinvent: Ammonia, liquid, at
X		Soda ash [kg]		1.21	regional storehouse/CH Ecoinvent: Soda, powder, at
Х	r	Sulphuric acid [kg]		1.24	Ecoinvent: Sulphuric acid, liquid, at
X		Electricity [MJ]		159	Ecoinvent: Electricity, medium
Х		H ₂ compressed gas [kg]		0.0076	Ecoinvent: Hydrogen sulphide, H2S, at plant/RER
X		N ₂ compressed gas [kg]		1.65	Ecoinvent: Nitrogen, liquid, at plant/RER
X		H ₂ S liquefied gas [kg]		0.32	Ecoinvent: Hydrogen, liquid, at plant/RER
X		Electricity [MJ]		77.2	Econvent: Electricity, medium
Х		NaOH [kg]		0.58	Ecoinvent: Sodium hydroxide, 50% in H2O, production mix, at plant/RER
Х		Water [kg]		2.84	Ecoinvent: cooling water
X		Carbon black [kg]		0.13	Ecoinvent: carbon black, at plant
X		Electricity [MJ]		164	Econvent: Electricity, medium
	X	Tungsten carbide [kg]		1	-
		LCI dataset 7-8:	: Metal ma	trix for cu	tting tools
			49%Fe-	57%Fe-	
X/	-	T CI 1	18%Co	25%Co	
			0.49	0.57	Econvent: iron ore, 65% Fe, at beneficiation
		Cobalt [kg]	0.18	0.25	Econvent: cobalt, at plant
	-	INICKEI [Kg]	0.06	0.12	Econvent: nickel, 99.5%, at plant
$\begin{vmatrix} \Lambda \\ \mathbf{v} \end{vmatrix}$	-	Cupper [Kg] Tungstan carbida [kg]	0.20	0.03	Croated: Tungston carbida
		Tin [kg]	0.04	0.01	Ecoinvent: tin at regional storage
1 × 3	1 1	[B]	0.00		

0.03

Tin [kg]

Ecoinvent: tin, at regional storage

	Γx	Metal matrix: for diamond cutting tools [kg] 1	1	
	- 11	LCI dataset 9: Sinte	ered diamo	nd bead
X		Electricity, IT grid mix [MJ]	0.36	Gabi: Electricity grid mix
X		Steel core [g]	3	Gabi: Steel billet (20MoCr4)
X		Cobalt [g]	7E-05	Ecoinvent: cobalt, at plant
Х		Copper [g]	0.00021	Gabi: Copper mix (99,999% from
				electrolysis)
Х		Iron [g]	3.5E-04	Ecoinvent: pig iron, at plant
Х	-	Nickel [g]	2.1E-05	Ecoinvent: nickel, 99.5%, at plant
Х		Tungsten [g]	3.5E-05	Created (cf. Par. 5.2.6): Tungsten (W)
Х	-	Diamond powder [g]	2E-05	Created (cf. Par. 5.2.9): Diamond
				powder
X		Thickener [kg]	2E-05	Gabi: Polymethylmethacrylate
				granulate (PMMA)
X		Hardener [kg]	5E-05	Ecoinvent: cobalt, at plant
Х	-	Silver weld [kg]	2.1E-04	Ecoinvent: silver, at regional storage
X		Nitrogen [kg]	0.0323	Gabi: Nitrogen
X		Hydrogen [kg]	9E-04	Gabi: Hydrogen
	X	Sintered diamond bead; for quarrying [g]	4	
	1	LCI dataset 10: Dia	mond secto	r
Х		Electricity [MJ]	255	Gabi: IT Electricity grid mix
Х	-	Graphite [kg]	0.0394	Ecoinvent: graphite, at plant
Х		Diamond powder [kg]	0.02	Created: Diamond powder
Х		Metal matrix; for diamond cutting tools [kg]	0.98	Created: Metal matrix; for diamond
				cutting tools; Mix 57%Fe-25%Co
				or
			7	Metal matrix; for diamond cutting tools;
			4	Mix 49%Fe-25%Co
	X	Diamond sector; for cutting tools [kg]	1	-

219 **Table 1:** Life Cycle Inventory of intermediate-products for the production of cutting and finishing tools. The data sources employed for the development of each dataset are the following. LCI dataset 5: Ali, 2011; Larsson et al., 220 2009; www.searates.com. LCI dataset 6: Archer et al., 2003; Bobba et al., 2016; Dahmus and Gutowski, 2004; 221 Novak et al., 2004; Syrrakou et al., 2005. LCI datasets 7-8: primary data from enterprises Stein Varz 222 223 (Crevoladossola) and MIMitalia (Vado Ligure); Umicore-Tungsten technical sheets. LCI dataset 9: primary data from enterprises Mega Diamant (Carrara) and MIMitalia (Vado Ligure); Umicore-Tungsten technical sheets; 224 Bobrovnitchii et al., 2003; de Oliveira et al., 2007; Karagöz and Zeren, 2001; Konstanty, 2007; Tillmann et al., 225 2010; Zeren and Karagöz, 2007, 2006. LCI dataset 10: primary data from enterprise Stein Varz (Crevoladossola); 226 technical sheets of the enterprises Diam Edil (Lumino), Cuts Diamant (Noceto), Unidiamant (Carpaneto 227 228 Piacentino).

229

230 3.3 LCI of abrasive technologies

Table 3 gathers the inventories related to the production chain of the most common abrasive tools 231 employed in the ornamental stone sector. In particular, LCI datasets have been developed for the 232 technologies of: sintered diamond wire (LCI dataset 11), highly widespread to separate soft stone benches 233 234 from the quarry bedrock, divide them into blocks and square shapeless blocks; giant diamond disks (LCI 235 dataset 12), commonly used in hard stone transformation plants to square shapeless blocks or to cut thick slabs according to the requests of customers; diamond disks of 400 mm diameter (LCI dataset 13) and 600 236 mm diameter (LCI datasets 14-15), commonly employed for cutting stone slabs into smaller parts. As 237 explained in detail in the "Supplementary Material", two datasets have been created for the 600 mm diameter 238 239 disk because its performance (and as a consequence the quantities of its input/output flows during its lifetime) significantly changes according to a prevalent use with soft or hard stones. Diamond blade (LCI 240 dataset 16) is a technology used for cutting soft stone blocks into slabs; rods (LCI dataset 17) and bits (LCI 241

dataset 18) are the most common tools employed to perform holes drilling in soft and hard stone quarries. In 242 addition, since the most common surface treatments for stone slabs are the smoothing and polishing 243 processes, the related technologies have been investigated. In particular, LCI datasets have been developed 244 on three types of abrasives: metal abrasive (LCI dataset 19), generally used for the smoothing phase; resin 245 246 diamond abrasive (LCI dataset 20), which is the most common tool for the polishing phase; magnesite

abrasive (LCI dataset 21), another polishing abrasive, currently less widespread than the resin diamond one. 247

TUPUI	OUTPUT	FLOW NAME [Unit of measure]		VALUE		LCI DATASETS OF REFERENCE
		LCI dataset 11: Si	amond	wire		
Х		Sintered diamond bead [kg]	1	0.042	7	Created: Sintered diamond bead; for
X X X		Electricity, IT grid mix [MJ] Steel rope [kg] Plastic coating [kg]		3.24 0.095 0.15		quarry diamond wires Gabi: IT Electricity grid mix Gabi: Steel wire rod Gabi- PlasticsEurope: Polyurethane flexible foam (PU)
X		Lorry transportation [kg*km]		3		Gabi: Lorry transport
	X X	Sintered diamond wire; for stone quarrying [m] Plastic waste [kg]		1 0.045		Ş
		LCI dataset 12: 0	Gian	t dia	mond di	isk
Х		Steel [kg]		12.4		Created: Sintered diamond bead; for
X X		Diamond segment [kg] Electricity [MJ]		12.4 515	/ / /	quarry diamond wires Gabi: IT Electricity grid mix Gabi: Steel wire rod
X		Transport [kg*km]		248		Gabi- PlasticsEurope: Polyurethane flexible foam (PU)
	Χ	Giant diamond disk [pcs]		1		-
	LCI dataset 13: Diamond disk; d=400 mm					
X X		Steel [kg] Diamond segment [kg]	1	1.39 0.504		Gabi: Stainless steel Quarto plate (304) Created: Diamond segment; for cutting tools; Mix 49%Fe-18%Co (or Mix 57%Fe-25%Co)
Х		Electricity [MJ]		107		Gabi: IT Electricity grid mix
Χ		Transport [kg*km]		18.9		Gabi: Lorry (22t) incl. fuel
	Χ	Diamond disk; d=400 mm [pcs]		1		-
		LCI dataset 14-15	: Dia	mon	<u>d disk; o</u>	1=600 mm
			50 sto		Haru stone	
X		Steel [kg]	2.4	9	1.07	Gabi: Stainless steel Quarto plate
X		Diamond segment [kg]	0.54	46	0.897	(304) Created: Diamond segment; for cutting tools; Mix 49%Fe-18%Co (or Mix 57%Fe-25%Co)
Х		Electricity [MJ]		149		Gabi: IT Electricity grid mix
X		Transport [kg*km]	72.	8	19.6	Gabi: Lorry (22t) incl. fuel
	Χ	Diamond disk; d=600 mm [pcs]	1			-
**		LCI dataset	t 16:	Diar	nond bl	ade
X X		Stainless steel [kg]		0.2 14.1		tools; Mix 49% Fe-25% Co Gabi: Stainless steel quarto plate (304)
Х		Electricity [MJ]		66.8		Gabi: IT Electricity grid mix

X		Transport [kg*km]	344	Gabi: Lorry transport	
	x	Diamond blade [kg]	14.3	Created	
	X	Stainless steel scrap	14.1	-	
		LCI dataset	17: Drilling ro	bd	
X		Steel rod [kg]	10.5	Gabi: Steel rebar	
X		Tungsten carbide [kg]	0.086	Created: Tungsten carbide	
X		Transport [kg*km]	525	Gabi: Lorry (22t) incl. fuel	
	Χ	Drilling rod; at quarry [m]	3.20	-	
	X	Iron scrap [kg]	10.5	-	
		LCI dataset	18: Drilling b	it	
Х		Steel [kg]	2.2	Gabi: Steel rebar	
Χ		Tungsten carbide [kg]	0.0058	Created: Tungsten carbide	
Χ		Transport [kg*km]	110	Gabi: Lorry (22t) incl. fuel	
	Χ	Drilling bit; at quarry [pcs]	1	-	
	Χ	Iron scrap [kg]	2.2	-	
		LCI dataset 19: N	Metal abrasive	2	
Х		Electricity [MJ]	12.6	PE: IT Electricity grid mix	
Х		Diamond segment [kg]		Created: Diamond segment; for cutting	
			0.144	tools; Mix 49%Fe-18%Co	
Х		Steel [kg]	2.22	PE: Steel hot rolled section	
Χ		Transportation [kg*km]	450	PE: Lorry (22t) incl. fuel	
	Χ	Metal abrasive; for stone surface treatment [pcs]	1	-	
		LCI dataset 20: Resin	diamond abr	asive	
Х		Epoxy resin [kg]	0.145	Gabi: Epoxy resin	
X		Diamond powder [kg]	0.034	Created: Diamond powder	
X		Silica sand [kg]		Gabi: Silica sand (Excavation and	
			0.121	processing)	
X		Ethanol [kg]	0.043	Gabi: Ethanol	
Х		Methylene [kg]	0.145	Gabi: Methylene diisocyanate (MDI)	
X		Silicon carbide [kg]	0.087	Ecoinvemt: silicon carbide, at plant	
X		Graphite [kg]	0.034	Ecoinvent: graphite, at plant	
X		Plastic [kg]	0.051	Gabi: Plastic injection moulding part	
11		- more [ng]	0.1	(unspecific)	
X		Electricity [MJ]	10.8	Gabi: IT Electricity grid mix	
X		Transportation [kg*km]	127	Gabi: Lorry (22t) incl. fuel	
	X	Resin diamond abrasive: for stone polishing [kg]	1	-	
		LCI dataset 21: Ma	gnesite abras	ive	
X		Phenolic resin [kg]	0.067	Ecoinvent: phenolic resin at plant	
X		Magnesium oxide [kg]	0.248	Ecoinvent: magnesium oxide, at plant	
X		Magnesium chloride [kg]	0.161	Gabi: Magnesium	
X		Water [kg]	0.063	Gabi: Tap water	
		Silicon carbide [kg]	0.005	Econvent: silicon carbide at plant	
$\begin{vmatrix} \Lambda \\ \mathbf{v} \end{vmatrix}$		Aluminium oxide	0.000	Econvent: aluminium ovide at plant	
$\begin{vmatrix} \Lambda \\ \mathbf{v} \end{vmatrix}$		Quartz cond [kg]	0.040	Cobi: Silico cond (Exception or 1	
Α			0.013	brocessing)	
\mathbf{v}		Plastic [kg]	0.015	Gabi Plastic injection moulding part	
Λ			0.1	(unspecific)	
x		Electricity [M]]	10.8	Gabi: IT Electricity orid mix	
		Transportation [kg*km]	10.0	Gabi: Lorry (22t) incl_fuel	
	\mathbf{v}	Magnesite abrasive: for stone polishing [kg]	1		
<u> </u>	Table 3: Life Cycle Inventory of the main dimension stone outting technologies. The data services employed for				

Table 3: Life Cycle Inventory of the main dimension stone cutting technologies. The data sources employed for
 the development of each dataset are the following. LCI dataset 11: primary data from enterprise Mega Diamant
 (Carrara); technical sheets of the enterprises Metalfuni and CO.FI.PLAST. LCI dataset 12-15: primary data from

enterprise Stein Varz (Crevoladossola) and from three stone transformation plants located in Piedmont and
Carrara. LCI dataset 16: primary data from enterprise Stein Varz (Crevoladossola); technical sheets from
enterprises BM and Dellas. LCI dataset 17-18: direct measurements on drilling rods/bits; technical sheets of
enterprises Geocom and Tenir. LCI dataset 19: primary data from enterprise Stein Varz (Crevoladossola) and a
transformation plants located in Carrara. LCI dataset 20: Scalari, 2007; Thimmappaiah et al., 1999; Wiand, 1995;
Yuhang and Zheng, 2006; Zhou et al., 2012. LCI dataset 21: Liu et al., 2012.

257 258

4. CONCLUSIONS

259 As several European Environmental policies are based on Life Cycle Thinking (LCT) to a large extent, the availability of good quality Life Cycle Inventory (LCI) data is recognized as an important step to turn the 260 approach into a true enhancement of sustainability. In this context, the present paper provides detailed 261 Inventories on the most widespread technologies currently employed in the ornamental stone sector. Datasets 262 are mainly based on primary data from Italian producers, while secondary data from literature, technical 263 sheets and patents were used to complete and cross-check primary data. Moreover, since some technologies 264 and/or their components are used in many different sectors (such as the mining and civil engineering ones), 265 the developed LCI datasets could result representative also in different contexts from the ornamental stone 266 one. The LCI datasets are provided both as Unit and System processes to enhance their versatility. 267 Furthermore, a significant added value is given by the parametrization of the Unit process datasets: 268 269 parameters allow users to easily modify, adapt or update the datasets. The developed LCI is therefore a 270 flexible and replicable tool able to practically support researchers, enterprises and LCA 271 practitioners/developers working in the field of sustainability and Circular Economy.

Datasets here described are freely available also in the ILCD file format in the Mendeley Data Repositoryfor their direct use into LCA software.

Further research should be carried out to enrich Life Cycle databases with datasets related to other common technologies employed in the ornamental stone sector, such as, for example, the tools used for the quite high variety of surface treatments (resins, materials employed for the techniques of flaming, waterjet, sand blasting).

Finally, the Life Cycle dataset of some intermediate products such as diamond powder and tungsten carbide should be further investigated through the collection of industrial primary data, in order to replace the literature data used in this paper.

281 282

289 290

ACKNOWLEDGMENTS

The authors thank the contributors to the research project presented in this paper. We thank in particular: Marilena Cardu for giving us detailed technical information and for her help in organizing the on-site visits; Simone Fazio for his support in the development of ILCD-compliant datasets; Roberto Paganoni for the significant information he shared about diamond cutting tools; Marco Bartoli for the information on diamond wires and their components; Luca Risso for his explanations on the sintering processes; David Palla for his aid on the explosive products.

REFERENCES

- Ali, S.H., 2011. Ecological Comparison of Synthetic versus Mined Diamonds.
 https://doi.org/10.1017/CBO9781107415324.004
- Archer, M., McCrindle, R.I., Rohwer, E.R., 2003. Analysis of cobalt, tantalum, titanium, vanadium and
 chromium in tungsten carbide by inductively coupled plasma-optical emission spectrometry. J. Anal.
 At. Spectrom. 18, 1493–1496. https://doi.org/10.1039/B310482F
- Bacci, A., 2005. E.C.E. Explosives and Civil Engineering. Scavi e demolizioni di strutture con l'uso di esplosivo, progetti di strutture civili e industriali normali e sottoposte ad azioni dinamiche da esplosioni, analisi di rischio da esplosioni e valutazione degli eff.
- Bai, S., Zhang, J., Wang, Z., 2016. Selection of a sustainable technology for cutting granite block into slabs.
 J. Clean. Prod. 112, 2278–2291. https://doi.org/https://doi.org/10.1016/j.jclepro.2015.10.052

- 301 Bianco, I., Blengini, G.A., 2019. Life Cycle Inventory of techniques for stone quarrying, cutting and 302 finishing: Contribution to fill data gaps. J. Clean. Prod. 225, 684–696. https://doi.org/https://doi.org/10.1016/j.jclepro.2019.03.309 303
- Bobba, S., Deorsola, F.A., Blengini, G.A., Fino, D., 2016. LCA of tungsten disulphide (WS2) nano-particles
 synthesis: state of art and from-cradle-to-gate LCA. J. Clean. Prod. 139, 1478–1484.
 https://doi.org/https://doi.org/10.1016/j.jclepro.2016.07.091
- Bobrovnitchii, G.S., Osipov, O.S., Filgueira, M., 2003. Some peculiarities of the diamond micro-powder
 sintering. Int. J. Refract. Met. Hard Mater. 21, 251–258. https://doi.org/https://doi.org/10.1016/S0263 4368(03)00049-0
- Cardu, M., 2013. Analisi delle tecniche estrattive adottate in un bacino italiano di pietra ornamentale per
 ottimizzare la produttività. Diam. Appl. Tecnol. 18, 55–65.
- Cardu, M., 2012. Analysis of the Excavation Techniques to Optimize the productivity in an Italian
 Dimension Stone Basin. Diam. Appl. Tecnol. 115–124.
- Castoldi Borlini Gadioli, M., Fernández Castro, N., De Andrade Pazeto, A., Ribeiro Wandermurem, C.E.,
 Fernandes de Almeida, P., Pimentel Tavares, D., 2012. Life-Cycle Inventory of Dimension Stones ,
 Brazil, in: Proceedings of Global Stone Congress 2012. Borba, Portugal.
- Catarino, J., Henriques, J., Maia, A., 2016. Eco-efficiency in Portuguese companies of marble sector. Int. J.
 Sustain. Eng. 9, 33–44. https://doi.org/10.1080/19397038.2015.1050479
- Crishna, N., Banfill, P.F.G., Goodsir, S., 2011. Resources, Conservation and Recycling Embodied energy 319 320 CO 2 in UK dimension stone. Resour. Conserv. Recycl. and 55. 1265-1273. https://doi.org/10.1016/j.resconrec.2011.06.014 321
- 322 Crivello, V., 2012. Coltivazione delle pietre ornamentali mediante splitting dinamico: analisi di tre cave di
 323 gneiss Piemontesi e relativi confronti. Politecnico di Torino.
- Dadalto Sahao, H., 2013. "Responsible small mining": discussion of socio- environmental and technical economic. Politecnico di Torino.
- Dahmus, J.B., Gutowski, T.G., 2004. An environmental analysis of machining, in: Proceedings of IMECE2004. Anaheim, California USA, pp. 1–10.
- 328 Davis, T.L., 1943. The chemistry of powder and explosives.
- de Oliveira, L.J., Bobrovnitchii, G.S., Filgueira, M., 2007. Processing and characterization of impregnated
 diamond cutting tools using a ferrous metal matrix. Int. J. Refract. Met. Hard Mater. 25, 328–335.
 https://doi.org/https://doi.org/10.1016/j.jirmhm.2006.08.006
- European Commission, 2015. Closing the loop An EU action plan for the Circular Economy.
 COM/2015/0614 final. Brussels.
- European Commission, 2012. International Reference Life Cycle Data System (ILCD) Data Network Compliance rules and entry-level requirements. Version 1.1. https://doi.org/10.2788/80302
- European Commission, 2010. A guide for business and policy makers to Life Cycle Thinking and
 Assessment. https://doi.org/10.2779/91521
- European Commission, 2003. Communication from the Commission to the Council and the European
 Parliament Integrated Product Policy. Building on Environmental Life-Cycle Thinking. Brussels.
- 340 Evonik Industries, 2014. GPS Safety Summary. Potassium Carbonate.
- Gazi, A., Skevis, G., Founti, M.A., 2012. Energy efficiency and environmental assessment of a typical
 marble quarry and processing plant. J. Clean. Prod. 32, 10–21.
 https://doi.org/10.1016/j.jclepro.2012.03.007
- Giuffrida, A., 2010. I materiali lapidei tradizionali nell'architettura contemporanea . La pietra di Siracusa.
 Università degli Studi di Catania.
- Gussoni, M., 2016. Stone Sector 2016. Bilancio e prospettive del commercio internazionale dei prodotti
 lapidei. Carrara.
- Ibáñez-Forés, V., Bovea, M.D., 2016. A decision support tool for communicating the environmental
 performance of products and organisations from the ceramic sector. Clean Technol. Environ. Policy 18,
 123–138. https://doi.org/10.1007/s10098-015-0999-5
- Karagöz, Ş., Zeren, M., 2001. The microstructural design of diamond cutting tools. Mater. Charact. 47, 89–
 91. https://doi.org/10.1016/S1044-5803(01)00156-5
- Konstanty, J., 2007. Powder metallurgy diamond tools--a review of manufacturing routes, in: Materials
 Science Forum. pp. 1121–1124.
- Larsson, H., Lindahl, M., Svensson, N., 2009. Life cycle assessment of floor care. A comparative study of
- the TwisterTM method and floor care methods using polish and wax, in: 6th International Symposium

- on Environmentally Conscious Design and Inverse Manufacturing, EcoDesign 2009. Sapporo (Japan).
- Liu, P., Zhang, Z., Li, T., 2012. Method for modifying magnesia grinding tool by using thermosetting
 phenolic resin. CN101885897 B.
- Masciullo, A., 2016. Valutazione ambientale di prodotti lapidei per le costruzioni. Applicazione al caso
 studio della pietra Leccese e proposte per la sua valorizzazione. Università degli Studi di Firenze.
- Mendoza, J.-M.F., Feced, M., Feijoo, G., Josa, A., Gabarrell, X., Rieradevall, J., 2014. Life cycle inventory
 analysis of granite production from cradle to gate. Int. J. Life Cycle Assess. 19, 153–165.
- Nicoletti, G.M., Notarnicola, B., Tassielli, G., 2002. Comparative Life Cycle Assessment of flooring
 materials : ceramic versus marble tiles. J. Clean. Prod. 10, 283–296.
- Novak, Z., Kotnik, P., Knez, Ž., 2004. Preparation of WO3 aerogel catalysts using supercritical CO2 drying.
 J. Non. Cryst. Solids 350, 308–313. https://doi.org/https://doi.org/10.1016/j.jnoncrysol.2004.06.045
- Palma Rojas, S., Oliveira Rodrigues, T., Coelho, D., 2013. Inventário de Ciclo de Vida das rochas
 ornamentais do Brasil. Brasilia (Brazil).
- 370 Primavori, P., 2011. I materiali lapidei della Sardegna, 1st ed. Sardegna Ricerche.
- 371 Primavori, P., 1999. Pianeta Pietra.

- Recchioni, M., Blengini, G.A., Torino, P., Recchioni, M., Blengini, G.A., 2015. Challenges and opportunities for web-shared publication of quality-assured life cycle data: the contributions of ...
 Challenges and opportunities for web-shared publication of quality-assured life cycle data: the contributions of the Life Cycle Data Net. https://doi.org/10.1007/s11367-015-0907-6
- Reza, A., Ibrahima, Z., Vaitekunas, T., 2014. Investigation and analysis of an explosion at the GOEX black
 powder manufacturing facility. Loss Prev. Bull.
- Scalari, M., 2007. European Patent Application. Rigid abrasive tool for facing and shaping stone-?like or
 ceramic materials and associated manufacturing method. EP 1862286 A1.
- 380 Selva, L., Nardin, G., 2013. Manuale corso formazione fochini: gestione degli esplosivi in sicurezza.
- Strazza, C., Del Borghi, A., Blengini, G.A., Gallo, M., 2010. Definition of the methodology for a Sector
 EPD (Environmental Product Declaration): case study of the average Italian cement. Int. J. Life Cycle
 Assess. 15, 540–548. https://doi.org/10.1007/s11367-010-0198-x
- Syrrakou, E., Papaefthimiou, S., Yianoulis, P., 2005. Environmental assessment of electrochromic glazing
 production. Sol. Energy Mater. Sol. Cells 85, 205–240.
 https://doi.org/https://doi.org/10.1016/j.solmat.2004.03.005
- The International Standards Organisation, 2006a. Environmental management Life cycle assessment —
 Principles and framework, Iso 14040. https://doi.org/10.1136/bmj.332.7550.1107
- The International Standards Organisation, 2006b. Environmental management Life cycle assessment —
 Requirements and guidelines, ISO 14044. https://doi.org/10.1007/s11367-011-0297-3
- Thimmappaiah, C.N., Kurubaran, M.K., Meyer, G.W., 1999. Resin bonded abrasive tool and method of
 making the tool. US5912216 A.
- Tillmann, W., Kronholz, C., Ferreira, M., Knote, A., Theisen, W., Schütte, P., Schmidt, J., 2010.
 Comparison of Different Metal Matrix Systems for Diamond Tools Fabricated by New Current Induced
 Short-Time Sintering Processes, in: PM2010 World Congress Diamond Tools.
- Torricelli, M.C., Palumbo, E., 2016. Measuring the sustainability of the sandstone of Firenzuola: the
 contribution of the life cycle assessment, in: Conference Proceedings Book 1st International
 Sustainable Stone Conference. Carrara, pp. 10–12.
- Torricelli, M.C., Palumbo, E., Cristofaro, L. De, 2009. Ciclo di vita di edifici in laterizio: analisi integrata
 ambiente, energia e costi, in: LCA Laterizi: Valutazione Del Ciclo Di Vita Di Materiali e Sistemi. pp.
 54–61.
- 402 Traverso, M., Rizzo, G., Finkbeiner, M., 2010. Environmental performance of building materials : life cycle
 403 assessment of a typical Sicilian marble. Int. J. Life Cycle Assess. 104–114.
 404 https://doi.org/10.1007/s11367-009-0135-z
- von Maltitz, I., 2003. Black Powder Manufacturing, Testing & Optimizing. American Fireworks News,
 United States of America.
- Weidema, B., Bauer, C., Hischier, R., 2013. Data quality guideline for the ecoinvent database version 3. [R].
 Overv. Methodol. Ecoinvent. Rep. 1 St. Gall. Ecoinvent Cent. 76–84.
- 409 Wiand, R.C., 1995. United States Patent. Molded abrasive article and process. 5607488.
- Yuhang, Y., Zheng, R., 2006. Abrasive tool of epoxy resin combined with compounded abrasive.
 CN101200053 B.
- 412 Zeren, M., Karagöz, Ş., 2007. Sintering of polycrystalline diamond cutting tools. Mater. Des. 28, 1055–1058.

- 413 https://doi.org/https://doi.org/10.1016/j.matdes.2005.09.018
- Zeren, M., Karagöz, Ş., 2006. Defect characterization in the diamond cutting tools. Mater. Charact. 57, 111–
 114. https://doi.org/https://doi.org/10.1016/j.matchar.2005.12.010
- Zhou, H., Yuhang, Y., Hongliang, T., 2012. Resin-bonded diamond abrasive tool, method and mold for
 producing resin-bonded diamond abrasive tool. CN102001054 B.
- 418
- 419
- 420