

Tunneling in heterogeneous rock masses with a block-in-matrix fabric

Original

Tunneling in heterogeneous rock masses with a block-in-matrix fabric / Napoli, MARIA LIA; Barbero, Monica; Scavia, Claudio. - In: INTERNATIONAL JOURNAL OF ROCK MECHANICS AND MINING SCIENCES. - ISSN 1365-1609. - ELETTRONICO. - 138:(2021), pp. 1-11. [10.1016/j.ijrmms.2021.104655]

Availability:

This version is available at: 11583/2866076 since: 2021-03-08T15:17:17Z

Publisher:

Elsevier

Published

DOI:10.1016/j.ijrmms.2021.104655

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

Elsevier postprint/Author's Accepted Manuscript

© 2021. This manuscript version is made available under the CC-BY-NC-ND 4.0 license
<http://creativecommons.org/licenses/by-nc-nd/4.0/>. The final authenticated version is available online at:
<http://dx.doi.org/10.1016/j.ijrmms.2021.104655>

(Article begins on next page)

Tunneling in heterogeneous rock masses with a block-in-matrix fabric

Maria Lia Napoli*, Monica Barbero, Claudio Scavia

*Department of Structural, Geotechnical and Building Engineering,
Politecnico di Torino, C.so Duca degli Abruzzi 24, Torino 10124, Italy*

** Corresponding author. E-mail address: maria.napoli@polito.it*

ABSTRACT

Heterogeneous rock masses composed of strong rock blocks embedded in a weaker matrix belong to complex formations and are often referred to as bimrocks (block-in-matrix-rocks). Due to the high spatial, dimensional, geo-hydrological and lithological variability of such rock bodies, a common geotechnical engineering design practice is not to consider the presence of the blocks and assign the strength and deformability properties of the weaker matrix to the whole rock mass. However, over the last decades, several case histories and many relevant studies on bimrocks have demonstrated that neglecting the presence of the blocks can produce wrong forecasts, which often lead to serious technical problems and severe economic repercussions during the construction of engineering works on and in these complex formations.

The aim of this study is to investigate the stability of a deep circular tunnel excavated in a heterogeneous rock mass with a chaotic block-in-matrix fabric. In order to determine how the presence of rock inclusions may influence the overall behavior of the bimrock during the excavation, different Volumetric Block Proportions (VBPs) are used. To take the inherent spatial and dimensional variability of the blocks into account, many heterogeneous tunnel configurations are generated for each VBP considered by means of a stochastic approach. The analyses are performed using the Finite Element code RS2.

Moreover, in order to highlight potential inaccuracies caused by neglecting the presence of the blocks at the design stage, simplified approaches commonly used by geopractitioners, which assume bimrocks to be homogeneous equivalent geomaterials, are also applied by way of comparison.

KEYWORDS

Bimrocks, heterogeneous rock masses, tunneling, stochastic approach, FEM

1 INTRODUCTION

Bimrocks (block-in-matrix rocks) are complex, heterogeneous and often chaotic formations composed of competent rock blocks embedded in a matrix of finer and often sheared texture.¹⁻³

38 These geomaterials are widespread all over the world and encompass many geological rock units
39 such as melanges, agglomerates, conglomerates, breccias, fault rocks, etc..⁴⁻¹⁰ Due to the high
40 spatial, dimensional, geo-hydrological and lithological variability that characterize these rock
41 formations, the determination of their geomechanical properties is extraordinary problematic.¹¹⁻
42¹⁵ As a consequence, geotechnical engineers often plan their work neglecting the contribution of
43 blocks to the overall bimrock strength, choosing instead to design on the basis of the strength and
44 deformation properties of the weaker matrix only.^{2,16-18} However, as documented by several case
45 histories reported in the literature, such a simplified assumption can cause mischaracterizations
46 and wrong forecasts in the planning phases, leading to unexpected technical problems and delays
47 during the construction of engineering works on and in these complex formations.^{6,18-24}
48 Many research studies (laboratory and in situ tests, as well as numerical simulations) conducted
49 on this topic over the last decades have demonstrated that the behavior of bimrocks is largely
50 controlled by the size, shape, position, orientation and content of the blocks within the rock mass.
51 Laboratory tests have been performed by many authors on artificial bimrock specimens since
52 1994 to study the effects that block proportion and orientation have on the mechanical properties
53 of melanges.^{3,7,17,25-28} A few authors have also performed laboratory tests on real bimrock
54 specimens^{13,29,30} developing empirical approaches for the determination of their uniaxial
55 compressive strength and elastic modulus on the basis of the Volumetric Block Proportion (VBP).
56 These works have also revealed that blocks strongly influence the mechanical behavior of such
57 geomaterials if rock inclusions represent at least 20% of the total rock mass volume.
58 Moreover, in situ large scale direct shear tests have been carried out on different rock-soil
59 mixtures.^{5,31-33} These experiments have demonstrated that the strength parameters of a bimrock
60 are correlated to the VBP and that the presence of rock inclusions controls the development,
61 position and shape of failure surfaces.
62 Numerical simulations of laboratory tests on bimrocks with different VBPs have also been carried
63 out in order to study the mechanical behavior and failure pattern of these complex
64 geomaterials.^{10,34-38}
65 Furthermore, slope stability in heterogeneous formations has been investigated using both
66 deterministic and stochastic approaches.^{22,39-43} The main findings of these studies show that
67 safety factors increase with increasing VBP and that both the position and shape of failure surfaces
68 are strongly affected by the presence of the blocks.
69 The aim of this paper was to examine how the presence of rock inclusions can affect the stability
70 conditions of a bimrock during the excavation of a deep tunnel. In fact, to the authors' knowledge,
71 very few works have been carried out on this specific topic. In particular, a theoretical circular
72 tunnel was supposed to be excavated in a chaotic melange with variable VBPs. In order to
73 generate the numerical models, a specific Matlab routine, performing Monte Carlo simulations,
74 was implemented. The Matlab code generates elliptical blocks with random dimensions,
75 orientations and positions within the rock mass, according to specific statistical rules and given

76 rock contents. For each VBP considered, ten extractions (generating ten bimrock configurations)
77 and, hence, ten numerical simulations were carried out by means of Finite Element (FE) analyses,
78 to achieve a statistical validity of the results.

79 A VBP value of 0%, corresponding to a matrix-only model, was also analyzed in order to
80 investigate potential inaccuracies and inconsistencies arising from the simplified design approach
81 (which neglects the presence of rock inclusions at the design stage), which is often used by
82 geopractitioners.

83 Furthermore, two empirical strength criteria available in the literature were applied to compare
84 the results obtained using homogeneous models rather than a (more complex) heterogeneous one.

85

86 2 TUNNELING IN BIMROCKS

87 Excavating tunnels in difficult ground conditions (e.g. soft rocks, fault zones, mixed face
88 conditions, weathered or fractured rock masses, and many others) often leads to critical situations
89 such as wall/face instabilities, breakdown or failure of excavation machine components,
90 uncontrolled over-excavations, heavy loading on preliminary supports and final linings, water
91 inflows, cutter wears, boreability problems, etc..^{21,44–47} All these aspects may have a significant
92 impact on the logistic of tunnel constructions, with serious delays, safety problems and cost
93 increments.^{48–50}

94 To date, to the authors' knowledge, not much research on tunneling in bimrocks has been carried
95 out.

96 A 2D Finite Element analysis has been performed by Pustow⁵¹ in order to investigate stress
97 redistributions and critical states during the “Spital” underground excavation (Austrian Alps) in
98 a melange with lenticular inclusions (i.e. tectonic melange). The author analyzed seven models,
99 five with a single block of variable dimension and position (from 7 m to 70 m) arranged at the
100 left sidewall of the tunnel, a matrix supported melange and a block supported melange. The results
101 show that the blocks are characterized by stress concentrations if in contact with each other, and
102 that block dimensions affect their distribution. Moreover, due to the increase of the rock mass
103 strength, the radial displacements around the tunnel decrease. Experiences gained during the
104 construction of the Spital and Steinhaus tunnels are also reported in other papers.^{21,45}

105 Moritz et al. (2004) have illustrated their experience with a shallow tunnel excavated in
106 heterogeneous formations located in the Eastern Alps of Austria. One of these geologic units is a
107 tectonic melange with a block-in-matrix fabric. The material is characterized by smaller blocks
108 embedded in a soft and weathered matrix, consisting of cataclastic phyllites. The authors highlight
109 how important is a continuous updating of observed ground conditions during underground
110 excavations (observational method) in these complex geomaterials. In particular, the evaluation
111 and interpretation of 3D displacement monitoring data can be used for on-site short term
112 prediction of the rock mass structure and quality.⁵⁰

Adam et al. (2014) worked on the city bypass tunnel of Waidhofen an der Ybbs (Austria), where difficult ground conditions were encountered due to the presence of a tectonic melange and creeping slopes. In particular, various tunneling methods were applied on the basis of the overburden and rock mass properties. Moreover, a sophisticated monitoring system was installed in order to face the complex geological and morphological situation.⁴⁷ The analyses have been performed on an equivalent homogeneous material applying the empirical approach proposed in 1994 by Lindquist³ and reported in Eq. (1):

$$\tau_p = c_{matrix}(1 - VBP) + \sigma \tan(\varphi_{matrix} + \Delta\varphi_{matrix}(VBP)) \quad (1)$$

where τ_p is the equivalent mass shear strength, c_{matrix} is the cohesion of the matrix (assumed to decrease with increasing VBP), φ_{matrix} is the internal friction angle of the matrix and $\Delta\varphi_{matrix}(VBP)$ is the increase of the internal friction angle, assumed by Lindquist to be, above 25% VBP, equal to 3° for every VBP increase of 10%.

Marinos et al. (2014) proposed a new Geological Strength Index (GSI) chart for heterogeneous rock masses such as flysch and a range of geotechnical parameters for 11 flysch types, according to their siltstone-sandstone proportion and tectonic disturbance. Moreover, the authors provided specific recommendations for temporary support measures in underground excavations through the different flysch types, based on their geotechnical behavior and critical failure mechanism.⁵²

Colmenares et al. (2017) worked on the Bogota-Villavicencio road, a very important connection between the Colombian capital and the eastern plains. Difficult ground conditions, characterized by a highly heterogeneous geology, favored the occurrence of multiple landslides over time. These instabilities have required many interventions since 1995, including underground excavations. Tunnel designs were mainly developed using the methodology proposed by the Austrian Society of Geomechanics. The approaches proposed by Medley and Lindquist⁵³ were followed to determine the ground properties and select the constitutive model, on the basis of rock contents and laboratory test results carried out on the matrix. Numerical simulations were also performed to design and back analyze the excavation processes during construction works.⁵⁴

All these studies concerning tunneling in complex formations with a block-in-matrix fabric highlight that appropriate ground investigations and numerical analyses must be performed, adequate construction and support methods must be used and appropriate monitoring systems are required in order to allow a safe tunnel construction.

143

144 3 2D SIMULTATIONS OF TUNNEL EXCAVATION IN BIMROCKS

The aim of this study was to investigate how different block proportions may affect the stability of a deep circular tunnel excavated in a heterogeneous rock mass with a chaotic block-in-matrix fabric, by means of numerical simulations. To this purpose, these simulations were carried out using different VBPs. In particular, 25%, 40%, 55% and 70% VBPs were examined. To take the innate spatial and dimensional variability of the blocks into account, the stochastic

approach proposed by Napoli et al. (2018)^{41,42} was applied. In particular, a Matlab routine was appositely implemented to randomly generate and locate elliptical blocks within the rock mass. For each VBP considered, ten tunnel configurations were created with the Matlab code. A 0% VBP configuration was also analyzed in order to evaluate potential inaccuracies that geopractitioners could make when designing on the basis of the strength and deformation properties of the matrix only. Moreover, numerical simulations were also carried out following both the Lindquist (1994a) and Kalender et al. (2014) empirical approaches. These approaches assume bimrocks to be equivalent homogeneous and isotropic materials. Altogether, the excavation of more than forty bimrock tunnels was simulated using the Finite Element Method (FEM) in two-dimensional conditions. The matrix and blocks mechanical parameters that were used in the analyses are reported in Table 1. Both materials present sufficient mechanical contrast ($E_{\text{block}}/E_{\text{matrix}} > 2$ and $\tan\phi_{\text{block}}/\tan\phi_{\text{matrix}} > 2$), as suggested by many authors.^{1,7,17,24,35,55-57} They were assumed to obey the Mohr-Coulomb failure criterion and to follow an elastic-perfectly plastic behavior.

3.1 GENERATION OF TUNNEL CONFIGURATIONS

In order to model the spatial and dimensional variability inherent in bimrocks, a specific Matlab routine, performing Monte Carlo simulations, was appositely implemented. The code generates elliptical rock inclusions with eccentricity equal to 0.5, and random dimensions and orientations. It also locates the blocks randomly within the rock mass, according to given geometric boundaries, VBPs and statistical block size distribution parameters.³⁶ The size of the blocks is strictly dependent on the characteristic engineering dimension, L_c , set equal to 10 m, corresponding to the diameter of the tunnel.^{2,58} To maximize the code performance, blocks placing is made from the largest to the smallest one.⁴¹ Moreover, the Matlab code verifies that blocks do not interpenetrate each other, otherwise it would have no physical meaning. To this reason, it was set a minimum distance between two blocks equal to 5 cm.

For the four VBPs considered (25%, 40%, 55% and 70% VBP), ten bimrock configurations were created.

The main Matlab code output consists of a text file containing, for each tunnel configuration, a list of the coordinates of both the center and the vertex of the semi-major axis and the length of the semi-minor axis of each ellipse, representing a block.

An example of the final geometry obtained with this process is shown in Fig. 1.

3.2 FINITE ELEMENT ANALYSES

Finite Element (FE) analyses were conducted using the 2D FEM software RS2 (vers. 9.0) from Rocscience. Six-node triangular elements were used to mesh the models.

187 Sensitivity analyses were carried out to evaluate the influence of external boundaries, geometry
 188 and mesh density. In particular, with the purpose of avoiding boundary effects, bimrock models
 189 were modified to include an outer layer $5L_c$ long (i.e. 50 m) on each side (Fig. 2). An elastic
 190 behavior and the same mechanical properties of the matrix were assigned to this extended part of
 191 the geometry of the bimrock models. To guarantee a high mesh quality, a non-uniform mesh size,
 192 denser near the blocks, was created (Fig. 3). Moreover, local mesh refinements were adopted
 193 where necessary.

194 A constant and isotropic field stress was assigned to the models, assuming an in situ state of stress
 195 (p_0) depending on the VBP. In particular, an increasing equivalent unit weight was assigned to
 196 the rock mass for higher block contents, obtaining p_0 values ranging from 1.65 MPa to 1.74 MPa.
 197 Furthermore, 12 excavation stages (the first in elastic conditions and without the presence of the
 198 tunnel) were simulated to reproduce the progressive underground excavation. The convergence-
 199 confinement method was used, which simulates the ongoing excavation by means of a progressive
 200 reduction of the stresses acting on each node located on the tunnel boundary. Each stage
 201 corresponds to a stress reduction of $10\%p_0$. An elastic perfectly plastic behavior was adopted for
 202 both the matrix and blocks belonging to the bimrock model, assigning the mechanical
 203 characteristics reported in Table 1.

204 As previously mentioned, an only-matrix model and ten bimrock configurations for each VBP
 205 considered, i.e. forty heterogeneous tunnel models, were simulated. Displacements and
 206 characteristic curves, stresses and yielded zones were analyzed in detail with particular reference
 207 to points R.S., C. and L.S. of the crown and the sidewalls, respectively (Fig. 3), under no support
 208 pressure either at the wall or at the face.

209 The results obtained indicate that for increasing VBP values displacements undergo an evident
 210 reduction with respect to those of the matrix (Fig. 4 and Fig. 5).

211 For the left sidewall (point L.S.), for example, the average maximum radial displacements
 212 (provided by the 10 simulations analyzed for each VBP considered) are 0.94 m, 0.87m, 0.44m
 213 and 0.14 m for the 25%, 40%, 55% and 70% VBP models, respectively, against the 1.57 m
 214 obtained with the matrix-only model (Table 2).

215 According to previous literature findings, the presence of blocks with a low VBP provides
 216 relatively little geomechanical advantage compared to the matrix-only model.^{1,3} However, the
 217 position, orientation, dimension and number of the blocks located near the tunnel strongly affects
 218 the results. As shown in Fig. 4 and Fig. 5, the radial displacements at the crown and sidewalls
 219 provided by the ten 25% VBP configurations presented the greatest data dispersion. On the other
 220 hand, for increasing rock contents a remarkable less data scattering is registered (Fig. 4, Fig. 6
 221 and Table 3). In fact, the standard deviations of the radial displacements registered at the crown
 222 (point C.) and sidewalls (points R.S. and L.S.) provided by the 10 tunnel models analyzed for
 223 each VBP are greatly reduced passing from 25% to 70% VBP bimrock models, e.g. the right
 224 sidewall standard deviations are reduced from 0.26 (for 25% VBP configurations) to 0.07 (for

70% VBP configurations). This outcome can be ascribed to the different block positions, dimensions and orientations as well as to block-poor zones of variable extension and location (within bimrock models having the same VBP), more evident for lower VBPs, which influence the rock mass behavior.

Moreover, Fig. 6 shows the variability and the non-uniformity of the radial displacements around the tunnel for the ten configurations analyzed for each VBP, due to the random location of the blocks within the rock mass. This also induces non-uniform stresses that have to be taken into account when designing the tunnel lining.

In order to better visualize the effects of the excavation on the different rock masses (from the 0% to the 70% VBPs), Fig. 7 and Fig. 9 illustrate the increasing in displacements with decreasing internal pressure (i.e. advancing tunnel face) on both tunnel sidewalls and crown. In particular, for each VBP considered, a variation band of radial displacements provided by the 10 tunnel models is shown. The upper and lower limits of each band were obtained by adding and subtracting from the average radial displacement the associated standard deviation. From these figures it is clear that blocks play a key role in the stability of the tunnels. For higher VBP values, in fact, the displacement bands depart from the red curve, which represents the displacements associated with the matrix-only model. Moreover, the greater the VBP the less thick the band, which indicates that a less data scattering is provided by the 10 models analyzed.

Stresses and yielded zones are also affected by the presence of the rock inclusions, especially by those located close to the tunnel (Fig. 10, Fig. 11, Fig. 12), and are considerably different from the uniform matrix-only results. Fig. 10 and Fig. 11 show that the blocks are characterized by stress concentrations, the distribution of which greatly depends on the block dimensions. In particular, higher stresses are observed in the blocks of greater dimension located in the vicinity of the tunnel, as well as at the block-matrix contacts. This result is in line with previous research.⁵¹ As illustrated in Fig. 12, the extension of the yielded zones greatly reduces for higher VBPs. It also varies from model to model with the same rock content, according to block sizes, locations and orientations. It is worth pointing out that plasticity occurs within the matrix only. As a consequence, the length of the plastic radius varies around the tunnel depending on the presence of the blocks.

As shown above, different stress distributions, yielded zones and displacements are provided by each tunnel configuration, even by those having the same VBP. This variability suggests the necessity of performing numerical simulations in these complex geomaterials according to a stochastic approach, which may avoid mistakes resulting from either only considering a homogeneous rock mass or just performing a deterministic analysis. In fact, since real block positions and dimensions cannot be predicted, a stochastic approach may be useful at the design stage to predict possible unfavorable conditions during the excavation works. Moreover, when the observational method is implemented during the construction process, the displacement measured at a given point should be compared and ought to be within the computed range of

displacements obtained with the stochastic approach. However, since many uncertainties exist when dealing with bimrocks, an observational method together with appropriate and continuous monitoring systems must always be used.

3.3 APPLICATION OF THE EMPIRICAL STRENGTH CRITERIA

In order to compare the results reported in Section 3.2 with those provided using equivalent homogeneous models, the empirical strength criteria proposed by Lindquist³ and Kalender et al.⁷ were applied to the tunnel models considered.

The equivalent bimrock cohesion and internal friction angle were evaluated, for all the previously analyzed VBP values, according to Eq. (1) for the Lindquist criterion and according to the following Eqs. (2-4) for the Kalender criterion (see Table 4). The other input parameters (E , ν , γ) were assumed to be equal to those assigned to the matrix and reported in Table 1.

$$\varphi_{bimrock} = \varphi_{matrix} \left[1 + \frac{1000 \left[\frac{\tan(\alpha)}{\tan(\varphi_{matrix})} - 1 \right]}{1000 + 5 \left(\frac{100 - VBP}{15} \right)} \left(\frac{VBP}{VBP + 1} \right) \right] \quad (2)$$

$$UCS_{bimrock} = \left[(A - A^{\frac{VBP}{100}}) / (A - 1) \right] UCS_{matrix} , \quad 0,1 \leq A \leq 500 \quad (3)$$

$$c_{bimrock} = UCS_{bimrock} [1 - \sin(\varphi_{bimrock})] / [2 \cos(\varphi_{bimrock})] \quad (4)$$

where α is the angle of repose of blocks, assumed as equal to 45° , UCS is the material uniaxial compressive strength and A is a parameter that can be defined according to both the adhesion strength between the matrix and blocks and parameter α , determined as equal to 4.

As shown in Fig. 13 and Fig. 15, the strength criterion proposed by Lindquist (1994a) yields conservative results, especially for lower VBP values. For the 25% and 40% VBP models, results are remarkably similar to those provided by the matrix-only model, although more conservative. In particular, the maximum radial displacements are 2.09 m and 1.69 m, respectively, greater than 1.57 m obtained with the matrix-only model.

Better conditions are provided by 55% and 70% VBP models, where the maximum radial displacements are 1.37 m and 1.25 m, respectively.

The results obtained using the Kalender et al. (2014) empirical approach are less conservative than both the matrix-only and the Lindquist models (Fig. 14). In fact, the maximum radial displacements are 1.39 m, 1.06 m, 0.94 and 1.03 m for 25%, 40%, 55% and 70% VBPs, respectively. However, especially for VBPs greater than 40%, they differ considerably from the results provided by the heterogeneous models, leading to an erroneous estimation of the mechanical response of the bimrock to the excavation process (Fig. 15).

Moreover, it is worth pointing out that the use of both the empirical criteria implies neglecting the presence of blocks and analyzing a homogeneous material. This assumption results in unrealistic final outcomes, since uniform stress distributions, plastic zones and radial displacements are obtained. However, the non uniformity shown by the heterogeneous models

cannot be neglected, because it takes primary importance in the design of the tunnel lining. Hence, these simplified approaches seem to be acceptable if used in predesign stages only.

300

301 CONCLUSIONS

302 This work investigates the effects of the VBP on the stability of deep circular tunnels
303 excavated in a complex formation with a block-in-matrix fabric and the reliability of designing
304 on the basis of the strength of the matrix only, as often happens in practice.

305 More than 40 2D numerical analyses were performed on different bimrock models, using the FEM
306 code RS2 from Rocscience. Block dimensions, orientations and positions within the rock masses
307 were randomly obtained using a stochastic approach performing numerical Monte Carlo
308 simulations. For each VBP considered, ten bimrock configurations were generated with the aim
309 of taking spatial and dimensional variability of rock inclusions into account. Furthermore, the
310 empirical strength models proposed by Lindquist (1994a) and Kalender et al. (2014), which
311 assume these geomaterials to be equivalent homogeneous, continuous and isotropic rock masses,
312 were applied by way of comparison.

313 The results obtained provided the following principal findings.

314 The use of a matrix-only model, neglecting the presence of blocks, leads to homogeneous yielded
315 zones and stress distributions which are unrealistic, since they are strongly affected by the
316 presence of the rock inclusions (e.g. yielded zones develop tortuously within the matrix), as
317 demonstrated in previous research. Moreover, severe overestimations of both displacements and
318 plastic zone extension and shape are provided. This overestimation becomes steadily more evident
319 as the VBP increases. Therefore, the choice of ignoring the contribution of blocks to the overall
320 bimrock strength, choosing instead to design using the strength and deformation properties of the
321 weaker matrix only, appears to be inappropriate and over conservative (i.e. uneconomical).

322 When analyzing bimrocks using the strength criterion proposed by Lindquist (1994a), the
323 analyses provide conservative results, remarkably similar to those of the 0% VBP model. In
324 particular, for a low VBP, some points around the tunnel showed even higher convergences than
325 the matrix-only model. More stable conditions are provided by 55% and 70% VBP models,
326 although these are considerably different from those yielded by the heterogeneous tunnel models.
327 The results obtained using the Kalender et al. (2014) empirical approach are less conservative
328 than both the matrix-only and the Lindquist models. However, especially for VBP greater than
329 40%, they too provide results which differ considerably from those of the heterogeneous
330 configurations.

331 All the same, it is worth pointing out that the use of these two empirical criteria implies neglecting
332 the presence of blocks and analyzing an equivalent homogeneous material. This assumption
333 results in many uncertainties in the final outcomes, as highlighted by previous findings^{41,42}, since
334 they underestimate the mechanical behavior of the bimrock. Hence, they seem to be acceptable if
335 used in predesign stages only. Moreover, it is worth mentioning that ignoring the presence of the

336 blocks can also lead to delays and unexpected technical problems during many engineering works,
337 with possible significant economic repercussions.^{6,18–24}

338 On the other hand, the simulations carried out for the heterogeneous models demonstrate that
339 blocks play a key role in the behavior of bimrocks during underground excavation processes.
340 Shear stresses, displacements and plastic zones are in fact strongly affected by the presence of
341 blocks located near the tunnel, as well as by their dimensions. Moreover, yielded zones develop
342 tortuously within the matrix according to previous literature findings. The FEM analyses on these
343 models demonstrate that even for a VBP equal to 25% the presence of blocks may induce quite
344 significant variations in the strength of the rock mass. This variation becomes more evident for
345 greater VBP values. However, very different results are yielded by the ten models with lower
346 VBP values. This behavior can be ascribed to the different block positions and variably extended
347 block-poor zones near the tunnel (within bimrock models having the same VBP), which influence
348 stresses and shear strain concentrations and, consequently, the stability of the rock mass. The non
349 uniformity of stresses and displacements around the tunnel can strongly influence the state of
350 stress induced in the tunnel lining, which affects its design. This problem is not taken into account
351 with the equivalent homogeneous models.

352 There is compelling evidence that deterministic analyses cannot take these particular
353 characteristics into account. Conversely, a stochastic approach seems to be more reliable to study
354 these complex formations, since it makes it possible to predict possible unfavorable conditions
355 during the excavation works, perceiving the variability in the results. The assumptions made
356 during the design phase and the numerical analysis results both have to be verified during
357 construction. In particular, when applying the observational method, actual ground displacements
358 at a given point should be compared and ought to be within the computed range of displacements
359 obtained with the stochastic approach. However, since many uncertainties exist when dealing
360 with bimrocks, an observational method together with appropriate and continuous monitoring
361 systems must always be used.

362 It is worth pointing out that the main limitation of this study is that plane strain conditions were
363 assumed for both the matrix and blocks by analyzing 2D bimrock configurations instead of more
364 realistic 3D models.

365 Hence, in order to investigate the implications that this assumption could have produced on the
366 results found in this paper, a future work will be to carry out statistical analyses of 3D tunnel
367 stability in the same bimrock formations and compare the results.

368

369 ACKNOWLEDGMENTS

370 The authors would like to acknowledge Eng. Paolo Dadone for his contribution to this paper.

371

372 REFERENCES

- 373 1. Medley EW. The engineering characterization of melanges and similar Block-in-matrix

- rocks (Bimrocks). 1994.
2. Medley EW. Bimrocks - Part 1: Introduction. Newsletter of the Hellenic Society of Soil Mechanics and Geotechnical Engineering. 2007;17-21.
3. Lindquist ES. The Strength and Deformation Properties of Melange. Ph.D. Thesis. 1994.
4. Afifipour M, Moarefvand P. Failure patterns of geomaterials with block-in-matrix texture: Experimental and numerical evaluation. *Arab J Geosci.* 2014;7(7):2781-2792. doi:10.1007/s12517-013-0907-4.
5. Xu W, Hu R, Tan R. Some geomechanical properties of soil-rock mixtures in the Hutiao Gorge area, China. *Géotechnique.* 2007;(3):255-264.
6. Haneberg WC. Simulation of 3D block populations to characterize outcrop sampling bias in bimrocks. *Felsbau.* 2004;22(5):19-26. <http://www.scopus.com/inward/record.url?eid=2-s2.0-5444265918&partnerID=tZOtx3y1>.
7. Kalender A, Sonmez H, Medley E, Tunusluoglu C, Kasapoglu KE. An approach to predicting the overall strengths of unwelded bimrocks and bimsoils. *Eng Geol.* 2014;183:65-79. doi:10.1016/j.enggeo.2014.10.007.
8. Wakabayashi J, Medley ED, Wilcox G, Ridsen C. *Tunnels through Fault Rocks and Tectonic Melanges: A Short Course for Engineering Geologists and Geotechnical Engineers.* (Lincoln Mathieson E, ed.). San Francisco; 2002.
9. Sonmez H, Ercanoglu M, Kalender A, Dagdelenler G, Tunusluoglu C. Predicting uniaxial compressive strength and deformation modulus of volcanic bimrock considering engineering dimension. *Int J Rock Mech Min Sci.* 2016;86:91-103. doi:10.1016/j.ijrmms.2016.03.022.
10. Gokceoglu C. A fuzzy triangular chart to predict the uniaxial compressive strength of the Ankara agglomerates from their petrographic composition. *Eng Geol.* 2002;66(1-2):39-51. doi:10.1016/S0013-7952(02)00023-6.
11. Akram MS. Physical and numerical investigation of conglomeratic rocks. Ph.D. Thesis. 2010.
12. Goodman RE, Ahlgren CS. Evaluating Safety of Concrete Gravity Dam on Weak Rock: Scott Dam. *J Geotech Geoenvironmental Eng.* 2000;126(5):429-442. doi:10.1061/(ASCE)1090-0241(2000)126:5(429).
13. Kahraman S, Alber M. Estimating unconfined compressive strength and elastic modulus of a fault breccia mixture of weak blocks and strong matrix. *Int J Rock Mech Min Sci.* 2006;43(8):1277-1287. doi:10.1016/j.ijrmms.2006.03.017.
14. Afifipour M, Moarefvand P. Mechanical behavior of bimrocks having high rock block proportion. *Int J Rock Mech Min Sci.* 2014;65:40-48. doi:10.1016/j.ijrmms.2013.11.008.
15. Sonmez H, Gokceoglu C, Medley EW, Tuncay E, Nefeslioglu HA. Estimating the uniaxial compressive strength of a volcanic bimrock. *Int J Rock Mech Min Sci.* 2006;43(4):554-

561. doi:10.1016/j.ijrmms.2005.09.014.

16. Medley EW, Goodman RE. Estimating the Block Volumetric Proportions of Melanges and Similar Block-in-Matrix Rocks (Bimrocks). In: *Proceedings of the 1st North American Rock Mechanics Symposium*. Austin, Texas; 1994:851-858.
17. Lindquist ES, Goodman RE. *Strength and Deformation Properties of a Physical Model Melange*. (Nelson PP, Laubach SE, eds.). Austin, Texas: A.A. Balkema; 1994.
18. Wakabayashi J, Medley EW. Geological Characterization of Melanges for Practitioners. *Felsbau*. 2004;22(5):10-18.
19. Lindquist ES. The mechanical properties of a physical model melange. In: *7th International IAEG Congress*. Balkema, Rotterdam; 1994:819-826.
20. Medley EW. Using stereological methods to estimate the volumetric proportions of blocks in melanges and similar block-in-matrix rock (bimrocks). In: *Proceedings 7th International Congress Association of Engineering Geology*. Lisbon, Portugal; 1994:1031-1040.
21. Button E, Riedmueller G, Schubert W, Klima K, Medley E. Tunnelling in tectonic melanges-accommodating the impacts of geomechanical complexities and anisotropic rock mass fabrics. *Bull Eng Geol Environ*. 2004;63(2):109-117. doi:10.1007/s10064-003-0220-7.
22. Kim C, Smell C, Medley EW. Shear strength of franciscan complex melange as calculated from back analysis of a landslide. In: *Proceedings of the Fifth International Conference on Case Histories in Geotechnical Engineering*. New York; 2004:13-17.
23. Tsiambaos G. Engineering Geological behaviour of heterogeneous and chaotic rock masses. In: *12th International Congress - Bulletin of the Geological Society of Greece*. Patras; 2010.
24. Medley EW, Zekkos D. Geopractitioner approaches to working with antisocial mélanges. In: Wakabayashi J, Dilek Y, eds. *Mélanges: Processes of Formation and Societal Significance - Geological Society of America Special Paper 480*. Vol 42. ; 2011:261-277. doi:10.1016/S0065-2156(09)70001-8.
25. Sonmez H, Altinsoy H, Gokceoglu C, Medley EW. Considerations in developing an empirical strength criterion for bimrocks. In: *4th Asian Rock Mechanics Symposium (ARMS 2006)*. Singapore, 6-10 Nov. 2006; 2006:7.
26. Afifipour M, Moarefvand P. Experimental study of post-peak behavior of bimrocks with high rock block proportions. *J Cent South Univ*. 2014;21(2):761-767. doi:10.1007/s11771-014-1999-z.
27. Pilgerstorfer T, Schubert W. Results of laboratory tests on artificial block-in-matrix rocks. In: *Rock Mechanics and Rock Engineering: Structures on and in Rock Masses - Proceedings of EUROCK 2014, ISRM European Regional Symposium*. ; 2014:381-386. doi:http://dx.doi.org/10.1016/B0-12-227410-5/00669-4.

450 28. Mahdevari S, Maarefvand P. Applying ultrasonic waves to evaluate the volumetric block
451 proportion of bimrocks. *Arab J Geosci.* 2017;10:204. doi:10.1007/s12517-017-2999-8.

452 29. Sonmez H, Tunusluoglu C. New considerations on the use of block punch index for
453 predicting the uniaxial compressive strength of rock material. *Int J Rock Mech Min Sci.*
454 2008;45(6):1007-1014. doi:10.1016/j.ijrmms.2007.11.001.

455 30. Sonmez H, Kasapoglu K, Coskun A, Tunusluglu C, Medley EW, Zimmerman RW. A
456 conceptual empirical approach for the overall strength of unwelded bimrocks. In: *ISRM*
457 *Regional Symposium, Rock Engineering in Difficult Ground Condition, Soft Rock and*
458 *Karst.*, Dubrovnik, Croatia, 29-31 Oct. 2009; 2009. [http://bimrocks.com/bimsite/wp-](http://bimrocks.com/bimsite/wp-content/uploads/2010/07/Sonmez_et_al2009_B050.pdf)
459 [content/uploads/2010/07/Sonmez_et_al2009_B050.pdf](http://bimrocks.com/bimsite/wp-content/uploads/2010/07/Sonmez_et_al2009_B050.pdf).

460 31. Li X, Liao QL, He JM. In situ tests and a stochastic structural model of rock and soil
461 aggregate in the Three Gorges reservoir area, China. *Int J Rock Mech Min Sci.*
462 2004;41(3):494. doi:10.1016/j.ijrmms.2003.12.030.

463 32. Coli N, Berry P, Boldini D. In situ non-conventional shear tests for the mechanical
464 characterisation of a bimrock. *Int J Rock Mech Min Sci.* 2011;48(1):95-102.
465 doi:10.1016/j.ijrmms.2010.09.012.

466 33. Xu W, Xu Q, Hu R. Study on the shear strength of soil-rock mixture by large scale direct
467 shear test. *Int J Rock Mech Min Sci.* 2011;48(8):1235-1247.
468 doi:10.1016/j.ijrmms.2011.09.018.

469 34. Barbero M, Bonini M, Borri-Brunetto M. Numerical simulations of compressive tests on
470 bimrock. *Electron J Geotech Eng.* 2012;17 X:3397-3414.

471 35. Barbero M, Bonini M, Borri-Brunetto M. Numerical Modelling of the Mechanical
472 Behaviour of Bimrock. In: *11th Congress of the International Society for Rock Mechanics*
473 *(ISRM 2007)*. Lisbon, Portugal: International Society for Rock Mechanics; 2007.

474 36. Barbero M, Bonini M, Borri-Brunetto M. Three-Dimensional Finite Element Simulations
475 of Compression Tests on Bimrock. In: *Proceedings of the 12th Int. Conference of*
476 *International Association for Computer Methods and Advances in Geomechanics*
477 *(IACMAG)*. Goa, India; 2008:631-637.

478 37. Yayong L, Xiaoguang J, Lin W, Zhitao L. Shear Strength and Failure Characteristics
479 Identification of Soil- Rock Mixture. *EJGE.* 2014;19:6827-6838.

480 38. Zhang S, Tang H, Zhan H, Lei G, Cheng H. Investigation of scale effect of numerical
481 unconfined compression strengths of virtual colluvial-deluvial soil-rock mixture. *Int J*
482 *Rock Mech Min Sci.* 2015;77:208-219. doi:10.1016/j.ijrmms.2015.04.012.

483 39. Minuto D, Morandi L. Geotechnical Characterization and Slope Stability of a Relict
484 Landslide in Bimsoils (Blocks in Matrix Soils) in DOWtown Genoa, Italy. *Eng Geol Soc*
485 *Territ Landslide Process.* 2015;2(January):1083-1088. doi:10.1007/978-3-319-09057-3.

486 40. Medley EW, Sanz Rehermann PF. Characterization of Bimrocks (Rock/Soil Mixtures)
487 With Application to Slope Stability Problems. *Eurock 2004 53rd Geomech colloquium.*

2004;(October).

41. Napoli ML, Barbero M, Ravera E, Scavia C. A stochastic approach to slope stability analysis in bimrocks. *Int J Rock Mech Min Sci.* 2018;101:41-49. doi:10.1016/j.ijrmms.2017.11.009.
42. Napoli ML, Barbero M, Scavia C. Analyzing slope stability in bimrocks by means of a stochastic approach. In: *European Rock Mechanics Symposium, EUROCK 2018*. 22-26 May 2018, Saint Petersburg; 2018.
43. Guerra CI, Pinzon JJ, Prada LF, Ramos AM. Multiscale Modelling of the Slope Stability of Block-in-Matrix Materials. In: *Geo-Chicago 2016 GSP 270 644.* ; 2016:658-667.
44. Barla G, Pelizza S. TBM tunnelling in difficult ground conditions. In: *GeoEng 2000, International Conference on Geotechnical & Geological Engineering.* ; 2000.
45. Button EA, Riedmueller G. Shallow Tunneling in a Tectonic Mélange : Rock Mass Characterization and Data Interpretation. *5th, North Am Rock Mech Symp.* 2002:1125-1132.
46. Zhou H, Zhang C, Li Z, Hu D, Hou J. Journal of Rock Mechanics and Geotechnical Engineering Analysis of mechanical behavior of soft rocks and stability control in deep tunnels. *J Rock Mech Geotech Eng.* 2014;6:219-226. doi:10.1016/j.jrmge.2014.03.003.
47. Adam D, Markiewicz R, Brunner M. Block-in-Matrix Structure and Creeping Slope: Tunneling in Hard Soil and/or Weak Rock. *Geotech Geol Eng.* 2014;32(6):1467-1476. doi:10.1007/s10706-012-9591-5.
48. Barla G. Full-face excavation of large tunnels in difficult conditions. *J Rock Mech Geotech Eng.* 2016;8(3):294-303. doi:10.1016/j.jrmge.2015.12.003.
49. Álvarez DL, Sjöberg J, Eriksson M, Bertilsson R, Mas Ivars D. Tunnelling and reinforcement in heterogeneous ground – A case study. In: *Ground Support.* ; 2016:1-14.
50. Moritz B, Grossauer K, Schubert W. Short term prediction of system behaviour of shallow tunnels in heterogeneous ground. *Felsbau.* 2004;22(5):44–52. <http://bimrocks.com/bimsite/wp-content/uploads/2010/07/MoritzFelsbau2004.pdf>.
51. Püstow CGH. Tunnelling in a tectonic melange of high structural complexity. 2001;(February).
52. Marinos V. Tunnel behaviour and support associated with the weak rock masses of flysch. *J Rock Mech Geotech Eng.* 2014;6(3):227-239. doi:10.1016/j.jrmge.2014.04.003.
53. Medley EW, Lindquist ES. The engineering significance of the scale-independence of some Franciscan melanges in California, USA. In: Daemen, J. J. K. and Schultz RA, ed. *Rock Mechanics Proceedings of the 35th U.S. Symposium.* Rotterdam; 1995:907-914.
54. Colmenares JE, Dávila JM, Vega J, Shin J. Tunnelling on terrace soil deposits : Characterization and experiences on the Bogota-Villavicencio road. In: *The 2017 World Congress on Advances in Structural Engineering and Mechanics (ASEM17)*. Ilsan(Seoul), Korea; 2017.

526 55. Medley EW. Orderly Characterization of Chaotic Franciscan Melanges. *Felsbau*.
527 2001;19(4).

528 56. Medley EW. Estimating Block Size Distributions of Melanges and Similar Block-in-
529 Matrix Rocks (Bimrocks). *Proc 5th North Am Rock Mech Symp*. 2002:509-606.

530 57. Riedmüller G, Brosch FJ, Klima K, Medley EW. Engineering Geological Characterization
531 of Brittle Faults and Classification of Fault Rocks. *Felsbau*. 2001;19(4):13-19.

532 58. Medley EW. Bimrocks - Part 2: Case Histories and Practical Guidelines. Newsletter of the
533 Hellenic Society of Soil Mechanics and Geotechnical Engineering. 2007:26-31.
534
535

LIST OF TABLES

Table 1 – Input parameters for the matrix and (elliptical) blocks (from ⁴⁷)

Table 2 – Minimum and maximum displacement around the tunnel and average maximum displacement registered at points R.S., C. and L.S., for each VBP analyzed and under no support pressure

Table 3 – Maximum radial displacements at the crown (point C), left sidewall (point L.S.) and right sidewall (point R.S.) of the tunnel for the ten configurations analyzed for each VBP, average displacements values and standard deviations

Table 4 – Bimrock equivalent strength parameters for the Lindquist (1994a) and Kalender et al. (2014) criteria

LIST OF FIGURES

Fig. 1. Example of a rock mass in bimrock generated with the Matlab code, where the excavation of a tunnel (circular cross section of 10 m diameter) will be simulated

Fig. 2. Example of a modified rock mass in bimrock including a homogeneous outer layer

Fig. 3. On the left: a 70% VBP bimrock model with the indication of the tunnel (red circle). On the right: a detail of the mesh generated for the block-in-matrix region of the same bimrock model

Fig. 4. Radial displacements at points L.S., C. and R.S. of the crown and sidewalls versus the VBP, for each configuration analyzed, under no support pressure

Fig. 5. Point L.S. (left sidewall): radial displacements versus distance from the tunnel for the ten configurations analyzed for each VBP and comparison with the matrix-only model result. The elastic zone corresponds to the outer layer

Fig. 6. Radial displacements vs. linearized tunnel contour length for the ten tunnel configurations analyzed for the different VBP considered

Fig. 7. Left sidewall (point L.S.): internal pressure versus radial displacements

Fig. 8. Crown (point C.): internal pressure versus radial displacements

Fig. 9. Right sidewall (point R.S.): internal pressure versus radial displacements

575 *Fig. 10. Minimum principal stress for the matrix-only model and for one of the ten configurations analyzed*
576 *for each VBP considered*

577

578 *Fig. 11. Maximum principal stress for the matrix-only model and for one of the ten configurations analyzed*
579 *for each VBP considered*

580

581 *Fig. 12. Yielded zones for one of the ten tunnel configurations analyzed for each VBP considered (from left*
582 *to right: 25%, 40%, 55% and 70% VBPs)*

583

584 *Fig. 13. Internal pressure versus radial displacements at the right sidewall (point R.S.) – Lindquist*
585 *(1994a) criterion*

586

587 *Fig. 14. Internal pressure versus radial displacements at the right sidewall (point R.S.) – Kalender et al.*
588 *(2014) criterion*

589

590 *Fig. 15. Comparison between the empirical approaches of Lindquist (1994a) and Kalender et al. (2014)*
591 *and the heterogeneous models*