# POLITECNICO DI TORINO Repository ISTITUZIONALE

## How underground systems can contribute to meet the challenges of energy transition

Original

How underground systems can contribute to meet the challenges of energy transition / Benetatos, C.; Bocchini, S.; Carpignano, A.; Chiodoni, A.; Cocuzza, M.; Deangeli, C.; Eid, C.; Ferrero, D.; Gerboni, R.; Giglio, G.; Lamberti, A.; Marasso, S.; Massimiani, A.; Menin, B.; Moscatello, A.; Panini, F.; Peter, C.; Pirri, F.; Quaglio, M.; Rocca, V.; Rovere, A.; Borello, E. S.; Serazio, C.; Uggenti, A. C.; Vasile, N.; Verga, F.; Viberti, D.. - In: GEAM. GEOINGEGNERIA AMBIENTALE E MINERARIA. - ISSN 1121-9041. - ELETTRONICO. - 58:2-3(2021), pp. 65-80. [10.19199/2021.163-164..121-9041.065] Availability:

This version is available at: 11583/2953352 since: 2022-01-26T11:08:34Z

*Publisher:* Patron Editore S.r.l.

Published DOI:10.19199/2021.163-164.1121-9041.065

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)



DX.DOI.ORG/10.19199/2021.2-3.1121-9041.065

# How underground systems can contribute to meet the challenges of energy transition

The paper provides an overview of the several scientific and technical issues and challenges to be addressed for underground storage of carbon dioxide, hydrogen and mixtures of hydrogen and natural gas. The experience gained on underground energy systems and materials is complemented by new competences to adequately respond to the new needs raised by transition from fossil fuels to renewables. The experimental characterization and modeling of geological formations (including geochemical and microbiological issues), fluids and fluid-flow behavior and mutual interactions of all the systems components at the thermodynamic conditions typical of underground systems as well as the assessment and monitoring of safety conditions of surface facilities and infrastructures require a deeply integrated teamwork and fit-for-purpose laboratories to support theoretical research. The group dealing with large-scale underground energy storage systems of Politecnico di Torino has joined forces with the researchers of the Center for Sustainable Future Technologies of the Italian Institute of Technology, also based in Torino, to meet these new challenges of the energy transition era, and evidence of the ongoing investigations is provided in this paper.

**Keywords:** hydrogen, underground storage, energy transition, well testing, reservoir modeling, microfluidics, offshore facilities, monitoring, biochemistry.

Il contributo dei sistemi sotterranei alle sfide della transizione energetica. L'articolo fornisce una panoramica dei numerosi aspetti tecnici e scientifici e delle sfide che devono essere affrontate per effettuare lo stoccaggio sotterraneo di anidride carbonica, idrogeno e miscele di idrogeno e gas naturale. L'esperienza acquisita sui sistemi energetici sotterranei e sui materiali viene integrata con nuove competenze per rispondere adeguatamente alle necessità connesse alla transizione dai combustibili fossili alle fonti rinnovabili. La caratterizzazione sperimentale e la modellizzazione delle formazioni geologiche (inclusi gli aspetti geochimici e microbiologici), il comportamento dei fluidi e del flusso e le reciproche interazioni tra tutti i componenti del sistema alle condizioni termodinamiche tipiche degli stoccaggi sotterranei nonché la valutazione e il monitoraggio delle condizioni di sicurezza degli impianti e delle infrastrutture di superficie richiedono una squadra di lavoro profondamente integrata e laboratori dedicati per supportare la ricerca teorica. Il gruppo del Politecnico di Torino che si occupa di sistemi di stoccaggio di energia a larga scala ha messo a sistema le sue competenze con quelle dei ricercatori del Center for Sustainable Future Technologies dell'Istituto Italiano di Tecnologia, sempre con sede a Torino, per rispondere a queste nuove sfide della transizione energetica. Nell'articolo viene fornita evidenza delle attività di ricerca attualmente in corso.

**Parole chiave**: Idrogeno, stoccaggio sotterraneo, transizione energetica, prove di pozzo, modellistica di giacimento, microfluidica, piattaforme offshore, monitoraggio, biochimica.

# 1. Introduction

According to the 2030 climate & energy framework defined in the Paris Agreement (https://ec.europa.eu/clima/policies/strate-gies/2030\_en), the key targets for 2030 are to cut greenhouse gas

emissions by at least 40% compared to the 1990 levels and to achieve at least a 32% share of renewable energy and at least a 32.5% improvement in energy efficiency.

Renewable sources are considered key to decarbonize energy systems and reduce dependency on Christoforos Benetatos\* Sergio Bocchini\*\* Andrea Carpignano\*\*\* Angelica Chiodoni\*\* Matteo Cocuzza\*\*\*\* Chiara Deangeli\* Celine Eid\* Dario Ferrero\*\*\*\* Raffaella Gerboni\*\*\* Giorgio Giglio\*\*\*\*\* Andrea Lamberti\*\*\*\* Simone Marasso\*\*\*\* Alice Massimiani\* Barbara Menin\*\* Alberto Moscatello\*\*\* Filippo Panini\* Costanzo Peter\*\* Fabrizio Pirri\*\*,\*\*\* Marzia Quaglio\*\*\*\* Vera Rocca\* Adriano Rovere\* Eloisa Salina Borello\* Cristina Serazio\* Anna Chiara Uggenti\*\*\* Nicolò Vasile\*\* Francesca Verga\* Dario Viberti\*

\* Politecnico di Torino, DIATI, Torino, Italy \*\* Istituto Italiano di Tecnologia, Torino , Italy \*\*\* Politecnico di Torino, DENERG, Torino, Italy \*\*\*\* Politecnico di Torino, DISAT, Torino, Italy \*\*\*\*\* Dream, Torino, Italy

Corresponding author: Francesca Verga francesca.verga@polito.it

fossil fuels, as stated by the Mission Innovation Program (http:// mission-innovation.net/). However, despite the availability of solar energy and wind power, technologies relying on these sources are not fully viable yet due to their unstable and intermittent nature (Rodrigues *et al.*, 2014; Benetatos *et al.*, 2019). Therefore, solutions to match the high-frequency va-





riation of renewable energy production with the electricity demand are fundamental for energy transition. In this view, large-scale energy storage can provide means for balancing supply and demand, increasing energy security, promoting a better management of the grid and allowing convergence towards a low carbon economy. To this end, both electrical storage technologies – such as rechargeable batteries and supercapacitors (Scalia et al., 2021; Lamberti et al., 2015) – and chemical storage are currently under investigation.

Chemical storage implies transforming electrical power into chemical energy in the form of  $H_2$ , which can then be used as such or combined with captured  $CO_2$  to produce green CH<sub>4</sub> (referred to as the gas-to-power technology), thus it is very versatile. One way to ensure large-scale storage of chemical energy is to use the storage capacity of underground reservoirs, since geological formations have the potential to store large volumes of fluids with minimal impact to the environment and society (Matos *et al.*, 2019).

Furthermore, strategies for  $CO_2$ capture and permanent storage have been developed to compensate for CO<sub>2</sub> emissions from burning fossil fuels and to meet the challenge of drastically reducing  $CO_2$  emissions in the next future. While long-term CO<sub>2</sub> underground storage is often regarded as an essential mitigation option to reduce greenhouse gases into the atmosphere and contrast climate change, temporary underground storage could be a strategy to match the quantity of captured  $CO_2$  and the quantity of  $CO_2$  that can be transformed into value-added fuels and chemicals.

Based on the above, it is evident that underground storage systems can play a fundamental role in the transition to a decarbonized and more sustainable energy future. To this end, the Underground Energy Systems group of Politecnico di Torino has teamed up with the researchers of the Center for Sustainable Future Technologies of the Italian Institute of Technology (IIT), also based in Torino, to work together and tackle these new challenges. By joining forces, we can complement expertise on rocks and fluids characterization, CO<sub>2</sub> capture and reduction, hydrogen, materials, conversion and safety of offshore facilities, numerical modeling and underground gas storage to address the issues posed by energy transition. New laboratory facilities within the Competence Center SEASTAR – Sustainable Energy Applied Sciences, Technology & Advanced Research have also been established to carry out experimental investigations in support of the ongoing research. Research on H<sub>2</sub> and CO<sub>2</sub> underground storage is under development.

# 2. Well testing: more than 20 years' experience in geo-energy

Pressure transient analysis to characterize underground formations from a production/shut-in sequence applied to a well began in the early 1930's both within and peripheral to petroleum engineering. Over the years, the technological improvement of pressure gauges and the mathematical development of interpretation models made these tests an oil industry standard methodology for well performance and reservoir characterization for various physical reservoir concepts and flow conditions (Gringarten *et al.*, 1979; Bourdet et al., 1983; Agarwal, 1980; Coelho *et al.*, 2005).

Conventional well testing consists of analyzing the pressure transient recorded down-hole during production of the reservoir fluids at either a constant or variable rate, and subsequent shut-in phase. Typically, during exploration activities there are no infrastructures to collect the hydrocarbons produced during well tests, thus it is common practice to flare them; this involves emissions of unburned hydrocarbons, carbon monoxide and nitrogen oxides. Over the last twenty years, significant evolution in HSE's policies, driven by technological advancements and a societal push toward sustainability, allowed alternative well testing methods to gain increased consideration. Alternative technologies fit into the sustainable path in different ways (Verga *et al.*, 2016): injection tests, suited for reservoir characterization without surface production and thus eliminating greenhouse gases emissions (they can be complemented with Wireline Formation Testing for reservoir fluid sampling) (Levitan, 2003; Beretta et al., 2007); harmonic pulse testing, suited for well monitoring in production and storage fields without interruption of ongoing operations (which could compromise conventional well test interpretation) and for well and thermal front monitoring in geothermal systems.

### 2.1. Injection Testing

An injection test consists in injecting a fluid (commonly brine, diesel or nitrogen) in a reservoir zone and monitoring the pressure response during the injection period and the subsequent fall-off period, in which the well is shut-in and the pressure tends to return to the initial equilibrium value. If the hydrocarbons originally in place and the injected fluid are not miscible, the physics of injection tests is characterized by the presence and movement of two phases in the reservoir. Along with analytical solutions (Levitan, 2003; Ramakrishnan & Kuchuck, 1993; Boughrara *et al.*, 2007; Habte & Onur, 2014) and numerical simulation (Verga *et al.*, 2008; Azarkish *et al.*, 2006; Verga *et al.*, 2011), an interpretation approach leveraging consolidated interpretive tools is presented in the technical literature (Beretta *et al.*, 2007; Verga *et al.*, 2012).

Examples of successful injection tests were published in the scientific literature: test of a naturally-fractured light-oil carbonate reservoir using brine as the injection fluid (Beretta *et al.*, 2007); test of a light oil reservoir in Algeria where diesel was injected (Tripaldi *et al.*, 2009); and, test of a depleted dry gas (i.e., methane) field, which could potentially be converted into an underground gas storage, where the injection fluid was nitrogen (Azzarone *et al.*, 2011).

# 2.2. Harmonic Pulse Testing (HPT)

HPT is a well testing technique in which the injection or production rate is varied periodically. The pressure response to the imposed rates, both in the pulser wells and in the observer well(s), can be analyzed in the frequency domain to evaluate the reservoir properties. Although harmonic testing entails a much longer rate sequence than conventional testing to obtain the same information (Hollaender et al., 2002), the main advantage of this approach is that it does not require the interruption of production nor the knowledge of the previous rate history. In storage scenarios, well monitoring is essential to guarantee market delivery targets (gas volume and rate) but interrupting the production before and during a test is often unfeasible for the very same reasons.

The concept of harmonic testing was first proposed by Kuo (1972) and later developed by several authors (Rosa & Horne, 1997; Hollaender et al., 2002; Ahn & Horne, 2010; Fokker & Verga, 2011; Fokker *et al.*, 2012; Fokker et al., 2013; Sun et al., 2015, Salina Borello et al., 2016, Fokker et al., 2017, Viberti et al., 2018). In Fokker et al. (2018) analytical models are presented for HPT interpretation on a graph analogous to the log-log diagnostic plot for the most common scenarios (I.A.R.F., single boundary, partial penetration, horizontal well, closed reservoir).

Real applications of HPT are documented in the literature for hydrocarbon reservoirs, aquifers, storage fields, and geothermal systems. Rochon et al. (2008) characterized single and multilayer reservoirs. Fokker et al. (2013) characterized heterogeneities of a sandstone aquifer (Renner & Messar, 2006). Salina Borello et al. (2016) assessed the deliverability of a gas well in a storage field and identified turbulence effects. Well deliverability estimation is provided by Shoaib et al. (2018). Recently, the application of harmonic pulse testing was successfully extended to geothermal systems (Salina Borello et al., 2019; Fokker et al., 2020).

# 3. Integrated multiscale static and dynamic modeling of underground porous media

The ability to predict the future performance of an underground system for different development, production or storage strategies mainly depends on the possibility to reliably describe the system – be it a reservoir, aquifer or storage – by integrating all the available geological, geophysical, petrophysical, testing and production information and simulating the fluid dynamics taking place within it (Benetatos & Viberti, 2010). To this end, it is common practice to rely on a 3D numerical reservoir model. The model is first generated to accurately reproduce the structural and petrophysical properties of the underground system (static modeling) and then implemented to describe the evolution of pressure and fluid saturations in space and time (dynamic modeling). Due to a generally enhanced awareness of environmental and safety issues the same model is often further extended to account for the rock mechanical properties and to simulate potential consequences of the induced variations of the stress conditions. Furthermore, dealing with  $CO_2$  or  $H_2$  storage also demand for including relevant geochemical phenomena such as rock dissolution or salt precipitation, which can alter the rock petrophysical properties.

### 3.1. Static reservoir modeling

The static model of a reservoir can be considered as the final product of the structural, stratigraphic, lithological and petrophysical modeling activities. A deep integration among them is necessary in order to generate a representative static model (Benetatos & Giglio, 2019).

The construction of a 3D static model begins with the dataset creation and the quality check of all the available well log, geophysical and geological data including sedimentological information. The available 2D seismic sections or 3D high resolution seismic datasets are used for the identification of the main horizons, geological trends and faults if present as well as for the extraction of seismically derived lithological and petrophysical properties. The structural model and the subsequent strati-





graphic model are of primary importance for the definition of the internal reservoir architecture and for the continuity and connectivity of the sedimentary bodies.

The volume of interest (i.e., the reservoir) is divided into elements called blocks (or cells). Each block is assigned values of the local petrophysical properties: fluid saturations and porosity dictate the amount of hydrocarbons stored in the reservoir, whereas permeability defines the ease with which fluids can flow through porous media and thus well productivity or injectivity. The values of the petrophysical parameters usually derive from well and core data (Viberti, 2010; Viberti *et al.*, 2012) but their distribution in the model is controlled by deterministic or statistical methods. In the last decades, geostatistics has become a valuable tool in geological modeling, offering techniques for the integration of multiscale data, mapping their uncertainties and distributing properties into 3D reservoir models.

# 3.2. Dynamic reservoir modeling

The objective of reservoir dynamic modeling is to build a 3D numerical model able to simulate the dynamic behavior of a given underground system. The main input data for dynamic reservoir modeling comes from different sources and includes: the static model, fluids thermodynamic behavior (Pressure-Volume-Temperature or PVT data), rock-fluid interaction properties, initial pressure and temperature conditions, well data, production history if any, and forecast targets and constraints. Pressure profiles versus depth are obtained through well measurements. Laboratory routine analyses on cores provide information about horizontal and vertical per-

meabilities; special core analyses are performed to obtain capillary pressures and relative permeability curves. Fluid samples are collected and analyzed in laboratories to obtain PVT fluid properties. Well testing is a common and powerful tool to get reliable estimates of well productivity, permeability of the formation, and evidence of possible heterogeneities within the test drainage area. The grid cells obtained from the static model are connected through flow equations describing the fluid flow under pressure variations.

The basic workflow consists of five steps: data acquisition, model design, initialization, history matching and forecast. The design of a simulation model is influenced by the type of process to be modeled, the complexity of the fluid-mechanics problem, the objectives of the study, the quality of the data, and the time and budget constraints. Common simulators consider only three fluids (black oil models), namely oil, water and gas, and isothermal conditions, with the temperature depending on the local geothermal gradient; more complex processes require to account for all the fluid components (compositional models) and for the thermal variations of the system. The initialization phase consists in assigning the initial saturation and pressure distributions, verifying the thermodynamic and hydrostatic equilibrium, and double-checking the hydrocarbons volumetric evaluations performed with the static model. In the history matching phase, the model is calibrated based on the available measured pressure and production data, by modifying the input parameters through a manual or assisted back analysis approach. Once the model is properly calibrated, productivity and recovery forecasts are performed for different field development scenarios.

The static and dynamic modeling approach for underground gas storage analysis follows the same workflow as a conventional reservoir study; however, there are issues, which are specifically relevant to gas storage. These include varying gas composition, reservoir temperature (slight) reduction due to repeated injection of "cold" gas, enhanced effects of petrophysical heterogeneities on the pressure response due to the cyclical withdrawal and injection of gas at high rates resulting in rapid and significant pressure variations and hysteresis of gas-water relative permeabilities (Verga, 2018).

The chemical composition of the stored gas can go from natural gas (typically methane with small percentages of heavier hydrocarbon components) to  $CO_2$ , to  $H_2$  or any mixture of the above.  $CO_2$  is very distinctive because it exhibits super-critical behavior at reservoir conditions. Obviously, composition variations affect the gas PVT behavior and thus the dynamics of the system, because pore pressure is intrinsically connected to gas compressibility which, in turn, is a function of gas composition. Compositional models are therefore needed to accurately simulate the effects induced by gas composition variations due to injection.

### 3.3. Microscale analysis

In recent years, the availability of new technologies to characterize pore spaces with a high level of detail supported the growing interest in pore-scale modeling. For example, X-ray micro-CT imaging allow reconstruction and visualization of a 3D porous medium with a resolution sufficient to identify grains and pores (Wildenschild & Sheppard, 2013). Thanks to this technique, a realistic representation of the reservoir rock can be obtained and used as an input for

further geometrical and hydrodynamic analyses. In addition, algorithms able to reproduce 3D synthetic porous media with given grain size distribution, porosity and anisotropy have become increasingly abundant. The output is a 3D binary image.

At macroscale, fluid flow is modeled by averaging the microscopic continuity and momentum equations over a representative elementary volume (REV) and the porous medium is parameterized mainly by porosity and permeability. The fundamental equation of fluid motion in porous media is Darcy's equation. However, at microscale, porous media are complex materials characterized by a chaotic structure and tortuous fluid flow, with pore and grain dimensions varying over a wide range. To address the crooked fluid paths through the porous structure, the concept of tortuosity (geometrical, which is based on distances, or hydraulic, which is based on the actual flow paths) was introduced. Moreover, to account for pore space interconnections, the concept of effective porosity was introduced. These microscale properties can be estimated through a geometrical investigation of the pore space using specific algorithms, such as medial axis or path-finding algorithms, and by performing hydrodynamic simulations at the pore-scale (Viberti et al., 2020). When fluids saturate the rock pores, the interactions between the different components depend on the physical and chemical properties of fluids and solid boundaries. All displacement phenomena are governed by local capillary pressure and by its instabilities. Fluid displacement on a pore-by-pore basis is composed of a sequence of equilibrium steps, where fluids reach an equilibrium position (energy balance) following Young-Laplace equation. In water-wet permeable media, non-equilibrium capillary

pressure conditions can cause water layers to swell and spontaneously fill the pore throats, thus disconnecting and trapping the non-wetting phase (Roman *et al.*, 2017): this is called snap-off, and is very relevant in many processes including  $CO_2$  sequestration.

#### 3.3.1. Microfluidics for porescale investigation

Microfluidics has expanded from chemical and biological applications to energy and environmental fields. Unlike traditional core flooding experiments, in which transport properties are indirectly calculated by measuring the pressure drop across a rock sample, microfluidic chips enable direct visualization of the fluid dynamics in synthetic porous media.

A microfluidic chip is a microdevice whose outer dimensions range from hundreds of microns to centimeters. The device is usually constituted of two layers: the lower layer hosts the microfluidic patterns and the optically transparent upper one seals the circuit and allows for the visualization of the fluid flow. For microfluidic devices simulating rocks, the microfluidic patterned core mimics the porous network, and the inlet and outlet channels connect the pore network to the inlet and outlet ports. The internal features range from nanometers to hundreds of microns. The devices can be fabricated with a variety of additive and subtractive manufacturing techniques and all the materials of technological relevance can be selected: glass, silicon, polymers, composites and geomaterials (Jahanbakhsh *et al.*, 2020).

Glass is one of the most commonly employed materials, and historically one of the first to be used, together with silicon. Its optical transparency, hardness, chemical and thermal stability are indeed extremely well suited for applications in the geological and petroleum engineering field. Among the very many types of Si/glass microfluidics fabrication methods (Park et al., 2004; Ciprian et al., 2007; Marasso et al., 2008; Marasso *et al.*, 2011; Henley *et al.*, 2012Ku *et al.*, 2018; Kumar Mishra *et al.*, 2019), micro powder blasting, relying on physical erosion by an abrasive powder jet accelerated towards the substrate, or laser micromachining are technological options enabling cheap, fast and complex three-dimensional micro-structuring. Pore network structures can also be generated on the surface of silicon wafers, using essentially the same methods as for the generation of pore network patterns on glass. Since silicon is opaque in the visible spectrum, direct optical visualization of fluid flow processes inside pore network structures is only possible at the surface of a silicon wafer bonded to a transparent substrate. To this purpose, a glass-silicon-glass architecture is typically used with anodic bonding as the dominant technology enabling complex multi-level microfluidic systems. The main advantage of using silicon over glass substrates is its ability to generate pore network structures with very high (sub-nanometer) resolution and accuracy.

Transparent polymers are also considered valid options for the fabrication of microfluidic devices, being significantly cheaper than silicon or glass (Marasso *et al.*, 2014; Tsao, 2016). Photolithography, 3D printing and/or molding processes are the most common manufacturing techniques (Vitale *et al.*, 2013; Vitale *et al.*, 2015; Bertana *et al.*, 2018). 3D printing is undoubtedly the most recent approach for microfluidics. It allows moving directly from digital design data to manufacturing. Though still limited for large volume needs, it is perfectly suited for microfluidic systems with moderate resolution but high



level of complexity, outrunning in this sense more conventional manufacturing techniques. Polymers are generally more versatile than silicon or glass, available in a wide range of compositions and thus of physicochemical properties, cheaper, allow for surface modification, and can easily be bonded. However, this also implies that the surface tends to undergo undesired modifications during processing, which requires additional stabilization. Moreover, polymers can be blended with nanostructured materials to provide composites with improved characteristics and performance (Quaglio *et al.*, 2011). The main drawbacks of polymers are their reduced chemical and mechanical resistances, that limit their application with solvents and make them unsuitable to withstand high temperatures and high differential pressures.

Main applications of microfluidics in the oil and gas field are related to the investigation of water/oil separation (Quaglio *et al.*, 2019), drainage and imbibition processes (Gunda *et al.*, 2011), enhanced oil recovery (Gaol *et al.*, 2020), CO<sub>2</sub> underground storage (Amarasinghe *et al.*, 2021), carbonate reservoirs and dissolution processes (Soulaine *et al.*, 2021) and PVT measurements (Molla and Mostowfi, 2021).

# 4. Underground storage

### 4.1. Storage as a discipline

The concept of storing natural gas underground in geologic formations arose from the need to balance the divergence between a constant gas supply and the seasonal and daily variability of gas consumption. The first successful underground storage of natural gas in a depleted gas reservoir occurred in 1915 in Ontario, Canada. Since

then, hundreds of facilities have been developed. Underground gas storage (UGS) may be defined as the long-term safe isolation of natural gas within geological formations. Thus, two of the most important characteristics of an underground storage are its ability to hold natural gas for future use and the rate at which that gas can be withdrawn. Depleted gas and oil reservoirs, deep saline formations, salt caverns and un-minable coal beds are the favorable candidates for safe geological storage of natural gas, but several reconditioned mines are also in use as gas storage facilities.

Historically, depleted gas or partially depleted gas reservoirs have been the most sizeable and commonly used formations for natural gas storage. A depleted field typically represents the most suitable option because of its proven ability to contain and trap gas on a geological timescale. Pressure is used to force the gas into and out of the porous and permeable reservoir while a sealing caprock prevents vertical fluid migration. However, if the original formation pressure is exceeded during storage operations to increase the working gas volume (i.e. deltapressure conditions are applied), there is a risk that the caprock may fail to confine the gas. Thus, both the hydraulic sealing capacity and the mechanical resistance of the caprock must be carefully investigated. Geomechanical analyses are also needed for evaluation of potential subsidence and induced (micro)seismicity. A significant advantage of depleted fields is the level of knowledge already gained and readily available: information about the geological, structural, petrophysical characteristics and fluid-flow properties are inherited from the exploration and production phases. From a commercial standpoint, depleted reservoirs typically provide very

good storage efficiency, both in terms of movable gas volume and injection/withdrawal gas rates. Deep saline aquifers represent a common alternative for UGS. The development and management of saline aquifers require that the original formation pressure is exceeded to displace the water initially saturating the pores of the rock to accommodate the gas. Therefore, the sealing capacity of the caprock, the presence of spill points (depths below which the gas may "escape" from the geological structure) as well as the rock mechanical integrity must be assessed in order to prevent gas leakage. Salt caverns and excavated rock caverns (such as coal and granite) are generally developed in regions where reservoirs are not available. They are typically much smaller in volume than either depleted reservoirs or aquifers but can provide high delivery rates (Benetatos *et al.*, 2013).

The successful development of a UGS must include an appropriate site selection based on subsurface information and subsequent performance analysis, preferably based on an integrated geological, geochemical, fluid-dynamic and geomechanical approach. To this end, the same basic sets of information as a typical reservoir study are used: geophysics, geology, well logging and core analysis, well testing and production history, rock compressibility. Furthermore, an adequate monitoring program to satisfy technical and safety regulations together with social and environmental concerns must also be conceived to ensure the long-term feasibility of the project, especially if delta-pressure conditions are applied. However, even though the UGS industry has borrowed much of its knowledge from other industries (primarily oil and gas reservoir engineering and production), it has also needed to develop a technology of its own to meet specific challenges and concerns (Verga, 2018).

#### 4.2. Carbon capture, utilization and storage and hydrogen storage

Underground storage of carbon dioxide and hydrogen is quite similar to the underground storage of natural gas. In fact, most of the past and ongoing underground  $CO_2$  and  $H_2$  storage projects use the experiences of the underground natural gas storage in each and every aspect, such as site specifications, storage techniques, monitoring and even cost life cycle or economic viability. The major difference is represented by the physiochemical properties of CO<sub>2</sub> and hydrogen that require more attention than natural gas especially in terms of leakage, monitoring, chemical affinity and potential chemical, biological or microbial reactions.

Long-term CO<sub>2</sub> underground storage is regarded as an essential mitigation option to reduce greenhouse gases in the atmosphere and contrast climate change. CCUS (Carbon Capture, Utilization and Storage) encompasses all the methods and technologies to remove CO<sub>2</sub> from the industrial flue gas and from the atmosphere, followed by CO<sub>2</sub> recycling or by safe and permanent storage options (IEA, 2020). In this perspective, a dualism exists between  $CO_2$  utilization and storage – as if one technology was alternative rather than complementary to the other. The authors believe that, as opposed to permanent geological sequestration, temporary underground storage should be part of the CCUS process as a strategy to efficiently couple CO<sub>2</sub> capture with  $CO_2$  valorization options, i.e. the storage acts like a "buffer". In this approach,  $CO_2$  storage is fully integrated with valorization technologies leading to a virtuous  $CO_2$ cycle, or the three C's: Capture, Cache and Convert (Bocchini et al., 2017). Each industrial segment

Dicembre 2021

could operate independently and optimize its own value chain with an expected significant efficiency enhancement, largely offsetting the cost due to storage. There are several technologies for CO<sub>2</sub> sequestration and re-use; some of them are already available in the market whereas others, at present, still need a further step of development to become industrially appealing, an example being the RE-CODE EU project (recodeh2020. eu). Furthermore, deploying all of them at the same site still requires significant efforts. The capture process can be attained either from the atmosphere or at the emission source, such as power plants, cement plants or biomass plants where a conversion process – *i.e.* combustion – produces carbon dioxide-rich flue gases. Among the possible separation techniques, the amine scrubbing technology is very mature and has been industrially employed for over 50 years in post-combustion separation. However, amines have major drawbacks: they are toxic/corrosive and require a large amount of energy to be regenerated. Other technologies such as the use of ionic liquids can solve some critical issues (Latini *et al*, 2019) as they feature negligible vapor pressure, non-corrosiveness and low energy demand (Davarpanah *et al*, 2020). Following CO2 capture, the valorization process to obtain chemicals and fuels can be exploited both as a direct conversion process, or as the final step of a value chain. Several (bio)chemical approaches can be designed to obtain the desired molecules, and each of them can be valueable in specific application conditions. The biocatalytic route exploits ad-hoc developed microorganism strain to obtain the desired products (Vasile et. al., 2021), electrochemical valorization (Zeng et al., 2018 and 2021; Bejtka et al., 2019, Zeng et al., 2021) exploits renewable energy sources to



power the system (Sacco et al., 2020), while thermocatalytic processes, can take advantage of hydrogen from renewables in the power to gas approach. In the chemical catalytic approaches, the challenge is to select and optimize processes and materials highly selective, efficient, inexpensive and environmentally friendly, able to be competitive in the energetic transition (Kamkeng *et al.*, 2020). At present, CO and formic acid are considered to be the most economically viable molecules in electro catalytical processes (Jouny et al., 2020), while thermocatalysis is more efficiently exploited to obtain methane, methanol and more complex C2 molecules (e.g. ethylene).

Currently, hydrogen is generally stored as a gas in very high-pressure vessels, or in liquid form at very low temperatures in heavily insulated vessels. Such vessels are expensive, heavy and inconvenient. Geological storage is a possible option to store large quantities of hydrogen and therefore large amounts of energy over long timescales. This is the reason why underground H<sub>2</sub> storages has been given serious consideration. Hydrogen can be stored using either salt caverns or porous formations like saline aquifers or depleted gas and oil fields. While hydrogen has already been stored successfully in salt caverns for industrial use, experiences with subsurface porous media hydrogen storage are relatively scarce. Although large-scale underground storage of hydrogen is possible thanks to the technology of underground storage of natural gas and carbon dioxide, additional investigations are needed to assess technical feasibility and safety with respect to caprock tightness, diffusivity, interactions with the reservoir rocks with potential subsequent changes of the storage properties, reactions with microbial communities and



compatibility with materials. All these aspects are currently being investigated by the PoliTO-IIT research team with equipment suitable to run experiments even at the challenging pressure and temperature conditions typical of deep underground geological formations.

# 4.2.1. EoS and phase behavior

Hydrogen and methane are in gaseous phase at both reservoir and standard conditions due to their critical constants and phase diagram. When storing  $H_2$  in a depleted reservoir, the description of the interaction between fluids  $(H_2, hydrocarbons and water)$  and the volumetric behavior of the resulting gas mixture requires the adoption of a compositional fluid model. The fluid behavior is defined by an Equation of State (EoS) which must be properly selected for the range of pressure and temperature conditions of the physical system under investigation. The two most used EoS implemented in compositional reservoir simulators are the cubic equations called Soave-Redlich-Kwong, originally conceived by Redlich and Kwong in 1949 and subsequently improved by Soave in 1972, and Peng-Robinson, in which a further modification to the Soave-Redlich-Kwong equation was introduced in 1976. The GERG-2008 EoS can also approximate well the thermodynamic properties of natural gases and other mixtures for a wide range of mixture compositions, pressure and temperature.

# 4.2.2. Diffusion

One of the issues to be addressed for gas storage is the sealing capacity of reservoir caprocks to prevent upward gas migration. In gas reservoirs evidence proves that methane diffusion through caprocks is negligible even over geological times. Conversely,  $H_2$  and  $CO_2$  diffusion through reservoir caprocks has to be properly evaluated as well as diffusion of any gas mixture in the case of storage in aquifers.

Hydrogen diffusivity mainly takes place in the water saturating the caprock (Hemme & Van Berk, 2018; Vinsot *et al.*, 2014); the gas first dissolves in the water and then diffuses through it. Solubility and diffusivity of  $CH_4$ ,  $H_2$  and  $CO_2$ in pure water are shown in Tab. 1.

Diffusivity coefficient measured at ambient pressure should represent an overestimation of diffusivity at reservoir pressure because theoretical values of free molecular diffusivity coefficient for most gases show a direct proportionality with temperature and an inverse proportionality with pressure (Roberts, 1972). Inverse correlations between diffusion coefficients and pressure were experimentally observed for diffusion of He in rocks (Pandey et al., 1974.), CH<sub>4</sub> in rocks (Schlomer et al., 2004),  $CH_4$  in coal (Wang et al., 2016) and  $H_2$  in clay (Boulin et al., 2008). Diffusion is higher for dry samples because hydrogen diffuses directly in the empty pore spaces: measurements on dried argillites samples were close to 10-7

Tab. 1 – Solubility and diffusivity of  $CH_4$ ,  $H_2$  and  $CO_2$  in pure water (Engineering toolbox, 2008; Wise & Houghton, 1966; Tamimi *et al.*, 1994).

Gas	Solubility in water (g/kg)		Diffusivity in water (m2/s)	
	@ 20°C, 0, 1 MPa	@ 60°C, 0,1 MPa	@ 20°C, 0,1 MPa	@ 60°C, 0,1 MPa
CH <sub>4</sub>	0.023	0.007	2.4 10-9	6.7 I 0 <sup>-9</sup>
H <sub>2</sub>	0.0016	0.0012	5.0 IO <sup>-9</sup>	3.   0 <sup>-9</sup>
CO <sub>2</sub>	0.16	0.6	1.67 10 <sup>-9</sup>	4.2 10-9

m<sup>2</sup>/s while tests on the same argillite at different water saturation values showed diffusion was two orders of magnitude lower than for dry samples. In water saturated clay rocks, measured H<sub>2</sub> diffusion was found in the range 10-12-10-10 m2/s (Krooss, 2008; Aertsens, 2009; Jacops et al., 2012; Vinsot et al., 2014; Jacops et al., 2015). Water salinity could also have an impact on diffusivity. According to Panfilov (2016) caprocks saturated with water represent an impermeable barrier to hydrogen, and numerical simulations with a hydrogeochemical modeling approach confirmed that the loss of hydrogen by diffusion through the caprock at reservoir conditions is negligible (Carden and Paterson 1979; Krooss, 2008; Hemme et al., 2018). The diffusion values of H2-CH4 mixtures measured by the PoliTO-IIT research team at standard pressure and reservoir temperature are also in the range 10-10-10- $11 \text{ m}^2$ /s and seem to confirm the sealing capacity of clayey caprocks.

## 4.2.3. Biochemistry

Biogeochemical analyses need to be carried out with the main aim of assessing the potential changes in the stored gas mixture and in petrophysical properties due to microbial activities within the reservoirs selected for underground storage of  $CO_2$  or  $H_2$ . Several studies have estimated that generally between  $10^3$  and  $10^6$  microbial cells per milliliter of water can be found in deep underground formations (Ivanova, 2007; Gniese, 2014; Itävaara, 2016) and it is well known that microbial communities can deeply affect the activity of UGS with respect to: (i) loss of stored gas and, as a result, loss of energy value; (ii) damage to plant and technical equipment due to biocorrosion and clogging caused by biofilm formation and biomass accumulation; (iii) safety risks to



operators mainly due to the production of hydrogen sulfide, which is highly toxic (West, 2011; Gniese, 2014).

The recent development of powerful molecular biology tools, such as high-throughput Next-Generation Sequencing (NGS) technologies, has allowed for a targeted and detailed study of the deep microbiota, characterized by non-culturable microorganisms that cannot be analyzed by standard laboratory techniques. Samples of formation fluids and sediments can be collected prior to injection for a baseline on microbial composition to be compared with changes induced by the presence of insufflated  $CO_2$  or  $H_2$ . In both cases, microbiological analysis is useful to identify and monitor the biogeochemical processes, which can affect the consumption and diffusion of the gas within the reservoir during storage. Numerous studies of microbial communities in the deep biosphere have revealed that - based on their metabolic pathways – four main classes of microorganisms can be distinguished: methanogens, sulphate reducers, homoacetogenic bacteria and iron reducers, with the first two posing the greatest risks to the storage site (Leung, 2014; Heinemann, 2021).

In the case of  $CO_2$  storage, it is extremely unlikely that microorganisms can survive direct exposure to supercritical CO<sub>2</sub>. However, it has been proven that, after the injection phase, different microbial classes can be exposed to the gaseous or dissolved phase of CO<sub>2</sub> and metabolize it to proliferate. The direct effect of  $CO_2$  is its potential role as oxidant compound that can be used as an energy source (e.g. for methane production), while the indirect effect is the reduction of the pH level, altering the composition of the microbiota and leading to a reduction in the microbial diversity (Gulliver, 2016). ). It

has been shown by experimental evidence that resilient microbial populations can have both favourable and unfavourable effects on the capacity, integrity and safety of a storage site (Gniese, 2014). For example, biofilm formation can potentially help to "lock in" the injected CO<sub>2</sub> and prevent its migration as plume. Conversely, the activation of some microbial metabolisms, e.g. methanogenesis, can lead to methane production and potential leakage (Mu & Moreau, 2015). Although the effects related to microbial activity may be small and almost undetectable at the beginning of the storage period, they can become very difficult to control and costly to remediate if autocatalytic reactions are triggered (West, 2011).

The studies needed to ensure safety and efficiency of a  $H_2$  storage are even more complex than those required for CO<sub>2</sub> since the experience and practical applications of underground  $H_2$  storage are to date very limited (Heinemann, 2021). From a biochemical point of view, the insufflation of hydrogen can trigger the proliferation of all the hydrogenotrophic microorganisms, which belong to the four aforementioned metabolic classes. It has been proven that the risks of H<sub>2</sub> loss is higher when more terminal electron acceptors for microbial metabolic activities, like CO<sub>2</sub> and sulfate, are available. Therefore, a detailed mineralogical-petrographic analysis of the reservoir and caprock is needed to assess the content of sulfate- and carbonate-based minerals (e.g. calcite, dolomite and siderite) (Flesch, 2018; Hemme & Van Berk, 2018).

The PoliTO-IIT research team is applying its expertise in microbiology and reactor engineering in order to: (i) carry out the characterization of microbial profile of the microbiota in depleted reservoirs of interest for potential conversion into storages, and (ii) study the microbial metabolic activities by means of a multiphase reactor system (installed in the SEASTAR facilities) that has been specifically designed to reproduce reservoir conditions (max pressure = 200 bar and max temperature = 150°C), with solid rock samples, microfluidic chips, bacteria and flow of gas/ liquid mixtures . The microbiological analysis is carried out by means of taxonomic and relative abundances determination of deep microbiota through NGS sequencing of the 16S ribosomal subunit, with specific targets for both bacteria and archaea populations. The study is complemented by the use of functional genes for the characterization of the metabolic activities of methanogenic archaea (mcrA) and sulphate-reducing bacteria (dsrB) (Ranchou-Peyruse, 2019).

#### 4.2.4. Geochemistry

Geochemistry plays an important role in  $CO_2$  storage. The reactivity of carbonate and silicate minerals is at the heart of porosity and pore geometry changes in rocks injected with CO<sub>2</sub>, which ultimately control the evolution of flow and transport properties of fluids in porous (Noiriel & Daval, 2017). Supercritical CO<sub>2</sub> at the pressure and temperature conditions typical of subsurface storage is soluble to a limited degree in water and saline brine but enough to transform the brine into a carbonic acid solution. The acidified brine can dissolve silicate minerals in the rocks, a form of silicate rock "weathering", the extent of which depends on the availability of divalent cations contained in silicate minerals and the kinetics of mineral dissolution. The second part of the weathering cycle, which can also occur in underground reservoirs, is the recombination of released divalent cations like Ca, Mg and Fe with dissolved CO<sub>2</sub> to form solid carbonate minerals. Intuiti-



vely, an increase in permeability is likely to occur due to dissolution while carbonation should lead to a permeability reduction by globally decreasing the reservoir porosity. However, the evolution of permeability also depends on how the pore space is affected by reactions, e.g.: non-uniform precipitation patterns emphasize the permeability decrease by increasing the pore roughness; crystallization pressure resulting from precipitation of carbonates or salts could induce fracturing and the creation of new flow paths. Thus the prediction of permeability evolution in reservoirs is somewhat challenging due to the number of factors that can affect the dynamics of flow path enlargement or clogging. In addition, sample-size limitations restrict the ability to predict reliable porosity-permeability relationships at larger scales.

### 4.3. Geomechanical issues

Pressure changes caused in geological formations by fluid production and/or storage affect the rock stress state. If the variations of the rock stress state are significant, they could jeopardize the formation integrity and induce microfracturing, faults (re)activation and ground movements. Therefore, current regulations and public concerns call for geomechanical analyses to assess safety conditions in terms of stored gas containment, earthquake hazard and subsidence magnitude and extension. Geomechanical models, based on mechanical properties derived from lab and in-situ measurements, are strongly connected to the static and dynamic models. The geomechanical model simulates the stress state variations. verifies rock integrity and potential fault slippage, and calculates the rock deformation, which can propagate to the surface and induce ground movements. If ground movement surveys are available, a back-analysis procedure is carried out: the rock mechanical parameters are calibrated until a satisfactory match is achieved between simulated and measured deformations. The Interferometric Synthetic Aperture Radar (InSAr) acquisition technique is widely adopted for ground movements surveys due to its high accuracy (millimeters) on large areas (Berardino *et al.*, 2003; Ferretti *et al.*, 2001).

In the case of natural gas storage, seasonal ground movements can be correlated with withdrawal/ injection operations. Gas pressure changes in the geological formations cause variations of effective stresses; if these variations are significant, they could affect the formation integrity and induce microfracturing, faults (re)activation and ground movements. Therefore, avoidance of these issues calls for geomechanical analyses to assess safety conditions.

The analysis of ground movement surveys induced by the storage systems located in the Po Plain, Italy (depth is in the range 1-1.5 km), shows a consistent relation between pressure variations and corresponding subsidence/ rebound at the surface level (Codegone et al., 2016; Coti et al., 2018; Benetatos *et al.*, 2020). This UGS-related pressure variations due to the withdrawal/injection phases affect the formation cyclically and over relatively short periods (typically 5-7 months). The correlation between gas injection/ extraction and upward/downward ground movements indicates that the formations behave elastically (Teatini *et al.*, 2011; Ferronato *et* al., 2013). When a depleted reservoir is converted into a storage, it is initially refilled with gas; this phase generates a pressure increase and thus a decrease of the effective stresses (unloading). The subsequent cycles of gas withdrawal (loading) occur in the elastic field, with a stiffer behaviour than in primary production, where the quasi-monotonic pressure decrease occurring over decades can induce a consistent time-dependent behaviour of the sandy reservoir materials (Musso et al., 2021). The simulation of the deformations induced by gas withdrawal/injection cycles requires an appropriate choice of the relevant parameters by selecting the reference range of strains of the process from lab tests (Marzano et al., 2019, Rocca et al., 2019). Furthermore, the transverse isotropy of the clastic formations can affect their mechanical response during storage cycles, as in the case of wellbores (Deangeli & Omwanghe, 2018; Parkash & Deangeli, 2019; Deangeli et al., 2021).

# 4.3.1. Microseismicity monitoring

Microseismic monitoring is the passive observation of very small-scale earthquakes (i.e. magnitude less than zero) which occur in the underground because of geothermal operations or gas storage which cause a stress state change. During stress redistribution, sudden slips can occur along pre-existing zones of weakness such as faults or fracture networks, releasing energy in the form of seismic waves which are known as microseismic events. These micro-earthquakes are typically too small to be felt on the surface but can be detected by borehole seismic sensors with an adequate resolution in order to register even very low magnitude events at the depths of the geological formations involved in the injection or withdrawal operations. The spatial and temporal variations in microseismicity can be used to monitor changes in the stress field and hence potentially be used to monitor perturbations



in fluid pathways as well as top-seal and well-bore integrity.

The design of a microseismic network for monitoring purposes must be based on a detailed analysis of the local and regional faults systems, especially in areas where infrastructures and/or urban settlements are present. Prior to installation of the instruments, a careful mapping of all the possible sources of noise is necessary as well as a quantitative analysis of the noise levels at the selected locations.

# 4.4. Conversion of offshore facilities

In the case of an offshore (partially) depleted reservoir to be converted into CH<sub>4</sub>-H<sub>2</sub> mixtures or  $CO_2$  storage facility, this also implies the conversion of the platform originally designed for hydrocarbon production. This option is particularly attractive because it allows minimizing the environmental impact that is typical of complete platform decommissioning, in particular for the subsea ecosystem that has grown around the jacket, and because it offers a cost-saving solution for the implementation of the equipment needed for underground gas storage.

The accidental release of dangerous (flammable and/or toxic) high pressure gases are one of the key safety issues for offshore platforms. Thus, an efficient CFD model has been developed (Carpignano et al., 2017; Moscatello et al., 2021) to simulate accidents with the aim of using the simulation results as a driver for effective design choices. The model, called SBAM model, is being validated by experimental activities, where model predictions are compared with the dispersion of a low concentration methane release into a scaled mock-up of an oil&gas platform (scaled 1:10) in the SEASTAR facilities of the PoliTO-IIT research team (Gerboni *et al.*, 2020; Moscatello *et al.*, 2020). The program of the research aims at extending the application of the model for the simulation of potential accidents involving  $CH_4$ - $H_2$  mixtures and  $CO_2$ .

Along with  $CH_4$ - $H_2$  or  $CO_2$  storage, other complementary conversion options have been taken into account for the production of photovoltaic (PV) energy and use of this renewable energy for the separation and delivery of desalinated seawater for civil use, and recovery of raw materials such as lithium from the resulting brine.

# References

- Agarwal, R.G., 1980. A New Method to Account for Producing Time Effects When Drawdown Type Curves Are Used To Analyze Pressure Buildup and Other Test Data. Presented at the SPE ATCE, Dallas, Texas, USA, SPE-9289-MS.
- Ahn, S., Horne, R., 2010. Estimating Permeability Distributions From Pressure Pulse Testing. ATCE, Florence, Italy. SPE-134391-MS.
- Amarasinghe, W., Farzaneh, S., Fjelde, I., Sohrabi, M., Guo, Y., 2021. A Visual Investigation of CO<sub>2</sub> Convective Mixing in Water and Oil at the Pore Scale Using a Micromodel Apparatus at Reservoir Conditions. Gases, Vol. 1 (1), pp. 53-67.
- Azarkish, A., Khaghani, E., Rezaeidoust, A., 2006. Interpretation of Water Injection/Fall Off Test (Response to M.Levitan,SPE 77532). Conference paper presented at the SPE International Oil & Gas Conference and Exhibition in Beijing, China, 5-7 December.
- Azin, R., Mahmoody, M., Jafari Raad, S.M., Osfouri, S., 2013. *Measurement* and modeling of CO<sub>2</sub> diffusion coefficient in saline aquifer at reservoir conditions. Cent Eur J Eng, 3(4), pp. 585-594.
- Azzarone, E., Beretta, E., Guglielmelli,

A., Nunzi, P., Mariotti, P., 2011. *Gas* Injection testing & *PLT – Off-shore Eni Experience*. OMC, Ravenna, Italy.

- Bejtka, K., Zeng, J., Sacco, A., Castellino, M., Hernández, S., Farkhondehfal, M.A., Savino, U., Ansaloni, S., Pirri, C.F., Chiodoni, A., 2019. Chainlike Mesoporous SnO<sub>2</sub> as a Well-Performing Catalyst for Electrochemical CO<sub>2</sub> Reduction. ACS Applied Energy Materials, 2(5), pp. 3081-3091.
- Benetatos, C., Codegone, G., Deangeli, C., Giani, G., Gotta, A., Marzano, F., Rocca, V., Verga, F., 2017, *Guidelines for the study of subsidence triggered by hydrocarbon production*, Geoingegneria Ambientale e Mineraria, 152(3), pp. 85-96
- Benetatos, C., Codegone, G., Ferraro, C., Mantegazzi, A., Rocca, V., Tango, G., Trillo, F., 2020. Multidisciplinary Analysis of Ground Movements: An Underground Gas Storage Case Study. Remote Sensing, 12, 3487.
- Benetatos, C., Codegone, G., Rocca, V., 2020. Subsidence analysis in the Italian Po Plain area: an extended case study. Proceedings of the 82nd EAGE Conference & Exhibition 2020.
- Benetatos, C., Giglio, G., 2021. Coping with uncertainties through an automated workflow for 3D reservoir modelling of carbonate reservoirs. Geoscience frontiers, (in press).
- Benetatos, C., Málek, J., Verga, F., 2013, Moment tensor inversion for two micro-earthquakes occurring inside the Háje gas storage facilities, Czech Republic, Journal of Seismology, 17(2), pp. 557-577
- Benetatos, C., Salina Borello, E., Peter, C., Rocca, V., Romagnoli, R., 2019. Considerations on energy transitions. GEAM. Geoingegneria Ambientale e Mineraria, Vol. 158 (3), pp. 26-31.
- Benetatos, C., Viberti, D., 2010. Fully integrated hydrocarbon reservoir studies: myth or reality? American Journal of Applied Sciences, Vol. 7(11), pp. 1477-1486.
- Berardino, P., Costantini, M., Franceschetti, G., Iodice, A., Pietranera, L., Rizzo, V., 2003. Use of differential SAR



interferometry in monitoring and modelling large slope instability at Maratea (Basilicata, Italy). Engineering Geology,Vol. 68, pp. 31-51.

- Beretta, E., Tiani, A., Lo Presti, G., Verga, F., 2007. Value of Injection testing as an Alternative of Conventional Well testing: Field Experience in a Sour-Oil Reservoir. SPEREE, Vol. 10 (2), pp. 112-121. SPE-100283-PA.
- Bertana, V., Potrich, C., Scordo, G., Scaltrito, L., Ferrero, S., Lamberti, A., Perrucci, F., Pirri, C.F., Pederzolli, C., Cocuzza, M., Marasso, S.L., 2018. 3D-printed microfluidics on thin Poly(methyl methacrylate) substrates for genetic applications, Journal of Vacuum Science and Technology B,Vol. 36(1), 01A106-1/7.
- Bocchini, S., Castro, C., Cocuzza, M., Ferrero, S., Latini, G., Martis, A., Rocca V., Viberti, D., 2017. *The virtuous CO<sub>2</sub> circle or the three Cs: capture, cache, and convert.* Journal of Nanomaterials. DOI: 10.1155/2017/6594151
- Boughrara, A.A., Peres, A.M., Chen, S., Machado, A.A.V., Reynolds, A.C., 2007. Approximate Analytical Solutions for the Pressure Response at a Water-Injection Well. SPE Journal, Vol. 12 (1), pp. 19-34.
- Boulin, P., Angulo-Jaramillo, R., Daian, J.F., Talandier, J., Berne, P., 2008. Experiments to estimate gas intrusion in Callovo-oxfordian argillites. Phys. Chem. Earth A/B/C 33, pp. 225-230.
- Bourdet, D., Whittle, T.M., Douglas, A.A., Pirard, V.M., 1983. A New Set of Type Curves Simplifies Well Test Analysis, in: WORLD OIL, May 1995.
- Boving, T.B., Grathwohl, P., 2001. *Tra*cer diffusion coefficients in sedimentaryrocks: correlation to porosity and hydraulic conductivity. Journal of Contaminant Hydrology, 53, pp. 85-100.
- Carden, P.O., Paterson, L., 1979. Physical, chemical and energy aspects of underground hydrogen storage. Int J Hydrog Energy, 4(6), pp. 559-56.
- Carpignano, A., Corti, T., Uggenti, A.C., Gerboni, R. 2017. Modelling of a supersonic accidental release in Oil&-Gas offshore: Characterisation of a source box. GEAM. Geoingegneria

Ambientale e Mineraria. 152:3, pp. 58-64.

- Ciprian I, Bangtao C, Jianmin M, editors, 2007. Deep wet etching-through Imm pyrex glass wafer for microfluidic applications. IEEE 20th International Conference on Micro Electro Mechanical Systems (MEMS); 2007 21-25 Jan. 2007.
- Codegone, G., Rocca, V., Verga, F., Coti, C., 2016. Subsidence modeling validation through back analysis for an Italian gas storage field. Geotechnical and Geological Engineering, Issue 6.
- Coelho, A.C.D., de Carmargo, C., Kato, E.T., Legrand, V.M., 2005. Utilizing Mini – DST for Formation Evaluation. Presented at the SPE Latin American and Caribbean Petroleum Engineering Conference in Rio de Janeiro, Brazil, June. SPE 94963.
- Coti, C., Rocca, V., Sacchi, Q., 2018. Pseudo-Elastic Response of Gas Bearing Clastic Formations: An Italian Case Study. Energies, 11, 2488.
- Davarpanah, E., Hernández, S., Latini, G., Pirri, C.F., Bocchini, S., 2020. Enhanced CO<sub>2</sub> absorption in organic solutions of biobased ionic liquids. Advanced Sustainable Systems, 4(1), 1900067.
- Deangeli, C., Cardu, M., Martinelli D., 2021. Analysis of the Stability of Openings Excavated in Anisotropic Rocks. In: Barla, M., Di Donna, A., Sterpi D. (eds) Challenges and Innovations in Geomechanics. IACMAG 2021. Lecture Notes in Civil Engineering, vol. 126. Springer, Cham. https://doi-org.ezproxy.biblio.polito. it/10.1007/978-3-030-64518-2\_43
- Deangeli, C., Omwanghe, O., 2018. Prediction of mud pressures for the stability of wellbores drilled in transversely isotropic rocks. Energies, 11(8), 1944.
- Dobereiner, L., 1984. Engineering geology of weak sandstones. University of London, United Kingdom.
- Engineering ToolBox, 2008. Solubility of Gases in Water. Retrieved from https://www.engineeringtoolbox. com/gases-solubility-water-d\_1148. html
- European Union. 2030 climate & energy framework. Retrieved from ht-

tps://ec.europa.eu/clima/policies/ strategies/2030\_en

- Ferretti, A., Prati, C., Rocca, F., 2001. *Permanent scatterers in SAR interferometry*. IEEE Transactions on Geoscience and Remote Sensing,Vol. 39, pp. 8-20.
- Ferronato, M., Castelletto, N., Gambolati, G., Janna, C., Teatini, P., 2015. Il cycle compressibility from satellite measurements. Géotechnique, Vol. 63(6), pp. 479-486.
- Flesch, S., Pudlo, D., Albrecht, D., Jacob, A., Enzmann, F., 2018. Hydrogen underground storage – Petrographic and petrophysical variations in reservoir sandstones from laboratory experiments under simulated reservoir conditions. International Journal of Hydrogen Energy, Vol. 43(45), pp. 20822-20835.
- Fokker, P.A., Renner, J., Verga, F., 2013. Numerical modeling of periodic pumping tests in wells penetrating a heterogeneous aquifer. American Journal Of Environmental Sciences, Vol. 9(1), pp. 1-13.
- Fokker, P.A., Salina Borello, E., Serazio, C., and Verga, F., 2012. *Estimating* reservoir heterogeneities from pulse testing. Journal of Petroleum Science and Engineering, Vol. 86-87, pp. 15-26.
- Fokker, P.A., Salina Borello, E., Verga, F., Viberti, D., 2017. *Harmonic Pulse Testing for Well and Reservoir Characterization.* In Proceedings 79th EAGE/ Europec Conference.
- Fokker, P.A., Salina Borello, E., Verga, F., Viberti, D., 2018. *Harmonic pulse testing for well performance monitoring.* Journal of Petroleum Science and Engineering, Vol. 162, pp. 446-459.
- Fokker, P.A., Salina Borello, E., Viberti, D., Verga, F., van Wees, J.D., 2020. Pulse Testing for Monitoring the Thermal Front in Aquifer Thermal Energy Storage. Geothermics, Vol. 89.
- Fokker, P.A., Verga, F., 2011. Application of Harmonic Pulse Testing to Water-Oil Displacement. JPSE, Elsevier, Journal of Petroleum Science and Engineering, Vol. 79, Issues 3-4, pp. 125-134.
- Gaol, C.L., Wegner, J., Ganzer, L., 2020.

Real structure micromodels based on reservoir rocks for enhanced oil recovery (EOR) applications. Lab on a Chip, Vol. 20(12), pp. 2197-2208.

- Gerboni, R., Carpignano, A., Gueccia, A., Ledda, G., Moscatello, A., Uggenti, A.C. 2020. Wind tunnel: a versatile infrastructure for validating gas releases simulations.. Presented at HYPOTHESIS XV HYdrogen POwer THeoretical and Engineering Solutions International Symposium, pp. 99-100
- Gniese, C., Bombach, P., Rakoczy, J., Hoth, N., Schlömann, M., Richnow, H.H., Krüger, M. 2014. Relevance of deep-subsurface microbiology for underground gas storage and geothermal energy production. Advances in Biochemical Engineering/Biotechnology, Vol. 142, pp. 95-121.
- Gringarten, A.C., Bourdet, D.P., Landel, P.A., 1979. A Comparison Between Different Skin and Wellbore Storage Type-Curves for Early-Time Transient Analysis. ATCE, Las Vegas, Nevada, USA. SPE-8205-MS.
- Gulliver, D.M., Lowry, G.V., Gregory, K.B., 2016. Comparative Study of Effects of CO<sub>2</sub> Concentration and pH on Microbial Communities from a Saline Aquifer, a Depleted Oil Reservoir, and a Freshwater Aquifer. Environmental Engineering Science, vol. 33(10), pp. 806-816.
- Gunda, N.S.K., Bera, B., Karadimitriou, N.K., Mitra, S.K., Hassanizadeh, S.M., 2011. Reservoir-on-a-Chip (ROC): A new paradigm in reservoir engineering. Lab on a Chip, Vol. 11(22), pp. 3785-3792.
- Habte, A.D., Onur, M., 2014. Laplace-Transform Finite-Difference and Quasistationary Solution Method for Water-Injection/Falloff Tests. SPE Journal, Vol. 19(3), pp. 398-409.
- Heinemann, N., Alcalde, J., Miocic, J.M., Hangx, S.J.T., Kallmeyer, J., Ostertag-Henning, C., Hassanpouryouzband, A., Thaysen, E.M., Strobel, G.J., Schmidt-Hattenberger, C., Edlmann, K., Wilkinson, M., Bentham, M., Haszeldine, R.S., Carbonell, R., and Rudloff, A., 2021. Enabling large-scale hydrogen storage in po-

rous media – the scientific challenges. Energy and Environmental Science, Vol. 14, pp. 853-864.

- Hemme, C., Van Berk, W., 2018. Hydrogeochemical Modeling to Identify Potential Risks of Underground Hydrogen Storage in Depleted Gas Fields. Applied Sciences, 8(11). 2282.
- Hemme, C., Van Berk, W., 2018. Hydrogeochemical modeling to identify potential risks of underground hydrogen storage in depleted gas fields. Applied Sciences, Vol. 8(11), pp. 2282.
- Henley WH, Dennis PJ, Ramsey JM., 2012. Fabrication of microfluidic devices containing patterned microwell arrays. Anal Chem. 84(3):1776-80. Aertsens, M., 2009. Re-evaluation of the experimental data of the MEGAS experiment on gas migration through Boom Clay. SCK-CEN ER-100. Mol, Belgium.
- Hollaender, F., Hammond, P.S., Gringarten, A.C., 2002. *Harmonic testing for continuous well and reservoir monitoring.* ATCE, San Antonio, Texas, USA. SPE 77692.
- IEA, 2020. CCUS in Clean Energy Transitions, IEA, Paris. Retrieved from https://www.iea.org/reports/ ccus-in-clean-energy-transitions.
- Itävaara, M., Salavirta, H., Marjamaa, K., Ruskeeniemi, T., 2016. Geomicrobiology and Metagenomics of Terrestrial Deep Subsurface Microbiology, Vol. vances in Applied Microbiology, Vol. 94, pp. 1-77.
- Ivanova, A.E., Borzenkov, I.A., Tarasov, A.L., Milekhina, E.I., Belyaev, S.S., 2007. A Microbiological Study of an Underground Gas Storage in the Process of Gas Injection. Microbiology, Vol. 76, 453.
- Jacops, E., Volckaert, G., Maes, N., Govaerts, J., Weetjens, E., 2012. Determination of gas diffusion coefficients in undisturbed Boom clay. Clays in natural and engineered barriers for radioactive waste confinement – 5. International meeting. Book of abstracts.
- Jacops, E., Wouters, K., Volckaert, G., Moors, H., Maes, N., Bruggeman, C. & Littke, R., 2015. Measuring the effective diffusion coefficient of dissolved hydrogen in saturated Boom Clay.

Applied Geochemistry, 61, pp. 175-184.

- Jahanbakhsh, A., Wlodarczyk, K.L., Hand, D.P., Maier, R.R., & Maroto-Valer, M.M., 2020. Review of Microfluidic Devices and Imaging Techniques for Fluid Flow Study in Porous Geomaterials. Sensors, Vol. 20(14), 4030.
- Jouny, M., Luc, W., Jiao, F., 2020. Correction to "General Techno-Economic Analysis of CO<sub>2</sub> Electrolysis Systems. Ing. Eng. Chem, Res. 2020, 59, 16, 8121-8123.
- Kamkeng, A.D.N., Wang, M., Hu, J., Du, W., Qian, F., 2021. Transformation technologies for CO<sub>2</sub> utilisation: Current status, challenges and future prospects. Chemical Engineering Journal, 409. 128138.
- Kanji, M.A., 2014. *Critical issues in soft* rocks. Journal of Rock Mechanics and Geotechnical Engineering, 6(3), pp. 186-195.
- Krooss, B., 2008. Evaluation of database on gas migration through clayey host rocks. Belgian National Agency for Radioactive Waste and Enriched Fissile Material (ONDRAFNIRAS). RWTH, Aachen.
- Ku X, Zhang Z, Liu X, et al. Low-cost rapid prototyping of glass microfluidic devices using a micromilling technique. Microfluidics and Nanofluidics. 2018 2018/07/21;22(8):82.
- Kumar Mishra D, Arab J, Pawar K, et al. Fabrication of Deep Microfeatures in Glass Substrate using Electrochemical Discharge Machining for Biomedical and Microfluidic Applications. 2019.
- Kunz, O., Wagner, W., 2012. The GERG-2008 wide-range equation of state for natural gases and other mixtures: an expansion of GERG-2004. Journal of chemical & engineering data, 57(11), pp. 3032-3091.
- Kuo, C.H., 1972. Determination of reservoir properties from sinusoidal and multirate flow tests in one or more wells. SPE Journal, Vol. 12(06), pp. 499-507. SPE 3632.
- Lamberti, A., Garino, N., Sacco, A., Bianco, S., Chiodoni, A., Gerbaldi, C. 2015. As-grown vertically aligned amorphous TiO<sub>2</sub> nanotube arrays as



high-rate Li-based micro-battery anodes with improved long-term performance. Electrochimica Acta 151, pp. 222-229.

- Latini, G., Signorile, M., Crocellà, V., Bocchini, S., Pirri, C.F., Bordiga, S., 2019. Unraveling the CO2 reaction mechanism in bio-based amino-acid ionic liquids by operando ATR-IR spectroscopy. Catalysis Today, 336, 148-160.
- Leung, D.Y.C., Caramanna, G., Maroto-Valer, M.M. 2014. An overview of current status of carbon dioxide capture and storage technologies. Renewable and Sustainable Energy Reviews, vol. 39, pp. 426-443.
- Levitan, M.M., 2003. Application of Water Injection/Falloff Tests for Reservoir Appraisal: New Analytical Solution Method for Two-Phase Variable Rate Problems. SPE Journal, vol. 8(4), pp. 341-349.
- Marasso, S.L., Canavese, G., Cocuzza, M., Ferrarini, A., Giuri, E., Lo Bartolo, S., Mantero, G., Perrone, D., Quaglio, M., Vallini, I., 2008. APEX protocol implementation on a lab-on-a-chip for SNPs detection. Microelectron. Eng., vol. 85, no. 5-6, pp. 1326-1329, 2008.
- Marasso, S.L., Giuri, E., Canavese, G., Castagna, R., Quaglio, M., Ferrante, I., Perrone, D., Cocuzza, M., 2011. A multilevel Lab on chip platform for DNA analysis, Biomed Microdevices, vol. 13, no. 1, pp. 19-27.
- Marasso, S.L., Mombello, D., Cocuzza, M., Casalena, D., Ferrante, I., Nesca, A., Poiklik, P., Rekker, K., Aaspollu, A., Ferrero, S., Pirri, C.F., 2014. A polymer Lab-on-a-Chip for genetic analysis using the arrayed primer extension on microarray chips, Biomed. Microdev., 16(5), pp. 661-670.
- Marzano, F., Pregliasco, M., Rocca, V., 2019. Experimental characterization of the deformation behavior of a gas-bearing clastic formation: Soft or hard rocks? A case study. Geomechanics and Geophysics for Geo-Energy and Geo-Resources, 6, 10.
- Matos, C., Carneiro, J.F., Pereira da Silva, P.P., 2019. Overview of Large-Scale Underground Energy Storage Technologies for Integration of Renewable Energies and Criteria for

Reservoir Identification. Journal of Energy Storage, Vol. 21, pp. 241-258.

- Mattax, C.C., Dalton, R.L., 1990. Reservoir Simulation, Society of Petroleum Engineers (U.S.), Henry L. Doherty series, vol. 13 SPE monograph series.
- Molla, S., Mostowfi, F., 2021. Novel Microfluidic Device for Dew Point Pressure Measurement of Retrograde Gas Condensates Using a Microfluidic Device. Energy & Fuels.
- Moscatello, A., Uggenti, A.C., Iuso, G., D'Ambrosio, D., Cafiero, G., Gerboni, R., Carpignano, A. 2020. Scaling procedure for designing accidental gas release experiment. ENGINEE-RING COMPUTATIONS.
- Moscatello, A., Uggenti, A.C., Gerboni, R., Carpignano, A. 2021. A novel approach to high-pressure gas releases simulations. Journal of Loss Prevention in the Process Industries.
- Mu, A., & Moreau, J.W. 2015. The geomicrobiology of CO<sub>2</sub> geosequestration: a focused review on prokaryotic community responses to field – scale CO<sub>2</sub> injection. Frontiers in microbiology, vol. 6, 263.
- Musso, G., Volonté, G., Gemelli, F., Corradi, A, Nguyen, S.K., Lancellotta, R., Brignoli, M., Mantica, S., 2021. Evaluating the subsidence above gas reservoirs with an elasto-viscoplastic constitutive law. Laboratory evidences and case histories. Geomechanics for Energy and the Environment. Paper no. 100246 (in press)
- Noiriel, C., Daval D. 2017. Pore-Scale Geochemical Reactivity Associated with CO<sub>2</sub> Storage: New Frontiers at the Fluid–Solid Interface. Acc. Chem. Res. 2017, 50, 759–768, DOI: 10.1021/acs.accounts.7b00019
- Pandey, G.N., Tek, M.R., Katz, D.L., 1974. Diffusion of fluid through porous media with implications in petroleum geology. AAPG Bulletin, 58(2), pp. 91-303.
- Panfilov, M., 2016. Underground and pipeline hydrogen storage. Woodhead Publishing Series in Energy, Compendium of Hydrogen Energy, Woodhead Publishing, pp. 91-115.
- Park D-S, Cho M-W, Lee H, Cho W-S.

2004. *Micro-Grooving of glass using micro-abrasive jet machining*. Journal of Materials Processing Technology. 2004 02/01;146:234-240.

- Parkash, D., Deangeli, C., 2019. Wellbore stability analysis in anisotropic shale formations. SPE/PAPG Pakistan Section Annual Technical Symposium and Exhibition.
- Peng, D.-Y., Robinson, D.B., 1976. A new two-constant equation of state. Industrial & Engineering Chemistry Fundamentals, 15 (1), pp. 59-64.
- Pirri, C.F. 2020, An Integrated Device for the Solar-Driven Electrochemical Conversion of CO<sub>2</sub> to CO, ACS Sustainable Chemistry and Engineering, Vol. 8 (20),pp. 7563-7568, 10.1021/ acssuschemeng.0c02088
- Quaglio, M., Bianco, S., Castagna, R., Cocuzza, M., Pirri, C.F., 2011. Elastomeric nanocomposite based on Carbon Nanotubes for Polymerase Chain Reaction device. Microelectronic Engineering, Vol. 88(8), pp. 1860-1863.
- Quaglio, M., Frascella, F., Marasso, S.L., Cocuzza, M., Viberti, D., Amendola, A., Carminati, S., & Pirri, C.F., 2019. Design and Characterization of Microfluidic Devices for Water/Oil Separation. OMC, Ravenna, Italy.
- Ramakrishnan, T.S., Kuchuk, F.J., 1993.
  Pressure transients during injection: Constant rate and convolution solutions. Transport in Porous Media, Vol. 10 (2), pp. 103-136. Kluwer Academic Publishers, The Nederlands.
- Ranchou-Peyruse, M., Auguet, J.C., Mazière, C., Restrepo-Ortiz, C.X., Guignard, M., Dequidt, D., Chiquet, P., Cézac, P., Ranchou-Peyruse, A., 2019. *Geological gas-storage shapes deep life*. Environmental Microbiology, vol. 21(10), pp. 3953-3964.
- Redlich, O., Kwong, J.N., 1949. On the thermodynamics of solutions. V. An equation of state. Fugacities of gaseous solutions. Chemical reviews, 44(1), pp. 233-244.
- Reitenbach, V., Ganzer, L., Albrecht, D., Hagemann, B., 2015. Influence of added hydrogen on underground gas storage: a review of key issues. Environmental Earth Sciences, Vol. 73, pp. 6927-6937.

- Renner, J., Messar, M., 2006. *Periodic pumping tests*. Geophysical Journal international, Wiley-Blackwell, 167, pp. 479-493.
- Roberts, R.C., 1972. *Molecular diffusion* of Gases. Gray D.E. (ed.), American Institute of Physics Handbook, Mc-Graw Hill Book Company, New York, pp. 2249-2252.
- Rocca, V., Cannata, A., Gotta, A., 2019. A critical assessment of the reliability of predicting subsidence phenomena induced by hydrocarbon production. Geomechanics for Energy and the Environment, Vol. 20, 100129.
- Rochon, J., Jaffrezic, V., Boutaud de La Combe, J.L., 2008. Method and application of cyclic well testing with production logging. ATCE, Denver, Colorado, USA
- Rodrigues, E.M.G., Godina, R., Santos, S.F., Bizuayehu, A.W., Contreras, J., Catalão, J.P.S., 2014. Energy storage systems supporting increased penetration of renewables in islanded systems. Energy, Vol. 75, pp. 265-280.
- Roman, S., Abu-Al-Saud, M.O., Tokunaga, T., Wan, J., Kovscek, A.R., Tchelepi, H.A., 2017. Measurements and simulation of liquid films during drainage displacements and snap-off in constricted capillary tubes. Journal of colloid and interface science, Vol. 507, pp. 279-289.
- Rosa, A.J., Horne, R.N., 1997. Reservoir description by well-test analysis by use of cyclic flow-rate variation. SPE Formation Evaluation, December 1997, Vol. 12 (4), pp. 247-254. SPE 22698.
- Sacco A, Speranza, R., Savino, U., Zeng, J., Farkhondehfal, M.A., Lamberti, A., Chiodoni, A.,
- Salina Borello, E., Fokker, P.A., Viberti, D., Espinoza, R.V., Verga, F., 2016. *Harmonic-Pulse Testing for Non-Darcy-Effects Identification*. SPE Reservoir Evaluation & Engineering. SPE-183649-PA.
- Salina Borello, E., Fokker, P.A., Viberti, D., Verga, F., Hofmann, H., Meier, P., Min, K.-B., Yoon, K., Zimmerman, G., 2019. Harmonic Pulse Testing for Well Monitoring: application to a fractured geothermal reservoir, in: Water

resources research, Vol. 55 (6), pp. 4727-4744.

- Scalia, A., Zaccagnini, P., Armandi, M., Latini, G., Versaci, D., Lanzio, V., Varzi, A., Passerini, S., Lamberti, A., 2021. Tragacanth Gum as Green Binder for Sustainable Water-Processable Electrochemical Capacitor.ChemSusChem 14.1, pp. 356-362.
- Schlomer, S., Krooss, B.M., 2004. Molecular transport of methane, ethane and nitrogen and the influence of diffusion on the chemical and isotopic composition of natural gas accumulations. Geofluids, 4, pp. 81-108.
- Shoaib, M., Viberti, D., Salina Borello, E., Verga, F., 2019. Harmonic pulse testing for gas well deliverability assessment., GEAM. Geoingegneria ambientale e mineraria, Vol. 158 (3), pp. 53-60.
- Soave, G., 1972. Equilibrium constants from a modified Redlich-Kwong equation of state. Chemical engineering science, 27(6), pp. 1197-1203.
- Soulaine, C., Maes, J., & Roman, S., 2021. Computational microfluidics for geosciences. Frontiers in Water, Vol. 3, pp. 11.
- Span, R., Wagner, W., 1996. A new equation of state for carbon dioxide covering the fluid region from the triple-point temperature to 1100 K at pressures up to 800 MPa. Journal of physical and chemical reference data, 25(6), pp. 1509-1596.
- Sun, A.Y., Lu, J., Hovorka, S., 2015. A harmonic pulse testing method for leakage detection in deep subsurface storage formations. Water Resources Research. AGU.
- Tamimi, A., Rinker, E.B., Sandall, O.C., 1994. Diffusion Coefficients for Hydrogen Sulfide, Carbon Dioxide, and Nitrous Oxide in Water over the Temperature Range 293-368 K. Journal of Chemical & Engineering Data, 39 (2), pp. 330-332.
- Teatini, P., Castelletto, N., Ferronato, M., Gambolati, G., Janna, C., Cairo, E., Marzorati, D., Colombo, D., Ferretti, A., Bagliani, A., 2011. Geomechanical response to seasonal gas storage in depleted reservoirs: A case study in the Po River basin, Italy. Jour-

nal Geophysical Research, 116, pp. 1-21.

- Tripaldi, G., Beretta, E., Bertolini, C., Gorlani, A., Costa, A., Latioui, S., Hachelaf, H., Di Gianvittorio, D., Benayad, N., Uematsu, H., Viberti, D., Verga, F., 2009. *Injection testing: an Innovative Field Application in Berkine Basin, Algeria.* Conference Paper presented at the OMC, Ravenna, Italy, 25-27 March.
- Tsao, C.W., 2016. Polymer Microfluidics: Simple, Low-Cost Fabrication Process Bridging Academic Lab Research to Commercialized Production. Micromachines, 7, pp. 225.
- Vasile, N.S., Cordara, A., Usai, G., Re, A., 2021. Computational analysis of dynamic light exposure of unicellular algal cells in a flat-panel photobioreactor to support light-induced CO2 bioprocess development, Frontiers in Microbiology, vol. 12, 1, 639482
- Verga, F., 2018. What's conventional and what's special in a reservoir study for underground gas storage. Energies, Vol. 11, Issue 5, DOI: 10.3390/ en11051245
- Verga, F., Salina Borello, E., 2016. Unconventional well testing: a brief overview. GEAM. Geoingegneria Ambientale E Mineraria, Vol. 149 (1106), pp. 45-54.
- Verga, F., Viberti, D., Salina Borello, E., 2008. A New 3-D Numerical Model to Effectively Simulate Injection Test. Europec/EAGE Conference and Exhibition in Rome, Italy. SPE-113832-MS.
- Verga, F., Viberti, D., Salina Borello, E., 2011. A new insight for reliable interpretation and design of injection tests. Journal of Petroleum Science and Engineering, Vol. 78(1), pp. 166-177.
- Verga, F., Viberti, D., Salina Borello, E., Serazio, C., 2015. Estimation of skin from the interpretation of injection tests in fractured reservoirs. Geoingegneria Ambientale e Mineraria., Vol. 146, n.3, pp. 45-52.
- Verga, F., Viberti, D., Serazio, C., 2012. Estimation of skin components for a partially completed damaged well from injection tests. Journal of Petroleum Science and Engineering, Vol. 90-91, pp. 165-174.





- Viberti, D., 2010. A rigorous mathematical approach for petrophysical properties estimation. American Journal of Applied Sciences, 7 (11), pp. 1509-1516. ISSN 1546-9239. DOI: 10.3844/ajassp.2010.1509.1516
- Viberti, D., Peter, C., Salina Borello, E., Panini, F., 2020. Pore structure characterization through path-finding and lattice Boltzmann simulation. Advances in Water Resources, Vol. 141.
- Viberti, D., Verga, F. 2012. An Approach for the Reliable Evaluation of the Uncertainties Associated to Petrophysical Properties. Mathematical Geosciences, vol. 44, Issue 3, pp. 327-341.
- Vinsot, A., Appelo, C.A.J., Lundy, M., Wechner, S., Lettry, Y., Lerouge, C., Fernández, A.M., Labat, M., Tournassat, C., De Canniere, P., Schwyn, B., Mckelvie, J., Dewonck, S., Bossart, P., Delay, J., 2014. Geological Society, London, Special Publications, 400, pp. 563-578.
- Vitale, A., Quaglio, M., Chiodoni, A., Bejtka, K., Cocuzza, M., Pirri, C.F. & Bongiovanni, R., 2015. Oxygen-Inhibition Lithography for the Fabrication of Multipolymeric Structures. Advan-

ced Materials, Vol. 27-31, pp. 4560-4565.

- Vitale, A., Quaglio, M., Marasso, S.L., Chiodoni, A., Cocuzza, M., & Bongiovanni, R., 2013. Direct photolithography of perfluoropolyethers for solvent-resistant microfluidics. Langmuir, Vol. 29(50), pp. 15711-15718.
- Wang, Y., Liu, S., 2016. Estimation of pressure-dependent diffusive permeability of coal using methane diffusion coefficient: laboratory measurements and modeling. Energy & Fuels, 30(11), pp. 8968-8976.
- West, J.W., McKinley, I.G., Palumbo-Roe, B., Rochelle, C.A., 2011. Potential impact of CO<sub>2</sub> storage on subsurface microbial ecosystems and implications for groundwater quality. Energy Procedia, Vol. 4, pp. 3163-3170.
- Wildenschild, D., Sheppard, A.P., 2013. X-ray imaging and analysis techniques for quantifying pore-scale structure and processes in subsurface porous medium systems. Advances in Water Resources, Vol. 51, pp. 217-246.
- Wilhelmsen, Ø., Skaugen, G., Jørstad, O., Li, H. 2012. Evaluation of SPUNG\* and Other Equations of State for Use

in Carbon Capture and Storage Modelling. Energy Procedia, 23, pp. 236-245.

- Wise, D.L., Houghton, G., 1966. The diffusion coefficients of ten slightly soluble gases in water at 10-60°C, Chemical Engineering Science, Vol. 21, Issue 11, pp. 999-1010.
- Zeng, J., Bejtka, K., Ju, W., Castellino, M., Chiodoni, A., Sacco, A., Farkhondehfal, M.A., Hernández, S., Rentsch, D., Battaglia, C., Pirri, C.F., 2018, Advanced Cu-Sn foam for selectively converting CO<sub>2</sub> to CO in aqueous solution. Applied Catalysis B: Environmental 236, pp. 475-482.
- Zeng, J., Castellino, M., Sacco, A., Chiodoni, A, Hernandez R.S.P., Pirri, C., 2021. Facile synthesis of cubic cuprous oxide for electrochemical reduction of carbon dioxide. Journal of Material Science, Vol. 56, pp. 1255-1271, 10.1007/ s10853-020-05278-y
- Zeng, J., Jagdale, P., Lourenço, M.A.O., Farkhondehfal, M.A., Sassone, D., Bartoli, M., Pirri, C.F., 2021. *Biochar-supported BiOx for effective electrosynthesis of formic acid from carbon dioxide reduction*. Crystals 11(4), pp. 363.