POLITECNICO DI TORINO Repository ISTITUZIONALE

Life cycle assessment and life cycle costing of advanced anaerobic digestion of organic fraction municipal solid waste

Original

Life cycle assessment and life cycle costing of advanced anaerobic digestion of organic fraction municipal solid waste / Demichelis, F.; Tommasi, T.; Deorsola, F. A.; Marchisio, D.; Mancini, G.; Fino, D.. - In: CHEMOSPHERE. - ISSN 0045-6535. - ELETTRONICO. - 289:(2022), p. 133058. [10.1016/j.chemosphere.2021.133058]

Availability: This version is available at: 11583/2955025 since: 2022-02-11T15:59:00Z

Publisher: Elsevier

Published DOI:10.1016/j.chemosphere.2021.133058

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright Elsevier postprint/Author's Accepted Manuscript

© 2022. This manuscript version is made available under the CC-BY-NC-ND 4.0 license http://creativecommons.org/licenses/by-nc-nd/4.0/.The final authenticated version is available online at: http://dx.doi.org/10.1016/j.chemosphere.2021.133058

(Article begins on next page)

Chemosphere

Life cycle assessment and life cycle costing of advanced anaerobic digestion of organic fraction municipal solid waste --Manuscript Draft--

Manuscript Number:	
Article Type:	VSI:Advances in AD
Section/Category:	Environmental Chemistry
Keywords:	organic fraction municipal solid waste (OFMSW); anaerobic digestion (AD); Life Cycle Analysis (LCA); Life Cycle Costing (LCC)
Corresponding Author:	Francesca Demichelis Politecnico di Torino Facoltà di Ingegneria: Politecnico di Torino Torino, 80380000100121140625 ITALY
First Author:	Francesca Demichelis
Order of Authors:	Francesca Demichelis
	Tonia Tommasi
	Fabio Alessandro Deorsola
	Daniele Marchisio
	Giuseppe Mancini
	Debora Fino
Abstract:	The aim of this study is the evaluation of the environmental sustainability by means of Life Cycle Assessment (LCA) and economic profitability through Life Cycle Costing (LCC) of the 18 AD configurations carried out on Organic Fraction Municipal Solid Waste (OFMSW) at three S:I ratios (1:2, 1:1 and 2:1) for three different inoculum incubation times (0, 5 and 10 d). The adopted approach was the eco-efficiency perspective, coming from the combination of technical, environmental (LCA) and economic (LCC) perspectives. The main findings of the study were that increasing both the S:I ratio and the inoculum incubation time (5 and 10 days) the environmental impacts decreased, and economic profitability increased. In detail, the lowest values of Climate Change were achieved by the AD performed with both inocula WAS and CAS for 10 days at S:I equal to 2:1: 28.67 and 27.72 kg CO 2 eq respectively. The minimum AD plant size for which all the 18 AD configurations was economically profitable after 5 year of amortisation was 30,000 t/y of OFMSW. Capital and operational costs decreased by increasing the incubation time of the inoculum and the S:I ratio, since higher specific biogas rate was reached, and smaller AD bio-reactor volume were adopted because hydraulic retention time decreased.
Suggested Reviewers:	Roland Schneider rschneider@atb-potsdam.de
	David Bolzonella david.bolzonella@univr.it
	Carminna Ottone carminna.ottone@pucv.cl
	Nicola Frison nicola.frison@univr.it
	Charlene Vance charlene.vance@ucd.ie
	Qilin Wang qilin.wang@uts.edu.au
Opposed Reviewers:	

- Environmental sustainability and economic profitability of anaerobic digestion (AD)
- Environmental impact drops by increasing S:I ratio and inoculum incubation time
- Capex and Opex drop by increasing the inoculum incubation time and the S:I ratio
- AD at the highest S:I ratio and inoculum incubation time reach the sustainability

Author contributions statement

Authors 'contributions are detailed in the following. F. Demichelis carried out Life Cycle Assssment (LCA) and Life Cycle Costing (LCC) studies and writes part of the paper. T. Tommasi supported the study of LCA and LCC. F.A. Deorsola contributed to realise the conceptualization, methodology and data curation of the study and contribute to write and review the manuscript. D. Marchisio reviewed the manuscript. G. Mancini reviewed the manuscript. D. Fino realised the conceptualization, methodology and supervision of the study.





Declaration of interests

 \boxtimes The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

□The authors declare the following financial interests/personal relationships which may be considered as potential competing interests:

Life cycle assessment and life cycle costing of advanced anaerobic digestion of organic fraction municipal solid waste

- Francesca Demichelis: Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (TO), Italy. Email francesca.demichelis@polito.it
- Tonia Tommasi: Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (TO), Italy. Email tonia.tommasi@polito.it
- Fabio Alessandro Deorsola: Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (TO), Italy. Email Fabio.deorsola@polito.it
- Daniele Marchisio: Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (TO), Italy. Email danile.marchisio@polito.it
- Giuseppe Mancini: Department of Electric, electronic and informatic engineering, Università degli Studi di Catania, Viale A. Doria 6, 95125, Catania (CT), Italy. Email gmancini@dica.unict.it
- Debora Fino: Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (TO), Italy. Email Debora.fino@polito.it

Corresponding author: Francesca Demichelis. Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (TO), Italy. **email**: francesca.demichelis@polito.it

Life cycle assessment and life cycle costing of advanced anaerobic digestion of							
organic fraction municipal solid waste							
F.Demichelis ^{1,*} , T.Tommasi ¹ , F.A. Deorsola ¹ , D.Marchisio ¹ , G. Mancini ² , D.Fino ¹							
¹ Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli							
Abruzzi 24, 10129 Torino (TO), Italy							
² Department of Electric, electronic and informatic engineering, Università degli Studi di Catania,							
Viale A. Doria 6, 95125, Catania, Italy							
*Corresponding author: Francesca Demichelis. Department of Applied Science and Technology (DISAT),							
Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino (TO), Italy. email:							
francesca.demichelis@polito.it							
Abbreviations							
AD anaerobic digestion							
CAS cow agricultural sludge							
ESI energy sustainable index							
LCA life cycle assessment							
LCC life cycle costing							
GWP global warming potential							
MBT mechanical biological treatments							
MSW municipal solid waste							
NPV Net Present Value							
OFMSW Organic fraction municipal solid waste							
ROI Return On Investment							
TS Total solids							
VS Volatile solids							
WAS Waste activated sludge							
1							

29 Abstract

30 The aim of this study is the evaluation of the environmental sustainability by means of Life Cycle Assessment 31 (LCA) and economic profitability through Life Cycle Costing (LCC) of the 18 AD configurations carried out 32 on Organic Fraction Municipal Solid Waste (OFMSW) at three S:I ratios (1:2, 1:1 and 2:1) for three different inoculum incubation times (0, 5 and 10 d). The adopted approach was the eco-efficiency perspective, coming 33 34 from the combination of technical, environmental (LCA) and economic (LCC) perspectives. The main findings of the study were that increasing both the S:I ratio and the inoculum incubation time (5 and 10 days) the 35 36 environmental impacts decreased, and economic profitability increased. In detail, the lowest values of Climate 37 Change were achieved by the AD performed with both inocula WAS and CAS for 10 days at S:I equal to 2:1: 38 28.67 and 27.72 kg CO_2 eq respectively. The minimum AD plant size for which all the 18 AD configurations was economically profitable after 5 year of amortisation was 30,000 t/y of OFMSW. Capital and operational 39 40 costs decreased by increasing the incubation time of the inoculum and the S:I ratio, since higher specific biogas rate was reached, and smaller AD bio-reactor volume were adopted because hydraulic retention time 41 42 decreased.

The AD plant size, for which maximal revenues and minimal capital and operational costs were detected, was
50,000 t/y OFMSW. Among all the AD configurations, the environmental sustainability and economic
profitability were reached by test performed with inocula WAS and CAS incubated for 5 and 10 d at the highest
S:I ratio 2:1.

47

48 Keywords: organic fraction municipal solid waste (OFMSW), anaerobic digestion (AD), Life Cycle Analysis
49 (LCA), Life Cycle Costing (LCC).

50

51 Introduction

In 2019, the production of Municipal Solid Waste (MSW) in Europe ranged from 280 kg per capita in Romania to 844 kg per capita in Denmark, and in Italy was equal to 500 kg per capita (Eurostat, 2021). In Europe, the Organic Fraction Municipal Solid Waste (OFMSW) represented an average of 27% of MSW, equal to a generation of 177 million tonnes (Eurostat, 2021). The traditional OFMSW treatments consist in mechanical 56 biological treatments (MBT), thermo-valorisation, composting and anaerobic digestion (AD). Among them, anaerobic digestion (AD) is one of the most efficient and environmentally sustainable techniques for organic 57 58 waste remediation and valorisation (Ardolino et al., 2018). OFMSW is considered as one of the major 59 contributors to climate change, human health risk and ecosystem damages. OFMSW is a biodegradable waste and so it could potentially be employed in renewable energy production processes. AD of OFMSW is a very 60 attractive option to convert the complex organic matter into a renewable and clean energy source, as biogas. 61 62 AD is a biochemical process by which complex organic matter are transformed into simple soluble compounds 63 in anaerobic environment. The main benefit of AD is the stabilisation of organic matter and pathogens by 64 converting them into biogas under anaerobic condition. The biogas is a gas mainly made up of methane and 65 carbon dioxide. In detail, AD is a multistep biological process made up of hydrolysis, acidogenesis, acetogenesis and methanogenesis. Hydrolysis is the first and rate-limiting step, since it must reduce both 66 67 organic matter and high molecular compounds as carbohydrate, proteins and lipids respectively into sugars, amminoacids and fatty acids. The AD of OFMSW is generally carried out at liquid state condition, which 68 69 means total solids (TS) ranged from 0.5 to 10%. In the present study liquid state AD was carried out, in detail 70 at 6% TS. The AD of organic matter is an environmental sustainable technique since is a carbon neutral 71 process, but it has disadvantages as long retention time, low removal efficiency organic compounds, strong 72 sensibility to the variation of pH, alkalinity, temperature, retention time, nitrogen, carbon availabilities and 73 Carbon Nitrogen (C:N) ratios which affects the AD process stability. To evaluate the environmental 74 sustainability of AD process, several studies of Life Cycle Assessment (LCA) were carried out on AD 75 performed with different organic waste as corn silage, dairy manure, food waste (Martinez-Sanchez et al., 76 2016) and agricultural waste (Ascher et al., 2020). LCA is a methodology to assess environmental impacts 77 which covers all the life cycle of product and process. The aim of the present study is the evaluation of the 78 environmental sustainability through Life Cycle Assessment (LCA) and economic profitability through Life 79 Cycle Costing (LCC) of the AD configurations tested in (Demichelis et al., under review).

The adopted approach was the eco-efficiency perspective, coming from the combination of technical, environmental (LCA) and economic (LCC) perspectives. In (Demichelis et al., under review) mesophilic AD was performed on real OFMSW supplied by San Carlo Spa (Fossano, Italy) with two inocula, one coming from the mesophilic digestate of waste activated sludge (WAS) provided by SMAT (a wastewater treatment 84 plant in the north of Italy), and the second from the mesophilic digestate of cow agricultural sludge (CAS) supplied by Cascina La Speranza (Candiolo, Italy) at three substrate inoculum ratios (S:I): 1:2, 1:1 and 2:1 for 85 86 three inoculum incubation times: 0, 5 and 10 days. Two inocula with different origins were selected to improve the C:N ratio, in particular animal sludge matter provided enhancement of C:N and buffering capacity. The 87 main output of the present study was the evaluation of optimal technical feasibility, environmental 88 89 sustainability, and economic profitability of AD configurations to scale them at the commercial -industrial 90 scales.

91

92 2 Materials and methods:

2.1. Environmental sustainability 93

Life cycle assessment was performed with SimaPro 9.0 software and it was based on ISO 14040 (2006) and 94 95 14044 (2006). Ecoinvent 3.0 was employed as database.

96

111

97 2.1.1 Goal and scope:

98 The goal of LCA was the evaluation of the best anaerobic digestion (AD) configurations among the 18 AD 99 configuration tested in (Demichelis et al., under review).

100 In the present study, the concept of best AD configuration means the AD configurations which reached the 101 highest technical-performances, the lowest environmental impacts and the highest economic profitability.

102 The functional unit (FU) was 1 t of wet OFMSW. The produced emissions, the consumed material and the required energy were referred to the FU. The choice of FU equal to 1 t of OFMSW allowed the comparison 103 with other studies available in the scientific literature (Ascher et al., 2020). The boundary conditions included: 104 105 the collection and the transport of OFMSW to the the AD plant, the transport of inoculum to the AD plant, the 106 AD process and the CHP unit. The OFMSW was collected in the town and then transported to the AD plant. 107 According to (Demichelis et al., under review) AD was performed in batch feeding at 6% TS on real OFMSW supplied by San Carlo Spa (Fossano, Italy), with two inocula, one coming from the mesophilic digestate of 108 109 waste activated sludge (WAS) provided by SMAT (a wastewater treatment plant in the north of Italy), and the second from the mesophilic digestate of cow agricultural sludge (CAS) supplied by Cascina La Speranza 110 (Candiolo, Italy) at three substrate inoculum ratios (S:I): 1:2, 1:1 and 2:1 for three inoculum incubation times: 112 0, 5 and 10 days. Two inocula with different origins were selected to improve the C:N ratio, in particular animal sludge matter provide enhancement of C:N and buffering capacity. Hence, a total of 18 configurations 113 114 of AD of OFMSW were tested. The AD was performed under mesophilic conditions 37°C with constant mixing at 300 rpm. AD has two outputs: biogas and digestate. The AD configurations adopted the following 115 code: TX Y ZZZ, where X can be 0, 5 or 10 days representing the incubation time of the inoculum, Y is the 116 S:I ratio, in detail 1 for S:I=1:2, 2 for S:I=1:1 and 3 for S:I=2:1 and ZZZ represents the origin of the inoculum 117 118 WAS or CAS. Biogas was sent to CHP unit to produce electric energy ($\eta = 0.45$) and heat ($\eta = 0.55$), while 119 digestate was not valorised, in order to focus the attention only on the benefits coming from biogas-energy 120 valorisation. The adopted approach was from cradle to gate according to (Wang et al., 2020).

121

122 2.1.2 Life cycle inventory (LCI)

The LCI defined all inputs and outputs involved in the processes. The primary data came from the study of 123 124 (Demichelis et al., under review) and in Table 1 these data are scaled up to FU equal to 1 t of OFMSW with a 125 correction factor 0.8 (Perry, 2008). The LHV of methane was assumed equal to 35.9 MJ/m³ according to 126 (Gonzàlez et al., 2020). In Table 1, six AD configurations were yellow coloured since they were energetically self-sufficient with Energy Sustainable Index higher than 1. The secondary data were taken from Ecoinvent 127 3.0. and reported in Table 2. According to (Brander et al., 2019) attributional LCA was applied. In detail, 128 129 attributional LCA means a modelling approach by which inputs and outputs were attributed to the FU of a 130 product system linking the unit processes of the system according to a normative rule. Collection and transport 131 of OFMSW were equal to 20 and 30 km respectively, while the transport of inocula, both for WAS and CAS 132 was equal to 20 km. Expansion system methodology was applied since electric and heat were re-integrated in 133 the AD system.

134

135 **2.1.3** Life cycle impact assessment (LCIA)

Life cycle impact assessment was performed with the ReCiPe Midpoint (H) method. The AD system was evaluated both as internal processes with energy productions and as external process including OFMSW collection, OFMSW and inocula transportations and energy consumption. Both internal and external processes affected global warming potential (GWP). In the present study, the analysed impact categories were: Climate change (kg CO_{2 eq}), Ozone depletion (kg CFC-11 eq), Human toxicity, (kg 1,4-DB eq), Cancer effects (CTUh),
Acidification (molc H+ eq), Terrestrial eutrophication (molc N eq), Marine eutrophication (kg N eq,) and Land
use (kg C deficit). The attention will be focused on Climate Change, because in scientific literature several
studies were available for comparison.

144

145 **2.1.4 Interpretation data e sensitivity analysis**

146 The last step of LCA was the interpretation of the results to evaluate the achievement of the goal. A double 147 sensitivity analysis was performed to measure and detect possible variation of AD response on environmental impacts. The first sensitive analysis was performed varying selected parameters as kilometre of transport and 148 collection of OFMSW, since recent studies prove that biomass yield density (t/ha·y) varied with biomass 149 supply distance (km) from biorefinery plant location. In detail, the study of (Golecha et al., 2016) stated a 150 mutual influence and dependency between biomass yield density (t/ha·y) and supply distance (km). The second 151 152 sensitivity analysis for LCA section was applied changing the low heating value (LHV) of biogas of the 18 tested AD configurations from -2.5 to+2.5% of CH₄ (%v/v) content, according to (Wang and al., 2020). 153

	D !						Energy	Energy			
	Biogas	CH4 (%)	CO ₂ (%)	Inoculum	OFMSW (t)	H ₂ O (m ³)	produced	consumed	ESI (-)	EE saved	ET saved
	(NL/kgvs)			(t)			(kWh)	(kWh)		(kWh)	(kWh)
T0_1_WAS	762.5	64.67	35.33	4.4	1	0.1	106.27	326.7	0.33	-99.19	-121.23
T0_2_WAS	731.24	62.76	37.24	2.2	1	0.47	98.91	226.51	0.44	-57.42	-70.18
T0_3_WAS	708.12	62.53	37.47	1.1	1	0.65	95.43	182.89	0.52	-39.36	-48.11
T0_1_CAS	782.58	66.01	33.99	3.74	1	0.76	111.33	326.7	0.34	-96.91	-118.45
T0_2_CAS	755.89	64.84	35.16	1.87	1	0.8	105.63	191.66	0.55	-38.71	-47.32
T0_3_CAS	748.89	61.74	38.26	0.94	1	0.81	99.65	169.83	0.59	-31.58	-38.6
T5_1_WAS	818.52	61.8	38.2	4.4	1	0.1	109.03	274.43	0.4	-74.43	-90.97
T5_2_WAS	835.95	62.8	37.2	2.2	1	0.47	113.15	217.8	0.52	-47.09	-57.56
T5_3_WAS	932.06	64.5	35.5	1.1	1	0.65	129.57	128	1.01	0.71	0.87
T5_1_CAS	840.49	63.82	36.18	3.74	1	0.76	115.61	248.29	0.47	-59.71	-72.97
T5_2_CAS	859.49	65	35	1.87	1	0.8	120.41	165.53	0.73	-20.3	-24.81
T5_3_CAS	948.68	67.57	32.43	0.94	1	0.81	138.16	117.58	1.18	9.26	11.32
T10_1_WAS	849.69	67.9	32.1	4.4	1	0.1	124.35	287.5	0.43	-73.42	-89.73
T10_2_WAS	890.96	68.2	31.8	2.2	1	0.47	130.97	121.97	1.07	4.05	4.95
T10_3_WAS	994.2	69	31	1.1	1	0.65	147.86	117.58	1.26	13.63	16.65

T1(0_1_CAS	846.41	68.31	31.69	3.74	1	0.76	124.62	222.16	0.56	-43.89	-53.65
T1(0_2_CAS	892.2	69.85	30.15	1.87	1	0.8	134.32	121.97	1.1	5.56	6.79
T1(0_3_CAS	997.81	70	30	0.94	1	0.81	150.54	117.58	1.28	14.84	18.13

Table 1: Primary data of LCI based on (Demichelis et al, under revision) scaled up to the FU = 1t of OFMSW

156

Transport	Transport, freight, lorry 16-32 metric tons, Euro 6
Electricity	Electricity, high voltage (IT) electricity production oil
Heat	Heat, central or small scale, other than natural gas (CH), heat production at heat pump 30kW
Water	Water from natural resource

Table 2: Secondary data from Ecoinvent 3.0

158 2.3 Economic analysis

Economic feasibility was studied by Life Cycle Costing (LCC). LCC is an assessment of all costs related to 159 160 the production of a product or service, considering the whole life cycle from production to usage until disposal. The LCC was carried out in three main modules: data collection, cost estimation and data interpretation. The 161 target of LCC was the evaluation of the economic cost of the whole life cycle of anaerobic digestion process, 162 with the aim to reduce and minimise the cost of production. In this study, the result of LCC is the definition of 163 164 the economic dimension of the AD process. LCC was performed from the viewpoint of producers. According to LCA (paragraph 2.1.1), the same goal and scope, system boundary and functional unit were adopted to 165 perform LCC to obtain an overall consistent analysis. 166

- LCC was calculated considering capital investment, operational costs, profitability of the anaerobic digestion,
 Net Present Value (NPV), Return On Investment (ROI) and payback time. The LCC was performed on the
- 169 minimum AD plant size for which economic profitability was achieved.

170 2.3.1 Capital cost evaluation

Capital cost (Table3) included the purchase of reactors and facilities for the construction and the installation.
The cost of land was not considered since the analysis was not geo-referred. In fact, the target of the economic
analysis was the evaluation of the economic profitability of the proposed AD configurations. The tax of interest
was equal to 2% with a 5-years of amortization. The amortization was calculated with Eq. 1:

175
$$A(euro) = C_0 \cdot \frac{i \cdot (1+i)^n}{(1+i)^{n-1}}$$
 (1)

where *A* means the amortization cost, C_o is the capital investment, *n* the number of years of amortisation and *i* is the tax of interest.

178

Technique	Unit	Cost(Euro/unit)	References
Grinder	kg/s	2323.3	(Eurostat, 2021)
Bio-digestor	m ³	2514.7	(Gonzàlez et al., 2020)
Stirrer	kW	46465.3	(Akeberg et al., 2000)
Centrifuge	kg/s	116163.2	(Akeberg et al., 2000)
Heat exchanger	m ²	889.96	(Akeberg et al., 2000)

Table 3: List of capital costs.

180

181 **2.3.2 Operational cost evaluation**

182 The operational costs (Table 4) included the cost of the collection and transport of OFMSW to the AD plant,

the maintenance of the equipment, the disposal of AD residues, the labours and the utilities necessary to run

the processes as fuel, steam, heat and electricity.

185

Technique	Operation	Unit	Cost (Euro/unit)	References	
Raw material	Collection of OFMSW	Euro/t	0.21	(ISPRA, 2021)	
	Inoculum	Euro/m ³	2.10	(Demichelis et al., 2018)	
	Process water	Euro/m ³	0.13	(Akeberg et al., 2000)	
Water and	Power	Euro/kWh	0.034	(Akeberg et al., 2000)	
energy	Electric power	Euro/MW	5.24	(Wingre et al., 2003)	
consumption	Steam boiler	Euro/MW	72.80	(Wingre et al., 2003)	
	Steam for AD process	Euro/kg	0.2	(Akeberg et al., 2000)	
	Waste disposal	Euro/t	40.00	(ISPRA, 2021)	
	Labor	Euro/year	44966.40	(ISTAT, 2021)	

Table 4: List of operational costs.

187

188 **2.3.3 Revenue and evaluation of profitability**

189 The market value of electric energy is 0.20 euro/kWh and thermal energy of 0.201 euro/kWh (Eurostat

statistic, 2021). The annual profit was the difference between the revenue and the sum of the amortisation and

191 operational costs.

192 To complete the evaluation of the profitability the NPV, ROI and payback time were calculated.

193 NPV (Eq. 2) pointed out the profitability of the AD configuration considering a plant lifetime of 20 years

194 considering a 5% discount for the future cash flows referring to the present value. According to (Pleissner et

al., 2016), NPV > 0 means that AD process is profitable.

196
$$NPV(euro) = \sum_{t=1}^{T} \frac{C_t}{(1+d)^t} - C_0$$
 (2)

where, C_t is the net cash flow during period *t*, C_0 is the initial capital investment, *t* is the plant lifetime and *d* is the discount rate.

199 *ROI* (Eq. 3) was defined as key parameter to evaluate the performance of the profitability of an investment

$$200 \quad ROI \ (\%) = \frac{Annual \, net \, profit}{Initial \, total \, investment} \cdot 100 \tag{3}$$

In details, to calculate ROI the annual net profit after 5 years of amortization was considered. Payback timestates the time required to regain the funds expended in capital costs.

203

204 2.3.4 Economic sensitivity analysis

Two sensitivity analysis were performed. The first sensitivity analysis for LCC was performed as sensitivity for LCA, by changing the LHV of CH₄ of the 18 AD configurations tested from -2.5 to+2.5% of CH₄ (% v/v) content, according to (Wang and al., 2020). The second sensitivity analysis was performed by floating the CH₄ price of $\pm 20\%$ according to (Li et al., 2020).

209

210 **3.Results:**

211

212 **3.1 Environmental sustainability.**

Life Cycle Assessment (LCA) was carried out on the 18 AD configurations tested in (Demichelis et al., under 213 214 review) and the following impact categories were analysed: Climate change ($kgCO_2$ eq), Ozone depletion (kg 215 CFC-11 eq), Human toxicity, Cancer effects (CTUh), Acidification (molc H+ eq), Terrestrial eutrophication 216 (molc N eq), Marine eutrophication (kg N eq.) and Land use (kg C deficit). Global warming potential (GWP) 217 was significantly affected by OFMSW management practices involving significant GHG emissions. The 218 emissions due to collection and transport of OFMSW, AD of OFMSW and biogas utilisation were summed 219 up. Conventional OFMSW managements were evaluated to underline the pros coming from to the proposed 220 AD management. In details, incineration and landfilling achieved 107 kg CO₂ eq and 209 kg CO₂ eq, respectively, these results agreed with (Cremiato et al., 2018). 221

In the present study, the reduction of GHG emission was due to the use of produced biogas as thermal energy to heat the bio-digestor. This pro was detected in the AD configurations with Energy Sustainable Index (ESI) major than 1; the AD performed both with inocula WAS and CAS for incubation time of 5 and 10 d at S:I ratios equal to 1: 1 and 2:1 (Table 1, yellow coloured): T5_3_WAS, T5_3_CAS, T10_2_WAS, T10_2_CAS, T10_3_WAS and T10_3_CAS. In Figure 1, the GWP reached by the 6 AD configuration with ESI major than 1 was depicted considering the GWP contribute of each phase of AD process. The highest environmental items were OFMSW and inoculum transport, according to (Golecha et al., 2016).

Since the produced biogas was employed as energy vector part of electric and thermal energy were saved and negative Climate change values were evaluated. It is important to underline that many LCA studies about organic waste, food waste and OFMSW were performed in scientific literature, but it is challenging to make analogies and comparisons due to the different system boundaries, FU, and life cycle impact methodologies.

233 Moreover, the most adopted AD system is made up of the following units: AD unit, biogas utilisation with a biogas engine and digestate treatment as fertiliser. In the present study, digestate valorisation was not 234 235 considered since the attention was focused only on pros and cons of biological waste to energy process based 236 on the experimental results achieved in (Demichelis et al., under review). Table 5 depicts that increasing both 237 the S:I ratio and the inoculum incubation time (5 and 10 days) the environmental impacts decreased, since higher amount of OFMSW was valorised and specific production of biogas with higher methane content was 238 239 achieved. In details, the environmental impacts of AD performed both with inocula WAS and CAS at the 240 lowest S:I (1:2) and lowest inoculum incubation time (0 days), were higher than the ones achieved by the AD performed both with inoculum WAS and CAS with the highest S:I (2:1) and the highest inoculum incubation 241 242 time (10 days).

	Climate	Ozone	Human toxicity, cancer	A • 1•0• 4•	Terrestrial	Marine	T 1
	change	depletion	effects	Acidification	eutrophication	eutrophication	Land use
Unit	kg CO ₂ eq	kg CFC-11 eq	CTUh	molc H+ eq	molc N eq	kg N eq	kg C deficit
T10_3_WAS	28.67	3.9E-03	2.1E-07	0.15	0.20	0.02	50.17
T10_2_WAS	38.19	5.2E-06	2.8E-07	0.19	0.27	0.02	68.67
T10_1_WAS	82.61	1.1E-05	6.4E-07	0.45	0.61	0.05	129.27
T5_3_WAS	37.00	5.2E-06	3.0E-07	0.21	0.29	0.03	59.73
T5_2_WAS	62.36	8.0E-06	4.7E-07	0.34	0.45	0.04	88.75
T5_1_WAS	85.63	1.1E-05	6.2E-07	0.43	0.59	0.05	126.77
T0_3_WAS	50.71	6.4E-06	3.8E-07	0.28	0.37	0.03	68.48
T0_2_WAS	64.37	8.2E-06	4.8E-07	0.35	0.46	0.04	90.42
T0_1_WAS	94.67	1.2E-05	7.1E-07	0.51	0.68	0.06	136.78
T10_3_CAS	27.52	3.7E-06	2.0E-07	0.14	0.19	0.02	47.68
T10_3_CAS	36.33	4.9E-06	2.7E-07	0.18	0.26	0.02	63.96
T10_1_CAS	68.40	9.0E-06	5.1E-07	0.36	0.49	0.04	108.61
T5_3_CAS	30.38	4.1E-06	2.2E-07	0.16	0.22	0.02	50.05
T5_2_CAS	49.23	6.4E-06	3.7E-07	0.26	0.35	0.03	74.67
T5_1_CAS	74.43	9.7E-06	5.6E-07	0.39	0.53	0.05	113.61
T0_3_CAS	47.17	6.0E-06	3.5E-07	0.26	0.34	0.03	64.01

	T0_2_CAS	55.25	7.1E-06	4.1E-07	0.30	0.40	0.04	79.67
	T0_1_CAS	92.51	1.2E-05	6.9E-07	0.50	0.67	0.06	128.63
244	Table 5: Environ	mental impacts	of the 18 AD config	gurations				
245								
246	In detail, the Clin	nate change of A	D with inoculum no	on incubated was + 69.9	8 % \pm 0.37, Ozone dep	bletion was + 68.29 % \pm	0.24, Human toxicity	was +70.61 % ±
247	0.40, the Acidific	ation was + 71.4	41 % \pm 0.47, Terres	trial eutrophication, was	$s + 70.45 \% \pm 0.41$, Ma	arine eutrophication was	+ 70.48 % \pm 0.41 and	Land use was +
248	$63.12\% \pm 0.27,1$	higher than AD	performed with inoc	cula incubated for 10 d a	at the highest S:I ratio	(2:1). We focused more a	attention on Climate c	hange, since it is
249	the most studied i	impact category	in scientific literatu	re. For the Climate chan	nge impact category, th	e present study considere	ed the contribution of	biogenic carbon,
250	with a factor of b	iogenic CO ₂ equ	ual to 1.					
251	In the present stu	dy, the highest	GWP values were re	eached by the following	configurations: AD p	erformed with inoculum	WAS and CAS with	out incubation (0
252	day) at S:I ratio e	qual to 1:2: T0_	1_WAS reached 94.	.67 kgCO ₂ /t OFMSW an	nd T0_1_CAS achieved	1 92.51 kgCO ₂ /t. These re	esults agreed with the	study of (Ascher
253	et al., 2020) who	performed the A	D of food waste bot	th neglecting and consid	lering the biogenic CO	2 and reached -97.27 and	140.50 kgCO ₂ eq per	1 t of food waste
254	and with the stud	y of (Jin et al., 2	015) which reached	96.97 kgCO ₂ /t of food v	waste in mesophilic liq	uid AD, with S:I ratio eq	ual to 1:2. In Climate	change category
255	(Figure 1, in whic	ch are reported of	nly the AD configura	ations with ESI >1), the	inoculum played a key	role, since decreasing the	S:I ratio (1:2) the amo	ount of inoculum
256	increased, increas	sing the reactor v	volume and the CO ₂	emissions rather than A	D configurations with	higher S:I (1:1 and 2:1).	Moreover, increasing	both the S:I ratio
257	and the incubatio	n time, the spec	ific biogas production	on and the CH ₄ content	in the biogas increased	d, with a consequential d	ecrease of CO ₂ emiss	ions and thermal
258	energy required t	to heat the bio-d	ligestor, since bioga	s was sent to CHP unit	. The GWP values of	T10_3_WAS and T10_3	CAS were 28.67 an	d 27.52 kg CO ₂ ,
259	respectively acco	rding to (Fei et a	al., 2021) which rea	ched 29.24 kg CO ₂ per	1 t of food waste treate	ed with solid and liquid A	AD processes. The AD	performed both

- with CAS and WAS incubated for 5 days at S:I equal to 1:2 (T5_1_WAS and T5_1_CAS) agreed with the study of (Fei et al., 2021) which reached 77.9 kg CO₂
- 261 per 1 t of food waste treated with solid and liquid AD processes.



Figure 1: Climate change values of the AD configuration with ESI major than 1

According to (Ascher et al., 2020) the CHP unit contribute to GWP ranged between 20-30% of total GWP estimated.

Usually, dairy waste management consists in stockpiling and land application which caused 307 and 204 kg CO₂ eq per ton respectively, according to (Adghim et al., 2020). In the present study, 9 AD configurations adopted as inoculum the digestate coming from cow agricultural sludge (CAS) and the reached GWP witnessed the positive valorisation of both matrix CAS (as inoculum) and OFMSW (as substrate), which achieved a minimum GWP with T10_3_CAS (27.52 kg CO₂ eq) and maximum T0_1_CAS (92.52 kg CO₂ eq). Moreover, the AD performed with inoculum CAS achieved GWP lower than the one using WAS as inoculum, in the range of -4.18 to -16.51%. This trend was in line with the study of (Cristóbal et al., 2018).

Considering the ESI (Table 1) and Climate change values (Table 5 and Figure 1) of all AD configurations with ESI major than 1; the decrease of kgCO₂ eq emissions matched with the increase of ESI values. In terms of kg CO₂ eq released, the best AD configurations were AD performed with both CAS and WAS inoculum incubated for 10 day at S:I ratio equal to 2:1 (T10_3_CAS and T10_3_WAS), AD with both CAS and WAS incubated for 10 d at S:I ratio equal to 1:1 (T10_2_CAS and T10_2_WAS), and AD with both CAS and WAS incubated for 5 d at S:I ratio equal to 2:1 (T5_3_CAS and T5_3_WAS). These trends agreed with multi-criteria decision ranking reported in (Demichelis et al., under review) performed with ELECTRE II. The AD performed both with inocula CAS and WAS at the highest S:I ratio (2:1) for the highest inocula incubation time (10 d) reached
the lowest Human toxicity, Ozone depletion, Cancer effect, Acidification, Terrestrial eutrophication, Marine
eutrophication, and Land uses values. These values agreed with (Fei et al., 2021). These outputs were due to
the higher valorisation of OFMSW reached working at higher S:I ratio and the correct disposal of digestate.
According to (Martinez-Sanchez et al., 2016) the main contribution to the above-mentioned impact categories
was the application of digestate as fertiliser.

286

287 **3.2.2** Environmental sensitivity analysis

288 Two sensitivity analysis were performed. The first sensitive analysis was performed varying the following 289 parameters: kilometre of transport and collection of OFMSW, since recent studies prove that biomass yield 290 density (t/ha·y) varied with biomass supply distance (km) from biorefinery plant location. The transport of 291 OFMSW was increased and decreased respectively of plus and minus 10 km. In detail, according to the study 292 of (Golecha et al., 2016) a mutual influence and dependency between biomass yield density $(t/ha \cdot y)$ and supply 293 distance (km) was detected and the trend of GWP of the 18AD configurations did not change, but increasing 294 the transport (km) the GWP increase about 23-18% (Figure 2). The second sensitivity analysis for LCA was 295 applied changing the LHV of biogas of the 18 tested AD configuration of $\pm 2.5\%$ of CH₄ (%v/v) content, 296 according to (Wang et al., 2020). Sensitivity analysis, performed by changing the LHV of CH₄, witnessed that 297 GWP values ranged from -1.68. to +5.65 %, but the trend of the tested 18 AD configurations did not change 298 (Figure 2). To conclude, the environmental analysis proved that increasing both the S:I ratio and the inoculum 299 incubation time the environmental impacts decreased.



300

Figure 2: Sensitivity analysis. Sensitivity analysis 1 obtained by changing the transports of inoculum and
OFMSW +10 km and -10 km. Sensitivity analysis 2 obtained by changing the LHV of methane, +2.5 % -2.5
%.

304

305 **3.3 Economic sustainability**

To develop economic analysis Life Cycle Costing was performed and a quantitative cost engineering technique was applied, in detail analytical technique, which considers product as a decomposition of a series of elementary operations and activities. In this way, the costs were estimated as a sum of all the components, both for investment and operational costs. The analytical technique was adopted since it was the most accurate and consistent approach for cost estimation, according to (Altavilla et al., 2015).

311 Value analysis was carried out and it should maximize the difference between value and cost, trying to reduce

312 waste, which is an element or part of the process that does not add value.

Capital and operational costs, revenues, incomes, ROI, NPV and payback time were calculated. The study was carried out on AD plant of 30,000 t of OFMSW per year since it was the minimum size for which all the 18 AD configurations were profitable after 5 years of amortisation.

316

317 **3.3.1** Capital cost

The AD plant had a service life equal to 20 years and 5 years of amortisation of capital cost according to (Li et al., 2020) AD feed mood was carried out in batch series, since the inoculum played a key role as proved in (Demichelis et al., under review) reaching methane yields +38.2 %v/v higher than traditionally AD of OFMSW. The capital costs included bio-reactor construction, CHP unit, and plant costs, which were both the direct and the indirect costs to realise the plant as buildings, purchase of equipment, instrumentation, and facilities according to (Li et al., 2020).

324

	HRT (d)	Inoculum (t)	H ₂ O (m ³)	Working.volume reactor(m ³)	Volume reattor(m ³)
T0_1_WAS	27	132000	2998.88	14849.9	18562.37
T0_2_WAS	27	66000	14000	9900	12375
T0_3_WAS	28	33000	19500	7700	9625

T5_1_WAS	20	132000	2998.88	10999.93	13749.91
T5_2_WAS	18	66000	14000	6600	8250
T5_3_WAS	16	33000	19500	4400	5500
T10_1_WAS	18	132000	2998.88	9899.93	12374.92
T10_2_WAS	16	66000	14000	5866.67	7333.33
T10_3_WAS	16	33000	19500	4400	5500
T0_1_CAS	27	133980	22755.1	16806.16	21007.7
T0_2_CAS	25	66990	23877.55	10072.3	12590.37
T0_3_CAS	27	33495	24438.78	7914.04	9892.55
T5_1_CAS	20	133980	22755.1	12449.01	15561.26
T5_2_CAS	21	66990	23877.55	8460.73	10575.91
T5_3_CAS	15	33495	24438.78	4396.69	5495.86
T10_1_CAS	16	133980	22755.1	9959.21	12449.01
T10_2_CAS	15	66990	23877.55	6043.38	7554.22
T10_3_CAS	19	33495	24438.78	5569.14	6961.42

Table 6: Detail of AD plant for size 30,000 t/y (the minimum size economic profitable for all the 18 AD
configuration tested).

327

In Table 6, the features of AD bio-reactor of a plant of 30,000 t of OFMSW per year and 2105.4 t of digestate
was reported.

330 30,000 t of OFMSW per year was studied since was the minimum size for which all the 18 AD configuration
331 were profitable after 5 years of amortisation.

The capital costs of the 18 AD configurations are depicted in Figure 3 as total investment costs (euro) and percentage contribute of each item (%). In detail, increasing the incubation time of the inoculum (5 and 10 d) and the S:I ratio both with CAS and WAS, the bio-reactor size decreased, because the HRT of the process decreased, and consequentially its purchase decreased from 49.00 % (T0_1_WAS) to 35.33% (T10_3_CAS) of total capital cost. Increasing the S:I ratio (1:1 and 2:1) and the inoculum incubation (5 and 10 d) the CHP unit cost contribution increased, since higher biogas rate was achieved. The capital costs of AD performed

- both with WAS and CAS inocula incubated for 10d at S:I ratio equal to 2:1 agreed with the ones reached by
- 339 (Patinvoh et al., 2017) with dry AD.
- 340 The capital costs of AD performed with inocula incubated for 5 and 10 d at higher S:I ratio (1:1 and 2:1) were
- 341 like the ones obtained with dry AD (Qian et al., 2015).





Figure 3: Capital costs (euro) and contribution percentage in capital costs (%)

345

346 3.3.2 Operational costs

Operational costs included the cost of the raw material (i.e. transport of inoculum, the collection and transport of OFMSW to the AD plant), the equipment maintenance, the disposal of waste and residues, the labours and the utilities necessary to run the processes as fuel, steam, heat and electricity.

The operational costs of the 18 AD configurations are depicted in Figure 4 as total operational costs (euro) and percentage contribute of each items (%). The costs of raw materials, equipment maintenance, waste disposal and labour costs were constant among the 18 configurations. The key item was the energy (electrical and thermal) costs. In details, two trends were detected. The first trend was: for AD performed with non incubated inoculum the energy required increase by increasing the S:I ratio, since low specific biogas rate and long HRT were reached. This trend agreed with liquid AD performed by (Li et al., 2020). The second trend was: for AD performed with incubated inoculum, the required energy decreased by

357 increasing the S:I ratio, since high specific biogas rate and short HRT were reached. This trend agreed with

358 (Qian et al., 2015).



360

361 Figure 4: Operational costs (euro) and percentage contribution (%)

F0_1_WAS T0_2_WAS T0_3_WAS T5_1_WAS T5_2_WAS T5_3_WAS ^{-10_1_}WAS [10_2_WAS [10_3_WAS T0_1_CAS T0_2_CAS T0_3_CAS T5_1_CAS T5_2_CAS T5_3_CAS 10_1_CAS [10_2_CAS 10_3_CAS

362

363 **3.3.3 Revenues**

Figure 5 depicts the incomes of the 18 AD configurations due to the differences between biogas trade and capital and operational costs, before and after 5 years of amortization and ROI after 5 years of amortization. In the first 5 years of life AD plant the only profitable configurations were AD performed with both inocula CAS and WAS incubated for 5 and 10 d at the highest S:I (2:1), respectively: T5_3_WAS, T10_3_WAS T5_3_CAS, T10_3_CAS. After 5 years of amortization all the 18 AD configurations were profitable and among them the most profitable were: T10_3_WAS, T10_3_CAS. followed by T5_3_CAS and T5_3_WAS.

370 The incomes achieved by these configurations agreed with wet AD performed (Demichelis et al., 2018) for

AD plant. To scrutinize the economic assessment of the above mentioned profitable configurations, Net

372 Present Value (NPV), Return of Investment (ROI) and payback time were calculated (Table 7).



373

Figure 5: Revenues (euro) and ROI (%)

AD configurations	ROI (%)	payback time (y)	NPV (euro)
T5_3_WAS	24.99	10	2,348,887.37
T10_3_WAS	28.45	11	2,810,068.86
T5_3_CAS	25.89	10	2,467,367.73
T10_3_CAS	22.47	12	2,534,258.31

Table 7: Economic key indicator to evaluate the profitability of the 18 AD configurations

376

In particular, only four AD configuration (the AD performed with inocula WAS and CAS incubated for 5 and 377 378 10 d at the highest S:I ratio) had payback time minor of 20 y (the life service of the AD plant), NPV positive and ROI higher than 20%. Among them, the T5_3_WAS reached best fit NPV, ROI and payback time, 379 380 respectively 2,810,068.86 euro, 28.45% and 11 y. The minimum size for which all the 18 AD configuration were profitable after 5 years of amortization was 30,000 t/y of OFMSW. To identify the best fit between 381 382 capital, operational costs and revenues the study of ROI was performed for AD plant size from 20,000 t/y to 383 100,000 t/y (Figure 6). The best fit of economic assessment was detected for AD plant size equal to 50,000 t/y 384 according to (Demichelis et al., 2018) (Arias et al., 2020).





Figure 6: Evaluation of the AD plant size to obtain the maximal benefit CAPEX and OPEX. On x -coordinateis reported the t of OFMSW per year considered.

389 3.3.4 Economic sensitivity analysis

390 Two sensitivity analysis were performed. The first economic sensitivity analysis (Figure 7) was carried out as 391 the sensitivity for LCA, by changing the LHV of biogas of the 18 tested AD configuration from -2.5 to+2.5 % of CH₄ (%v/v) content, according to (Wang et al., 2020). The sensitivity analysis was performed considering 392 393 the net revenues in the first 5 years of amortisation. Even if, the LHV of CH₄ was increased and decreased of 394 \pm 2.5 %, the AD configuration economic profitable in the first 5 years of amortisation were T5_3_WAS, T10_3_WAS, T5_3_CAS, T10_3_CAS. These results confirmed the outputs of economic assessment 395 396 described in sections 3.3.1, 3.3.2 and 3.3.3. In detail, among the profitable configurations: 1) increasing the LHV of +2.5 % the revenues in the first 5 years of amortization was increased in the range from +22.42 % to 397 398 +42.71 %, respectively for T5_3_WAS and T10_3_CAS.; 2) decreasing the LHV of -2.5 % the revenues in

- the first 5 years of amortization was decreased from 21.73% to 31.7 % respectively for T5_3_WAS and T10_3_CAS. The second sensitivity analysis (Figure 7) was performed by floating the biogas price of $\pm 20\%$ according to (Li et al., 2020).
- 402 Even if, the price of CH_4 was increased and decreased of ± 20 %, the AD configuration economic profitable in
- 403 the first 5 year of amortisation were T5_3_WAS, T10_3_WAS T5_3_CAS, T10_3_CAS. Among the
- 404 profitable configurations: 1) increasing the price of CH_4 of +20 % the revenues in the first 5 years of
- 406 T10_3_CAS; 2) decreasing the price of CH_4 of -20% the revenues in the first 5 years of amortization were

amortization were increased in the range from 20.11 % to 41.54 %, respectively for T5_3_WAS and

- 407 decreased from 19.8 % to 29.72 % respectively for T5_3_WAS and T10_3_CAS. To conclude the economic
- 408 sensitivity analysis, the following state con be asserted: by changing the LHV of CH₄ about ± 2.5 % and the
- 409 price of CH₄ in the range of ± 20 %, the AD configuration economically profitable were always: T5_3_WAS,
- 410 T10_3_WAS T5_3_CAS, T10_3_CAS.

405





Figure 7: Economic sensitivity analysis. Sensitivity analysis 1 obtained by changing the LHV of CH₄ about ± 2.5 %. The second sensitivity analysis was performed changing the price of CH₄ in the range of ± 20 %. The sensitivity analysis was carried out on net revenues before 5 years of amortisation.

416

417 Conclusions

The aim of the present study was the evaluation of the environmental sustainability through Life Cycle Assessment (LCA) and economic profitability through Life Cycle Costing (LCC) of the 18 AD configurations carried out on OFMSW at three S:I ratio (1:2, 1:1 and 2:1) for three different inoculum incubation times (0, 5 and 10 d). The adopted approach was the eco-efficiency perspective, coming from the combination of 422 technical, environmental (LCA) and economic (LCC) perspectives. From environmental perspective: increasing both the S:I ratio and the inoculum incubation time (5 and 10 days) the environmental impacts 423 424 decreased, since higher amount of OFMSW was valorised and specific production of biogas with higher methane content was achieved. The lowest values of Climate change were achieved by T10_3_WAS and 425 T10_3_CAS: 28.67 and 27.72 kgCO₂ eq, respectively. LCC was developed to evaluate the economic 426 profitability of the 18 AD configurations tested. The minimum AD plant size for which all the 18 AD 427 428 configurations were profitable after 5 year of amortisation was 30,000 t/y of OFMSW. Capital and operational 429 costs decreased by increasing the incubation time of the inoculum and the S:I ratio, since a higher specific biogas rate was reached, and smaller AD bio-reactor volume was adopted since HRT decreased. The AD plant 430 size, for which maximal revenues and minimal capital and operational costs were evaluated, was 50,000 t/y 431 OFMSW. To conclude, the AD configurations which reached both the environmental sustainability and 432 economic profitability were: the AD performed both with inoculum WAS and CAS incubated for 5 and 10 d 433 at the highest S:I ratio 2:1: T5_3_WAS, T5_3_CAS, T10_3_WAS and T10_3_CAS. 434

435

436 Acknowledgement

437 The Authors gratefully acknowledge San Carlo SpA to provide the OFMSW and SMAT (Società
438 Metropolitana Acque Torino) and Cascina la Speranza to provide the inocula.

439 This research was part of the project BIOENPRO4TO (funded project POR/FESR Piemonte 333-201).

440

441 **References**

- 442 Eurostat. Municipal waste statistics. 2021. https://ec.europa.eu/eurostat/statistics-
- 443 <u>explained/index.php/Municipal_waste_statistics#Municipal_waste_generation</u> Accessed 30 March.2021
- 444 Ardolino F., Parrillo F., Arena U. 2018. Biowaste-to-biomethane or biowaste-to-energy? An LCA study on
- anaerobic digestion of organic waste. J. Clean. Prod. 174, 462-476.
- 446 https://doi.org/10.1016/j.jclepro.2017.10.320
- 447 Martinez-Sanchez V., Tonini D., Moller F., Astrup T:F. 2016. Life cycle costing of food waste management
- 448 in Denmark: importance of indirect effects. Env. S. Technol. 50, 4513-4523.
- 449 https://doi.org/10.1021/acs.est.5b03536

- 450 Ascher S., Li W., You S. 2020. Life cycle assessment and net present worth analysis of a community-based
- 451 food waste treatment system. Biores. Technol. 305. https://doi.org/10.1016/j.biortech.2020.123076
- 452 Demichelis F., Tommasi T., Deorsola F.A., Marchisio D., Fino D. Effect of inoculum origin and substrate-
- 453 inoculum ratio to enhance the anaerobic digestion of organic fraction municipal solid waste (OFMSW).
- 454 Under review.
- 455 Perry H.R., Green D.W. 2008 Perry's Chemical Engineers' Handbook, McGraw-Hill Education
- 456 Gonzàlez R., Rosa J.G., Blanco D., Smith R., Martinez E.J., Bueis R.P., Gòmez X. 2020. Anaerobic
- 457 digestion of fourth range fruit and vegetable products: comparison of three different scenarios for its
- 458 valorisation by life cycle assessment and life cycle costing. Env.Monit Assess. 192(8):551.
- 459 https://doi.org/10.1007/s10661-020-08521
- 460 Brander, M., Burritt, R. L., & Christ, K. L. 2019. Coupling attributional and consequential life cycle
- 461 assessment : A matter of social responsibility. J. of Cleaner Produ J. Clean. Prod. 215, 514–521.
- 462 https://doi.org/10.1016/j.jclepro.2019.01.066
- 463 Golecha R, Gan J. 2016. Biomass transport cost from field to conversion facility when biomass yield density
- and road network vary with transport radius. Appl. Energy 164:321-331. DOI:
- 465 10.1016/j.apenergy.2015.11.070
- 466 Wang D., he J., Tang Yt, Higgitt D., Robinson D. 2020. Life cycle assessment of municipal solid waste
- 467 management in Notthingam, England: Past and future perspectives. J. Clean. Prod. 251.
- 468 <u>https://doi.org/10.1016/j.jclepro.2019.119636</u>
- 469 Akeberg, C., Zacchi, G. 2000. An economic evaluation of fermentative production of lactic acid from wheat
- 470 flour. Bioresour. Technol 75, 119-126.
- 471 ISPRA, Rapporto Rifiuti urbani. Edizione 2020.
- 472 https://www.isprambiente.gov.it/files2020/pubblicazioni/rapporti/rapportorifiutiurbani_ed-2020_n-331-
- 473 1.pdf. Accessed 1 April 2021
- 474 Demichelis F., Fiore S., Pleissner D., Venus J. 2018. Technical and economic assessment of food waste
- 475 valorization through a biorefinery chain. Ren. Sust. Ene. Rev. 4, pp 38-48.
- 476 <u>https://doi.org/10.1016/j.rser.2018.05.064</u>

- 477 Wingre, A., Galbe, M., Zacchi, G. 2003. Techno-Economic-Evaluation of Producing Ethanol from
- 478 Softwood: Comparison of SSF and SHF and Identification of Bottlenecks. Biotechnol. 19, 1109-1117. DOI
- 479 10.1021/bp0340180
- 480 ISTAT, Retribuzioni e mondo del lavoro. (2020)
- 481 https://www.istat.it/it/archivio/retribuzioni#:~:text=La%20retribuzione%20oraria%20media%20%C3%A8,1
- 482 <u>6%2C2%20per%20gli%20uomini&text=Tipo%20di%20documento%3A,Comunicato%20stampa (Accessed</u>
- 483 2 April 2021)
- 484 Eurostat, Statistiche costo energia. 2021. https://ec.europa.eu/eurostat/statistics-
- 485 <u>explained/index.php?title=Electricity_price_statistics/it&oldid=488327</u> (Accessed 2 April 2021)
- 486 Pleissner D, Qi Q, Gao C, Perez Riveroe C, We C, Lin C, et al. 2016. Valorization of organic residues for the
- 487 production of added value chemicals: A contribution to the bio-based economy. Biochem Eng J 2016;116:3–
- 488 16. DOI 10.1016/j.bej.2015.12.016
- 489 Li Y. Han Y., Zhang Y., Luo W., Li G. 2020. Anaerobic digestion of different agricultural wastes: A techno-
- 490 economic assessment. Bioresour. Technol. 315:123836. DOI 10.1016/j.biortech.2020.123836
- 491 Cremiato, R., Laura, M., Tagliaferri, C., Zaccariello, L., & Lettieri, P. 2018. Environmental impact of
- 492 municipal solid waste management using Life Cycle Assessment : The effect of anaerobic digestion,
- 493 materials recovery and secondary fuels production. Ren. Energy. 1–9.
- 494 https://doi.org/10.1016/j.renene.2017.06.033
- Jin Y., Chen T., Chen X., Yu Z. 2015. Life-cycle assessment of energy consumption and environmental
- 496 impact of an integrated food waste-based biogas plant. Appl. En. 151, 227-236. DOI
- 497 10.1016/j.apenergy.2015.04.058
- 498 Fei X., Jia W., Chen T., Ling Y. 2021. Life-cycle assessment of two food waste disposal processes based on
- 499 anaerobic digestion in China. J. Clean. Prod. 293(8): 126113DOI: 10.1016/j.jclepro.2021.126113
- 500 Adghim, M., Abdallah, M., Saad, S., Shanableh, A., Sartaj, M., & El Mansouri, A. E. Comparative life cycle
- 501 assessment of anaerobic co-digestion for dairy waste management in large-scale farms. J. Clean. Prod.
- 502 (2020), 256, 120320. https://doi.org/10.1016/j.jclepro.2020.120320
- 503 Cristóbal, J., Castellani, V., Manfredi, S., & Sala, S. Prioritizing and optimizing sustainable measures for
- food waste prevention and management. Waste Management 2018 72, 3–16.

- 505 https://doi.org/10.1016/j.wasman.2017.11.007
- Altavilla S., Montagna F. 2015. When costs from being a constraint become a driver for concept generation.
- 507 INTERNATIONAL CONFERENCE ON ENGINEERING DESIGN, ICED15
- 508 Patinvoh, R.J., Osadolor, O.A., Sárvári Horváth, I., Taherzadeh, M.J. 2017. Cost effective dry anaerobic
- digestion in textile bioreactors: experimental and economic evaluation. Bioresour. Technol. 245, 549–559.
- 510 DOI: 10.1016/j.biortech.2017.08.081
- 511 Qian, M., Li, R., Li, J., Wedwitschka, H., Nelles, M., Stinner, W., Zhou, H. 2015. Industrial scale garage-
- 512 type dry fermentation of municipal solid waste to biogas. Bioresour. Technol. 217, 82–89.
- 513 https://doi.org/10.1016/j.biortech.2016.02.076
- Arias A., Feijoo G., Moreira M.T. 2020. What is the best scale for implementing anaerobic digestion
- according to environmental and economic indicators? J.W. Process Eng. 35, 82-89.
- 516 https://doi.org/10.1016/j.biortech.2016.02.076



30th September 2021

Francesca Demichelis,

Phone: +39 011 090 4671; e-mail: <u>francesca.demichelis@polito.it</u> Department of Applied Science and Technology (DISAT), Politecnico di Torino Corso Duca degli Abruzzi 24, 10129 Torino (TO) – Italy

Dear Editor,

We kindly ask you to consider the submission of our manuscript entitled "Life cycle assessment and life cycle costing of advanced anaerobic digestion of organic fraction municipal solid waste" for publication in the **CHEMOSPHERE**, Elsevier.

The present study evaluated environmental sustainability and economic profitability of optimised anaerobic digestion of organic fraction municipal solid waste (OFMSW) supplied by a real OFMSW treatment plant, to produce methane.

The aim of this study is the evaluation of the environmental sustainability by means of Life Cycle Assessment (LCA) and economic profitability through Life Cycle Costing (LCC) of the 18 AD configurations carried out on Organic Fraction Municipal Solid Waste (OFMSW) at three S:I ratios (1:2, 1:1 and 2:1) for three different inoculum incubation times (0, 5 and 10 d). The adopted approach was the eco-efficiency perspective, coming from the combination of technical, environmental (LCA) and economic (LCC) perspectives. We believe that these results can be of great significance to any readership and make a profound resonance on hot topics such as OFMSW valorisation, through anaerobic digestion and biogas production, considering as fundamental pillar the sustainability. LCA and LCC are performed through SimaPro software. Sensitivity analysis is performed both for environmental and economic assessment to prove the robustness of the results.

I declare that this work is linked to a work presented at THESSALONIKI 2021 8th International Conference on Sustainable Solid Waste Management, and it has been selected for the special issue "Recent Advancements in Anaerobic Digestion" of Chemosphere.

Yours sincerely, on behalf of all the authors, Francesca Demichelis Researcher at Politecnico di Torino