

Excitons and light-emission in semiconducting MoSi₂X₄ two-dimensional materials

Original

Excitons and light-emission in semiconducting MoSi₂X₄ two-dimensional materials / Sun, M.I., Re Fiorentin, M., Schwingenschlogl, U., Palumbo, M. - In: NPJ 2D MATERIALS AND APPLICATIONS. - ISSN 2397-7132. - ELETTRONICO. - 6:1(2022). [10.1038/s41699-022-00355-z]

Availability:

This version is available at: 11583/2974212 since: 2024-12-13T12:15:39Z

Publisher:

NATURE

Published

DOI:10.1038/s41699-022-00355-z

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

COMMENTS AND CORRECTIONS

Corrections to “Techno-Economic Optimization of the NbTi DTT Feeders”

DANIELE PLACIDO¹, GIANLUCA DE MARZI², LUIGI MUZZI², (Senior Member, IEEE), AND LAURA SAVOLDI¹, (Member, IEEE)

¹Dipartimento Energia “Galileo Ferraris,” Politecnico di Torino, 10129 Turin, Italy

²Superconductivity Section, FSN Department, ENEA, 00044 Frascati, Italy

Corresponding author: Laura Savoldi (laura.savoldi@polito.it)

In the above article [1], an error in the units of measurement in Fig. 12 was identified. This error does not invalidate the discussion of the article findings and conclusions, as they were put in the form of comparison among different feeders. Fig. 12 with the corrected measurements units is included in this correction document, together with an explanation of the error and a calculation example.

Fig. 12 shows the estimated operating cost per year for the selected feeder configurations. By applying (8), a conversion coefficient was overlooked, leading to an operational cost expressed in M€/y rather than in k€/y as it results from the correct application of (8).

$$C_{power} = e \times \tau \times P_{feeder} \quad (8)$$

As an example, we propose below the evaluation of the operating cost for the A1 configuration of the Jumper feeder, considering a mass flow rate of 5 g/s.

The average power to be removed by the cooling system can be estimated from Fig. 8, and it is approximately 10 W, which, from (7), corresponds to a cryostat power of approximately 3.2 kW. For the jumpers the considered operation time is 180 d/y, equivalent to 4320 h/y. So, applying (8), we get:

$$C_{power, TFA_1} = 0.3 \frac{\text{€}}{\text{kWh}} \times 4320 \frac{\text{h}}{\text{y}} \times 3.2 \text{kW} \cong 4.15 \frac{\text{k€}}{\text{y}}$$




FIGURE 12. Operation cost estimated for the CS3U2 feeder (a), PF61 feeder (b) and TF jumper (c), respectively, reported as a function of the computed minimum temperature margin during the investigated plasma pulse, for different configurations and operating mass flow rate values: circle 2 g/s, square 5 g/s, diamond 10 g/s, respectively. The value of ΔT_{min}^{CS} is also reported (dashed line).

REFERENCES

- [1] D. Placido, G. De Marzi, L. Muzzi, and L. Savoldi, “Techno-economic optimization of the NbTi DTT feeders,” *IEEE Access*, vol. 11, pp. 15144–15152, 2023, doi: 10.1109/ACCESS.2023.3244984.