

Sustainable Pavement Design: LCA perspective & biogenic - A comprehensive analysis of environmental impact in infrastructure construction

Original

Sustainable Pavement Design: LCA perspective & biogenic - A comprehensive analysis of environmental impact in infrastructure construction / Mehraban, RAJAB ALI; Tsantilis, Lucia; Riviera, PIER PAOLO; Santagata, Ezio. - ELETTRONICO. - (2024). (Intervento presentato al convegno 6th International Symposium on Pavement, Roadway, and Bridge Life Cycle Assessment Paving the Way to Sustainability and Bridging the Gaps in Life Cycle Assessment tenutosi a Arlington (VA, USA) nel June 6-8, 2024).

Availability:

This version is available at: 11583/2992920 since: 2024-09-30T09:36:54Z

Publisher:

Virginia Tech Transportation Institute

Published

DOI:

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Sustainable Pavement Design

LCA Perspective & Biogenic: A Comprehensive Analysis of Environmental Impact in Infrastructure Construction


Authors: Eng. Rajab Ali Mehraban, Prof. Lucia Tsantilis, Prof. Pier Paolo Riviera, Prof. Ezio Santagata.

This study examines the environmental impacts of Hot Mix Asphalt (HMA) and Warm Mix Asphalt (WMA), produced at 180 °C at 140 °C, respectively. A Life Cycle Assessment (LCA) was performed with a cradle-to-gate approach. The findings of this study revealed a notable advantage of WMA, with CO₂ equivalent emissions being 14% lower compared to HMA. This stems from a reduced production temperature, which allows a significant enhancement of the environmental sustainability of pavements containing WMA.


Furthermore, the research investigated the environmental implications of integrating biogenic materials (such as biodiesel) into infrastructure construction practices, with the specific purpose of mitigating ecological impacts. By employing the LCA methodology, this study thoroughly evaluates the benefits of employing biodiesel in the plant-production of asphalt mixtures, highlighting substantial reductions in CO₂ equivalent emissions, which were found to be of the order of 50%.

LCA Perspective (HMA & WMA)


Environmental LCA for the production phase of HMA & WMA (SimaPro impact assessment results)




Carbon Footprint (CO₂eq) for the production phase of HMA & WMA (Ecosynergy360 results)



Carbon Footprint (CO₂eq) results for the production of 1 ton of HMA and WMA




Carbon Footprint (CO₂eq) relative results for HMA and WMA production




LCA Carbon-Credit (Biogenic material)

Carbon-Credit calculation for Biodiesel in Wheel-To-Wheel method (g CO₂eq/MJ)




Bio-Credit: CO₂ is released back into the atmosphere when 1 MJ of the fuel is fully combusted. Equivalent to the amount of CO₂ initially captured by the tree during the photosynthesis process (zero net effect).
Source: JRC - JEC WTW report v5

Carbon Footprint (CO₂eq) results for full combustion of different diesel products



Bio-credit for biodiesel DIC (Direct Injection Compression Ignition) with different sources compared to fossil diesel without bio-credit



Source: Adapted from JRC - JEC WTW report v5