

Active thermography for the investigation of corrosion in steel surfaces

Original

Active thermography for the investigation of corrosion in steel surfaces / Marguerite Dugand, Marie; Francesca, Cura; Sesana, Raffaella; Lazzaro, Silvia. - ELETTRONICO. - 1:(2021), pp. 157-157. (The International Conference on Structural Integrity 2021 Madeira (Po) 30 Agosto-2 Settembre).

Availability:

This version is available at: 11583/2972605 since: 2022-10-26T12:06:56Z

Publisher:

The International Conference on Structural Integrity

Published

DOI:

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

CUF Multifield Models for Virtual Manufacturing of Composites

Enrico Zappino¹, Navid Zobeiry², Rebecca Masia¹, Martina Santori¹, Erasmo Carrera¹, Marco Petrolo^{1*}

¹MUL2 Lab, Politecnico di Torino, Italy

²Department of Materials Science and Engineering, University of Washington, Seattle, WA, USA

*marco.petrolo@polito.it

MS number: 1, Integrated Computational Materials Engineering (ICME)

Keywords: CUF, Composites, Curing, Virtual Manufacturing, Process-Induced Defects.

Abstract. This paper uses refined structural theories to predict process-induced defects (PID) in composite parts originating from curing. PID may affect the final shape of composite parts and their mechanical properties [1]; spring-in angles, warpage, and residual stress distributions may arise during the curing process and cause significant time and economic loss. Using numerical models to predict such defects and propose countermeasures is desirable but challenging due to the multifield nature of the thermo-chemo-mechanical phenomena involved in curing [2-4].

The multifield modeling of displacement and stress fields, temperature, and degree of cure is carried out through the Carrera Unified Formulation (CUF) [5] using 1D component-wise structural theories to avoid computationally expensive 3D solid elements. The computational efficiency of the numerical models proposed allows for parametric analysis considering the influence of process parameters – e.g., curing temperatures and time – and structural features – e.g., stacking sequence – on PID. Furthermore, various structural configurations can be considered, including flat and curved parts, spars, and stiffeners.

The results show the capability of the proposed formulation to obtain the complete 3D distribution of displacement, stress, temperature, and degree of cure during the entire process and the possibility of evaluating mitigation strategies, such as using additional layers or unbalanced stacking sequences. Moreover, the possibility of coupling the formulation with machine learning is drawn.

References

- [1] Zappino E., Zobeiry N., Petrolo M., Vaziri R., Carrera E., Poursartip A. Analysis of process-induced deformations and residual stresses in curved composite parts considering transverse shear stress and thickness stretching, (2020), Composite Structures, Vol. 241, DOI: 10.1016/j.compstruct.2020.112057
- [2] Schoenholz C., Zappino E., Petrolo M., Zobeiry N. Efficient analysis of composites manufacturing using multi-fidelity simulation and probabilistic machine learning, (2024), Composites. Part B, Engineering, Vol. 280, 111499,8, DOI: 10.1016/j.compositesb.2024.111499
- [3] Zappino E., Santori M., Masia R., Zobeiry N., Petrolo M. Numerical Analysis of the Impact of Process Parameters on the Residual Stress of a Flat Composite Part, Aerotecnica Missili & Spazio, In Press. DOI: 10.1007/s42496-024-00231-7
- [4] Zappino E., Masia R., Zobeiry N., Petrolo M., & Carrera E. Development of mitigation strategies for process-induced deformations through finite elements, Mechanics of Advanced Materials and Structures, In Press. DOI: 10.1080/15376494.2024.2343326

[5] Scano D., Carrera E., Petrolo M. Use of the 3D Equilibrium Equations in the Free-Edge Analyses for Laminated Structures with the Variable Kinematics Approach, (2024), *Aerotecnica Missili & Spazio*, Vol. 103 (2), pp. 179-195, DOI: 10.1007/s42496-023-00177-2