POLITECNICO DI TORINO
Repository ISTITUZIONALE

Data-Driven Fault Diagnosis for Rotating Industrial Paper-Cutting Machinery

Original
Data-Driven Fault Diagnosis for Rotating Industrial Paper-Cutting Machinery / Viale, L., Daga, A.P., Ronchi, I., Caronia, S.. - In: MACHINES. - ISSN 2075-1702. - 13:8(2025). [10.3390/machines13080688]

Availability:
This version is available at: 11583/3002448 since: 2025-08-18T11:11:11Z

Publisher:
MDPI

Published
DOI:10.3390/machines13080688

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

01 November 2026

machines

MDPI

Article

Data-Driven Fault Diagnosis for Rotating Industrial Paper-Cutting Machinery †

Luca Viale [1,*], Alessandro Paolo Daga [1], Ilaria Ronchi [2] and Salvatore Caronia [2]

[1] Department of Mechanical and Aerospace Engineering, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy; alessandro.daga@polito.it
[2] Tecnau SRL, 10015 Ivrea, Italy; scaronia@tecnau.com (S.C.)
* Correspondence: luca.viale@polito.it
† This paper is a conference extension paper published in Viale, L.; Daga, A.P.; Garibaldi, L.; Caronia, S.; Ronchi, I. Feasibility Study for the Development of a Diagnostic and Prognostic System on a High-Speed Rotating Cutter. In Proceedings of the Advances in Italian Mechanism Science; Quaglia, G., Boschetti, G., Carbone, G., Eds.; Springer Nature: Cham, Switzerland, 2024; pp. 351–359.

Abstract

Machine learning and artificial intelligence have transformed fault detection and maintenance strategies for industrial machinery. This study applies well-established data-driven techniques to a rarely explored industrial application—the condition monitoring of high-precision paper cutting machines—enhancing condition-based maintenance to improve operational efficiency, safety, and cost-effectiveness. A key element of the proposed approach is the integration of an infrared pyrometer into vibration monitoring, utilizing accelerometer data to evaluate the state of health of machinery. Unlike traditional fault detection studies that focus on extreme degradation states, this work successfully identifies subtle deviations from optimal, which even expert technicians struggle to detect. Building on a feasibility study conducted with Tecnau SRL, a comprehensive diagnostic system suitable for industrial deployment is developed. Endurance tests pave the way for continuous monitoring under various operating conditions, enabling real-time industrial diagnostic applications. Multi-scale signal analysis highlights the significance of transient and steady-state phase detection, improving the effectiveness of real-time monitoring strategies. Despite the physical similarity of the classified states, simple time-series statistics combined with machine learning algorithms demonstrate high sensitivity to early-stage deviations, confirming the reliability of the approach. Additionally, a systematic analysis to downgrade acquisition system specifications identifies cost-effective sensor configurations, ensuring the feasibility of industrial implementation.

Keywords: machine diagnostics; condition-based maintenance; vibration monitoring; signal processing; multi-scale analysis; machine learning

check for updates

Academic Editor: Hui Ma

Received: 6 May 2025
Revised: 16 July 2025
Accepted: 25 July 2025
Published: 5 August 2025

Citation: Viale, L.; Daga, A.P.; Ronchi, I.; Caronia, S. Data-Driven Fault Diagnosis for Rotating Industrial Paper-Cutting Machinery. *Machines* **2025**, *13*, 688. https://doi.org/10.3390/machines13080688

Copyright: © 2025 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

1. Introduction

In recent years, artificial intelligence (AI) has significantly impacted various scientific disciplines, including mechanical engineering. In the context of Industry 4.0, the implementation of AI techniques has become essential for enhancing fault monitoring and diagnosis of industrial machinery, offering rapid computation, increased accuracy, and robust performance [1]. These advancements not only improve timely detection of anomalies but also contribute to minimizing downtime and extending machinery lifespan. The integration of advanced machine learning (ML) [2] and deep learning (DL) [3] techniques has driven

progress in this area, particularly in optimizing the safety and reliability of industrial systems. Data-driven approaches enable the identification of patterns that are not easily recognizable through alternative methods, such as model-based ones. One of the most notable advancements is in the field of predictive maintenance, which has evolved rapidly due to the enhanced ability to monitor and forecast the machinery's state of health (SOH). This approach, corresponding to condition-based maintenance (CBM), seeks to enhance operational efficiency, reduce costs, and promote a safer working environment, particularly in technologically advanced and complex industrial settings [4].

In contrast to time-based maintenance (TBM), which entails scheduled preventive maintenance [5], CBM is a strategy focused on detecting abnormalities to reduce unnecessary tasks. This approach involves three essential steps [6]: (1) acquiring relevant data inherent to the system SOH; (2) processing and analyzing this information to gain valuable insights; and finally, (3) making decisions about maintenance tasks. A fundamental element of CBM is vibration monitoring (VM). VM is recognized as a highly effective and widely utilized technique, which employs accelerometers to measure and analyze vibrations produced by machinery during operation [7,8]. VM allows for a comprehensive evaluation of the health status of mechanical systems, thanks to its versatility, reliability, and cost-effectiveness. Indeed, VM guarantees rapid responses to sudden machine changes with respect to other techniques [9]. In addition, accelerometers are not only cost-effective and reliable but also compact and lightweight, allowing for easy integration into machines. Several works in the literature report the industrial applications of VM, highlighting its relevance in the field of CBM of mechanical systems [10–13].

The analysis of accelerometric signals for classifying machinery health conditions is enabled by advanced data processing techniques. Among these, novelty detection (ND) has proven to be a robust method for detecting anomalies. The main goal of ND is to assess a system's dynamic response to identify whether it significantly deviates from a reference condition, enabling the timely detection of abnormal operating conditions. ND operates under the assumption that the system does not encounter significant variations in environmental and operational conditions that could affect its dynamic characteristics. To mitigate the influence of confounding factors or to account for changes in the system, specific methods can be applied to enhance ND [14]. The integration of ND with optimization algorithms, such as heuristic techniques, has shown considerable promise in diagnosing complex machinery, significantly enhancing the formulation of preventive and predictive maintenance strategies [15].

Data-driven methods provide powerful tools to analyze complex systems and generate accurate models. However, the large volumes of data involved entail significant challenges, such as increased computational demands that require considerable resources, and the potential for overfitting, where models may capture irrelevant noise instead of meaningful patterns. In addition, the continuous growth of data generated by modern industrial systems intensifies difficulties related to both data management and analysis [16]. The implementation of robust big data strategies [17] is necessary to effectively manage these complexities. Various techniques, including data extraction, selection, and dimensionality reduction, have been developed to enhance the efficiency and accuracy of data analysis, particularly in machinery condition monitoring [18]. These approaches are crucial for developing effective CBM strategies, which aim to improve operational efficiency and ensure the maximum availability of industrial systems.

In the field of machinery diagnostics and prognostics, the development of data-driven models typically involves several phases to ensure accurate condition monitoring and predictive maintenance [19]. The main stages include (1) data acquisition, (2) data preprocessing, (3) feature extraction and feature selection, and (4) model training and validation.

Within the vast literature on machinery diagnostics and prognostics, specific attention has been given to studies focused on rotating machinery diagnostics and prognostics [20–23].

This research, conducted in partnership with Tecnau SRL [24], aims to create an innovative data-driven diagnostic system suitable for industrial use, both in specific control cycles and for real-time diagnostics during operational conditions, designed for industrial applications and capable of functioning both in specific control cycles and for real-time diagnostics under operational conditions. Unlike traditional approaches, this work does not propose a fundamentally new diagnostic technique; rather, it adapts and integrates well-established methodologies from the literature for a novel industrial application. Notably, a review of the state-of-the-art reveals that studies focused on the adjustment of rotating blades in industrial machinery are remarkably scarce, despite the presence of extensive research on diagnosing other common faults in rotating machinery [25,26], such as bearing faults [27,28], gear wear [29,30], or mass unbalances [31]. Even slight blade misalignment can significantly impact product quality and production efficiency, leading to increased costs. By enabling early and reliable detection of such deviations, our approach provides a cost-effective diagnostic solution for industrial deployment. For this reason, as demonstrated by a leading industry partner, it is essential to identify the state of the rotating blade quickly and reliably, even if only through a binary classification. The two conditions analyzed in this classification—a well-aligned blade and one exhibiting incipient damage—are physically similar and difficult to distinguish, even for expert technicians. Successfully classifying these subtle differences validates the system's sensitivity to early-stage damage, thus addressing a gap in current diagnostic systems. The condition of incipient damage refers to early-stage wear, not complete degradation. Given the high precision required by machinery, even a slight blade misalignment could compromise both product quality and the entire production process. For this reason, the proposed classification approach does not compare the two extreme SOHs of the blade. Instead, it focuses on detecting a critical threshold near the optimal operating condition. To simplify further discussion, the two analyzed conditions will be referred to as *healthy* and *damaged*, following standard practice in diagnostic binary classifications.

The present study builds upon prior work [32], where the feasibility of implementing a diagnostic system was initially evaluated. That preliminary analysis provided a foundation for the proposed development of a diagnostic framework using ML techniques, such as classification. The machine under investigation is part of the "Revolution 50" series, which is used for paper processing and on-demand book production. A previous study focused on a different machine, also produced by the same company, which was designed for similar purposes in the book production phases. Although [33] pursued a similar goal in predictive maintenance, the two systems differ considerably in their approaches to machinery health assessment due to differences in the machines themselves. In this case, the Revolution 50 uses rotating blades mounted on cylinders for cutting, whereas the system in [33] employed a linear impulsive cutting mechanism.

This work focuses on CBM by incorporating temperature sensors (including an infrared pyrometer and thermocouples) alongside the accelerometer-based VM system, with potential integration into a Supervisory Control and Data Acquisition (SCADA) system. In the previous feasibility study, the experimental campaign was set up using Design of Experiments (DOE) techniques [34]. Based on those initial outcomes, data from endurance tests under various operating conditions have now been collected for continuous monitoring. Rather than developing new signal features, this study demonstrates that even simple statistical features, when paired with an optimized classification pipeline, can effectively detect subtle degradation, ensuring industrial feasibility. The performance of these models was evaluated using specific indicators,

and overall, the results demonstrate a high level of accuracy in recognizing the SOH of the machinery. Additionally, the analysis of the diagnostic system's downgrade helped identify the optimal trade-offs between accuracy and cost, ensuring the system's readiness for industrial implementation.

The article is organized as follows. Section 2 provides a detailed description of the machinery under investigation, the data collected, and the complete data acquisition system. Sections 3 and 4, respectively, outline the methodology and present the results. Finally, the conclusions of the study are summarized in Section 5.

2. System and Dataset Description

This section briefly describes the machinery under study, the definition of tests for the condition monitoring of the machinery, and the related choices regarding the proposed diagnostic system in terms of sensors and the acquisition system implemented on the test bench.

2.1. Test Bench

The machinery designed and manufactured by Tecnau SRL (Ivrea, Italy) is part of the "Revolution 50" series, depicted in Figure 1. It features a sophisticated cutting system engineered for integration with high-speed printing systems. This system is primarily equipped with either single or double rotating cutters, providing exceptional performance at elevated operating speeds.



Figure 1. "Revolution 50" series by Tecnau SRL, which contains the machinery under investigation.

The rotating blades are critical components of the machinery, acting as its primary elements. These cylindrical blades permit the cutting of paper rolls into sheets of various sizes, utilizing variable rotational speeds. Each machine is predominantly constructed with two rotating blades and corresponding counter-blades, which undergo periodic impacts during operation. Figure 2 provides a simplified representation of the cutting machine and its key components. Consequently, the analysis focuses on these elements, with the experimental campaign designed to measure the signals generated by the rotation and the impacts of the blades, primarily focusing on transmitted vibrations and temperature.




Figure 2. A qualitative scheme describing the structure and the main elements of the cutting machine.

2.2. Sensors

To enable a comprehensive condition monitoring system, a combination of vibration and temperature sensors was deployed. Vibration measurements were acquired using two PCB 355B03 monoaxial accelerometers (PCB Piezotronics, Inc., Depew, NY, USA) and one PCB 356A16 triaxial accelerometer (PCB Piezotronics, Inc., Depew, NY, USA). With a sensitivity of approximately 100 mV/g and an operational range of $\pm$50 g, these sensors provided precise measurements of the mechanical oscillations occurring during the cutting process. The combination of monoaxial and triaxial configurations allowed for a detailed characterization of the dynamic behavior of the system, enhancing fault detection capabilities. The accelerometers were mounted using cyanoacrylate glue, with a thin insulating layer (e.g., adhesive tape) placed between the sensor and the surface. This approach ensures electrical isolation, reducing noise and interference, while maintaining reliable mechanical coupling.

In addition to vibration monitoring, temperature measurements played a crucial role in assessing the thermal behavior of the system. An Optris CT4M fast temperature sensor (Optris GmbH & Co. KG, Berlin, Germany), a high-speed pyrometer with an exposure time of 90 µs, was implemented to obtain real-time and highly accurate measurements of the blade temperature. Furthermore, three thermocouples were placed at key points on the supporting structure to monitor temperature variations, offering valuable insights into heat dissipation and potential thermal effects on machinery performance. This integrated sensor setup was optimized to ensure high sensitivity to both mechanical and thermal deviations. Importantly, the pyrometer was utilized not solely for temperature acquisition but was also innovatively exploited to infer the angular position and rotational velocity of the blade, effectively removing the necessity for an external encoder. This novel approach simplifies the sensor setup while maintaining high accuracy in assessing the blade operational state. Figure 3 illustrates the positioning of the sensors, which was determined based on the operational characteristics of the machinery. For example, the triaxial accelerometer has been strategically located near the counter-blade to minimize the transmission path from the source of the phenomenon and, consequently, from the critical component being monitored.




Figure 3. Sensor positioning, where TS represents thermocouples, TB is the infrared pyrometer, and M and T represent the uniaxial and the triaxial accelerometers, respectively.

2.3. Data Acquisition

The data acquisition system employed in this study was designed to ensure high-fidelity signal recording and precise synchronization of measurements. A cDAQ-9185 chassis was used as the central unit, housing three NI-9234 modules, each featuring four channels with a maximum sampling frequency of 51.2 kS/s per channel and an input range of ± 5 V, allowing for accurate acquisition of vibration signals from the accelerometers. Additionally, a NI-9203 module with eight current inputs (± 20 mA) was utilized for acquiring signals from the temperature sensors, ensuring reliable monitoring of thermal variations. This setup enabled seamless integration of multiple sensor types, providing a comprehensive dataset for condition monitoring and diagnostic analysis. In order to properly picture the machine dynamics, a sampling frequency of 25.6 kHz was selected. Notably, all sensors have a resonance frequency above 25 kHz to ensure accurate measurement without significant interference from structural resonance, thereby preserving the integrity and reliability of the acquired data across the operating frequency range.

The employed acquisition system is characterized by a significant cost attributed to its ability to ensure high precision. One of the objectives in developing a diagnostic system is to reduce expenses, making it more suitable for industrial applications. To achieve this, a systematic downgrade of the system has been explored to decrease sensor specifications and find an optimal cost–performance trade-off.

2.4. Dataset Description

The dataset used in this study was acquired through a series of controlled tests designed to evaluate the SOH of a high-speed industrial rotating blade under varying operational conditions. These experiments, involving the definition of a healthy and damaged state, were carefully planned at the DOE stage.

A damaged condition refers to a state of the blade that is not normal, which leads to reduced cutting performance. Such a state can both refer to a slight degradation of the blade edge or to a non-optimal blade mounting. Indeed, blade adjustment is an intricate process that necessitates the expertise of highly skilled technicians. This condition, which can be considered as incipient damage, is then physically barely recognizable, but ultimately leads

to poorer paper cutting, conditions which should be detected and avoided by the herein proposed diagnostic system.

Obviously, several confounding factors may affect the measurements, such as the rotational speed of the blades, the type of processed paper, the room temperature, the machine temperature and gradients, and the single or simultaneous activation of the blades (two pairs, as visible in Figure 2).

To limit the influence of these parameters and foster the diagnostic process, the incipient damaged condition was simulated by an expert Tecnau technician introducing a slight blade mis-adjustment, and a standard test cycle was defined for the measurements. This mistuning is not visually detectable nor easily quantifiable; however, it is highly repeatable when induced by rotating the tuning screws by a predetermined amount. This adjustment, defined by Tecnau based on their expertise and referenced from the ideal setting, is intended to simulate the effects of wear conditions. It was selected to (a) focus on one pair of blades alone, which is one blade and one counter-blade, (b) keep a constant rotational speed, (c) run the machine without paper, and (d) assume the room temperature to be constant. The repeatability of these parameters and of the blade adjustments was likely to be a crucial aspect of the study. Given such consideration, the sequence of tests was carefully organized to minimize the need for blade disassembly, thereby ensuring that comparisons between different conditions are both feasible and repeatable.

Two datasets were ultimately collected. The first was intended for an exploratory preliminary analysis aimed at characterizing the dynamic and thermal behavior of the machine. Given that dynamic and thermal responses occur on distinct time scales, a multi-scale analysis was necessary to properly capture the dual nature of the system behavior. Due to the slow evolution of thermal transients, endurance tests were conducted—one with a healthy blade and one with a damaged blade—lasting until steady-state conditions were reached. These tests enabled the assessment of both transient and steady-state phases. The following fine-scale classification results are based on 800 samples, evenly split between blades in healthy and damaged states (50% each). Each sample comprises a set of features extracted from a single cutting cycle, recorded at a sampling rate of 25.6 kHz. The environmental conditions during the two test sessions (for healthy and damaged blades, respectively) were highly comparable, as the tests were conducted on consecutive days. If environmental variations were present, temperature decorrelation methods could be applied (see temperature decorrelation in the Conclusions section); however, once thermal steady-state is achieved, such differences are expected to have minimal impact.

Following this initial analysis, and once the sensor layout was finalized, as illustrated in Figure 3, a second dataset was acquired using the same measurement protocol as the first, but on a different day and under potentially different environmental conditions. Unlike the first dataset, the second acquisition focused mainly on the dynamic response of the blade–machine system and on damage detection, which both require higher temporal resolution and thus a micro-scale analysis. Given that the transient and steady-state phases had already been identified, the duration of the second acquisition was reduced accordingly to minimize data volume while preserving the most informative portions of the machine operational behavior.

In summary, endurance tests were planned and executed to develop the diagnostic system as the operating conditions (such as the absolute temperature and the temperature gradients of the machine) vary. Indeed, endurance tests allow the analysis of both transient and steady-state conditions.

3. Methodology

In [32], a preliminary study was conducted to analyze and understand the behavior of the machinery. Starting from those findings, this work aims to develop a diagnostic system suitable for industrial applications. This section begins by outlining the multi-scale analysis employed for feature extraction. The diagnostic system incorporates ML algorithms; thus, the methodology of the classification process is thoroughly detailed. Lastly, to ensure the system implementation within an industrial context, a comprehensive analysis of system performance downgrade is conducted, focusing on the impact of reduced sampling frequency and the quantity of sensors. Finally, based on the outcomes of the analysis, a possible temperature decorrelation strategy is proposed to enhance classification accuracy.

The proposed methodology is summarized in the block diagram presented in Figure 4, which outlines the structured sequence of operations of the study phase to develop a reliable and industrializable diagnostic system. This includes key steps such as multi-scale analysis and signal downgrade. These steps demonstrate the methodological flexibility and adaptability of the framework, which can be generalized and extended to other machinery with appropriate modifications and tuning. The final diagnostic system, streamlined for real-world applications, is depicted in Figure 13.




Figure 4. A block diagram representing the proposed methodology.

3.1. Feature Extraction

In the field of machinery fault detection, a correlation between specific symptoms observed in vibration signals and the presence of damage is assumed by identifying underlying patterns within the data. However, raw vibration signals usually represent the contribution of complex effects and noise. The process of extracting and selecting features is fundamental for ensuring accurate damage detection. Indeed, a feature is defined as a measurable characteristic derived from raw signals, which should consistently correlate with the level of damage.

In the present work, the most used features were extracted from the signals. Most of them were statistical moments, and they are reported in the following list for the sake of completeness:

- **Mean value:**

$$MEAN = \frac{\sum_{k=1}^{N} y(t_k)}{N} \tag{1}$$

- **Variance:**

$$VAR = E\left[\left(\frac{y(t_k) - \overline{y}(t_k)}{\sigma_y}\right)^2\right] \tag{2}$$

- **Skewness:**

$$SKEW = E\left[\left(\frac{y(t_k) - \overline{y}(t_k)}{\sigma_y}\right)^3\right] \tag{3}$$

- **Kurtosis:**

$$KURT = E\left[\left(\frac{y(t_k) - \overline{y}(t_k)}{\sigma_y}\right)^4\right] \tag{4}$$

- **Positive peak:**

$$PEAK^+ = \max(y(t_k)) \tag{5}$$

- **Negative peak:**

$$PEAK^- = \min(y(t_k)) \tag{6}$$

where $y(t_k)$ represents the acceleration signal as a quantity discretized during the acquisition process, and N is the number of samples, which defines the multi-scale time window. The feature extraction procedure is identical across all scales; however, the difference lies in the length of the time window used for analysis. Specifically, in the macro-scale analysis, features were extracted over fixed 60 s windows to capture long-term thermal and dynamic behavior. In contrast, the micro-scale feature extraction was guided by the infrared pyrometer signal, which monitored the temperature of the rotating blade. For the latter scale, features related to the accelerometer signals were computed over time intervals corresponding to a single full rotation of the blade. While the exact rotational speed is confidential and, therefore, the precise time window cannot be disclosed, it is worth noting that the micro-scale windows are several orders of magnitude shorter than the macro-scale ones.

The mean and standard deviation were computed for each of the four temperature channels, while variance, skewness, kurtosis, and positive/negative peaks were calculated for each acceleration signal. In total, 33 features were extracted, but only the 25 acceleration-related features were utilized for the classification process due to the encouraging results observed in the preliminary vibration monitoring analysis (temperature features were dropped). These latter features were converted into z-scores to standardize the magnitude orders recorded by the different channels. As a preliminary analysis, simple time-domain features were selected due to their suitability for real-time computation [35]. More complex features were not explored at this stage, given the satisfactory performance achieved with the current feature set (see Section 4.3).

3.2. Multi-Scale Analysis

To understand the functioning of the machinery and how its operational conditions vary throughout a working cycle, endurance tests with extended duration were performed. Due to the substantial amount of data to analyze, a multi-scale approach was implemented to reduce the computational burden. In this study, multi-scale analysis refers to examining the cutter system at different temporal resolutions, enabling the detection of both short-term fluctuations and long-term trends. Specifically, temporal multi-scale analysis is an approach that decomposes a signal or phenomenon into various time scales to study its characteristics at different levels. This method is particularly useful for analyzing complex systems or signals containing information distributed across multiple time scales. An example of applying multi-scale analysis in bearing defect diagnostics is provided by Wu et al. in [36].

3.2.1. Coarse Scale Analysis

The initial focus was placed on the macro-scale, which provides a high-level understanding of the overall behavior of the machinery. At the macro-scale, features were extracted using coarse time intervals, with the mean and standard deviation calculated over a 60 s time window. This approach enabled the identification of temperature trends, which

evolve gradually and are more apparent at longer time scales. The macro-scale analysis provides insights into the general behavior of the machine, including identifying transient and steady-state phases, and reduces the volume of data requiring further analysis. The first operational phase covers the machine's activation and the initial transient stage, while the second phase represents the steady-state conditions, which occur after several hours of operation. As a result, the subsequent micro-scale analysis can concentrate on a smaller, more specific subset of the data, allowing for direct comparisons under equivalent conditions.

3.2.2. Fine Scale Analysis

Following the coarse-scale evaluation, the analysis was refined to a micro-scale perspective to investigate the dynamic behavior of the system with greater temporal resolution. While the macro-scale provided insights into broad thermal and operational trends, the micro-scale focuses on the mechanical dynamics of the system. Specifically, this analysis focuses on short time windows corresponding to a single full rotation of the blade, allowing for the detection of subtle dynamic variations that may indicate incipient faults. Features extracted at this finer time scale will be used to classify and assess the SOH of the machine.

A key novelty of this approach lies in the dual use of the infrared pyrometer not only for thermal monitoring but also to infer the blade rotational speed, effectively serving as a virtual encoder. This enabled the segmentation of vibration data into rotation-synchronized intervals without requiring additional hardware. Figure 5 illustrates the temperature trend recorded by the pyrometer, clearly distinguishing between the blade and the rotating cylindrical body. The micro-scale analysis applies the same feature extraction methodology used at the macro scale—namely, the computation of statistical descriptors such as mean and standard deviation—but over significantly shorter windows. The temporal window depends on the rotation speed of the blade, and it is generally several orders of magnitude smaller than the time window used in the macro-scale analysis.




Figure 5. An example of a temperature signal acquired by the pyrometer (raw signal in yellow, smoothed signal in black) to highlight the blade rotation and the micro-scale time window.

The micro-scale analysis targets subtle variations in the mechanical behavior of the system, as captured by the high-frequency accelerometer signals. Therefore, it is crucial to extract acceleration features at this scale in order to detect potential differences caused by the SOH of the blade. The extracted features were standardized as z-scores with respect to the ideal blade condition for the sake of a fair comparison. This process involved calculating the mean and standard deviation of the features corresponding to the ideal state, using data from the endurance test conducted under consistent operating conditions.

3.3. Classification

The multi-scale analysis was designed to exploit the complementary nature of coarse and fine temporal resolutions. At the macro-scale, the focus was on capturing slow thermal dynamics and identifying broader operational phases—such as transient behavior and steady-state conditions—across the endurance tests. This provided contextual insight into the system overall behavior. Conversely, the micro-scale analysis targeted the fast mechanical dynamics of the blade–machine interaction by extracting features over time intervals corresponding to a single blade rotation. This level of resolution was essential for capturing subtle vibrational patterns indicative of early-stage degradation. Based on the outcomes of the multi-scale analysis, classification algorithms were then implemented to distinguish between healthy and damaged blade conditions during both transient and steady-state phases. Notably, the classification relied exclusively on micro-scale features, which are better suited for real-time fault detection due to their high sensitivity to rapid mechanical changes and their compatibility with online monitoring frameworks.

The inputs to the classifiers consist of five features (variance, skewness, kurtosis, positive, and negative peaks) computed for each of the five accelerometric channels, resulting in a total of 25 features. Features related to temperature measurements were excluded from this stage, particularly as the results of the preliminary analysis were promising. Before analyzing the performance of different types of classifiers, the features were standardized as z-scores with respect to the ideal blade conditions. To evaluate the performance of the proposed method across different algorithm types, five of the most widely used supervised (and semi-supervised) machine learning algorithms were applied: Linear Discriminant Analysis (LDA), k-Nearest Neighbor (kNN) with k = 10, Decision Trees (DTs), Linear Support Vector Machine (SVM), and Gaussian Naive Bayes (GNB).

To build a classification model, it is essential to have both a training dataset and a separate dataset for validation. The selection of these datasets can be conducted in various ways. One common approach is k-fold Cross-Validation (CV), which involves partitioning the data into k groups. In each iteration, one group is designated as the validation dataset, while the remaining $k-1$ groups serve as the training dataset. This process is repeated k times (with k = 5 in this study) to ensure that each group is used for validation once. For a general CV, varying data splits can lead to differences in model generation and accuracy outcomes. To mitigate this variability and obtain more reliable performance metrics, Monte Carlo Cross-Validation (MCCV) [37] was utilized, as described in [38].

MCCV is a robust method that involves random partitioning of the samples into training and validation sets, followed by repeated execution of this process over N = 50 iterations. This approach significantly reduces computational complexity while ensuring that the average accuracy converges toward the theoretical value of the model. As the number of iterations N increases, the performance metrics derived from MCCV tend to stabilize and become more reliable.

The performance of the proposed method is evaluated using some selected comparative indices. While this is not a multi-class application—only two conditions, healthy and damaged, are analyzed—multiple performance indices are examined to provide a comprehensive evaluation of the diagnostic system. The following indices are introduced to measure the effectiveness of the methods:

- **Accuracy:**

$$Acc = \frac{True\ Positive + True\ Negative}{Total\ Cases} \tag{7}$$

- **Missed Alarms:**

$$M.A. = \frac{False\ Negative}{Total\ Cases} \tag{8}$$

- **False Alarms:**

$$F.A. = \frac{False\ Positive}{Total\ Cases} \tag{9}$$

- **AUC**: the area under the Receiver Operating Characteristic (ROC) curve. The AUC offers an aggregate measure of performance across all possible classification thresholds.

In this initial phase, lightweight classification methods were intentionally selected to ensure computational efficiency and facilitate real-time implementation. The use of more complex models, such as deep learning approaches, was not pursued due to the limited size of the available dataset. Deep learning models, including neural networks, typically require large amounts of training data, which were not available in this study. Given the satisfactory performance achieved with simpler methods, more advanced techniques were not considered necessary at this stage.

3.4. Downgrade

In view of industrial implementation, it is essential to assess the robustness of the proposed diagnostic framework when subject to hardware constraints, which are the reductions in sampling frequency and the number of acquisition channels (and consequently, sensors). The aim is to evaluate the impact of these downgrades on classification performance, identifying sensor configurations that strike an optimal trade-off between diagnostic accuracy and cost-efficiency. This approach promotes the development of a simplified, low-cost diagnostic system without compromising reliability, paving the way for large-scale deployment in production environments. In the following subsections, the effects of these two downgrade types—sampling frequency and sensor quantity—are analyzed separately. This approach will enable drawing the necessary conclusions to define and establish a new setup for a diagnostic system ready for industrialization.

3.4.1. Sampling Frequency Downgrade

The acquired data recordings were resampled at new sampling frequencies, $\frac{f_s}{r}$, where f_s = 25.6 kHz (i.e., the sampling frequency used during the experimental phase) and r is a reduction factor defined by the following values, r = 2, 4, 6, 8, 10, 20, 40, 60, 80, 100. The results presented below refer to these fractions of f_s, representing a decimation of the recorded values by a factor of $1/r$. The decrease in sample rate by the integer factor r was performed using the MATLAB R2023a command *decimate*, which uses an 8th-order Chebyshev Type I lowpass Infinite Impulse Response (IIR) filter to prevent aliasing. It is important to note that, at this stage, all accelerometric channels ($M1$, $M2$, Tx, Ty, Tz) were still considered.

3.4.2. Sensors Downgrade

After analyzing the downgrade in terms of sampling frequency, a further reduction in the number of channels, and consequently sensors, was implemented. In addition to maintaining the reduction by a factor r in sampling frequency, a reduction in the number of channels was introduced, starting from the five currently used ($M1$, $M2$, Tx, Ty, Tz). Specifically, two reductions were analyzed. The first considered only the triaxial accelerometer channels Tx, Ty, and Tz, eliminating all uniaxial sensors. The second reduction further decreased the number of channels, selecting only the Ty channel. This channel was presumed to be the most relevant due to its positioning and orientation.

4. Results

To evaluate the performance of the proposed diagnostic methodology, the results are presented following the same structure as the methodology: beginning with the macro-scale analysis, followed by the micro-scale used for the classification, and finally the system downgrade study. This structured approach ensures clarity and allows each level of analysis to build upon the insights gained in the previous phase.

4.1. Coarse-Scale Preliminary Analysis

In the macro-scale analysis, features were extracted over coarse time windows—specifically 60 s intervals—allowing the detection of slow-evolving trends in the system's physical behavior. This approach helps capture the overall trends in the recorded physical quantities and to identify specific segments for closer examination. Systems, such as the one studied here, often display behaviors or properties that change noticeably across different time scales, such as during the shift from a transient phase to steady-state conditions, making this method particularly useful. The macro-scale analysis employed temperature-related features, which evolve gradually and become more evident over longer time scales, to identify and compare the operational conditions and evaluate the validity of comparisons among them. Figures 6 and 7 present the outcomes of this analysis. Specifically, Figure 6 presents the trends of the average temperatures recorded each minute, along with their standard deviations in healthy conditions. Overall, tests conducted with the healthy blade exhibited higher levels of overheating in the machinery. This observation can be attributed to the well-adjusted blade, which is designed to generate more friction against the counter-blade to achieve a more efficient paper cut. Consequently, this increased friction leads to greater heat generation and, in turn, results in enhanced overheating of the machine.




Figure 6. Temperature trends extracted by the endurance tests analyzed in the preliminary analysis on the macro-scale. The lashed lines represent the mean value, while the continuous lines represent the standard deviation, ±σ.

The macro-scale results reveal a consistent ascending trend in temperature for all sensors, attributable to the operation of the machinery. Sensors TS2 and TS3 display similar curves due to their symmetrical positioning, although sensor TS2 records lower temperatures, which may be influenced by varying environmental and operational factors. Additionally, it is worth noting that the standard deviation values recorded by the pyrometer (which measures the blade temperature) increase as the test continues, suggesting that

the blade temperature rises significantly more than that of its cylindrical body, leading to a greater temperature gradient. Finally, an analysis of the slopes of the four temperature curves suggests that the primary heat source is located near the lateral sensors, which exhibit a more rapid temperature increase. In contrast, the average temperatures recorded by the pyrometer (monitoring the rotating blade) and sensor TS1 rise more gradually, indicating a delayed thermal response in those areas.




Figure 7. Acceleration trends extracted by the endurance tests analyzed in the preliminary analysis on the macro-scale.

Figure 7 illustrates the trend of standard deviations throughout the endurance test. Mean values are not displayed since the mean values of accelerations are expected to be zero, given that accelerometers do not experience displacement. As shown, all sensors exhibit a decreasing trend, reaching a minimum or knee point at different times. This behavior is closely correlated with the previously observed temperature profile and directly depends on it. The anisotropic thermal deformations of the machinery induce variations in its dynamic response during the operational phase. Specifically, the observed trend shows that the machinery vibrational energy decreases during the transient phase until it stabilizes under near-steady-state conditions.

4.2. Fine-Scale Analysis and Classification

Building on the insights from the macro-scale analysis—particularly the identification of transient and steady-state phases—the subsequent multi-scale analysis allowed for the extraction of dynamic features essential for real-time fault detection. These extracted features laid the groundwork for the subsequent classification process, enabling a more subtle understanding of the machine's SOH.

Figure 8 illustrates comparisons of the extracted features on the micro-scale to highlight the differences due to the SOH of the blade. For the sake of conciseness, only the comparisons from the initial transient phase are presented, and the mean values are omitted since they are theoretically null and not relevant for identifying blade conditions. Upon visual inspection, the charts reveal a clear and objective distinction in the distributions of the features corresponding to the two machine SOH, suggesting that the features hold significant potential for accurate classification. A true statistical testing of the class separability was then avoided, and classification was directly implemented. Notice that classifiers like Linear Discriminant Analysis (LDA) are actually closely related to Fisher class separability scores, as LDA generalizes the concept of the Fisher score to multiple dimensions (features). For the sake of completeness, LDA projection vector weights are shown in Figure 9 to

show which features and sensor channels contribute most to linear classification. As LDA shows good results in classification (see Table 1), this can be considered valid proof of class separability in the original space, under linear assumptions.




Figure 8. A comparison of the micro-scale features extracted from the transient phase to highlight the differences between the two SOHs of the blade (Samples n. 1–800: healthy blade; samples n. 801–1600: damaged blade).




Figure 9. LDA projection vector weights averaged across the MCCV iterations.

Table 1. Performance indices for different classification algorithms inherent to the transient phase of the machinery after the downgrade of the sampling frequency by a factor of $r = 40$ and considering all the accelerometric channels.

Index	LDA	KNN	DT	SVM	GNB
Accuracy	98.2%	99.1%	98.3%	99.1%	97.1%
Missed Alarms	0.0%	0.0%	1.0%	0.4%	1.8%
False Alarms	1.8%	0.8%	0.8%	0.5%	1.2%
AUC	1.00	1.00	1.00	1.00	0.99

The classification process was then applied to the features extracted from both the transient and steady-state phases. The results from the transient operational phase were highly successful, with 100% accuracy achieved by all classifiers, except for GNB, which achieved 99.6% accuracy. However, for the steady-state phase, a slight decrease in accuracy was observed, ranging from 95.9% to 99.8%. This decrease can be attributed to the multidimensional feature space in steady-state conditions, where the paths of data points representing different endurance tests begin to overlap, making the separation between conditions more difficult. As an example, Figure 10 illustrates the feature points in a 2D projection (variance of sensors $M1$ and $M2$, respectively) of the multivariate space. It demonstrates how the paths during the machinery steady-state phase for both healthy and damaged blades intersect in certain regions. As a result, the classifiers have difficulty accurately distinguishing the class of features located in these regions, leading to a slight reduction in accuracy.




Figure 10. Trends (highlighted by yellow arrows) of the features within a 2D subspace (generated by $M1$ and $M2$ variances, here Feature #1 and Feature #2, respectively) during the endurance tests with healthy (blue) and damaged (red) blades.

4.3. Downgrade Analysis

Given the excellent recognition of blade regulation conditions achieved by all types of classifiers, the analysis can proceed with the study of system downgrades. For brevity, the results related to the transient phase of the machinery will be presented.

4.3.1. Sampling Frequency Downgrade

After applying the a posteriori resampling based on the proposed method, the MCCV technique was repeated to derive the performance indices of the different classifiers. As shown in Figure 11, all indices appear to experience slight performance declines as the reduction factor r increases (i.e., as the simulated sampling frequency decreases), until

reaching a plateau around $r = 80$. Based on these results, it may be feasible to reduce the sampling frequency to 640 Hz (corresponding to $r = 40$), as this would provide an optimal trade-off between downgrade and performance. Furthermore, in this case, there would be no need to modify the feature extraction method, as with $r = 40$, the window length would still contain a statistically significant number of samples.




Figure 11. The trend of performance indices as the reduction factor r increases (i.e., as the simulated sampling frequency decreases), considering all 5 accelerometric channels.

Table 1 presents the performance indices obtained after downgrading the sampling frequency by a factor $r = 40$. Comparing these results with those without downgrading, it can be observed that the classifier performances remain excellent despite the reduction in information, and they allow for accurate recognition of the blade condition.

4.3.2. Sensors Downgrade

This subsection explores the impact of reducing the number of sensors in the diagnostic system. Two different conditions are analyzed: the first condition considers the full triaxial accelerometer setup, utilizing all three channels, while the second condition evaluates the performance using only a single channel, simulating the use of a simpler uniaxial accelerometer, which could be more suitable for industrial applications. This comparison aims to assess the trade-off between sensor complexity, costs, and diagnostic accuracy, providing valuable insights for potential industrial implementation. For the sake of brevity, Figure 12 presents the results obtained by reducing the channels to *Ty* only, while Tables 2 and 3 show the performance indices for both cases analyzed.

The results show that it is possible to achieve accuracy values consistently above 90% by using at least one channel (e.g., *Ty*) and reducing the sampling frequency to $f_s = 640$ Hz. This could represent a good cost–performance trade-off for the diagnostic system and the new sensor technology to be selected for industrialization. It is worth noting that, since downsampling was performed using appropriate filters to prevent aliasing, the obtained result indicates that the most relevant diagnostic information related to the correct adjustment of the blade is primarily contained within the identified frequency range.




Figure 12. The trend of performance indices as the reduction factor r increases (i.e., as the simulated sampling frequency decreases), considering only the *Ty* channel.

Table 2. Performance indices for different classification algorithms inherent to the transient phase of the machinery after the downgrade of the sampling frequency by a factor of $r = 40$ and considering only the *Tx*, *Ty*, and *Tz* channels.

Index	LDA	kNN	DT	SVM	GNB
Accuracy	98.1%	98.7%	98.1%	99.1%	96.1%
Missed Alarms	0.0%	0.1%	0.9%	0.3%	2.5%
False Alarms	1.9%	1.2%	1.0%	0.6%	1.4%
AUC	1.00	1.00	1.00	1.00	0.99

Table 3. Performance indices for different classification algorithms inherent to the transient phase of the machinery after the downgrade of the sampling frequency by a factor of $r = 40$ and considering only the *Ty* channel.

	LDA	kNN	DT	SVM	GNB
Accuracy	95.8%	98.3%	97.4%	98.2%	89.4%
Missed Alarms	0.3%	0.7%	1.3%	0.6%	3.8%
False Alarms	3.9%	1.0%	1.3%	1.2%	6.8%
AUC	1.00	1.00	1.00	1.00	0.97

This analysis can be extended to steady-state data to investigate the real-time recognition of blade regulation (during the machine operation) or further explore and integrate blade wear detection. However, the company did not pursue this type of analysis, as even minor blade damage significantly affects product quality. Consequently, damage must be detected immediately at machine start-up, without waiting for steady-state conditions to be established.

To conclude, Figure 13 shows the block diagram of the final diagnostic system, optimized for industrial implementation. Unlike the extended methodology illustrated in Figure 4, the final system omits certain phases—such as the multi-scale analysis and down-

grade procedures—that were essential during the development but not required in the industrial environment. This streamlined design highlights the practical feasibility of the solution while confirming the broader applicability of the proposed method to different types of machinery, provided that the preliminary phase is tailored accordingly.




Figure 13. A block diagram showing the finalized structure of the diagnostic system designed for industrial deployment.

5. Conclusions

This study presented a comprehensive approach to assessing the health conditions of industrial machinery by combining endurance testing with a multi-scale analysis to observe the overall trends in the recorded signals, gain insights into the mechanical behavior of the machinery, and identify the most critical phases for analysis. Focus was placed on both the transient and steady-state conditions to assess the accuracy of recognizing blade conditions during different operational phases of the machinery. Initially, damage detection was established through a preliminary cycle when the machinery starts from a standstill. Conversely, the steady-state phase demonstrated the feasibility of a real-time monitoring strategy.

The aim of the present work is not to propose a novel diagnostic technique but rather to adapt and combine well-established methodologies from the literature (e.g., novelty detection, signal processing techniques, and feature extraction) for the specific application. The obtained results suggest that the development of a diagnostic and prognostic system could effectively identify the health conditions of the analyzed machinery. The proposed method enabled a 100% accurate classification of the blade condition, utilizing the maximum amount of measured information. The study of the system downgrade demonstrates that satisfactory accuracy levels can be achieved while reducing the specifications of the employed acquisition system. Indeed, by reducing the number of sensors used and simulating a lower sampling frequency, it was still possible to achieve accuracy values ranging from 96% to 99% on average for most classifiers. Identifying the optimal trade-off between the performance of the diagnostic system and its costs has led to the definition of a scalable system, suitable for industrial applications [39]. Clearly, while the total cost of implementing the diagnostic system largely depends on the type and number of sensors employed [40], further optimization may be needed in data acquisition and processing to enable real-time analysis. Nevertheless, the use of simple features and well-established classification algorithms is expected to keep implementation costs relatively low, virtually negligible compared to the overall cost of the machine.

To enhance diagnostic accuracy across all operating conditions, temperature data, previously unused, could help align current measurements with similar conditions in the training set. While building a comprehensive temperature-based dataset would be complex and potentially cost-ineffective given already high accuracy levels, temperature information might still be useful. Specifically, it could be used with PCA to remove temperature-related trends and transients from accelerometer signals, improving the consistency of blade damage detection.

Despite the positive results, this work can be extended by exploring additional aspects and further improving the accuracy of the diagnostic system. For example, studying the decorrelation of temperature-dependent effects could be incorporated into the data

preprocessing phase to reduce confounding effects and, consequently, enhance classification outcomes. Additionally, recognizing blade regulation in real-time during the machine operation could be a valuable direction for further development, along with deepening and integrating the detection of blade wear. However, accurately identifying the blade wear would require significantly more data to develop a multi-level—or ideally, a continuous—classification. Finally, since the data used in this study were acquired from a single machine, it would be valuable to expand the analysis to a larger population of machines to generalize the model and explore different configurations and additional parameters, such as in a real industrial environment. The proposed system, if integrated into actual production, could help establish the huge database necessary for such an analysis.

Author Contributions: Conceptualization, L.V., A.P.D., I.R. and S.C.; methodology, L.V. and A.P.D.; software, L.V. and A.P.D.; validation, L.V. and A.P.D.; formal analysis, L.V. and A.P.D.; investigation, L.V., A.P.D., I.R. and S.C.; resources, L.V., A.P.D., I.R. and S.C.; data curation, L.V., A.P.D., I.R. and S.C.; writing—original draft preparation, L.V. and A.P.D.; writing—review and editing, L.V., A.P.D., I.R. and S.C.; visualization, L.V. and A.P.D.; supervision, A.P.D. and S.C.; project administration, A.P.D. and S.C.; All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Data Availability Statement: Restrictions apply to the availability of these data. Data were obtained from Tecnau SRL and are not available.

Acknowledgments: The authors sincerely express their gratitude to Tecnau SRL for their collaboration and for providing access to their machinery, which made the experimentation and data collection possible. Their support was essential to the success of this work.

Conflicts of Interest: Authors I.R. and S.C. were employed by the company Tecnau SRL This study was developed as part of a research collaboration between Tecnau srl and Politecnico di Torino, funded under the "IR2—Industrializzazione dei Risultati della Ricerca" program, part of the Regional Operational Program "Competitività regionale e occupazione" F.E.S.R. 2014/2020. The funding and institutional partnership facilitated the research activities but had no influence on the study design, data collection and analysis, interpretation of the results, or the decision to publish. The authors declare that there are no additional commercial or financial relationships that could be construed as a potential conflict of interest.

Abbreviations

AI	Artificial Intelligence
AUC	Area Under the Curve
CBM	Condition-Based Maintenance
CV	Cross-Validation
DL	Deep Learning
DOE	Design of Experiments
DT	Decision Tree
GNB	Gaussian Naive Bayes
IIR	Infinite Impulse Response
kNN	k-Nearest Neighbor
LDA	Linear Discriminant Analysis
MCCV	Monte Carlo Cross-Validation
ML	Machine Learning
ND	Novelty Detection
PCA	Principal Component Analysis
ROC	Receiver Operating Characteristic
SCADA	Supervisory Control And Data Acquisition
SOH	State of Health

SVM	Support Vector Machine
TBM	Time-Based Maintenance
VM	Vibration Monitoring

References

1. Singh, V.; Gangsar, P.; Porwal, R.; Atulkar, A. Artificial Intelligence Application in Fault Diagnostics of Rotating Industrial Machines: A State-of-the-Art Review. *J. Intell. Manuf.* **2023**, *34*, 931–960. [CrossRef]
2. Surucu, O.; Gadsden, S.A.; Yawney, J. Condition Monitoring Using Machine Learning: A Review of Theory, Applications, and Recent Advances. *Expert Syst. Appl.* **2023**, *221*, 119738. [CrossRef]
3. Matania, O.; Dattner, I.; Bortman, J.; Kenett, R.S.; Parmet, Y. A Systematic Literature Review of Deep Learning for Vibration-Based Fault Diagnosis of Critical Rotating Machinery: Limitations and Challenges. *J. Sound Vib.* **2024**, *590*, 118562. [CrossRef]
4. Quatrini, E.; Costantino, F.; Di Gravio, G.; Patriarca, R. Condition-Based Maintenance—An Extensive Literature Review. *Machines* **2020**, *8*, 31. [CrossRef]
5. Peng, Y.; Dong, M.; Zuo, M.J. Current Status of Machine Prognostics in Condition-Based Maintenance: A Review. *Int. J. Adv. Manuf. Technol.* **2010**, *50*, 297–313. [CrossRef]
6. Jardine, A.K.S.; Lin, D.; Banjevic, D. A Review on Machinery Diagnostics and Prognostics Implementing Condition-Based Maintenance. *Mech. Syst. Signal Process.* **2006**, *20*, 1483–1510. [CrossRef]
7. Tiboni, M.; Remino, C.; Bussola, R.; Amici, C. A Review on Vibration-Based Condition Monitoring of Rotating Machinery. *Appl. Sci.* **2022**, *12*, 972. [CrossRef]
8. Randall, R.B. *Vibration-Based Condition Monitoring: Industrial, Automotive and Aerospace Applications*; John Wiley & Sons: Hoboken, NJ, USA, 2021.
9. Daga, A.P.; Garibaldi, L. Machine Vibration Monitoring for Diagnostics through Hypothesis Testing. *Information* **2019**, *10*, 204. [CrossRef]
10. Daga, A.P.; Garibaldi, L.; He, C.; Antoni, J. Key-Phase-Free Blade Tip-Timing for Nonstationary Test Conditions: An Improved Algorithm for the Vibration Monitoring of a SAFRAN Turbomachine from the Surveillance 9 International Conference Contest. *Machines* **2021**, *9*, 235. [CrossRef]
11. Tiboni, M.; Remino, C. Condition Monitoring of Pneumatic Drive Systems Based on the AI Method Feed-Forward Backpropagation Neural Network. *Sensors* **2024**, *24*, 1783. [CrossRef]
12. Zhan, Y.; Makis, V.; Jardine, A.K.S. Adaptive Model for Vibration Monitoring of Rotating Machinery Subject to Random Deterioration. *J. Qual. Maint. Eng.* **2003**, *9*, 351–375. [CrossRef]
13. Pająk, M.; Muślewski, Ł.; Kluczyk, M.; Kolar, D.; Landowski, B.; Kałaczyński, T. Identification of Reliability States of a Ship Engine of the Type Sulzer 6AL20/24. *SAE Int. J. Engines* **2021**, *15*, 527–542. [CrossRef]
14. Sohn, H.; Worden, K.; Farrar, C.R. Novelty Detection under Changing Environmental Conditions. In Proceedings of the SPIE Smart Structures and Materials 2001: Smart Systems for Bridges, Structures, and Highways, Newport Beach, CA, USA, 5–7 March 2001; Volume 4330, pp. 108–118.
15. Viale, L.; Daga, A.P.; Fasana, A.; Garibaldi, L. Dimensionality Reduction Methods of a Clustered Dataset for the Diagnosis of a SCADA-Equipped Complex Machine. *Machines* **2023**, *11*, 36. [CrossRef]
16. Xu, Y.; Sun, Y.; Wan, J.; Liu, X.; Song, Z. Industrial Big Data for Fault Diagnosis: Taxonomy, Review, and Applications. *IEEE Access* **2017**, *5*, 17368–17380. [CrossRef]
17. Daga, A.P.; Fasana, A.; Garibaldi, L.; Marchesiello, S. Big Data Management: A Vibration Monitoring Point of View. In Proceedings of the 2020 IEEE International Workshop on Metrology for Industry 4.0 & IoT, Rome, Italy, 3–5 June 2020; pp. 548–553.
18. Carreira-Perpinán, M.A. *A Review of Dimension Reduction Techniques*; Technical Report CS-96-09; Department of Computer Science, University of Sheffield: Sheffield, UK, 1997; Volume 9, pp. 1–69.
19. Lei, Y.; Jia, F.; Lin, J.; Xing, S.; Ding, S.X. An Intelligent Fault Diagnosis Method Using Unsupervised Feature Learning Towards Mechanical Big Data. *IEEE Trans. Ind. Electron.* **2016**, *63*, 3137–3147. [CrossRef]
20. Chen, J.; Lin, C.; Peng, D.; Ge, H. Fault Diagnosis of Rotating Machinery: A Review and Bibliometric Analysis. *IEEE Access* **2020**, *8*, 224985–225003. [CrossRef]
21. Viale, L.; Daga, A.P.; Fasana, A.; Garibaldi, L. Least Squares Smoothed K-Nearest Neighbors Online Prediction of the Remaining Useful Life of a NASA Turbofan. *Mech. Syst. Signal Process.* **2023**, *190*, 110154. [CrossRef]
22. Wei, Y.; Li, Y.; Xu, M.; Huang, W. A Review of Early Fault Diagnosis Approaches and Their Applications in Rotating Machinery. *Entropy* **2019**, *21*, 409. [CrossRef]
23. Romanssini, M.; de Aguirre, P.C.C.; Compassi-Severo, L.; Girardi, A.G. A Review on Vibration Monitoring Techniques for Predictive Maintenance of Rotating Machinery. *Eng* **2023**, *4*, 1797–1817. [CrossRef]
24. Tecnau SRL. Available online: https://www.tecnau.com/ (accessed on 14 April 2022).
25. Randall, R.B. State of the Art in Monitoring Rotating Machinery—Part 1. *Sound Vib.* **2004**, *38*, 14–21.

26. Randall, R.B. State of the Art in Monitoring Rotating Machinery—Part 2. *Sound Vib.* **2004**, *38*, 10–17.
27. Randall, R.B.; Antoni, J. Rolling Element Bearing Diagnostics—A Tutorial. *Mech. Syst. Signal Process.* **2011**, *25*, 485–520. [CrossRef]
28. Smith, W.A.; Randall, R.B. Rolling Element Bearing Diagnostics Using the Case Western Reserve University Data: A Benchmark Study. *Mech. Syst. Signal Process.* **2015**, *64–65*, 100–131. [CrossRef]
29. Feng, K.; Ji, J.C.; Ni, Q.; Beer, M. A Review of Vibration-Based Gear Wear Monitoring and Prediction Techniques. *Mech. Syst. Signal Process.* **2023**, *182*, 109605. [CrossRef]
30. Kumar, A.; Gandhi, C.P.; Zhou, Y.; Kumar, R.; Xiang, J. Latest Developments in Gear Defect Diagnosis and Prognosis: A Review. *Measurement* **2020**, *158*, 107735. [CrossRef]
31. Edwards, S.; Lees, A.W.; Friswell, M.I. Fault Diagnosis of Rotating Machinery. *Shock Vib. Dig.* **1998**, *30*, 4–13. [CrossRef]
32. Viale, L.; Daga, A.P.; Garibaldi, L.; Caronia, S.; Ronchi, I. Feasibility Study for the Development of a Diagnostic and Prognostic System on a High-Speed Rotating Cutter. In *Advances in Italian Mechanism Science*; Quaglia, G., Boschetti, G., Carbone, G., Eds.; Springer Nature: Cham, Switzerland, 2024; pp. 351–359.
33. Viale, L.; Daga, A.P.; Garibaldi, L.; Caronia, S.; Ronchi, I. Books Trimmer Industrial Machine Knives Diagnosis: A Condition-Based Maintenance Strategy Through Vibration Monitoring via Novelty Detection. In Proceedings of the ASME 2022 International Mechanical Engineering Congress and Exposition, Columbus, OH, USA, 30 October–3 November 2022; American Society of Mechanical Engineers Digital Collection: New York, NY, USA, 2023.
34. Antony, J. *Design of Experiments for Engineers and Scientists*; Elsevier: Amsterdam, The Netherlands, 2014.
35. Praveenkumar, T.; Sabhrish, B.; Saimurugan, M.; Ramachandran, K.I. Pattern Recognition Based On-Line Vibration Monitoring System for Fault Diagnosis of Automobile Gearbox. *Measurement* **2018**, *114*, 233–242. [CrossRef]
36. Wu, S.-D.; Wu, C.-W.; Wu, T.-Y.; Wang, C.-C. Multi-Scale Analysis Based Ball Bearing Defect Diagnostics Using Mahalanobis Distance and Support Vector Machine. *Entropy* **2013**, *15*, 416–433. [CrossRef]
37. Xu, Q.-S.; Liang, Y.-Z. Monte Carlo Cross Validation. *Chemom. Intell. Lab. Syst.* **2001**, *56*, 1–11. [CrossRef]
38. Viale, L.; Daga, A.P.; Fasana, A.; Garibaldi, L. From Novelty Detection to a Genetic Algorithm Optimized Classification for the Diagnosis of a SCADA-Equipped Complex Machine. *Machines* **2022**, *10*, 270. [CrossRef]
39. Zhang, L.; Leach, M.; Bae, Y.; Cui, B.; Bhattacharya, S.; Lee, S.; Im, P.; Adetola, V.; Vrabie, D.; Kuruganti, T. Sensor Impact Evaluation and Verification for Fault Detection and Diagnostics in Building Energy Systems: A Review. *Adv. Appl. Energy* **2021**, *3*, 100055. [CrossRef]
40. Zhang, L.; Leach, M.; Chen, J.; Hu, Y. Sensor Cost-Effectiveness Analysis for Data-Driven Fault Detection and Diagnostics in Commercial Buildings. *Energy* **2023**, *263*, 125577. [CrossRef]

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.