

Effect of Geometric Parameters on the Failure Index of Composite Deployable Booms

Original

Effect of Geometric Parameters on the Failure Index of Composite Deployable Booms / Augello, R., Carrera, E., Latini, F., Petrolo, M.. - (2026). (V International Conference on Mechanics of Advanced Materials and Structures (ICMAMS) Toulouse, France 1-3 July 2026).

Availability:

This version is available at: 11583/3012649 since: 2026-07-03T05:29:46Z

Publisher:

JN Reddy, E. Carrera

Published

DOI:

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Effect of Geometric Parameters on the Failure Index of Composite Deployable Booms

Riccardo Augello^{*,1a}, Erasmo Carrera^{1b}, Francesco Latini^{2c}, Marco Petrolo^{1d}

¹MUL2 lab, Department of Mechanical and Aerospace Engineering, Politecnico di Torino, Italy

²Agenzia Spaziale Italiana, Italy

^{*}riccardo.augello@polito.it, ^berasmo.carrera@polito.it, ^cfrancesco.latini@asi.it,

^dmarco.petrolo@polito.it

Keywords: Composite Deployables, Failure Index, Geometric Parameters, Carrera Unified Formulation (CUF)

Composite deployable booms are increasingly used in aerospace applications because they combine lightweight design, compact stowage capability, and high deployment efficiency [1]. However, their structural response is heavily influenced by geometry, which impacts not only the overall nonlinear behavior but also the onset of local failure mechanisms. In this context, understanding how geometric parameters alter the evolution of the failure index is essential for designing reliable next-generation deployable structures. This work explores the relationship between geometric features and failure index in composite deployable booms, considering tape and Triangular Rollable And Collapsible (TRAC) configurations.

The numerical analysis is conducted within the framework of the Carrera Unified Formulation (CUF), using a refined one-dimensional beam model where the deployable boom is described along a single reference axis. The cross-sectional kinematics are enhanced by higher-order expansions [2, 3]. This method enables the capture of the nonlinear response of slender composite deployable members with less computational effort compared to full three-dimensional models, while still accounting for the influence of cross-sectional mechanics on the overall response [4]. Failure assessment involves tracking the evolution of the failure index during loading. In this study, the material behavior is assumed to be linear elastic, without including progressive damage evolution; thus, the computed failure indices serve to identify the onset and development of critical conditions.

The results highlight a clear sensitivity of the nonlinear response to the geometric features of the boom. For both tape and TRAC configurations, longer booms generally show larger achievable rotation angles under the same material and section properties. In the tape case, the peak moment varies non-monotonically with length, while failure consistently begins with matrix compression. At later stages, delamination indicators may also exceed one, although this trend is likely affected by the lack of a progressive damage model. In reverse-sign loading, the same geometric trend appears, but numerical convergence becomes more critical for certain lengths. For TRAC booms, matrix compression again is the main failure mode, while the longest configurations also show coupling with local buckling in the curved region. Overall, these findings confirm that geometry significantly influences moment-rotation behavior, convergence stability, and failure initiation in composite deployable booms, and support a broader parametric study on sectional geometry.

Acknowledgements

This study was carried out within the DISPCOMP funded by the Italian Space Agency, ASI, under contract n. 2024-38.I.0.

References

- [1] Pellegrino, S. (2001). Deployable structures in engineering. In Deployable structures (pp. 1-35). Vienna: Springer Vienna.
- [2] Carrera, E., Giunta, G., & Petrolo, M. (2011). Beam structures: classical and advanced theories. John Wiley & Sons.
- [3] Scano, S., Carrera, E., Petrolo, M. (2024). Use of the 3D Equilibrium Equations in the Free-Edge Analyses for Laminated Structures with the Variable Kinematics Approach. *Aerotec. Missili Spaz.* 103, 179–195.
- [4] Pagani, A., & Carrera, E. (2017). Large-deflection and post-buckling analyses of laminated composite beams by Carrera Unified Formulation. *Composite Structures*, 170, 40-52.